

STANDARD
DEPARTURE
CHART

D-ATIS (DEP)	131.700
DEP (N)	126.200
DEP (S)	121.025
TWR (N)	118.750
TWR (S)	119.550
GMC-1	118.350
GMC-2	121.650

DUBAI / Intl.
OMNI DIRECTIONAL DEPARTURE
RWY 12L/R & RWY 30L/R



ATC will issue clearance for departure between indicated tracks as follows:

TL	FL150
TA	13000

AFTER DEPARTURE FLY HEADING DEG CLIMB TO FEET

After departure remain on Tower frequency until instructed to change frequency

Minimum climb gradient 5.0% to 8000 FT (300 FT per NM) see OMDB AD 2.22.4

Advise ATC at startup if unable to comply.

(Procedures design gradient until passing 2000 FT : RWY 12L/R 3.3%, RWY 30L/R 5.0%)

Aircraft shall climb straight ahead to 1000 FT then turn to assigned heading.

Turn before the departure end of runway prohibited.

NOTES

Do not climb above ATC cleared level.

Loss of communications

Conform to the requirements specified in ICAO Annex 2, Chapter 3, paragraph 3.6.5.2

Note: The requirement maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 7 minutes is amended to 3 minutes.

Following unsuccessful attempts to communicate via RTF call Dubai Approach on +971 4 813 3579