

STANDARD DEPARTURE CHART-
INSTRUMENT (SID) - ICAO

AD ELEV 83 FT

ABU DHABI / ZAYED INTL

RNAV 1 SID RWY 13L

ATUDO 5F, BOSEV 1F, DAXIB 1F, KANIP 3F, LORID 1F, MEKRI 1F, ORNEL 1F, TULON 1F

CHANGES: Added R86. Editorial.

ATIS	119.675
ABU DHABI RADAR (W)	128.100
ABU DHABI RADAR (C)	124.400
ABU DHABI DIRECTOR (S)	118.000
ABU DHABI DIRECTOR (N)	118.425
ABU DHABI RADAR (E)	133.550
ABU DHABI INFO	127.500
TWR	119.200(S) 118.675(N)
GND	123.975(S) 121.950(N) 120.425(C)

FOR ROUTE DESCRIPTION
SEE OMAA AD 2.22
TRANSITION ALTITUDE
13,000 FT

BEARINGS ARE MAGNETIC
ELEV, ALT, HGT IN FEET
Refer ENR 5.1 for vertical limits details

VAR 2° (2017)

Contour Legend
6000
5000
4000
3000
2000
1000

NOTES
Do not climb above ATC cleared level.

RESTRICTIONS
On DEP climb to 4000 FT only. Further climb when instructed by Abu Dhabi RADAR

MINM required climb gradient 5% to 8,000 FT (300 FT per NM)

MAX 250 KIAS below 10,000 FT

DEP ACFT shall CTC ABU DHABI RADAR (C) on 124.400 MHz as soon as possible APSPG 1000 FT unless otherwise instructed by ABU DHABI TWR.

