


LEGEND	
TWY CL	
TWY MARKING	
RWY MARKING	
ATC SERVICE BOUNDARY	
THR POINT	
ARP	
RVR	
HELIPAD	
APRONS - ASPHALT	
APRONS - CONCRETE	
TWY SHOULDERS	
TWY NO ENTRY	
TWY CLOSED	
STAND NR	101
RHP PATTERN-A	
WDI	
BLDG	
AIRSIDE SECURITY FENCE	
VOR/DME	
GP/DME	
PAPI	
RWY STRIP	
CWY	
RESA	

- Remarks:
- For Taxiway details refer to UAE AIP OMAA AD 2.8.
 - For Stop bars and ITHPs information refer to OMAA AD-2-26 chart.
 - For AIRFIELD GROUND LIGHTS information refer to OMAA AD-2-21C chart.
- Notes:
- TWY E3A, TWY E3B, TXL E4S, TXL E4N, and TWY E9 south of the intersection with TXL S not available for aircraft types with wingspan greater than 36 M.
 - Where taxiway centre line markings or lights are not visible, pilots shall stop taxiing immediately, hold position and request taxi instructions from ATC.

RWY	MARKING	THR COORDINATES	THR ELEV (FT)	GUND (FT)	BEARING STRENGTH (PCR)
13R	PRECISION	242639.88N 0543806.67E	78	-109.3	680/F/A/W/U
31L	PRECISION	242518.12N 0544001.86E	83	-109.2	
13L	PRECISION	242754.29N 0543817.71E	62	-109.2	1010/F/A/W/T
31R	PRECISION	242632.64N 0544012.76E	72	-109.1	

Service	Call Sign	CHANNEL (MHz)
APP	Abu Dhabi Radar Central	PRI 124.400 SRV 124.625
	Abu Dhabi Radar West	PRI 128.100 SRV 124.625
	Abu Dhabi Radar North	PRI 135.150 SRV 135.350
	Abu Dhabi Director North	PRI 118.425 SRV 121.150
TWR	Abu Dhabi Tower North	PRI 118.675 SRV 121.750
	Abu Dhabi Tower West	S 123.975 N 121.950
	Abu Dhabi Ground	C 120.425 SRV 119.425
	Abu Dhabi Delivery	125.100
ATIS	Abu Dhabi ATIS (ARR)	119.975
	Abu Dhabi ATIS (DEP)	119.675



ELEVATIONS IN FEET
DIMENSIONS IN METRES
BEARINGS ARE MAGNETIC
ANNUAL RATE OF CHANGE 0.05° E