Organisation requirements for Air Operations

RECORD OF REVISIONS

Issue no.	Date of issue Date of applicability	Change
01	16 May 2021 Refer to Cover Regulation, Article 11.G for the date of applicability and Article 7 for the transitional period.	Initial issue based on NPA 2020-12 and associated CRD.
02	01 July 2022 Date of applicability: Refer to Cover Regulation, Article 7, point (e).	ORO.GEN.110, point (c): deleted the word 'approved'.
		AMC2 ORO.GEN.110(c).G: Duties of flight operations officer/ flight dispatcher added.
		AMC3 ORO.GEN.160.G: deleted. AMC1 ORO.GEN.160 point (c).G has the same mandate.
		ORO.SEC.110.G: Re-instating CAR-OPS 1/3 requirements regarding search procedure checklist for aircraft engaged in CAT.
		AMC3 ORO.FC.115, point (d) added to mandate initial acceptance by the competent authority of personnel conducting assessments on flight crew CRM trainers.
		ORO.FC.140, point (a): added 'or equivalent'.
		AMC1 ORO.FC.220&230, point (d) amended
		AMC2 ORO.FC.220&230, point (d) amended
		ORO.FC.230 references under points (b)(5) and (c)(2) are corrected.
		ORO.CC.115, point (e): The word 'instructor' replaced by 'trainer' in two places.
		AMC2 ORO.CC.115(d).G amended to exclude first-aid checking personnel.
		AMC3 ORO.CC.115(e), point (d): added to mandate initial acceptance by the competent authority of personnel conducting assessments on cabin crew CRM trainers.
		ORO.FTL.100.G point (d): added to facilitate application for FDTL Variation for helicopter operators.

TABLE OF CONTENTS

Organisation requirements for Air Operations 1
RECORD OF REVISIONS 1
TABLE OF CONTENTS 2
PART - ORO 14
ORO.GEN.005 Scope 14
SUBPART GEN — GENERAL REQUIREMENTS 15
Section 1 — General 15
ORO.GEN.105 Competent authority 15
ORO.GEN.110 Operator responsibilities 15
AMC1 ORO.GEN.110(a) Operator responsibilities 16
AMC2 ORO.GEN.110(a) Operator responsibilities 17
GM1 ORO.GEN.110(a) Operator responsibilities 17
AMC1 ORO.GEN.110(c) Operator responsibilities 17
GM1 ORO.GEN.110(c) Operator responsibilities 17
AMC1 ORO.GEN.110(e) Operator responsibilities 18
AMC2 ORO.GEN.110(e) Operator responsibilities 18
GM1 ORO.GEN.110(e) Operator responsibilities 18
GM2 ORO.GEN.110(e) Operator responsibilities 18
AMC1 ORO.GEN.110(f) Operator responsibilities 19
GM1 ORO.GEN.110(f) Operator responsibilities 19
AMC1 ORO.GEN.110(f)(h) Operator responsibilities 20
ORO.GEN.115 Application for an AOC 21
GM1 ORO.GEN.115.G Application for an AOC 21
ORO.GEN.120 Means of compliance 22
AMC1 ORO.GEN.120(a) Means of compliance 22
ORO.GEN.125 Terms of approval and privileges of an AOC holder 22
AMC1 ORO.GEN.125 Terms of approval and privileges of an AOC holder 22
ORO.GEN.130 Changes related to an AOC holder 22
AMC1 ORO.GEN.130 Changes related to an AOC holder 23
GM1 ORO.GEN.130(a) Changes related to an AOC holder 23
GM2 ORO.GEN.130(a) Changes related to an AOC holder 24
AMC1 ORO.GEN.130(b) Changes related to an AOC holder 24
GM1 ORO.GEN.130(b) Changes related to an AOC holder 24
ORO.GEN.135 Continued validity of an AOC 25
ORO.GEN.140 Access 26
ORO.GEN.150 Findings 26
AMC1 ORO.GEN.150(b) Findings 26

GM1 ORO.GEN.150 Findings 26
ORO.GEN.155 Immediate reaction to a Safety Problem 26
GM1 ORO.GEN.155(b).G Immediate reaction to a Safety Problem 27
ORO.GEN.160 Occurrence Reporting 27
AMC1 ORO.GEN.160 Occurrence reporting 27
AMC2 ORO.GEN.160 Occurrence reporting 28
AMC3 ORO.GEN.160.G Occurrence reporting 28
Section 2 — Management 29
ORO.GEN.200 Management system 29
GM1 ORO.GEN.200(a)(1);(2);(3);(4).G Management system 29
AMC1 ORO.GEN.200(a)(1);(2);(3);(5) Management system 29
AMC1 ORO.GEN.200(a)(1) Management system 30
GM1 ORO.GEN.200(a)(1) Management system 31
GM2 ORO.GEN.200(a)(1) Management system 31
GM3 ORO.GEN.200(a)(1) Management system 32
AMC1 ORO.GEN.200(a)(2) Management system 32
GM1 ORO.GEN.200(a)(2) Management system 32
AMC1 ORO.GEN.200(a)(3) Management system 33
GM1 ORO.GEN.200(a)(3) Management system 34
GM2 ORO.GEN.200(a)(3) Management system 34
GM3 ORO.GEN.200(a)(3) Management system 42
GM4 ORO.GEN.200(a)(3) Management system 43
AMC1 ORO.GEN.200(a)(4) Management system 43
GM1 ORO.GEN.200(a)(4) Management system 44
AMC1 ORO.GEN.200(a)(5) Management system 44
AMC2 ORO.GEN.200(a)(5) Management system 44
GM1 ORO.GEN.200(a)(5) Management system 45
AMC1 ORO.GEN.200(a)(6) Management system 45
GM1 ORO.GEN.200(a)(6) Management system 47
GM2 ORO.GEN.200(a)(6) Management system 48
GM3 ORO.GEN.200(a)(6) Management system 49
GM4 ORO.GEN.200(a)(6) Management system 50
AMC1 ORO.GEN.200(b) Management system 50
ORO.GEN.205 Contracted activities 51
AMC1 ORO.GEN.205 Contracted activities 51
AMC2 ORO.GEN.205 Contracted activities 51
GM1 ORO.GEN.205 Contracted activities 52
GM2 ORO.GEN.205 Contracted activities 52

ORO.GEN.210 Personnel requirements 53
AMC1 ORO.GEN.210(a) Personnel requirements 53
GM1 ORO.GEN.210(a) Personnel requirements 53
AMC1 ORO.GEN.210(b).G Personnel requirements 53
AMC1 ORO.GEN.210(a)(b).G Personnel requirements 54
ORO.GEN.215 Facility requirements 54
ORO.GEN.220 Record-keeping 54
AMC1 ORO.GEN.220(b) Record-keeping 54
GM1 ORO.GEN.220(b) Record-keeping 55
Section 3 — Additional organisational requirements 56
ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations 56
GM1 ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations 57
GM2 ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations 58
GM1 ORO.GEN.310(a)(2) Use of aircraft listed on an AOC for non-commercial operations and specialised operations 58
AMC1 ORO.GEN.310(b);(e) Use of aircraft listed on an AOC for non-commercial operations and specialised operations 58
GM1 ORO.GEN.310(d) Use of aircraft listed on an AOC for non-commercial operations and specialised operations 59
AMC1 ORO.GEN.310(b);(d);(f) Use of aircraft listed on an AOC for non-commercial operations and specialised operations 59
SUBPART AOC — AIR OPERATOR CERTIFICATION 61
ORO.AOC.100 Application for an air operator certificate 61
AMC1 ORO.AOC.100 Application for an air operator certificate 61
GM1 ORO.AOC.100.G Application for an air operator certificate 61
AMC1 ORO.AOC.100(a) Application for an air operator certificate 61
GM1 ORO.AOC.100(c) Application for an air operator certificate 62
ORO.AOC.105 Operations specifications and privileges of an AOC holder 62
ORO.AOC.110 Leasing agreement 62
AMC1 ORO.AOC.110 Leasing agreement 63
GM1 ORO.AOC.110.G Leasing agreement 63
AMC1 ORO.AOC.110(c) Leasing agreement 63
AMC2 ORO.AOC.110(c) Leasing agreement 64
GM1 ORO.AOC.110(c) Leasing agreement 64
AMC1 ORO.AOC.110(f) Leasing agreement 64
ORO.AOC.115 Code-share agreements 64
AMC1 ORO.AOC.115(a)(1) Code share agreements 65

GM1 ORO.AOC.115(a)(2).G Code share agreements 65
AMC1 ORO.AOC.115(b) Code-share arrangements 65
AMC2 ORO.AOC.115(b) Code-share agreements 66
ORO.AOC.120 Approvals to provide cabin crew training and to issue cabin crew attestations 66
ORO.AOC.125 Non-commercial operations of aircraft listed in the operations specifications by the holder of an AOC 67
AMC1 ORO.AOC.125(a) Non-commercial operations of an AOC holder with aircraft listed on its AOC 67
AMC2 ORO.AOC.125(a) Non-commercial operations of an AOC holder with aircraft listed on its AOC 68
AMC1 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC 68
AMC2 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC 69
GM1 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC 69
ORO.AOC.130 Flight data monitoring — aeroplanes 70
AMC1 ORO.AOC.130 Flight data monitoring — aeroplanes 70
GM1 ORO.AOC.130 Flight data monitoring — aeroplanes 72
GM2 ORO.AOC.130 Flight data monitoring — aeroplanes 78
GM3 ORO.AOC.130 Flight data monitoring - aeroplanes 80
ORO.AOC.135 Personnel requirements 80
AMC1 ORO.AOC.135(a) Personnel requirements 81
AMC2 ORO.AOC.135(a) Personnel requirements 81
GM1 ORO.AOC.135(a) Personnel requirements 81
GM2 ORO.AOC.135(a) Personnel requirements 81
ORO.AOC.140 Facility requirements 82
GM1 ORO.AOC.140(b);(c) Facility requirements 82
ORO.AOC.150 Documentation requirements 83
SUBPART DEC — DECLARATION 84
ORO.DEC.100 Declaration 84
AMC1 ORO.DEC.100(a).G Declaration 84
AMC1 ORO.DEC.100(d) Declaration 84
GM1 ORO.DEC.100 Declaration 84
GM2 ORO.DEC.100.G Declaration process 85
SUBPART SPO — COMMERCIAL SPECIALISED OPERATIONS 86
ORO.SPO.100 Common requirements for commercial specialised operators 86
AMC1 ORO.SPO.100(a) Personnel requirements 86
AMC2 ORO.SPO.100(a) Personnel requirements 87

GM1 ORO.SPO.100(a) Personnel requirements....87
GM2 ORO.SPO.100(a) Personnel requirements....87
AMC1 ORO.SPO.100(c) Common requirements for commercial specialised operators 88
GM1 ORO.SPO.100(c) Common requirements for commercial specialised operators ..88
AMC1 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators 88
AMC2 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators 89
GM1 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators 89
ORO.SPO.110 Authorisation of high risk commercial specialised operations....89
GM1 ORO.SPO.110(a) Authorisation of high-risk commercial specialised operations...90
GM2 ORO.SPO.110(a) Authorisation of high-risk commercial specialised operations...90
ORO.SPO.115 Changes 90
GM1 ORO.SPO.115(a) Changes....90
ORO.SPO.120 Continued validity....90
SUBPART MLR — MANUALS, LOGS AND RECORDS....92
ORO.MLR.100 Operations manual — general....92
AMC1 ORO.MLR.100 Operations manual — general....93
AMC2 ORO.MLR.100 Operations manual — general....93
AMC3 ORO.MLR.100 Operations manual — general....94
AMC4 ORO.MLR.100 Operations manual — general....111
AMC5 ORO.MLR.100 Operations manual — general....115
GM1 ORO.MLR.100(k) Operations manual — general 115
ORO.MLR.101 Operations manual — structure for commercial air transport 115
ORO.MLR.105 Minimum equipment list 116
GM1 ORO.MLR.105(a) Minimum equipment list....117
AMC1 ORO.MLR.105(b).G Minimum equipment list 118
AMC1 ORO.MLR.105(c) Minimum equipment list 119
AMC1 ORO.MLR.105(d) Minimum equipment list....119
AMC1 ORO.MLR.105(d)(1) Minimum equipment list 120
AMC1 ORO.MLR.105(d)(3) Minimum equipment list 120
AMC2 ORO.MLR.105(d)(3) Minimum equipment list 120
GM1 ORO.MLR.105(d)(3) Minimum equipment list 120
GM2 ORO.MLR.105(d)(3) Minimum equipment list 121
GM1 ORO.MLR.105(e);(f) Minimum equipment list 121
AMC1 ORO.MLR.105(f) Minimum equipment list....121
GM1 ORO. MLR.105(f) Minimum equipment list....122
AMC1 ORO.MLR.105(g) Minimum equipment list....122

GM1 ORO.MLR.105(g) Minimum equipment list 122
AMC1 ORO.MLR.105(h) Minimum equipment list 123
AMC1 ORO.MLR.105(j) Minimum equipment list 123
GM1 ORO.MLR.105(j) Minimum equipment list 123
ORO.MLR.110 Journey log 123
AMC1 ORO.MLR.110 Journey log 123
GM1 ORO.MLR.110 Journey log 124
ORO.MLR.115 Record-keeping 124
AMC1 ORO.MLR.115 Record-keeping 125
GM1 ORO.MLR.115(c) Record-keeping 126
GM1 ORO.MLR.115(d) Record-keeping 126
SUBPART SEC — SECURITY 127
ORO.SEC.100 Flight crew compartment security – aeroplanes 127
ORO.SEC.105 Flight crew compartment security – helicopters 127
SUBPART FC — FLIGHT CREW 128
ORO.FC.005 Scope 128
Section 1 — Common requirements 129
ORO.FC.100 Composition of flight crew 129
AMC1 ORO.FC.100(c) Composition of flight crew 129
ORO.FC.105 Designation as pilot-in-command/commander 129
AMC1 ORO.FC.105(b)(2);(c) Designation as pilot-in-command/ commander 130
AMC1 ORO.FC.105(c) Designation as pilot-in-command/commander 131
AMC2 ORO.FC.105(c) Designation as pilot-in-command/commander 131
GM1 ORO.FC.105 (b)(2) Route and aerodrome knowledge 132
GM1 ORO.FC.105(d) Designation as pilot-in-command/commander 132
ORO.FC.110 Flight engineer 132
ORO.FC.115 Crew resource management (CRM) training 133
AMC1 ORO.FC.115 Crew resource management (CRM) training 133
AMC2 ORO.FC.115 Crew resource management (CRM) training 138
AMC3 ORO.FC.115 Crew resource management (CRM) training 139
GM1 ORO.FC.115 Crew resource management (CRM) training 141
GM2 ORO.FC.115 Crew resource management (CRM) training 141
GM3 ORO.FC.115 Crew resource management (CRM) training 142
GM4 ORO.FC.115 Crew resource management (CRM) training 142
GM5 ORO.FC.115 Crew resource management (CRM) training 143
GM6 ORO.FC.115 Crew resource management (CRM) training 144
GM7 ORO.FC.115 Crew resource management (CRM) training 145
ORO.FC.120 Operator conversion training 146

AMC1 ORO.FC.120&130 Operator conversion training and checking & recurrent training and checking 146
ORO.FC.125 Differences training and familiarisation training 147
AMC1 ORO.FC.125 Differences training and familiarisation training 147
ORO.FC.130 Recurrent training and checking 147
ORO.FC.135 Pilot qualification to operate in either pilot's seat 147
ORO.FC.140 Operation on more than one type or variant 147
ORO.FC.145 Provision of training, checking and assessment 148
AMC1 ORO.FC.145(b) Provision of training, checking and assessment 148
AMC1 ORO.FC.145(d) Provision of training, checking and assessment 148
ORO.FC.146 Personnel providing training, checking and assessment 149
AMC1 ORO.FC.146(c) Personnel providing training, checking and assessment 149
AMC2 ORO.FC.146(c) Personnel providing training, checking and assessment 151
GM1 ORO.FC.146(c) Personnel providing training, checking and assessment 151
GM2 ORO.FC.146(c) Personnel providing training, checking and assessment 152
GM3 ORO.FC.146(c) Personnel providing training, checking and assessment 152
Section 2 — Additional requirements for commercial air transport operations 155
ORO.FC.200 Composition of flight crew 155
AMC1 ORO.FC.200(a) Composition of flight crew 155
ORO.FC.A.201 In-flight relief of flight crew members 156
ORO.FC.202 Single-pilot operations under IFR or at night 157
ORO.FC.205 Command course 158
AMC1 ORO.FC.205 Command course 158
ORO.FC.215 Initial operator's crew resource management (CRM) training 158
AMC1 ORO.FC.215 Initial operator's crew resource management (CRM) training 158
ORO.FC.220 Operator conversion training and checking 159
AMC1 ORO.FC.220 Operator conversion training and checking 159
AMC2 ORO.FC.220 Operator conversion training and checking 162
GM1 ORO.FC.220(b) Operator conversion training and checking 162
GM1 ORO.FC.220(c) Operator conversion training and checking 163
GM1 ORO.FC.220(d) Operator conversion training and checking 163
AMC1 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking 163
AMC2 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking 166
AMC3 ORO.FC.220&230.G Operator conversion training and checking & recurrent training and checking 167
GM1 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking 167
GM2 ORO.FC.220&230 Operator conversion training and checking & recurrent training

and checking....168
GM3 ORO.FC.220&230 Operator conversion training and checking & Recurrent training and checking....168
GM4 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking....170
GM5 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking....171
ORO.FC.230 Recurrent training and checking....171
AMC1 ORO.FC.230 Recurrent training and checking....172
AMC2 ORO.FC.230 Recurrent training and checking....179
GM1 ORO.FC.230 Recurrent training and checking....179
GM1 ORO.FC.230(a);(b);(f) Recurrent training and checking....179
ORO.FC.231 Evidence-based training....182
AMC1 ORO.FC.231(a) Evidence-based training....185
AMC2 ORO.FC.231(a) Evidence-based training....186
AMC3 ORO.FC.231(a) Evidence-based training....186
GM1 ORO.FC.231(a) Evidence-based training....187
GM2 ORO.FC.231(a) Evidence-based training....187
GM3 ORO.FC.231(a) Evidence-based training....187
GM4 ORO.FC.231(a) Evidence-based training....188
AMC1 ORO.FC.231(a)(1) Evidence-based training....188
AMC1 ORO.FC.231(a)(2) Evidence-based training....188
AMC2 ORO.FC.231(a)(2) Evidence-based training....189
GM1 ORO.FC.231(a)(2) Evidence-based training....189
GM2 ORO.FC.231(a)(2) Evidence-based training....189
GM3 ORO.FC.231(a)(2) Evidence-based training....190
AMC1 ORO.FC.231(a)(3) Evidence-based training....190
GM1 ORO.FC.231(a)(3) Evidence-based training....190
AMC1 ORO.FC.231(a)(4) Evidence-based training....190
GM1 ORO.FC.231(a)(4) Evidence-based training....191
AMC1 ORO.FC.231(a)(5) Evidence-based training....191
GM1 ORO.FC.231(a)(5) Evidence-based training....192
AMC1 ORO.FC.231(b) Evidence-based training....193
AMC2 ORO.FC.231(b) Evidence-based training....196
GM1 ORO.FC.231(b) Evidence-based training....196
AMC1 ORO.FC.231(c) Evidence-based training....197
AMC2 ORO.FC.231(c)&(d) Evidence-based training....197
GM1 ORO.FC.231(c) Evidence-based training....198
GM2 ORO.FC.231(c) Evidence-based training....198

AMC1 ORO.FC.231(d)(1) Evidence-based training 199
AMC2 ORO.FC.231(d)(1) Evidence-based training 199
AMC3 ORO.FC.231(d)(1) Evidence-based training 200
AMC4 ORO.FC.231(d)(1) Evidence-based training 200
GM1 ORO.FC.231(d)(1) Evidence-based training 202
GM2 ORO.FC.231(d)(1) Evidence-based training 202
AMC1 ORO.FC.231(d)(2) Evidence-based training 206
GM1 ORO.FC.231(d)(2) Evidence-based training 207
GM2 ORO.FC.231(d)(2) Evidence-based training 212
AMC1 ORO.FC.231(e) Evidence-based training 212
AMC1 ORO.FC.231(f) Evidence-based training 213
AMC1 ORO.FC.231(f)(3) Evidence-based training 213
GM1 ORO.FC.231(f) Evidence-based training 213
GM2 ORO.FC.231(f) Evidence-based training 215
GM3 ORO.FC.231(f) Evidence-based training 215
GM4 ORO.FC.231(f) Evidence-based training 215
AMC1 ORO.FC.231(g) Evidence-based training 216
AMC2 ORO.FC.231(g) Evidence-based training 217
GM1 ORO.FC.231(g) Evidence-based training 217
GM2 ORO.FC.231(g) Evidence-based training 217
AMC1 ORO.FC.231(h) Evidence-based training 218
AMC2 ORO.FC.231(h) Evidence-based training 218
AMC1 ORO.FC.231(h)(3) Evidence-based training 218
GM1 ORO.FC.231(h) Evidence-based training 219
GM1 ORO.FC.231(h)(4) Evidence-based training 219
AMC1 ORO.FC.231(i) Evidence-based training 219
GM1 ORO.FC.231(i) Evidence-based training 222
GM2 ORO.FC.231(i) Evidence-based training 222
ORO.FC.232 EBT programme assessment and training topics 222
AMC1 ORO.FC.232 EBT programme assessment and training topics 223
AMC2 ORO.FC.232 EBT programme assessment and training topics 224
AMC3 ORO.FC.232 EBT programme assessment and training topics 241
AMC4 ORO.FC.232 EBT programme assessment and training topics 258
AMC5 ORO.FC.232 EBT programme assessment and training topics 275
AMC6 ORO.FC.232 EBT programme assessment and training topics 276
AMC7 ORO.FC.232 EBT programme assessment and training topics 293
AMC8 ORO.FC.232 EBT programme assessment and training topics 293
GM1 ORO.FC.232 EBT programme assessment and training topics 294

GM2 ORO.FC.232 EBT programme assessment and training topics 295
AMC1 ORO.FC.232(b)(1) EBT programme assessment and training topics 295
AMC1 ORO.FC.232(b)(3) EBT programme assessment and training topics 297
ORO.FC.235 Pilot qualification to operate in either pilot's seat 298
AMC1 ORO.FC.235(d) Pilot qualification to operate in either pilot's seat 298
GM1 ORO.FC.235(f);(g) Pilot qualification to operate in either pilot's seat 298
ORO.FC.240 Operation on more than one type or variant 299
AMC1 ORO.FC.240 Operation on more than one type or variant 299
AMC2 ORO.FC.240 Operation on more than one type or variant 302
ORO.FC.A.245 Alternative training and qualification programme 310
AMC1 ORO.FC.A.245 Alternative training and qualification programme 311
GM1 ORO.FC.A.245 Alternative training and qualification programme 316
GM2 ORO.FC.A.245 Alternative training and qualification programme 316
AMC1 ORO.FC.A.245(a) Alternative training and qualification programme 317
AMC1 ORO.FC.A.245(d)(e)(2) Alternative training and qualification programme 317
ORO.FC.A.250 Commanders holding a CPL(A) 317
ORO.FC.H.250 Commanders holding a CPL(H) 317
Section 3 — Additional requirements for commercial specialised operations and CAT operations referred to in ORO.FC.005 b(1) and (2) 319
ORO.FC.330 Recurrent training and checking — operator proficiency check 319
SUBPART CC — CABIN CREW 320
ORO.CC.005 Scope 320
Section 1 — Common requirements 321
ORO.CC.100 Number and composition of cabin crew 321
AMC1 ORO.CC.100 Number and composition of cabin crew 321
GM1 ORO.CC.100 Number and composition of cabin crew 322
AMC1 ORO.CC.100(d)(2) Number and composition of cabin crew 322
GM1 ORO.CC.100(d)(2) Number and composition of cabin crew 323
ORO.CC.110 Conditions for assignment to duties 323
ORO.CC.115 Conduct of training courses and associated checking 324
GM1 ORO.CC.115 Conduct of training courses and associated checking 324
AMC1 ORO.CC.115(c) Conduct of training courses and associated checking 325
AMC1 ORO.CC.115(d) Conduct of training courses and associated checking 326
AMC2 ORO.CC.115(d).G Conduct of training courses and associated checking 326
AMC1 ORO.CC.115(e) Conduct of training courses and associated checking 326
AMC2 ORO.CC.115(e) Conduct of training courses and associated checking 331
AMC3 ORO.CC.115(e) Conduct of training courses and associated checking 331
GM1 ORO.CC.115(e) Conduct of training courses and associated checking 333

GM2 ORO.CC.115(e) Crew resource management (CRM) training 333
GM3 ORO.CC.115(e) Crew resource management (CRM) training 334
GM4 ORO.CC.115(e) Crew resource management (CRM) training 334
GM5 ORO.CC.115(e) Conduct of training courses and associated checking 335
ORO.CC.120 Initial training course 336
AMC1 ORO.CC.120(a)(1) Initial training course 336
ORO.CC.125 Aircraft type specific training and operator conversion training 336
AMC1 ORO.CC.125(c) Aircraft type specific training and operator conversion training 337
AMC1 ORO.CC.125(d) Aircraft type-specific training and operator conversion training 338
AMC1 ORO.CC.125 & ORO.CC.130 Aircraft type specific training and operator conversion training & differences training 341
AMC1 ORO.CC.125(b) & ORO.CC.130(c) Aircraft type specific training and operator conversion training & differences training 341
ORO.CC.130 Differences training 341
ORO.CC.135 Familiarisation 342
AMC1 ORO.CC.135 Familiarisation 342
ORO.CC.140 Recurrent training 343
AMC1 ORO.CC.140 Recurrent training 344
ORO.CC.145 Refresher training 345
AMC1 ORO.CC.145 Refresher training 346
GM1 ORO.CC.145 Refresher training 346
Section 2 — Additional requirements for commercial air transport operations 347
ORO.CC.200 Senior cabin crew member 347
AMC1 ORO.CC.200(c) Senior cabin crew member 347
AMC1 ORO.CC.200(d) Senior cabin crew member 348
AMC1 ORO.CC.200(e) Senior cabin crew member 348
AMC2 ORO.CC.200(e) Senior cabin crew member 349
GM1 ORO.CC.200(e) Senior cabin crew member 349
GM2 ORO.CC.200(e) Senior cabin crew member 349
ORO.CC.205 Reduction of the number of cabin crew during ground operations and in unforeseen circumstances 349
GM1 ORO.CC.205(a) Reduction of the number of cabin crew during ground operations and in unforeseen circumstances 350
GM1 ORO.CC.205(b)(2) Reduction of the number of cabin crew during ground operations and in unforeseen circumstances 351
AMC1 ORO.CC.205(c)(1) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances 351
AMC1 ORO.CC.205(d) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances 352

AMC2 ORO.CC.205(d) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances 352
ORO.CC.210 Additional conditions for assignment to duties 353
GM1 ORO.CC.210(d) Additional conditions for assignment to duties 353
GM2 ORO.CC.210(d).G Additional conditions for assignment to duties 353
ORO.CC.215 Training and checking programmes and related documentation 353
GM1 ORO.CC.215(b)(2) Training and checking programmes and related documentation 354
ORO.CC.250 Operation on more than one aircraft type or variant 354
AMC1 ORO.CC.250(b) Operation on more than one aircraft type or variant 354
GM1 ORO.CC.250 Operation on more than one aircraft type or variant 355
ORO.CC.255 Single cabin crew member operations 355
SUBPART TC — TECHNICAL CREW IN HEMS, HHO OR NVIS OPERATIONS 357
ORO.TC.100 Scope 357
ORO.TC.105 Conditions for assignment to duties 357
GM1 ORO.TC.105 Conditions for assignment to duties 357
ORO.TC.110 Training and checking 358
AMC1 ORO.TC.110 Training and checking 358
AMC1 ORO.TC.110 (a) Training and checking 358
ORO.TC.115 Initial training 358
AMC1 ORO.TC.115 Initial training 359
ORO.TC.120 Operator conversion training 360
AMC1 ORO.TC.120&.125 Operator conversion training and differences training 360
AMC2 ORO.TC.120&.125 Operator conversion training and differences training 361
ORO.TC.125 Differences training 361
ORO.TC.130 Familiarisation flights 362
ORO.TC.135 Recurrent training 362
AMC1 ORO.TC.135 Recurrent training 362
ORO.TC.140 Refresher training 363
AMC1 ORO.TC.140 Refresher training 363
SUBPART FTL — FLIGHT AND DUTY TIME LIMITATIONS AND REST REQUIREMENTS 364
Section 1 — General 364
ORO.FTL.100.G Applicability 364
APPENDIX TO PART-ORO 365
Appendix I to Part-ORO 365

PART - ORO

ORO.GEN.005 Scope

This Part establishes requirements to be followed by an air operator conducting:

(a) commercial air transport operations (CAT);

(b) commercial specialised operations;

(c) non-commercial operations with complex motor-powered aircraft;

(d) non-commercial specialised operations with complex motor-powered aircraft.

SUBPART GEN — GENERAL REQUIREMENTS

Section 1 — General

ORO.GEN.105 Competent authority

For the purpose of this Regulation, the GCAA is the competent authority exercising oversight over operators having the principal place of business in the territory of the UAE.

ORO.GEN.110 Operator responsibilities

(a) The operator is responsible for the operation of the aircraft in accordance with Annex I to CAR-BR, as applicable, the relevant requirements of this Part and its air operator certificate (AOC) or specialised operation authorisation (SPO authorisation) or declaration.

(b) Every flight shall be conducted in accordance with the provisions of the operations manual.

(c) The operator shall establish and maintain a system for exercising operational control over any flight operated under the terms of its certificate, SPO authorisation or declaration.

Responsibility for operational control shall be delegated only to the pilot-in-command/commander and to a flight operations officer/flight dispatcher if an operator's method of control and supervision of flight operations requires the use of flight operations officer/flight dispatcher personnel. Those flight operations officers/flight dispatchers shall be licensed and maintained current in accordance with the provision of CAR-FDL.

(d) The operator shall ensure that its aircraft are equipped and its crews are qualified as required for the area and type of operation.

(e) The operator shall ensure that all personnel assigned to, or directly involved in, ground and flight operations are properly instructed, have demonstrated their abilities in their particular duties and are aware of their responsibilities and the relationship of such duties to the operation as a whole.

(f) The operator shall establish procedures and instructions for the safe operation of each aircraft type, containing ground staff and crew member duties and responsibilities, for all types of operation on the ground and in flight. Those procedures and instructions shall not require crew members to perform any activities during critical phases of flight other than those required for the safe operation of the aircraft. Procedures and instructions for a sterile flight crew compartment shall also be included.

(g) The operator shall ensure that all personnel are made aware that they shall comply with the laws, regulations and procedures of those States in which operations are conducted and that are pertinent to the performance of their duties.

(h) The operator shall establish a checklist for each aircraft type to be used by crew members in all phases of flight under normal, abnormal and emergency conditions in order to ensure that the operating procedures in the operations manual are followed. The design and the useage of checklists shall observe human factors principles and take into account the latest relevant documentation from the design approval holder.

(i) The operator shall specify flight planning procedures to provide for the safe conduct of the flight based on considerations of aircraft performance, other operating limitations and relevant expected conditions on the route to be followed and at the aerodromes or operating sites concerned. These procedures shall be included in the operations manual.

(j) The operator shall establish and maintain dangerous goods training programmes for personnel as required by the technical instructions. Such training programmes shall be commensurate with the responsibilities of personnel. Training programmes of operators performing CAT, whether they transport dangerous goods or not, and of operators conducting operations other than CAT referred to in points (b), (c) and (d) of point ORO.GEN.005 that transport dangerous goods, whether they transport dangerous goods or not, shall be subject to review and approval by the competent authority.

(k) Notwithstanding point (j), operators conducting commercial operations with either of the following aircraft shall ensure that the flight crew has received an appropriate dangerous goods training or briefing, to enable them to recognise undeclared dangerous goods brought on-board by passengers or as cargo:

(1) a single-engined propeller-driven aeroplane having a MCTOM of 5 700 kg or less and a MOPSC of 5 or less, operated in a flight taking off and landing at the same aerodrome or operating site, under VFR by day;

(2) an other-than-complex motor-powered helicopter, single-engined, with an MOPSC of 5 or less, operated in a flight taking off and landing at the same aerodrome or operating site, under VFR by day.

AMC1 ORO.GEN.110(a) Operator responsibilities

SECURITY TRAINING PROGRAMME FOR CREW MEMBERS — CAT OPERATIONS

Without prejudice to CAR PART VII - Aviation Security, the CAT operator should establish and maintain a security training programme for crew members, including theoretical and practical elements. This training should be provided at the time of operator conversion training and thereafter at intervals not exceeding three years. The content and duration of the training should be adapted to the security threats of the individual operator and should ensure that crew members act in the most appropriate manner to minimise the consequences of acts of unlawful interference. This programme should include the following elements:

(a) determination of the seriousness of the occurrence;

(b) crew communication and coordination;

(c) appropriate self-defence responses;

(d) use of non-lethal protective devices assigned to crew members whose use is authorised by the UAE;

(e) understanding of behaviour of terrorists so as to facilitate the ability of crew members to cope with hijacker behaviour and passenger responses;

(f) in case where cabin crew are required, live situational training exercises regarding various threat conditions;

(g) flight crew compartment procedures to protect the aircraft;

(h) aircraft search procedures, in accordance with CAR PART VII - Aviation Security, including identification of prohibited articles; and

(i) guidance on the least risk bomb locations.

AMC2 ORO.GEN.110(a) Operator responsibilities

SECURITY TRAINING PROGRAMME FOR GROUND PERSONNEL — CAT OPERATIONS

In accordance with CAR Part VII, the CAT operator should establish and maintain a security training programme for ground personnel to acquaint appropriate employees with preventive measures and techniques in relation to passengers, baggage, cargo, mail, equipment, stores and supplies intended for carriage so that they contribute to the prevention of acts of sabotage or other forms of unlawful interference.

GM1 ORO.GEN.110(a) Operator responsibilities

SECURITY TRAINING PROGRAMME FOR CREW MEMBERS

ICAO Security Manual Doc 9811 (restricted access) contains guidance on the development of training programmes.

AMC1 ORO.GEN.110(c) Operator responsibilities

OPERATIONAL CONTROL

The organisation and methods established to exercise operational control should be included in the operations manual and should cover at least a description of responsibilities concerning the initiation, continuation and termination or diversion of each flight.

AMC2 ORO.GEN.110(c).G Operator responsibilities

DUTIES OF FLIGHT OPERATIONS OFFICER/FLIGHT DISPATCHER

(a) A flight operations officer/flight dispatcher in conjunction with a method of control and supervision of flight operations should:

(1) assist the commander/pilot-in-command in flight preparation and provide the relevant information;

(2) assist the commander/pilot-in-command in preparing the operational and ATS flight plans, sign when applicable and file the ATS flight plan with the appropriate ATS unit;

(3) furnish the commander/pilot-in-command while in flight, by appropriate means, with information which may be necessary for the safe conduct of the flight; and

(4) notify the appropriate ATS unit when the position of the aeroplane cannot be determined by an aircraft tracking capability, and attempts to establish communication are unsuccessful.

(b) In the event of an emergency, a flight operations officer/flight dispatcher should:

(1) initiate such procedures as outlined in the operations manual while avoiding taking any action that would conflict with ATC procedures; and

(2) convey safety-related information to the commander/pilot-in-command that may be necessary for the safe conduct of the flight, including information related to any amendments to the flight plan that become necessary in the course of the flight.

GM1 ORO.GEN.110(c) Operator responsibilities

OPERATIONAL CONTROL

Reserved

AMC1 ORO.GEN.110(e) Operator responsibilities

MEL TRAINING PROGRAMME

(a) The operator should develop a training programme for ground personnel dealing with the use of the MEL and detail such training in the continuing airworthiness maintenance exposition CAME and OM as appropriate. Such training programme should include:

(1) the scope, extent and use of the MEL;

(2) placarding of inoperative equipment;

(3) deferral procedures;

(4) dispatching; and

(5) any other operator's MEL related procedures.

(b) The operator should develop a training programme for crew members and detail such training in the Operations Manual. Such training programme should include:

(1) the scope, extent and use of the MEL;

(2) the operator's MEL procedures;

(3) elementary maintenance procedures in accordance with CAR PART V; and

(4) pilot-in-command/commander responsibilities.

AMC2 ORO.GEN.110(e) Operator responsibilities

GROUND OPERATIONS WITH PASSENGERS ON BOARD IN THE ABSENCE OF FLIGHT CREW

For ground operations, whenever passengers are embarking, on board or disembarking in the absence of flight crew members, the operator should:

(a) establish procedures to alert the aerodrome services in the event of ground emergency or urgent need; and

(b) ensure that at least one person on board the aircraft is qualified to apply these procedures and ensure proper coordination between the aircraft and the aerodrome services.

GM1 ORO.GEN.110(e) Operator responsibilities

GROUND PERSONNEL

For the purpose of the MEL training programme referred to in AMC1 ORO.GEN.110(e) ground personnel include maintenance personnel, flight dispatchers and operations officers.

GM2 ORO.GEN.110(e) Operator responsibilities

AERODROME SERVICES

Aerodrome services refer to units available at an aerodrome that could be of assistance in responding to an urgent need or an emergency, such as rescue and firefighting services, medical and ambulance services, air traffic services, security services, police, aerodrome operations, air operators.

AMC1 ORO.GEN.110(f) Operator responsibilities

STERILE FLIGHT CREW COMPARTMENT

(a) Sterile flight crew compartment procedures should ensure that:

(1) flight crew activities are restricted to essential operational activities; and

(2) cabin crew and technical crew communications to flight crew or entry into the flight crew compartment are restricted to safety or security matters.

(b) The sterile flight crew compartment procedures should be applied:

(1) during critical phases of flight;

(2) during taxiing (aeroplanes);

(3) below 10 000 feet above the aerodrome of departure after take-off and the aerodrome of destination before landing, except for cruise flight; and

(4) during any other phases of flight as determined by the pilot-in-command or commander.

(c) All crew members should be trained on sterile flight crew compartment procedures established by the operator, as appropriate to their duties.

GM1 ORO.GEN.110(f) Operator responsibilities

STERILE FLIGHT CREW COMPARTMENT

(a) Establishment of procedures

The operator should establish procedures for flight, cabin, and technical crew that emphasise the objectives and importance of the sterile flight crew compartment. These procedures should also emphasise that, during periods of time when the sterile flight deck compartment procedures are applied, cabin crew and technical crew members should call the flight crew or enter the flight crew compartment only in cases related to safety or security matters. In such cases, information should be timely and accurate.

(b) Flight crew activities

When sterile flight crew compartment procedures are applied, flight crew members are focused on their essential operational activities without being disturbed by non-safety related matters. Examples of activities that should not be performed are:

(1) radio calls concerning passenger connections, fuel loads, catering, etc.;

(2) non-critical paperwork; and

(3) mass and balance corrections and performance calculations, unless required for safety reasons.

(c) Communication to the flight crew

Cabin crew and technical crew use their own discretion to determine whether the situation is related to safety or security matters and whether to call the flight crew. Situations requiring information to the flight crew may include:

(1) any outbreak of fire inside the cabin or in an engine;

(2) a burning smell in the cabin or presence of smoke inside or outside;

(3) fuel or fluid leakage;

(4) exit door unable to be armed or disarmed;

(5) localised extreme cabin temperature changes;

(6) evidence of airframe icing;

(7) cabin/galley equipment or furniture malfunction/breakage posing a hazard to the occupants;

(8) suspicious object;

(9) disruptive passenger;

(10) security threat;

(11) abnormal vibration or noise;

(12) medical emergency;

(13) general drop-down of the oxygen masks in the cabin; and

(14) any other condition deemed relevant by a cabin crew or technical crew member.

AMC1 ORO.GEN.110(f)(h) Operator responsibilities

ESTABLISHMENT OF PROCEDURES

(a) An operator should establish procedures to be followed by cabin crew covering at least:

(1) arming and disarming of slides;

(2) operation of cabin lights, including emergency lighting;

(3) prevention and detection of cabin, galley and toilet fires;

(4) actions to be taken when turbulence is encountered;

(5) actions to be taken in the event of an emergency and/or an evacuation; and

(6) Safety aspects of the in-flight entertainment (IFE) system, if installed.

(b) When establishing procedures and a checklist system for cabin crew with respect to the aircraft cabin, the operator should take into account at least the following duties:

Duties	Pre-take off	In-flight	Pre-landing	Post- landing
(1) Briefing of cabin crew by the senior cabin crew member prior to commencement of a flight or series of flights	x			
(2) Check of safety and emergency equipment in accordance with operator's policies and procedures	x			
(3) Security checks as applicable	x			x
(4) Passenger embarkation and disembarkation	x			x
(5) Securing of passenger cabin (e.g. seat belts, cabin cargo/baggage, IFE system)	x		x	
(6) Securing of galleys and stowage of equipment	x	if required	x	
(7) Arming of door/exit slides	x			
(8) Safety briefing/information to passengers	x	x	x	x
(9) 'Cabin secure' report to flight crew	x	if required	x	
(10) Operation of cabin lights	x	if required	x	x
(11) Safety aspects of the IFE system (if installed)	x	x	x	x
(12) Cabin crew at assigned crew stations	x	if required	x	x
(13) Surveillance of passenger cabin	x	x	x	x
(14) Prevention and detection of fire in the cabin (including the combi-cargo area, crew rest areas, galleys, lavatories and any other cabin remote areas) and instructions for actions to be taken	x	x	x	x
(15) Actions to be taken when turbulence is encountered		x		
(16) Actions to be taken in case of in-flight incidents (e.g. medical emergency)		x		
(17) Actions to be taken in the event of emergency situations	x	x	x	x
(18) Disarming of door/exit slides				x
(19) Reporting of any deficiency and/or un-serviceability of equipment and/or any incident	x	x	x	x

(c) The operator should specify the contents of safety briefings for all cabin crew members prior to the commencement of a flight or series of flights.

ORO.GEN.115 Application for an AOC

(a) The application for an air operator certificate or an amendment to an existing certificate shall be made in a form and manner established by the competent authority, taking into account the applicable requirements of CAR-BR and the applicable rules.

(b) Applicants for an initial certificate shall provide the competent authority with documentation demonstrating how they will comply with the requirements established in CAR-BR and the applicable rules. Such documentation shall include a procedure describing how changes not requiring prior approval will be managed and notified to the competent authority.

GM1 ORO.GEN.115.G Application for an AOC

Refer to AMC-08.

ORO.GEN.120 Means of compliance

(a) Alternative means of compliance to those adopted by the competent authority may be used by an operator to establish compliance with CAR-BR and the applicable rules.

(b) When an operator subject to certification, declaration or an SPO authorisation wishes to use an alternative means of compliance to the acceptable means of compliance (AMC) adopted by the competent authority to establish compliance with CAR-BR and the applicable rules, it shall, prior to implementing it, provide the competent authority with a full description of the alternative means of compliance. The description shall include any revisions to manuals or procedures that may be relevant, as well as an assessment demonstrating that the applicable rules are met.

The operator may implement these alternative means of compliance subject to prior approval and upon receipt of the notification from the competent authority.

(c) Reserved

(d) Reserved

AMC1 ORO.GEN.120(a) Means of compliance

DEMONSTRATION OF COMPLIANCE

In order to demonstrate that the applicable rules are met, a risk assessment should be completed and documented. The result of this risk assessment should demonstrate that an equivalent level of safety to that established by the Acceptable Means of Compliance (AMC) adopted by the competent authority is reached.

ORO.GEN.125 Terms of approval and privileges of an AOC holder

A certified operator shall comply with the scope and privileges defined in the operations specifications attached to the operator's certificate.

AMC1 ORO.GEN.125 Terms of approval and privileges of an AOC holder

MANAGEMENT SYSTEM DOCUMENTATION

The management system documentation should contain the privileges and detailed scope of activities for which the operator is certified, as relevant to the applicable requirements. The scope of activities defined in the management system documentation should be consistent with the terms of approval.

ORO.GEN.130 Changes related to an AOC holder

(a) Any change affecting:

(1) the scope of the certificate or the operations specifications of an operator; or

(2) any of the elements of the operator's management system as required in ORO.GEN.200 (a)(1) and ORO.GEN.200(a)(2),

shall require prior approval by the competent authority.

(b) For any changes requiring prior approval in accordance with CAR-BR and the applicable rules, the operator shall apply for and obtain an approval issued by the competent authority. The application shall be submitted before any such change takes place, in order to enable the competent authority to determine continued compliance with CAR-BR and the Applicable Rules and to amend, if necessary, the operator certificate and related terms of approval

attached to it.

The operator shall provide the competent authority with any relevant documentation.

The change shall only be implemented upon receipt of formal approval by the competent authority.

The operator shall operate under the conditions prescribed by the competent authority during such changes, as applicable.

(c) All changes not requiring prior approval shall be managed and notified to the competent authority as defined in the procedure approved by the competent authority.

AMC1 ORO.GEN.130 Changes related to an AOC holder

APPLICATION TIME FRAMES

(a) The application for the amendment of an air operator certificate (AOC) should be submitted at least 30 days before the date of the intended changes.

(b) In the case of a planned change of a nominated person in accordance with ORO.GEN.210(b) or of a safety manager as defined under AMC1 ORO.GEN.200(a)(1), the operator should inform the competent authority at least 20 days before the date of the proposed change.

(c) Unforeseen changes should be notified at the earliest opportunity, in order to enable the competent authority to determine continued compliance with the applicable requirements and to amend, if necessary, the AOC and related terms of approval.

GM1 ORO.GEN.130(a) Changes related to an AOC holder

GENERAL

(a) Typical examples of changes that may affect the air operator certificate or the operations specifications or the operator's management system, as required in ORO.GEN.200(a)(1) and (a)(2), are listed below:

(1) the name of the operator;

(2) a change of legal entity;

(3) the operator's principal place of business;

(4) the operator's scope of activities;

(5) additional locations of the operator;

(6) the accountable manager referred to in ORO.GEN.210(a);

(7) reporting lines between the accountable manager and the nominated person;

(8) the operator's documentation, as required by this Part, safety policy and procedures;

(9) the facilities.

(b) Prior approval by the competent authority is required for any changes to the operator's procedure describing how changes not requiring prior approval will be managed and notified to the competent authority.

(c) Changes requiring prior approval may only be implemented upon receipt of formal approval by the competent authority.

GM2 ORO.GEN.130(a) Changes related to an AOC holder

CHANGE OF NAME

A change of name requires the operator to submit a new application as a matter of urgency.

Where this is the only change to report, the new application can be accompanied by a copy of the documentation previously submitted to the competent authority under the previous name, as a means of demonstrating how the operator complies with the applicable requirements.

AMC1 ORO.GEN.130(b) Changes related to an AOC holder

MANAGEMENT OF CHANGES REQUIRING PRIOR APPROVAL

For changes requiring prior approval, the operators should conduct a safety risk assessment and provide it to the competent authority upon request.

GM1 ORO.GEN.130(b) Changes related to an AOC holder

CHANGES REQUIRING PRIOR APPROVAL

The following list is a non-exhaustive checklist of items that require prior approval from the competent authority as specified in the applicable rules:

(a) alternative means of compliance;

(b) procedures regarding items to be notified to the competent authority;

(c) cabin crew:

  (1) conduct of the training, examination and checking required by CAR-CC and issue of cabin crew attestations;

  (2) procedures for cabin crew to operate on four aircraft types;

  (3) training programmes, including syllabi;

(d) leasing agreements;

(e) procedure for the use of aircraft included in an AOC by other operators for NCC, NCO and specialised operations, as required by ORO.GEN.310;

(f) specific approvals in accordance with Part-SPA;

(g) dangerous goods training programmes;

(h) flight crew:

  (1) alternative training and qualification programmes (ATQPs);

  (2) procedures for flight crew to operate on more than one type or variant;

  (3) training and checking programmes, including syllabi and use of flight simulation training devices (FSTDs);

(i) fuel policy;

(j) helicopter operations:

  (1) over a hostile environment located outside a congested area, unless the operator holds an approval to operate according to Subpart J of Part-SPA (SPA.HEMS);

  (2) to/from a public interest site;

  (3) without an assured safe forced landing capability;

(k) mass and balance:

standard masses for load items other than standard masses for passengers and checked baggage;

(l) minimum equipment list (MEL):

(1) MEL, in accordance with point (b) of ORO.MLR.105 and AMC1 ORO.MLR.105(b).G;

(2) operating other than in accordance with the MEL, but within the constraints of the master minimum equipment list (MMEL);

(3) rectification interval extension (RIE) procedures;

(m) minimum flight altitudes:

(1) the method for establishing minimum flight altitudes;

(2) descent procedures to fly below specified minimum altitudes;

(n) performance:

(1) increased bank angles at take-off (for performance class A aeroplanes);

(2) short landing operations (for performance class A and B aeroplanes);

(3) steep approach operations (for performance class A and B aeroplanes);

(4) reduced required landing distance operations (for performance class A and B aeroplanes);

(o) isolated aerodrome: using an isolated aerodrome as destination aerodrome for operations with aeroplanes;

(p) approach flight technique:

(1) all approaches not flown as stabilised approaches for a particular approach to a particular runway;

(2) non-precision approaches not flown with the continuous descent final approach (CDFA) technique for each particular approach/runway combination;

(q) maximum distance from an adequate aerodrome for two-engined aeroplanes without an extended range operations with two-engined aeroplanes (ETOPS) approval:

(1) air operations with two-engined performance class A aeroplanes with a maximum operational passenger seating configuration (MOPSC) of 19 or less and a maximum take-off mass less than 45 360 kg, over a route that contains a point further than 120 minutes from an adequate aerodrome, under standard conditions in still air;

(r) aircraft categories:

(1) Applying a lower landing mass than the maximum certified landing mass for determining the indicated airspeed at threshold (V_{AT}).

(s) commercial air transport operations with single-engined turbine aeroplanes in instrument meteorological conditions or at night (CAT SET-IMC).

ORO.GEN.135 Continued validity of an AOC

(a) The operator's certificate shall remain valid subject to:

(1) the operator remaining in compliance with the relevant requirements of CAR-BR and the applicable rules, taking into account the provisions related to the handling of findings as specified under ORO.GEN.150 of this Part;

(2) the competent authority being granted access to the operator as defined in point ORO.GEN.140 to determine continued compliance with the relevant requirements of CAR-BR and the applicable rules;

(3) the certificate not being surrendered or revoked.

(b) Upon revocation or surrender the certificate shall be returned to the competent authority without delay.

ORO.GEN.140 Access

(a) For the purpose of determining compliance with the relevant requirements of CAR-BR and its applicable rules, the operator shall grant access at any time to any facility, aircraft, document, records, data, procedures or any other material relevant to its activity subject to certification, SPO authorisation or declaration, whether it is contracted or not, to any person authorised by the competent authority.

(b) Access to the aircraft mentioned under (a) shall, in the case of CAT, include the possibility to enter and remain in the aircraft during flight operations unless otherwise decided by the commander for the flight crew compartment in accordance with CAT.GEN.MPA.135 in the interest of safety.

ORO.GEN.150 Findings

After receipt of notification of findings, the operator shall:

(a) identify the root cause of the non-compliance;

(b) define a corrective action plan; and

(c) demonstrate corrective action implementation to the satisfaction of the competent authority within a period agreed with that authority.

AMC1 ORO.GEN.150(b) Findings

GENERAL

The corrective action plan defined by the operator should address the effects of the non-compliance, as well as its root cause.

GM1 ORO.GEN.150 Findings

GENERAL

(a) Preventive action is the action to eliminate the cause of a potential non-compliance or other undesirable potential situation.

(b) Corrective action is the action to eliminate or mitigate the root cause(s) and prevent recurrence of an existing detected non-compliance or other undesirable condition or situation. Proper determination of the root cause is crucial for defining effective corrective actions to prevent reoccurrence.

(c) Correction is the action to eliminate a detected non-compliance.

ORO.GEN.155 Immediate reaction to a Safety Problem

The operator shall implement:

(a) any safety measures mandated by the competent authority; and

(b) any relevant mandatory safety information issued by other states, including airworthiness directives.

GM1 ORO.GEN.155(b).G Immediate reaction to a Safety Problem

'Other states' means:

(a) the state in which the aircraft is operated; and

(b) the state of design of the aircraft.

ORO.GEN.160 Occurrence Reporting

(a) The operator shall report to the competent authority, and to any other organisation required to be informed by the State of the operator, any accident, serious incident and occurrence as defined in Accident Investigation Regulations.

(b) Without prejudice to point (a) the operator shall report to the competent authority and to the organisation responsible for the design of the aircraft any incident, malfunction, technical defect, exceeding of technical limitations or occurrence that would highlight inaccurate, incomplete or ambiguous information contained in the operational suitability data established in accordance with CAR 21 or other irregular circumstance that has or may have endangered the safe operation of the aircraft and that has not resulted in an accident or serious incident.

(c) Without prejudice to Accident Investigation Regulations and CAR Part X, the reports referred in paragraphs (a) and (b) shall be made in a form and manner established by the competent authority and shall contain all pertinent information about the conditions known to the operator.

(d) Reports shall be made as soon as practicable, but in accordance with the timeframes prescribed by the competent authority, unless exceptional circumstances prevent this.

(e) Where relevant, the operator shall produce a follow-up report to provide details of actions it intends to take to prevent similar occurrences in the future, as soon as these actions have been identified. This report shall be produced in a form and manner established by the competent authority.

AMC1 ORO.GEN.160 Occurrence reporting

GENERAL

(a) The operator should report all occurrences defined in Accident Investigation Regulations and AMC-22.

(b) In addition to the reports required by Accident Investigation Regulations and AMC-22, the operator should report volcanic ash clouds encountered during flight.

(c).G The operator should comply with the reporting timeframes and other requirements stated in AMC-22.

AMC2 ORO.GEN.160 Occurrence reporting

REPORTABLE EVENTS OF PBN OPERATIONS

(a) A reportable event should be an event that adversely affects the safety of the operation and may be caused by actions or events external to the functioning of the aircraft navigation system.

(b) Technical defects and the exceedance of technical limitations, including:

(1) significant navigation errors attributed to incorrect data or a database coding error;

(2) unexpected deviations in lateral/vertical flight path not caused by flight crew input or erroneous operation of equipment;

(3) significant misleading information without a failure warning;

(4) total loss or multiple navigation equipment failure; and

(5) loss of integrity, e.g. RAIM function, whereas integrity was predicted to be available during preflight planning,

should be considered a reportable event.

(c) The operator should have in place a system for investigating a reportable event to determine if it is due to an improperly coded procedure or a navigation database error. The operator should initiate corrective actions for such an event.

Section 2 — Management

ORO.GEN.200 Management system

(a) The operator shall establish, implement and maintain a management system that includes:

(1) clearly defined lines of responsibility and accountability throughout the operator, including a direct safety accountability of the accountable manager;

(2) a description of the overall philosophies and principles of the operator with regard to safety, referred to as the safety policy;

(3) the identification of aviation safety hazards entailed by the activities of the operator, their evaluation and the management of associated risks, including taking actions to mitigate the risk and verify their effectiveness;

(4) maintaining personnel trained and competent to perform their tasks;

(5) documentation of all management system key processes, including a process for making personnel aware of their responsibilities and the procedure for amending this documentation;

(6) a function to monitor compliance of the operator with the relevant requirements. Compliance monitoring shall include a feedback system of findings to the accountable manager to ensure effective implementation of corrective actions as necessary; and

(7) any additional requirements that are prescribed in the relevant Subparts of this Part or other applicable Parts.

(b) The management system shall correspond to the size of the operator and the nature and complexity of its activities, taking into account the hazards and associated risks inherent in these activities.

GM1 ORO.GEN.200(a)(1);(2);(3);(4).G Management system

SAFETY MANAGEMENT SYSTEM

This regulation and CAR Part X are interchangeable and are intended to address the SMS of an aircraft operator. Should there be any contradiction between both regulations, CAR Part X takes precedence; unless otherwise accepted by the competent authority.

AMC1 ORO.GEN.200(a)(1);(2);(3);(5) Management system

NON-COMPLEX OPERATORS — GENERAL

(a) Safety risk management may be performed using hazard checklists or similar risk management tools or processes, which are integrated into the activities of the operator.

(b) The operator should manage safety risks related to a change. The management of change should be a documented process to identify external and internal change that may have an adverse effect on safety. It should make use of the operator's existing hazard identification, risk assessment and mitigation processes.

(c) The operator should identify a person who fulfils the role of safety manager and who is responsible for coordinating the safety management-related processes and tasks. This person may be the accountable manager or a person with an operational role within the operator.

(d) Within the operator, responsibilities should be identified for hazard identification, risk assessment and mitigation.

(e) The safety policy should include a commitment to improve towards the highest safety standards, comply with all applicable legal requirements, meet all applicable standards, consider best practices and provide appropriate resources.

(f) The operator should, in cooperation with other stakeholders, develop, coordinate and maintain an emergency response plan (ERP) that ensures orderly and safe transition from normal to emergency operations and return to normal operations. The ERP should provide the actions to be taken by the operator or specified individuals in an emergency and reflect the size, nature and complexity of the activities performed by the operator.

AMC1 ORO.GEN.200(a)(1) Management system

COMPLEX OPERATORS — ORGANISATION AND ACCOUNTABILITIES

The management system of an operator should encompass safety by including a safety manager and a safety review board in the organisational structure.

(a) Safety manager

(1) The safety manager should act as the focal point and be responsible for the development, administration and maintenance of an effective safety management system.

(2) The functions of the safety manager should be to:

(i) facilitate hazard identification, risk analysis and management;

(ii) monitor the implementation of actions taken to mitigate risks, as listed in the safety action plan;

(iii) provide periodic reports on safety performance;

(iv) ensure maintenance of safety management documentation;

(v) ensure that there is safety management training available and that it meets acceptable standards;

(vi) provide advice on safety matters; and

(vii) ensure initiation and follow-up of internal occurrence/accident investigations.

(3) If more than one person is designated for the safety management function, the accountable manager should identify the person who acts as the unique focal point (i.e. the 'safety manager').

(b) Safety review board

(1) The safety review board should be a high level committee that considers matters of strategic safety in support of the accountable manager's safety accountability.

(2) The board should be chaired by the accountable manager and be composed of heads of functional areas.

(3) The safety review board should monitor:

(i) safety performance against the safety policy and objectives;

(ii) that any safety action is taken in a timely manner; and

(iii) the effectiveness of the operator's safety management processes.

(c) The safety review board should ensure that appropriate resources are allocated to achieve the established safety performance.

(d) The safety manager or any other relevant person may attend, as appropriate, safety review

board meetings. He/she may communicate to the accountable manager all information, as necessary, to allow decision making based on safety data.

GM1 ORO.GEN.200(a)(1) Management system

SAFETY MANAGER

(a) Depending on the size of the operator and the nature and complexity of its activities, the safety manager may be assisted by additional safety personnel for the performance of all safety management related tasks.

(b) Regardless of the organisational set-up it is important that the safety manager remains the unique focal point as regards the development, administration and maintenance of the operator's safety management system.

COMPETENCIES OF THE SAFETY MANAGER

(c) The safety manager as defined under AMC1 ORO.GEN.200(a)(1) is expected to support, facilitate and lead the implementation and maintenance of the safety management system, fostering an organisational culture for an effective safety management, risk management and occurrence reporting. The competencies for a safety manager should thus include, but not be limited to, the following:

(1) Knowledge of:

(i) ICAO standards and UAE requirements and provisions on safety management;

(ii) basic safety investigation techniques; and

(iii) human factors in aviation.

(2) Relevant and documented work experience, preferably in a comparable position, in:

(i) management systems including compliance monitoring systems and safety management;

(ii) risk management; and

(iii) the operations of the organisation.

(3) Other suitable competencies

(i) the promotion of a positive safety culture;

(ii) interpersonal, influencing and leadership skills;

(iii) oral and written communication skills;

(iv) data management, analytical and problem-solving skills;

(v) professional integrity.

GM2 ORO.GEN.200(a)(1) Management system

COMPLEX OPERATORS — SAFETY ACTION GROUP

(a) A safety action group may be established as a standing group or as an ad-hoc group to assist or act on behalf of the safety review board.

(b) More than one safety action group may be established depending on the scope of the task and specific expertise required.

(c) The safety action group should report to and take strategic direction from the safety review board and should be comprised of managers, supervisors and personnel from operational areas.

(d) The safety action group should:

(1) monitor operational safety;

(2) define actions to mitigate the identified safety risks;

(3) assess the impact on safety of operational changes; and

(4) ensure that safety actions are implemented within agreed timescales.

(e) The safety action group should review the effectiveness of previous safety recommendations and safety promotion.

GM3 ORO.GEN.200(a)(1) Management system

MEANING OF THE TERMS 'ACCOUNTABILITY' AND 'RESPONSIBILITY'

In the English language, the notion of accountability is different from the notion of responsibility. Whereas 'accountability' refers to an obligation which cannot be delegated, 'responsibility' refers to an obligation that can be delegated.

AMC1 ORO.GEN.200(a)(2) Management system

COMPLEX OPERATORS — SAFETY POLICY

(a) The safety policy should:

(1) be endorsed by the accountable manager;

(2) reflect organisational commitments regarding safety and its proactive and systematic management;

(3) be communicated, with visible endorsement, throughout the operator; and

(4) include safety reporting principles.

(b) The safety policy should include a commitment:

(1) to improve towards the highest safety standards;

(2) to comply with all applicable legislation, meet all applicable standards and consider best practices;

(3) to provide appropriate resources;

(4) to enforce safety as one primary responsibility of all managers; and

(5) not to blame someone for reporting something which would not have been otherwise detected.

(c) Senior management should:

(1) continually promote the safety policy to all personnel and demonstrate their commitment to it;

(2) provide necessary human and financial resources for its implementation; and

(3) establish safety objectives and performance standards.

GM1 ORO.GEN.200(a)(2) Management system

SAFETY POLICY

The safety policy is the means whereby the operator states its intention to maintain and, where

practicable, improve safety levels in all its activities and to minimise its contribution to the risk of an aircraft accident as far as is reasonably practicable.

The safety policy should state that the purpose of safety reporting and internal investigations is to improve safety, not to apportion blame to individuals.

AMC1 ORO.GEN.200(a)(3) Management system

COMPLEX OPERATORS — SAFETY RISK MANAGEMENT

(a) Hazard identification processes

(1) Reactive and proactive schemes for hazard identification should be the formal means of collecting, recording, analysing, acting on and generating feedback about hazards and the associated risks that affect the safety of the operational activities of the operator.

(2) All reporting systems, including confidential reporting schemes, should include an effective feedback process.

(b) Risk assessment and mitigation processes

(1) A formal risk management process should be developed and maintained that ensures analysis (in terms of likelihood and severity of occurrence), assessment (in terms of tolerability) and control (in terms of mitigation) of risks to an acceptable level.

(2) The levels of management who have the authority to make decisions regarding the tolerability of safety risks, in accordance with (b)(1), should be specified.

(c) Internal safety investigation

(1) The scope of internal safety investigations should extend beyond the scope of occurrences required to be reported to the competent authority.

(d) Safety performance monitoring and measurement

(1) Safety performance monitoring and measurement should be the process by which the safety performance of the operator is verified in comparison to the safety policy and objectives.

(2) This process should include:

(i) safety reporting, addressing also the status of compliance with the applicable requirements;

(ii) safety studies, that is, rather large analyses encompassing broad safety concerns;

(iii) safety reviews including trends reviews, which would be conducted during introduction and deployment of new technologies, change or implementation of procedures, or in situations of structural change in operations;

(iv) safety audits focussing on the integrity of the operator's management system, and periodically assessing the status of safety risk controls; and

(v) safety surveys, examining particular elements or procedures of a specific operation, such as problem areas or bottlenecks in daily operations, perceptions and opinions of operational personnel and areas of dissent or confusion.

(e) The management of change

The operator should manage safety risks related to a change. The management of change should be a documented process to identify external and internal change that may have an adverse effect on safety. It should make use of the operator's existing hazard identification, risk assessment and mitigation processes.

(f) Continuous improvement

The operator should continuously seek to improve its safety performance. Continuous improvement should be achieved through:

(1) proactive and reactive evaluations of facilities, equipment, documentation and procedures through safety audits and surveys;

(2) proactive evaluation of individuals' performance to verify the fulfilment of their safety responsibilities; and

(3) reactive evaluations in order to verify the effectiveness of the system for control and mitigation of risk.

(g) The emergency response plan (ERP)

(1) An ERP should be established that provides the actions to be taken by the operator or specified individuals in an emergency. The ERP should reflect the size, nature and complexity of the activities performed by the operator.

(2) The ERP should ensure:

(i) an orderly and safe transition from normal to emergency operations;

(ii) safe continuation of operations or return to normal operations as soon as practicable; and

(iii) coordination with the emergency response plans of other organisations, where appropriate.

GM1 ORO.GEN.200(a)(3) Management system

INTERNAL SAFETY REPORTING SCHEME

(a) The overall purpose of the internal safety reporting scheme is to use reported information to improve the level of the safety performance of the operator and not to attribute blame.

(b) The objectives of the scheme are to:

(1) enable an assessment to be made of the safety implications of each relevant incident and accident, including previous similar occurrences, so that any necessary action can be initiated; and

(2) ensure that knowledge of relevant incidents and accidents is disseminated, so that other persons and operators may learn from them.

(c) The scheme is an essential part of the overall monitoring function and it is complementary to the normal day-to-day procedures and 'control' systems and is not intended to duplicate or supersede any of them. The scheme is a tool to identify those instances where routine procedures have failed.

(d) All occurrence reports judged reportable by the person submitting the report should be retained as the significance of such reports may only become obvious at a later date.

GM2 ORO.GEN.200(a)(3) Management system

RISK MANAGEMENT OF FLIGHT OPERATIONS WITH KNOWN OR FORECAST VOLCANIC ASH CONTAMINATION

(a) Responsibilities

The operator is responsible for the safety of its operations, including within an area with known

or forecast volcanic ash contamination.

The operator should complete this assessment of safety risks related to known or forecast volcanic ash contamination as part of its management system before initiating operations into airspace forecast to be or aerodromes/operating sites known to be contaminated with volcanic ash.

This process is intended to ensure the operator takes account of the likely accuracy and quality of the information sources it uses in its management system and to demonstrate its own competence and capability to interpret data from different sources in order to achieve the necessary level of data integrity reliably and correctly resolve any conflicts among data sources that may arise.

In order to decide whether or not to operate into airspace forecast to be or aerodromes/operating sites known to be contaminated with volcanic ash, the operator should make use of the safety risk assessment within its management system, as required by ORO.GEN.200.

The operator's safety risk assessment should take into account all relevant data including data from the type certificate holders (TCHs) regarding the susceptibility of the aircraft they operate to volcanic cloud- related airworthiness effects, the nature and severity of these effects and the related pre-flight, in-flight and post-flight precautions to be observed by the operator.

The operator should ensure that personnel required to be familiar with the details of the safety risk assessments receives all relevant information (both pre-flight and in-flight) in order to be in a position to apply appropriate mitigation measures as specified by the safety risk assessments.

(b) Procedures

The operator should have documented procedures for the management of operations into airspace forecast to be or aerodromes/operating sites known to be contaminated with volcanic ash.

These procedures should ensure that, at all times, flight operations remain within the accepted safety boundaries as established through the management system allowing for any variations in information sources, equipment, operational experience or organisation. Procedures should include those for flight crew, flight planners, dispatchers, operations, continuing airworthiness personnel such that they are in a position to evaluate correctly the risk of flights into airspace forecast to be contaminated by volcanic ash and to plan accordingly.

Continuing airworthiness personnel should be provided with procedures allowing them to correctly assess the need for and to execute relevant continuing airworthiness interventions.

The operator should retain sufficient qualified and competent staff to generate well supported operational risk management decisions and ensure that its staff are appropriately trained and current. It is recommended that the operator make the necessary arrangements for its relevant staff to take up opportunities to be involved in volcanic ash exercises conducted in their areas of operation.

(c) Volcanic activity information and operator's potential response

Before and during operations, information valuable to the operator is generated by various volcano agencies worldwide. The operator's risk assessment and mitigating actions need to take account of, and respond appropriately to, the information likely to be available during each phase of the eruptive sequence from pre-eruption through to end of eruptive activity. It is nevertheless noted that eruptions rarely follow a deterministic pattern of behaviour. A typical operator's response may consist of the following:

(1) Pre-eruption

The operator should have in place a robust mechanism for ensuring that it is constantly vigilant for any alerts of pre-eruption volcanic activity relevant to its operations. The staff involved need to understand the threat to safe operations that such alerts represent.

An operator whose routes traverse large, active volcanic areas, for which immediate International Airways Volcano Watch (IAVW) alerts may not be available, should define its strategy for capturing information about increased volcanic activity before pre-eruption alerts are generated. For example, an operator may combine elevated activity information with information concerning the profile and history of the volcano to determine an operating policy, which could include re-routing or restrictions at night. This would be useful when dealing with the 60% of volcanoes which are unmonitored.

Such an operator should also ensure that its crews are aware that they may be the first to observe an eruption and so need to be vigilant and ready to ensure that this information is made available for wider dissemination as quickly as possible.

(2) Start of an eruption

Given the likely uncertainty regarding the status of the eruption during the early stages of an event and regarding the associated volcanic cloud, the operator's procedures should include a requirement for crews to initiate re-routes to avoid the affected airspace.

The operator should ensure that flights are planned to remain clear of the affected areas and that consideration is given to available aerodromes/operating sites and fuel requirements.

It is expected that the following initial actions will be taken by the operator:

(i) determine if any aircraft in flight could be affected, alert the crew and provide advice on re- routing and available aerodromes/operating sites as required;

(ii) alert management;

(iii) for flight departures, brief flight crew and revise flight and fuel planning in accordance with the safety risk assessment;

(iv) alert flight crew and operations staff to the need for increased monitoring of information

(e.g. special air report (AIREP), volcanic activity report (VAR), significant weather information (SIGMET), NOTAMs and company messages);

(v) initiate the gathering of all data relevant to determining the risk; and

(vi) apply mitigations identified in the safety risk assessment.

(3) On-going eruption

As the eruptive event develops, the operator can expect the responsible Volcanic Ash Advisory Centre (VAAC) to provide volcanic ash advisory messages (VAA/VAGs) defining, as accurately as possible, the vertical and horizontal extent of areas and layers of volcanic clouds. As a minimum, the operator should monitor, and take account of, this VAAC information as well as of relevant SIGMETs and NOTAMs.

Other sources of information are likely to be available such as VAR/AIREPs, satellite imagery and a range of other information from State and commercial organisations. The operator should plan its operations in accordance with its safety risk assessment taking into account the information that it considers accurate and relevant from these additional sources.

The operator should carefully consider and resolve differences or conflicts among the information sources, notably between published information and observations (pilot reports, airborne measurements, etc.).

Given the dynamic nature of the volcanic hazards, the operator should ensure that the situation is monitored closely and operations adjusted to suit changing conditions.

The operator should be aware that the affected or danger areas may be established and presented in different ways.The operator should require reports from its crews concerning any encounters with volcanic emissions. These reports should be passed immediately to the appropriate air traffic services (ATS) unit and to the operator's competent authority.

For the purpose of flight planning, the operator should treat the horizontal and vertical limits of the temporary danger area (TDA) or airspace forecast to be contaminated by volcanic ash as applicable, to be overflown as it would mountainous terrain, modified in accordance with its safety risk assessment. The operator should take account of the risk of cabin depressurisation or engine failure resulting in the inability to maintain level flight above a volcanic cloud, especially when conducting ETOPS operations. Additionally, minimum equipment list (MEL) provisions should be considered in consultation with the TCHs.

Flying below volcanic ash contaminated airspace should be considered on a case-by-case basis. It should only be planned to reach or leave an aerodrome/operating site close to the boundary of this airspace or where the ash contamination is very high and stable. The establishment of Minimum Sector Altitude (MSA) and the availability of aerodromes/operating sites should be considered.

(d) Safety risk assessment

When directed specifically at the issue of intended flight into airspace forecast to be or aerodromes/operating sites known to be contaminated with volcanic ash, the process should involve the following:

(1) Identifying the hazards

The generic hazard, in the context of this document, is airspace forecast to be or aerodromes/operating sites known to be contaminated with volcanic ash, and whose characteristics are harmful to the airworthiness and operation of the aircraft.

This GM is referring to volcanic ash contamination since it is the most significant hazard for flight operations in the context of a volcanic eruption. Nevertheless, it might not be the only hazard and therefore the operator should consider additional hazards which could have an adverse effect on aircraft structure or passengers safety such as gases.

Within this generic hazard, the operator should develop its own list of specific hazards taking into account its specific aircraft, experience, knowledge and type of operation, and any other relevant data stemming from previous eruptions.

(2) Considering the severity and consequences of the hazard occurring (i.e. the nature and actual level of damage expected to be inflicted on the particular aircraft from exposure to that volcanic ash cloud).

(3) Evaluating the likelihood of encountering volcanic ash clouds with characteristics harmful to the safe operation of the aircraft.

For each specific hazard within the generic hazard, the likelihood of adverse consequences should be assessed, either qualitatively or quantitatively.

(4) Determining whether the consequent risk is acceptable and within the operator's risk performance criteria.

At this stage of the process, the safety risks should be classified as acceptable or unacceptable. The assessment of tolerability will be subjective, based on qualitative data and expert judgement, until specific quantitative data are available in respect of a range of parameters.

(5) Taking action to reduce the safety risk to a level that is acceptable to the operator's management.

Appropriate mitigation for each unacceptable risk identified should then be considered in order to reduce the risk to a level acceptable to the operator's management.

(e) Procedures to be considered when identifying possible mitigations actions

When conducting a volcanic ash safety risk assessment, the operator should consider the following non-exhaustive list of procedures and processes as mitigation:

(1) Type certificate holders

Obtaining advice from the TCHs and other engineering sources concerning operations in potentially contaminated airspace and/or aerodromes/operating sites contaminated by volcanic ash.

This advice should set out:

(i) the features of the aircraft that are susceptible to airworthiness effects related to volcanic ash;

(ii) the nature and severity of these effects;

(iii) the effect of volcanic ash on operations to/from contaminated aerodromes/operating sites, including the effect on take-off and landing aircraft performance;

(iv) the related pre-flight, in-flight and post-flight precautions to be observed by the operator including any necessary amendments to aircraft operating manuals, aircraft maintenance manuals, master minimum equipment list/dispatch deviation or equivalents; and

(v) the recommended inspections associated with operations in volcanic ash potentially contaminated airspace and operations to/from volcanic ash contaminated aerodromes/operating sites; this may take the form of instructions for continuing airworthiness or other advice.

(2) Operator/contracted organisations' personnel

Definition of procedures for flight planning, operations, engineering and maintenance ensuring that:

(i) personnel responsible for flight planning are in a position to evaluate correctly the risk of encountering volcanic ash contaminated airspace, or aerodromes/operating sites, and can plan accordingly;

(ii) flight planning and operational procedures enable crews to avoid areas and aerodromes/ operating sites with unacceptable volcanic ash contamination;

(iii) flight crew are aware of the possible signs of entry into a volcanic ash cloud and execute the associated procedures;

(iv) continuing airworthiness personnel are able to assess the need for and to execute any necessary maintenance or other required interventions; and

(v) crews are provided with appropriate aircraft performance data when operating to/from aerodromes/operating sites contaminated with volcanic ash.

(3) Provision of enhanced flight watch

This should ensure:

(i) close and continuous monitoring of VAA, VAR/AIREP, SIGMET, NOTAM, ASHTAM and other relevant information, and information from crews, concerning the volcanic ash cloud hazard;

(ii) access to plots of the affected areas from SIGMETs, NOTAMs and relevant company information for crews and personnel responsible for the management and the supervision of the flight operations; and

(iii) communication of the latest information to crews and personnel responsible for the management and the supervision of the flight operations in a timely fashion.

(4) Flight planning

Flexibility of the process to allow re-planning at short notice should conditions change.

(5) Departure, destination and alternate aerodromes

For the airspace to be traversed, or the aerodromes/operating sites in use, parameters to evaluate and take account of:

(i) the probability of contamination;

(ii) any additional aircraft performance requirements;

(iii) required maintenance considerations;

(iv) fuel requirements for re-routeing and extended holding.

(6) Routing policy

Parameters to evaluate and take account of:

(i) the shortest period in and over the forecast contaminated area;

(ii) the hazards associated with flying over the contaminated area;

(iii) drift down and emergency descent considerations;

(iv) the policy for flying below the contaminated airspace and the associated hazards.

(7) Diversion policy

Parameters to evaluate and take account of:

(i) maximum allowed distance from a suitable aerodrome/operating site;

(ii) availability of aerodromes/operating sites outside the forecast contaminated area;

(iii) diversion policy after an volcanic ash encounter.

(8) Minimum equipment list (MEL)

Additional provisions in the MEL for dispatching aircraft with unserviceabilities that might affect the following non-exhaustive list of systems:

(i) air conditioning packs;

(ii) engine bleeds;

(iii) pressurisation system;

(iv) electrical power distribution system;

(v) air data system;

(vi) standby instruments;

(vii) navigation systems;

(viii) de-icing systems;

(ix) engine-driven generators;

(x) auxiliary power unit (APU);

(xi) airborne collision avoidance system (ACAS);

(xii) terrain awareness warning system (TAWS);

(xiii) autoland systems;

(xiv) provision of crew oxygen;

(xv) supplemental oxygen for passengers.

(9) Standard operating procedures

Crew training to ensure they are familiar with normal and abnormal operating procedures and particularly any changes regarding but not limited to:

(i) pre-flight planning;

(ii) in-flight monitoring of volcanic ash cloud affected areas and avoidance procedures;

(iii) diversion;

(iv) communications with ATC;

(v) in-flight monitoring of engine and systems potentially affected by volcanic ash cloud contamination;

(vi) recognition and detection of volcanic ash clouds and reporting procedures;

(vii) in-flight indications of a volcanic ash cloud encounter;

(viii) procedures to be followed if a volcanic ash cloud is encountered;

(ix) unreliable or erroneous airspeed;

(x) non-normal procedures for engines and systems potentially affected by volcanic ash cloud contamination;

(xi) engine-out and engine relight;

(xii) escape routes; and

(xiii) operations to/from aerodromes/operating sites contaminated with volcanic ash.

(10) Provision for aircraft technical log

This should ensure:

(i) systematic entry in the aircraft technical log related to any actual or suspected volcanic ash encounter whether in-flight or at an aerodrome/operating site; and

(ii) checking, prior to flight, of the completion of maintenance actions related to an entry in the aircraft technical log for a volcanic ash cloud encounter on a previous flight.

(11) Incident reporting

Crew requirements for:

(i) reporting an airborne volcanic ash cloud encounter (VAR);

(ii) post-flight volcanic ash cloud reporting (VAR);

(iii) reporting non-encounters in airspace forecast to be contaminated; and

(iv) filing a mandatory occurrence report in accordance with ORO.GEN.160.

(12) Continuing airworthiness procedures

Procedures when operating in or near areas of volcanic ash cloud contamination:

(i) enhancement of vigilance during inspections and regular maintenance and appropriate adjustments to maintenance practices;

(ii) definition of a follow-up procedure when a volcanic ash cloud encounter has been reported or suspected;

(iii) thorough investigation for any sign of unusual or accelerated abrasions or corrosion or of volcanic ash accumulation;

(iv) reporting to TCHs and the relevant authorities observations and experiences from operations in areas of volcanic ash cloud contamination;

(v) completion of any additional maintenance recommended by the TCH or by the competent authority.

(f) Reporting

The operator should ensure that reports are immediately submitted to the nearest ATS unit using the VAR/AIREP procedures followed up by a more detailed VAR on landing together with, as applicable, a report, as defined in Accident Investigation Regulations, CAR Part X and AMC-22, and an aircraft technical log entry for:

(1) any incident related to volcanic clouds;

(2) any observation of volcanic ash activity; and

(3) any time that volcanic ash is not encountered in an area where it was forecast to be.

(g) References

Further guidance on volcanic ash safety risk assessment is given in ICAO Doc. 9974 (Flight safety and volcanic ash — Risk management of flight operations with known or forecast volcanic ash contamination).

GM3 ORO.GEN.200(a)(3) Management system

SAFETY RISK ASSESSMENT — RISK REGISTER

The results of the assessment of the potential adverse consequences or outcome of each hazard may be recorded by the operator in a risk register, an example of which is provided below.

Hazard		Incident Sequence Description	Existing Controls	Outcome (Pre-Mitigation)			Additional Mitigation required	Outcome (Post-Mitigation)			Actions and Owners	Monitoring and Review Requirements
No.	Description			Severity	Likelihood	Risk		Severity	Likelihood	Risk		

GM4 ORO.GEN.200(a)(3) Management system

COMPLEX ORGANISATIONS — SAFETY RISK MANAGEMENT — INTERFACES BETWEEN ORGANISATIONS

(a) Hazard identification and risk assessment start with an identification of all parties involved in the arrangement, including independent experts and non-approved organisations. It extends to the overall control structure, assessing, in particular, the following elements across all subcontract levels and all parties within such arrangements:

(1) coordination and interfaces between the different parties;

(2) applicable procedures;

(3) communication between all parties involved, including reporting and feedback channels;

(4) task allocation responsibilities and authorities; and

(5) qualifications and competency of key personnel.

(b) Safety risk management focuses on the following aspects:

(1) clear assignment of accountability and allocation of responsibilities;

(2) only one party is responsible for a specific aspect of the arrangement — no overlapping or conflicting responsibilities, in order to eliminate coordination errors;

(3) existence of clear reporting lines, both for occurrence reporting and progress reporting;

(4) possibility for staff to directly notify the operator of any hazard suggesting an obviously unacceptable safety risk as a result of the potential consequences of this hazard.

AMC1 ORO.GEN.200(a)(4) Management system

TRAINING AND COMMUNICATION ON SAFETY

(a) Training

(1) All personnel should receive safety training as appropriate for their safety responsibilities.

(2) Adequate records of all safety training provided should be kept.

(b) Communication

(1) The operator should establish communication about safety matters that:

(i) ensures that all personnel are aware of the safety management activities as appropriate for their safety responsibilities;

(ii) conveys safety critical information, especially relating to assessed risks and analysed hazards;

(iii) explains why particular actions are taken; and

(iv) explains why safety procedures are introduced or changed.

(2) Regular meetings with personnel where information, actions and procedures are discussed may be used to communicate safety matters.

GM1 ORO.GEN.200(a)(4) Management system

TRAINING AND COMMUNICATION ON SAFETY

The safety training programme may consist of self-instruction via the media (newsletters, flight safety magazines), classroom training, e-learning or similar training provided by training service providers.

AMC1 ORO.GEN.200(a)(5) Management system

MANAGEMENT SYSTEM DOCUMENTATION — GENERAL

(a) The operator's management system documentation should at least include the following information:

(1) a statement signed by the accountable manager to confirm that the operator will continuously work in accordance with the applicable requirements and the operator's documentation, as required by this Part;

(2) the operator's scope of activities;

(3) the titles and names of persons referred to in ORO.GEN.210 (a) and (b);

(4) an operator chart showing the lines of responsibility between the persons referred to in ORO.GEN.210;

(5) a general description and location of the facilities referred to in ORO.GEN.215;

(6) procedures specifying how the operator ensures compliance with the applicable requirements;

(7) the amendment procedure for the operator's management system documentation.

(b) The operator's management system documentation may be included in a separate manual or in (one of) the manual(s), as required by the applicable subpart(s). A cross-reference should be included.

AMC2 ORO.GEN.200(a)(5) Management system

COMPLEX OPERATORS — SAFETY MANAGEMENT MANUAL

(a) The safety management manual (SMM) should be the key instrument for communicating the approach to safety for the whole of the operator. The SMM should document all aspects of safety management, including the safety policy, objectives, procedures and individual safety responsibilities.

(b) The contents of the safety management manual should include all of the following:

(1) scope of the safety management system;

(2) safety policy and objectives;

(3) safety accountability of the accountable manager;

(4) safety responsibilities of key safety personnel;

(5) documentation control procedures;

(6) hazard identification and risk management schemes;

(7) safety action planning;

(8) safety performance monitoring;

(9) incident investigation and reporting;

(10) emergency response planning;

(11) management of change (including organisational changes with regard to safety responsibilities);

(12) safety promotion.

(c) The SMM may be contained in (one of) the manual(s) of the operator.

GM1 ORO.GEN.200(a)(5) Management system

MANAGEMENT SYSTEM DOCUMENTATION — GENERAL

(a) It is not required to duplicate information in several manuals. The information may be contained in any of the operator manuals (e.g. operations manual), which may also be combined.

(b) The operator may also choose to document some of the information required to be documented in separate documents (e.g. procedures). In this case, it should ensure that manuals contain adequate references to any document kept separately. Any such documents are then to be considered an integral part of the operator's management system documentation.

AMC1 ORO.GEN.200(a)(6) Management system

COMPLIANCE MONITORING — GENERAL

(a) Compliance monitoring

The implementation and use of a compliance monitoring function should enable the operator to monitor compliance with the relevant requirements of this Part and other applicable Parts.

(1) The operator should specify the basic structure of the compliance monitoring function applicable to the activities conducted.

(2) The compliance monitoring function should be structured according to the size of the operator and the complexity of the activities to be monitored;

(b) Organisations should monitor compliance with the procedures they have designed to ensure safe activities. In doing so, they should as a minimum, and where appropriate, monitor compliance with the following:

(1) privileges of the operator;

(2) manuals, logs, and records;

(3) training standards;

(4) management system procedures and manuals;

(5) activities of the organisation carried out under the supervision of the nominated persons in accordance with ORO.GEN.210(b); and

(6) any outsourced activities in accordance with ORO.GEN.205, for compliance with the contract.

(c) Organisational set up

(1) To ensure that the operator continues to meet the requirements of this Part and other applicable Parts, the accountable manager should designate a compliance monitoring manager. The role of the compliance monitoring manager is to ensure that the activities of the operator are monitored for compliance with the applicable regulatory requirements, and

any additional requirements as established by the operator, and that these activities are carried out properly under the supervision of the relevant head of functional area.

(2) The compliance monitoring manager should be responsible for ensuring that the compliance monitoring programme is properly implemented, maintained and continually reviewed and improved.

(3) The compliance monitoring manager should:

(i) have direct access to the accountable manager;

(ii) not be one of the other persons referred to in ORO.GEN.210 (b);

(iii) be able to demonstrate relevant knowledge, background and appropriate experience related to the activities of the operator, including knowledge and experience in compliance monitoring; and

(iv) have access to all parts of the operator, and as necessary, any contracted operator.

(4) In the case of a non-complex operator, this task may be exercised by the accountable manager provided he/she has demonstrated having the related competence as defined in (c)(3)(iii).

(5) In the case the same person acts as compliance monitoring manager and as safety manager, the accountable manager, with regards to his/her direct accountability for safety, should ensure that sufficient resources are allocated to both functions, taking into account the size of the operator and the nature and complexity of its activities.

(6) The independence of the compliance monitoring function should be established by ensuring that audits and inspections are carried out by personnel not responsible for the function, procedure or products being audited.

(7) If more than one person is designated for the compliance monitoring function, the accountable manager should identify the person who acts as the unique focal point (i.e. the 'compliance monitoring manager').

(d) Compliance monitoring documentation

(1) Relevant documentation should include the relevant part(s) of the operator's management system documentation.

(2) In addition, relevant documentation should also include the following:

(i) terminology;

(ii) specified activity standards;

(iii) a description of the operator;

(iv) the allocation of duties and responsibilities;

(v) procedures to ensure regulatory compliance;

(vi) the compliance monitoring programme, reflecting:

(A) schedule of the monitoring programme;

(B) audit procedures including an audit plan that is implemented, maintained, and continually reviewed and improved;

(C) reporting procedures;

(D) follow-up and corrective action procedures; and

(E) recording system.

(vii) the training syllabus referred to in (e)(2);

(viii) document control.

(e) Training

(1) Correct and thorough training is essential to optimise compliance in every operator. In order to achieve significant outcome of such training, the operator should ensure that all personnel understand the objectives as laid down in the operator's management system documentation.

(2) Those responsible for managing the compliance monitoring function should receive training on this task. Such training should cover the requirements of compliance monitoring, manuals and procedures related to the task, audit techniques, reporting and recording.

(3) Time should be provided to train all personnel involved in compliance management and for briefing the remainder of the personnel.

(4) The allocation of time and resources should be governed by the volume and complexity of the activities concerned.

GM1 ORO.GEN.200(a)(6) Management system

COMPLIANCE MONITORING — GENERAL

(a) The organisational set-up of the compliance monitoring function should reflect the size of the operator and the nature and complexity of its activities. The compliance monitoring manager may perform all audits and inspections himself/herself or appoint one or more auditors by choosing personnel having the related competence as defined in AMC1 ORO.GEN.200(a)(6) point (c)(3)(iii), either from, within or outside the operator.

(b) Regardless of the option chosen it must be ensured that the independence of the audit function is not affected, in particular in cases where those performing the audit or inspection are also responsible for other functions for the operator.

(c) In case external personnel are used to perform compliance audits or inspections:

(1) any such audits or inspections are performed under the responsibility of the compliance monitoring manager; and

(2) the operator remains responsible to ensure that the external personnel has relevant knowledge, background and experience as appropriate to the activities being audited or inspected; including knowledge and experience in compliance monitoring.

(d) The operator retains the ultimate responsibility for the effectiveness of the compliance monitoring function, in particular for the effective implementation and follow-up of all corrective actions.

GM2 ORO.GEN.200(a)(6) Management system

COMPLEX OPERATORS — COMPLIANCE MONITORING PROGRAMME

(a) Typical subject areas for compliance monitoring audits and inspections for operators should be, as applicable:

(1) actual flight operations;

(2) ground de-icing/anti-icing;

(3) flight support services;

(4) load control;

(5) technical standards.

(b) Operators should monitor compliance with the operational procedures they have designed to ensure safe operations, airworthy aircraft and the serviceability of both operational and safety equipment. In doing so, they should, where appropriate, additionally monitor the following:

(1) operational procedures;

(2) flight safety procedures;

(3) operational control and supervision;

(4) aircraft performance;

(5) all weather operations;

(6) communications and navigational equipment and practices;

(7) mass, balance and aircraft loading;

(8) instruments and safety equipment;

(9) ground operations;

(10) flight and duty time limitations, rest requirements, and scheduling;

(11) aircraft maintenance/operations interface;

(12) use of the MEL;

(13) flight crew;

(14) cabin crew;

(15) dangerous goods;

(16) security.

GM3 ORO.GEN.200(a)(6) Management system

NON-COMPLEX OPERATORS — COMPLIANCE MONITORING

(a) Compliance monitoring audits and inspections may be documented on a 'Compliance Monitoring Checklist', and any findings recorded in a 'Non-compliance Report'. The following documents may be used for this purpose.

COMPLIANCE MONITORING CHECKLIST Year:			
Subject	Date checked	Checked by	Comments/Non-compliance Report No.
Flight Operations			
Aircraft checklists checked for accuracy and validity			
Minimum five flight plans checked and verified for proper and correct information			
Flight planning facilities checked for updated manuals, documents and access to relevant flight information			
Incident reports evaluated and reported to the appropriate competent authority			
Ground Handling			
Contracts with ground handling organisations established and valid, if applicable			
Instructions regarding fuelling and de-icing issued, if applicable			
Instructions regarding dangerous goods issued and known by all relevant personnel, if applicable			
Mass & Balance			
Min. five load sheets checked and verified for proper and correct information, if applicable			
Aircraft fleet checked for valid weight check, if applicable			
Minimum one check per aircraft of correct loading and distribution, if applicable			
Training			
Training records updated and accurate			
All pilot licenses checked for currency, correct ratings and valid medical check			
All pilots received recurrent training			
Training facilities & Instructors approved			
All pilots received daily inspection (DI) training			
Documentation			
All issues of operations manual (OM) checked for correct amendment status			
AOC checked for validity and appropriate operations specifications, if applicable			
Aviation requirements applicable and updated			
Crew flight and duty time record updated, if applicable			
Flight documents record checked and updated			
Compliance monitoring records checked and updated			

– NON-COMPLIANCE REPORT – No:		
To Compliance Monitoring Manager	Reported by:	Date:
Category Flight Operations ❑ Ground Handling ❑ Mass & Balance ❑ Training ❑ Documentation ❑ Other ❑		
Description:	Reference:	
Level of finding:		
Root-cause of non-compliance:		
Suggested correction:		
Compliance Monitoring Manager: ❑Corrective action required ❑ Corrective action not required		
Responsible Person:	Time limitation:	
Corrective action:	Reference:	
Signature Responsible Person:	Date:	
Compliance Monitoring Manager ❑Correction and corrective action verified ❑ Report Closed		
Signature Compliance Monitoring Manager:	Date:	

GM4 ORO.GEN.200(a)(6) Management system

AUDIT AND INSPECTION

(a) 'Audit' means a systematic, independent and documented process for obtaining evidence and evaluating it objectively to determine the extent to which requirements are complied with.

(b) 'Inspection' means an independent documented conformity evaluation by observation and judgement accompanied as appropriate by measurement, testing or gauging, in order to verify compliance with applicable requirements.

AMC1 ORO.GEN.200(b) Management system

SIZE, NATURE AND COMPLEXITY OF THE ACTIVITY

(a) An operator should be considered as complex when it has a workforce of more than 20 full time equivalents (FTEs) involved in the activity subject to CAR-BR and the applicable rules.

(b) Operators with up to 20 FTEs involved in the activity subject to CAR-BR and the applicable rules may also be considered complex based on an assessment of the following factors:

(1) in terms of complexity, the extent and scope of contracted activities subject to the approval;

(2) in terms of risk criteria, the extent of the following:

(i) operations requiring a specific approval;

(ii) high-risk commercial specialised operations;

(iii) operations with different types of aircraft used; and

(iv) operations in challenging environment (offshore, mountainous area, etc.).

ORO.GEN.205 Contracted activities

(a) When contracting or purchasing any services or products as a part of its activities, the operator shall ensure all of the following:

(1) that the contracted or purchased services or products comply with the applicable requirements;

(2) that any aviation safety hazards associated with contracted or purchased services or products are considered by the operator's management system.

(b) When the certified operator or the SPO authorisation holder contracts any part of its activity to an organisation that is not itself certified or authorised in accordance with this Part to carry out such activity, the contracted organisation shall work under the approval of the operator. The contracting organisation shall ensure that the competent authority is given access to the contracted organisation, to determine continued compliance with the applicable requirements.

AMC1 ORO.GEN.205 Contracted activities

RESPONSIBILITY WHEN CONTRACTING ACTIVITIES

(a) The operator may decide to contract certain activities to external organisations.

(b) A written agreement should exist between the operator and the contracted organisation clearly defining the contracted activities and the applicable requirements.

(c) The contracted safety-related activities relevant to the agreement should be included in the operator's safety management and compliance monitoring programmes.

(d) The operator should ensure that the contracted organisation has the necessary authorisation or approval when required, and commands the resources and competence to undertake the task.

AMC2 ORO.GEN.205 Contracted activities

THIRD-PARTY PROVIDERS

(a) The initial audit and/or the continuous monitoring of contracted organisations may be performed by a third-party provider on behalf of the operator when it is demonstrated that:

(1) a documented arrangement has been established with the third-party provider;

(2) the audit standards applied by the third-party provider address the scope of this Regulation in sufficient detail;

(3) the third-party provider uses an evaluation system, designed to assess the operational, management and control systems of the contracted organisation;

(4) the independence of the third-party provider, its evaluation system as well as the impartiality of the auditors is ensured;

(5) the auditors are appropriately qualified and have sufficient knowledge, experience and training, including on-the-job training, to perform their allocated tasks;

(6) audits are performed on-site;

(7) access to the relevant data and facilities is granted to the level of detail necessary to verify compliance with the applicable requirements;

(8) access to the full audit report is granted;

(9) procedures have been established for monitoring continuous compliance of the contracted organisation with the applicable requirements; and

(10) procedures have been established to notify the contracted organisation of any non-compliance with the applicable requirements, the corrective actions to be taken, the follow-up of these corrective actions, and closure of findings.

(b) The use of a third-party provider for the initial audit or the monitoring of continuous compliance of the contracted organisation does not exempt the operator from its responsibility under the applicable requirements.

(c) The operator should maintain a list of the contracted organisations monitored by the third-party provider. This list and the full audit report prepared by the third-party provider should be made available to the competent authority upon request.

GM1 ORO.GEN.205 Contracted activities

CONTRACTING — GENERAL

(a) Operators may decide to contract certain activities to external organisations for the provision of services related to areas such as:

(1) ground de-icing/anti-icing;

(2) ground handling;

(3) flight support (including performance calculations, flight planning, navigation database and dispatch);

(4) training; and

(5) manual preparation.

(b) Contracted activities include all activities within the operator's scope of approval that are performed by another organisation either itself certified or authorised to carry out such activity or if not certified or authorised, working under the operator's approval.

(c) The ultimate responsibility for the product or service provided by external organisations should always remain with the operator.

GM2 ORO.GEN.205 Contracted activities

RESPONSIBILITY WHEN CONTRACTING ACTIVITIES

(a) Regardless of the approval status of the contracted organisation, the contracting operator is responsible for ensuring that all contracted activities are subject to hazard identification and risk management, as required by ORO.GEN.200 (a)(3), and to compliance monitoring, as required by ORO.GEN.200 (a)(6).

(b) When the contracted organisation is itself certified or authorised to carry out the contracted activities, the operator's compliance monitoring should at least check that the approval effectively covers the contracted activities and that it is still valid.

ORO.GEN.210 Personnel requirements

(a) The operator shall appoint an accountable manager, who has the authority for ensuring that all activities can be financed and carried out in accordance with the applicable requirements. The accountable manager shall be responsible for establishing and maintaining an effective management system.

(b) A person or group of persons shall be nominated by the operator, with the responsibility of ensuring that the operator remains in compliance with the applicable requirements. Such person(s) shall be ultimately responsible to the accountable manager.

(c) The operator shall have sufficient qualified personnel for the planned tasks and activities to be performed in accordance with the applicable requirements.

(d) The operator shall maintain appropriate experience, qualification and training records to show compliance with point (c).

(e) The operator shall ensure that all personnel are aware of the rules and procedures relevant to the exercise of their duties.

AMC1 ORO.GEN.210(a) Personnel requirements

INFORMATION ON THE ACCOUNTABLE MANAGER

As part of being granted an air operator certificate (AOC), the operator should provide the competent authority with the following detailed information regarding the accountable manager:

(a) name of the accountable manager;

(b) position within the organisation;

(c) information on means to ensure that all activities can be financed and carried out;

(d) qualification relevant to the position; and

(e) work experience relevant to the position.

GM1 ORO.GEN.210(a) Personnel requirements

FUNCTION OF THE ACCOUNTABLE MANAGER

(a) The accountable manager should have the overall responsibility for running the organisation.

(b) When the accountable manager is not the chief executive officer, the competent authority should be assured that the accountable manager has direct access to the chief executive officer and has the necessary air operations funding allocation.

AMC1 ORO.GEN.210(b).G Personnel requirements

NON-COMMERCIAL OPERATIONS WITH COMPLEX MOTOR-POWERED AIRCRAFT

An operator engaged in non-commercial operations with complex motor-powered aircraft (NCC) should comply with ORO.AOC.135.

AMC1 ORO.GEN.210(a)(b).G Personnel requirements

ACCEPTANCE OF PERSONNEL BY THE COMPETENT AUTHORITY

Except in the case of an operator exclusively engaged in non-commercial specialised operations with complex motor-powered aircraft, operator personnel for the following positions should be accepted by the competent authority:

(a) Accountable Manager;

(b) Personnel responsible for the following areas:

(1) flight operations;

(2) crew member training;

(3) ground operations;

(4) continuing airworthiness or for the continuing airworthiness management contract;

(c) Safety Manager/Focal;

(d) Compliance Monitoring Manager/Focal; and

(e) Cabin Crew Manager/Focal – For AOC holders those required to carry cabin crew.

ORO.GEN.215 Facility requirements

The operator shall have facilities allowing the performance and management of all planned tasks and activities in accordance with the applicable requirements.

ORO.GEN.220 Record-keeping

(a) The operator shall establish a system of record–keeping that allows adequate storage and reliable traceability of all activities developed, covering in particular all the elements indicated in ORO.GEN.200.

(b) The format of the records shall be specified in the operator's procedures.

(c) Records shall be stored in a manner that ensures protection from damage, alteration and theft.

AMC1 ORO.GEN.220(b) Record-keeping

GENERAL

(a) The record-keeping system should ensure that all records are accessible whenever needed within a reasonable time. These records should be organised in a way that ensures traceability and retrievability throughout the required retention period.

(b) Records should be kept in paper form or in electronic format or a combination of both. Records stored on microfilm or optical disc format are also acceptable. The records should remain legible throughout the required retention period. The retention period starts when the record has been created or last amended.

(c) Paper systems should use robust material which can withstand normal handling and filing. Computer systems should have at least one backup system which should be updated within 24 hours of any new entry. Computer systems should include safeguards against the ability of unauthorised personnel to alter the data.

(d) All computer hardware used to ensure data backup should be stored in a different location from

that containing the working data and in an environment that ensures they remain in good condition. When hardware or software changes take place, special care should be taken that all necessary data continues to be accessible at least through the full period specified in the relevant subpart. In the absence of such indication, all records should be kept for a minimum period of 5 years.

GM1 ORO.GEN.220(b) Record-keeping

RECORDS

Microfilming or optical storage of records may be carried out at any time. The records should be as legible as the original record and remain so for the required retention period.

Section 3 — Additional organisational requirements

ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations

(a) Aircraft listed on an operator's AOC may remain on the AOC if it is operated in any of the following situations:

(1) by the AOC holder itself, for specialised operations in accordance with Part-SPO;

(2) by other operators, for non-commercial operations with motor-powered aircraft or for specialised operations performed in accordance with Part-NCC, Part-NCO or Part-SPO, provided that the aircraft is used for a continuous period not exceeding 30 days.

(b) When the aircraft is used in accordance with point (a)(2), the AOC holder providing the aircraft and the operator using the aircraft shall establish a procedure:

(1) clearly identifying which operator is responsible for the operational control of each flight and to describe how the operational control is transferred between them;

(2) describing the handover procedure of the aircraft upon its return to the AOC holder.

That procedure shall be included in the operations manual of each operator or in a contract between the AOC holder and the operator using the aircraft in accordance with point (a)(2). The AOC holder shall establish a template of such contract. Point ORO.GEN.220 shall apply to the record-keeping of those contracts.

The AOC holder and the operator using the aircraft in accordance with point (a)(2) shall ensure that the procedure is communicated to the relevant personnel.

(c) The AOC holder shall submit to the competent authority the procedure referred to in point (b) for prior approval.

The AOC holder shall agree with the competent authority on the means and on the frequency of providing it with information about transfers of operational control in accordance with point ORO.GEN.130(c).

(d) The continuing airworthiness of the aircraft used in accordance with point (a) shall be managed by the organisation responsible for the continuing airworthiness of the aircraft included in the AOC, in accordance with CAR PART V.

(e) The AOC holder providing the aircraft in accordance with point (a) shall:

(1) indicate in its operations manual the registration marks of the provided aircraft and the type of operations conducted with those aircraft;

(2) remain informed at all times and keep record of each operator that holds the operational control of the aircraft at any given moment until the aircraft is returned to the AOC holder;

(3) ensure that its hazard identification, risk assessment and mitigation measures address all the operations conducted with those aircraft.

(f) For operations under Part-NCC and Part-SPO, the operator using the aircraft in accordance with point (a) shall ensure all of the following:

(1) that every flight conducted under its operational control is recorded in the aircraft technical log system;

(2) that no changes to the aircraft systems or configuration are made;

(3) that any defect or technical malfunction occurring while the aircraft is under its operational control is reported to the organisation referred to in point (d);

(4) that the AOC holder receives a copy of any occurrence report related to the flights performed with the aircraft, completed in accordance with CAR Part X and AMC-22.

GM1 ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations

EXAMPLES OF POSSIBLE SCENARIOS FOR THE USE OF AIRCRAFT LISTED ON AN AOC

'Aircraft listed on an AOC' means any aircraft included in the AOC certification process, to which the privileges of the AOC apply. The registration marks of these aircraft are indicated either in the operations specifications form or in the operations manual of the AOC holder.

The following examples provide possible scenarios with organisations and operators to which this rule applies:

(a) The same AOC holder providing the aircraft, using the aircraft either:

(1) as a declared operator for SPO (commercial or non-commercial, including high-risk SPO) in accordance with Part-ORO and Part-SPO for operations with complex motor-powered aircraft. In such a case, the provisions of Part-SPO and Part-ORO apply. This implies that the operator submits a declaration for its SPO activities and applies for an authorisation if it performs high-risk SPO; or

(2) as a training organisation (approved training organisation (ATO) or declared training organisation (DTO)) for operations performed in accordance with Part-NCC or Part-NCO.

(b) Another AOC holder:

(1) as a declared operator, using complex motor-powered aircraft for NCC operations in accordance with Part-ORO and Part-NCC or for SPO activities (commercial or non-commercial), including high-risk SPO in accordance with Part-ORO and Part-SPO;

(2) as a training organisation (ATO or DTO), using the aircraft for operations performed in accordance with Part-NCC or Part-NCO; or

(3) using other than complex motor-powered aircraft for NCO operations.

(c) An NCC operator or a SPO operator, for operations performed in accordance with Part-ORO and Part-NCC or in accordance with Part-ORO and Part-SPO (commercial or non-commercial), including high-risk SPO.

(d) An NCO operator or a SPO operator conducting non-commercial operations with other than complex motor-powered aircraft in accordance with Part-NCO.

(e) A training organisation (ATO or DTO), commercial or non-commercial, conducting operations in accordance with Part-NCC or Part-NCO.

GM2 ORO.GEN.310 Use of aircraft listed on an AOC for non-commercial operations and specialised operations

SPECIFIC APPROVALS

(a) Specific approvals (SPA) of the AOC holder using its aircraft for non-commercial operations and specialised operations

(1) When the AOC holder performs operations in accordance with Part-NCC or Part-NCO, the SPA granted for the AOC extend over these operations, as in such cases the provisions of ORO.AOC.125 apply.

(2) When the AOC holder performs operations in accordance with Part-SPO, as a declared operator, either:

(i) the SPA applicable to its SPO activities for the same aircraft are already granted within its AOC. In this case, the operator does not need to apply for them again; or

(ii) the SPA applicable to its SPO activities for the same aircraft are partially different from the SPA already granted within its AOC. In this case, the specific approval will cover all the different aspects involved in SPO operation or training of relevant personnel; or

(iii) the SPA are not granted within its AOC. In this case, the operator applies for the relevant SPA to its competent authority, in accordance with Part-SPA. This means that all the elements required for a SPA will be provided to the competent authority: evidence of the relevant airworthiness approval, specific equipment approval, operational procedures, and training programme specific for each of the SPA applied for.

(b) SPA of any other operator, regardless of whether it also holds an AOC, using the aircraft as a declared operator or as a(n) ATO/DTO. The declared operator performing NCC operations or SPO or the ATO/DTO has to comply with Part-SPA and apply for the SPA required for the type of operation it intends to conduct with that aircraft.

MINIMUM EQUIPMENT LIST (MEL)

The operator that uses the aircraft listed on the AOC of another operator is still responsible for obtaining the approval of the MEL for its own operations, to cover all the aircraft that it operates.

GM1 ORO.GEN.310(a)(2) Use of aircraft listed on an AOC for non-commercial operations and specialised operations

EXCEEDING 30 DAYS OF CONTINUOUS OPERATION

When the other operator uses or intends to use the aircraft without returning it to the AOC holder for a duration that exceeds 30 days, then the provisions of ORO.GEN.310 no longer apply; instead, the provisions of ORO.AOC.110 apply and the AOC holder has to remove that aircraft from its AOC.

AMC1 ORO.GEN.310(b);(e) Use of aircraft listed on an AOC for non-commercial operations and specialised operations

RESPONSIBILITIES OF THE AOC HOLDER

(a) The AOC holder providing the aircraft should include the following information in the respective parts of its operations manual:

(1) how the relevant personnel are informed about which of the operators is responsible for the operational control of each flight;

(2) when possible, which of the aircraft are used by the AOC holder itself, when conducting operations as a different operator (SPO operator, ATO or DTO), or by other operators;

(3) when possible, the name of the other operators using the aircraft for operations performed in accordance with ORO.GEN.310;

(4) when possible, the frequency with which the aircraft is used by the other operators;

(5) the means of instructing the relevant personnel on the continuing airworthiness procedure covering the use of the aircraft by other operators; and

(6) a customised list of occurrences that the other operators have to report to the AOC holder when using the aircraft in accordance with ORO.GEN.310. This list may be adjusted to fit the aircraft used by the other operators, as well as the type of operation for which it is used. The AOC holder should communicate this list to the other operators.

(b) The AOC holder should ensure that the operations specifications form of the respective aircraft is not carried on board when that aircraft is used by other operators for their NCC, NCO or SPO operations.

GM1 ORO.GEN.310(d) Use of aircraft listed on an AOC for non-commercial operations and specialised operations

CONTINUING AIRWORTHINESS MANAGEMENT

In accordance with CAR-M and CAR-ML, the management of the continuing airworthiness of the aircraft by the continuing airworthiness management organisation (CAMO) or the combined airworthiness organisation (CAO) of the AOC holder means that the other operator has established a written contract as per CAR-M or CAR-ML with this CAMO or CAO.

AMC1 ORO.GEN.310(b);(d);(f) Use of aircraft listed on an AOC for non-commercial operations and specialised operations

RESPONSIBILITIES OF THE OTHER OPERATOR

The other operator using the aircraft listed on an AOC for operations under ORO.GEN.310 should include the following elements in its procedure:

(a) a description of the way in which the shifting of operational control is communicated, including how, when and to whom the information is communicated;

(b) a description of the specific responsibilities resulting from having the operational control of the flight performed with the aircraft listed on the AOC;

(c) a description of the means to ensure that the relevant personnel are instructed to:

(1) contact the organisation responsible for the management of continuing airworthiness of the aircraft of the AOC holder (CAMO or CAO) for any defect or technical malfunction which occurs before or during the operation. The information about any defect or malfunction should be transmitted to the CAMO or CAO of the AOC holder before the aircraft is used for the next flight. The same information should be confirmed by the entries in the aircraft technical log system; and

(2) report any occurrence in accordance with the applicable rules and the internal procedures; and

(d) a customised list of occurrences, as developed by the AOC holder, which the other operator should use when informing the AOC holder of any safety-relevant issue or event that occurred while the aircraft was under its operational control.

SUBPART AOC — AIR OPERATOR CERTIFICATION

ORO.AOC.100 Application for an air operator certificate

(a) Prior to commencing commercial air transport operations, the operator shall apply for and obtain an air operator certificate (AOC) issued by the competent authority.

(b) The operator shall provide the following information to the competent authority:

(1) the official name and business name, address, and mailing address of the applicant;

(2) a description of the proposed operation, including the type(s), and number of aircraft to be operated;

(3) a description of the management system, including organisational structure;

(4) the name of the accountable manager;

(5) the names of the nominated persons required by ORO.AOC.135(a) together with their qualifications and experience;

(6) a copy of the operations manual required by ORO.MLR.100;

(7) a statement that all the documentation sent to the competent authority have been verified by the applicant and found in compliance with the applicable requirements.

(c) Applicants shall demonstrate to the competent authority that:

(1) they comply with all the requirements of Annex V to CAR-BR, this Part, Part-CAT and Part-SPA to this Regulation and the applicable Airworthiness Regulation.

(2) all aircraft operated have a certificate of airworthiness (CofA) in accordance with CAR 21 or are dry leased in accordance with ORO.AOC.110 (d); and

(3) its organisation and management are suitable and properly matched to the scale and scope of the operation.

AMC1 ORO.AOC.100 Application for an air operator certificate

APPLICATION TIME FRAMES

The application for the initial issue of an AOC should be submitted at least 90 days before the intended start date of operation. The operations manual may be submitted later, but in any case not later than 60 days before the intended start date of operation.

GM1 ORO.AOC.100.G Application for an air operator certificate

Refer to AMC-08 for further guidance.

AMC1 ORO.AOC.100(a) Application for an air operator certificate

OPERATOR SECURITY PROGRAMME

In accordance with CAR PART VII - Aviation Security, as part of granting the AOC, the CAT operator should provide the competent authority with the operator's security programme, including security training. The security programme should be adapted to the type and area of operation, as well as to the aircraft operated.

GM1 ORO.AOC.100(c) Application for an air operator certificate

MEANING OF CERTIFICATE OF AIRWORTHINESS

A certificate of airworthiness means either a certificate of airworthiness or a restricted certificate of airworthiness issued in accordance with applicable Airworthiness Regulations.

ORO.AOC.105 Operations specifications and privileges of an AOC holder

The privileges of the operator, including those granted in accordance with Part-SPA, shall be specified in the operations specifications of the certificate.

ORO.AOC.110 Leasing agreement

Any lease-in

(a) Any lease agreement concerning aircraft used by an operator certified in accordance with this Part shall be subject to prior approval by the competent authority.

(b) The operator certified in accordance with this Part shall not lease-in aircraft included in the list of operators subject to operational restrictions, registered in a State of which all operators under its oversight are subject to an operating ban or from an operator that is subject to an operating ban pursuant to CAR-FOR.

Wet lease-in

(c) The applicant for the approval of the wet lease-in of an aircraft from a foreign operator shall demonstrate to the competent authority all of the following:

(1) that the foreign operator holds a valid AOC issued in accordance with Annex 6 to the Convention on International Civil Aviation;

(2) that the safety standards of the foreign operator with regard to continuing airworthiness and air operations are equivalent to the applicable requirements established by CAR M and this Regulation;

(3) that the aircraft has a standard CofA issued in accordance with Annex 8 to the Convention on International Civil Aviation.

Dry lease-in

(d) An applicant for the approval of the dry lease-in of an aircraft registered in another State shall demonstrate to the competent authority that:

(1) an operational need has been identified that cannot be satisfied through leasing an aircraft registered in the UAE;

(2) the duration of the dry lease-in does not exceed seven months in any 12 consecutive month period;

(3) compliance with the applicable requirements of CAR-M is ensured; and

(4) the aircraft is equipped in accordance with the UAE regulations for Air Operations.

Dry lease-out

(e) The operator certified in accordance with this Part intending to dry lease-out one of its aircraft shall apply for prior approval by the competent authority. The application shall be accompanied by copies of the intended lease agreement or description of the lease provisions, except financial arrangements, and all other relevant documentation.

Wet lease-out

(f) Prior to the wet lease-out of an aircraft, the operator certified in accordance with this Part shall notify the competent authority.

AMC1 ORO.AOC.110 Leasing agreement

GENERAL

(a) The operator intending to lease-in an aircraft should provide the competent authority with the following information:

(1) the aircraft type, registration markings and serial number, as soon as available;

(2) the name and address of the registered owner;

(3) a copy of the valid certificate of airworthiness;

(4) a copy of the lease agreement or description of the lease provisions, except financial arrangements; and

(5) duration of the lease;

(b) In case of wet lease-in, a copy of the AOC of the non-UAE operator and the areas of operation.

(c) The information mentioned above should be accompanied by a statement signed by the lessee that the parties to the lease agreement fully understand their respective responsibilities under the applicable regulations.

GM1 ORO.AOC.110.G Leasing agreement

TERMINOLOGY

(a) 'Dry leased aircraft' is an aircraft that is leased without cockpit or cabin crew.

(b) 'Wet leased aircraft' is an aircraft that is leased with cockpit and cabin crew.

(c) 'Damp lease' is a wet lease that includes cockpit crew but not cabin crew.

AMC1 ORO.AOC.110(c) Leasing agreement

WET LEASE-IN AGREEMENT WITH A FOREIGN OPERATOR

If the operator is not intending to apply UAE safety requirements for air operations and continuing airworthiness when wet leasing-in an aircraft registered in another State, it should demonstrate to the competent authority that the standards complied with are equivalent to the following requirements:

(a) Part-CAT;

(b) Part-ORO:

(1) ORO.GEN.110 and Section 2 of Subpart GEN;

(2) ORO.MLR, excluding ORO.MLR.105;

(3) ORO.FC;

(4) ORO.CC, excluding ORO.CC.200 and ORO.CC.210(a);

(5) ORO.TC;

(6) ORO.FTL; and

(7) ORO.SEC;

(c) Part-SPA, if applicable;

(d) for continuing airworthiness management of the foreign operator, CAR-M Subpart-B, Subpart-C and Subpart-G, excluding M.A.707, and M.A.710;

(e) for the maintenance organisation used by the foreign operator during the lease period:CAR-145;

(f) retroactive airworthiness requirements in accordance with CAR-26; and

(g) the operator should provide the competent authority with a full description of the flight time limitation scheme(s), operating procedures and safety assessment demonstrating compliance with the safety objectives set out in points (b)(1)-(6).

AMC2 ORO.AOC.110(c) Leasing agreement

WET LEASE-IN

The lessee should maintain a record of occasions when lessors are used, for inspection by the State that issued its AOC.

GM1 ORO.AOC.110(c) Leasing agreement

SHORT-TERM WET LEASE-IN WITH A FOREIGN OPERATOR

In anticipation of an operational need the operator may enter into a framework agreement with more than one foreign operator provided that these operators comply with ORO.AOC.110 (c). These foreign operators should be placed in a list maintained by the lessee.

AMC1 ORO.AOC.110(f) Leasing agreement

WET LEASE-OUT

When notifying the competent authority, the operator intending to wet lease-out an aircraft should provide the competent authority with the following information:

(a) the aircraft type, registration markings and serial number;

(b) the name and address of the lessee;

(c) a copy of the lease agreement or description of the lease provisions, except financial arrangements; and

(d) the duration of the lease agreement

ORO.AOC.115 Code-share agreements

(a) Without prejudice to applicable UAE safety requirements for foreign operators and aircraft, an operator certified in accordance with this Part shall enter into a code-share agreement with a foreign operator only after:

(1) having verified that the foreign operator complies with the applicable ICAO standards; and

(2) having provided the competent authority with the applicable documented information.

(b) When implementing the code-share agreement the operator shall monitor and regularly assess the ongoing compliance of the foreign operator with the applicable ICAO standards.

(c) The operator certified in accordance with this Part shall not sell and issue tickets for a flight operated by a foreign operator when the foreign operator is subject to an operating ban pursuant to CAR-FOR or is failing to maintain compliance with the applicable ICAO standards.

AMC1 ORO.AOC.115(a)(1) Code share agreements

INITIAL VERIFICATION OF COMPLIANCE

(a) In order to verify the foreign operator's compliance with the applicable ICAO standards, in particular ICAO Annexes 1, 2, 6, Part I and III, as applicable, 8, 18 and 19, the UAE operator should conduct an audit of the foreign operator, including interviews of personnel and inspections carried out at the foreign operator's facilities.

(b) The audit should focus on the operational, management and control systems of the operator.

GM1 ORO.AOC.115(a)(2).G Code share agreements

DOCUMENTED INFORMATION

For the purpose of evaluation by the competent authority, as a minimum, the UAE operator should submit the following to the competent authority:

(a) A document verifying that the foreign operator complies with the applicable ICAO standards;

(b) An audit compliance statement to demonstrate that the foreign operator meets all the applicable safety standards following the closure of all findings identified during the audit conducted by the UAE operator; and

(c) A declaration that the UAE operator:

(1) has established a code-share audit programme for monitoring continuous compliance of the foreign country operator with the applicable ICAO standards; and

(2) will not sell and issue tickets for a flight operated by the foreign operator when it is subject to an operating ban pursuant to CAR-FOR or is failing to maintain compliance with the applicable ICAO standards.

AMC1 ORO.AOC.115(b) Code-share arrangements

CODE-SHARE AUDIT PROGRAMME

(a) Operators should establish a code-share audit programme for monitoring continuous compliance of the foreign operator with the applicable ICAO standards. Such a code-share audit programme should include:

(1) the audit methodology (audit report and compliance statements);

(2) details of the specific operational areas to audit;

(3) criteria for defining satisfactory audit results;

(4) a system for reporting and correcting findings;

(5) a continuous monitoring system;

(6) auditor qualification and authorisation; and

(7) the frequency of audits.

(b) The foreign code-share operator should be audited at periods not exceeding 24 months. The beginning of the first 24-month oversight planning cycle is determined by the date of the first audit and should then determine the start and end dates of the recurrent 24-month planning cycle. The interval between two audits should not exceed 24 months.

(c) The UAE operator should ensure a renewal audit of each foreign code-share operator prior to the audit expiry date of the previous audit. The audit expiry date for the previous audit becomes the audit effective date for the renewal audit provided the closing meeting for the renewal audit is within 150 days prior to the audit expiry date for the previous audit. If the closing meeting for the renewal audit is more than 150 days prior to the audit expiry date from the previous audit, then the audit effective date for the renewal audit is the day of the closing meeting of the renewal audit. Renewal audits are valid for 24 consecutive months beginning with the audit effective date and ending with the audit expiry date.

(d) A code-share audit could be shared by several operators. In case of a shared audit, the report should be made available for review by all duly identified sharing operators by any means.

(e) After closure of all findings identified during the audit, the UAE operator should submit an audit compliance statement to the competent authority demonstrating that the foreign operator meets all the applicable safety standards.

AMC2 ORO.AOC.115(b) Code-share agreements

THIRD-PARTY PROVIDERS

(a) The initial audit and/or the continuous monitoring may be performed by a third party provider on behalf of the UAE operator in accordance with AMC2 ORO.GEN.205 on contracted activities.

(b) The use of a third-party provider for the initial audit or the monitoring of continuous compliance of the foreign code-share operator does not exempt the UAE operator from its responsibility under ORO.AOC.115.

(c) The UAE operator should maintain a list of the foreign code-share operators monitored by the third-party provider. This list and the full audit report prepared by the third-party provider should be made available to the competent authority upon request.

ORO.AOC.120 Approvals to provide cabin crew training and to issue cabin crew attestations

(a) When intending to provide the training course required in CAR-CC, the operator shall apply for and obtain an approval issued by the competent authority. For this purpose, the applicant shall demonstrate compliance with the requirements for the conduct and content of training course established in CC.TRA.215 and CC.TRA.220 of that CAR and shall provide the competent authority with:

(1) the date of intended commencement of activity;

(2) the personal details and qualifications of the instructors as relevant to the training elements to be covered;

(3) the name(s) and address(es) of the training site(s) at which the training is to be conducted;

(4) a description of the facilities, training methods, manuals and representative devices to be used; and

(5) the syllabi and associated programmes for the training course.

(b) If the competent authority decides, in accordance with CAR-PART II, that operators may be approved to issue cabin crew attestations, the applicant shall, in addition to (a):

(1) demonstrate to the competent authority that:

(i) the organisation has the capability and accountability to perform this task;

(ii) the personnel conducting examinations are appropriately qualified and free from conflict of interest; and

(2) provide the procedures and the specified conditions for:

(i) conducting the examination required by CC.TRA.220;

(ii) issuing cabin crew attestations; and

(iii) supplying the competent authority with all relevant information and documentation related to the attestations it will issue and their holders, for the purpose of record-keeping, oversight and enforcement actions by that authority.

(c) The approvals referred to in (a) and (b) shall be specified in the operations specifications.

ORO.AOC.125 Non-commercial operations of aircraft listed in the operations specifications by the holder of an AOC

(a) The AOC holder may conduct non-commercial operations in accordance with Part-NCC or Part-NCO with aircraft listed in the operations specifications of its AOC or in its operations manual, provided that the AOC holder describes such operations in detail in the operations manual, including the following:

(1) an identification of the applicable requirements;

(2) a description of any differences between operating procedures used when conducting CAT operations and non-commercial operations;

(3) means of ensuring that all personnel involved in the operations are fully familiar with the associated procedures;

(b) An AOC holder shall comply with:

(1) Part-SPO when conducting maintenance check flights with complex motor-powered aircraft;

(2) Part-NCO when conducting maintenance check flights with other than complex motor-powered aircraft.

(c) An AOC holder conducting operations referred to in points (a) and (b) shall not be required to submit a declaration in accordance with this Part.

(d) The AOC holder shall specify the type of flight, as listed in its operations manual, in the flight-related documents (operational flight plan, loadsheet and other equivalent documents).

AMC1 ORO.AOC.125(a) Non-commercial operations of an AOC holder with aircraft listed on its AOC

FLIGHT AND DUTY TIME LIMITATIONS AND REST REQUIREMENTS

When aircrew members are assigned to perform a series of flights that combine several types of operation (CAT, NCC/NCO), the operator should:

(a) comply at any time with the provisions for cumulative flight times and duty periods for any CAT operation; and
(b) include any combination of types of operation in its safety risk management process to ensure that the fatigue risks arising from such operations do not affect the CAT operation.

AMC2 ORO.AOC.125(a) Non-commercial operations of an AOC holder with aircraft listed on its AOC

APPLICABLE REQUIREMENTS

An AOC holder should apply either of the options below to its non-commercial operations:

(a) the same operational procedures as those used for its CAT operations. In this case, the AOC holder should state this option in the operations manual and ensure that the procedures comply with Part-CAT. No further descriptions are required; or

(b) different operational procedures from those used for its CAT operations. In this case, the procedures should comply with Part-ORO, except for Subpart-DEC, and Part-NCC for complex motor-powered aircraft or with Part-NCO for other than complex motor-powered aircraft, as appropriate.

AMC1 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC

DIFFERENT OPERATING PROCEDURES FOR NON-COMMERCIAL OPERATIONS

When developing operating procedures for non-commercial operations that are different from the ones used for its CAT operations, the AOC holder should identify the hazards and assess and mitigate the risks associated with each specific non-commercial operation, as part of the safety risk management process in compliance with ORO.GEN.200.

This process should consider at least the following elements:

(a) Flight profile (including manoeuvres to be performed, any simulated abnormal situations in flight, duties and responsibilities of the crew members);

(b) Continuing airworthiness, as applicable. This includes the case when the aircraft is returned to the AOC holder after having been used by another operator for operations in accordance with ORO.GEN.310;

(c) Levels of functional equipment and systems (MEL, CDL);

(d) Operating procedures, minima, and dispatch criteria;

(e) Operating a flight with a double purpose (e.g. a relocation flight used as a line training flight or a maintenance check flight used as a line training flight);

(f) Specific approvals held by the AOC holder;

(g) Flight and duty time limitations and rest requirements and cumulative fatigue;

(h) Selection, composition, and training of flight crew and cabin crew;

(i) Multi-pilot operation as per Part-CAT vs. single-pilot operation when operating according to Part-NCC or Part-NCO;

(j) Flights performed with aircrew that includes aircrew members of another operator, who have not completed a familiarisation training and who may not be familiar with the AOC holder's operational procedures;

(k) Categories of passengers on board, including when non-commercial operations are performed with no cabin crew.

AMC2 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC

PLANNING FLIGHTS WITH AN INCREASED LEVEL OF RISK

(a) Significant aspects such as the ones below should be addressed in the risk assessment and risk mitigation process by any operator conducting such flights:

(1) which pilots are involved in their operation;

(2) what is the purpose of the flight; and

(3) how it is to be accomplished — what flight procedures are to be applied.

(b) The AOC holder should prepare the non-commercial operations with an increased level of risk taking into consideration the following elements, as applicable:

(1) pre-flight briefing;

(2) duties and responsibilities of the flight crew members involved, task sharing;

(3) special operating procedures;

(4) manoeuvres to be performed in flight, minimum and maximum speeds and altitudes for all portions of the flight;

(5) operational limitations;

(6) potential risks and contingency plans;

(7) adequate available airspace and coordination with the air traffic control (ATC);

(8) selection of flight crew members; and

(9) additional flight crew training at regular intervals to ensure recency (considering also a flight of a similar risk profile in the simulator, if needed).

GM1 ORO.AOC.125(a)(2) Non-commercial operations of an AOC holder with aircraft listed on its AOC

EXAMPLES OF DIFFERENT OPERATING PROCEDURES APPLIED TO NON-COMMERCIAL OPERATIONS

The provisions of ORO.AOC.125 enable an AOC holder to apply the most appropriate requirements when conducting non-commercial operations, based on the risk assessment and risk mitigation processes. Below is a non-exhaustive list of elements that an AOC holder may identify and describe as being different in its non-commercial operations from those used for its CAT operation and for which the provisions of Part-ORO and Part-NCC or the provisions of Part-NCO should apply as appropriate:

(a) Qualification, training and experience of aircrew members, including aerodrome and route competence requirements.

(b) Flight crew and cabin crew composition requirements

(1) CAT operations contain more stringent requirements for aircrew members, e.g. multi-pilot vs. single-pilot requirements.

(2) The AOC holder should specify the minimum number of flight crew and cabin crew and the applicable aircrew composition.

(c) Fuel requirements

(d) Performance requirements

(e) Serviceable instruments, data and equipment and MEL considerations

(f) Non-ETOPS/ETOPS

ETOPS are applicable to CAT operations only and thus a flight operated according to Part NCC/Part-NCO may be performed without the ETOPS restrictions.

(g) Non-commercial flights with no cabin crew (see ORO.CC.100(d) and the associated AMC).

ORO.AOC.130 Flight data monitoring — aeroplanes

(a) The operator shall establish and maintain a flight data monitoring programme, which shall be integrated in its management system, for aeroplanes with a maximum certificated take-off mass of more than 27 000 kg.

(b) The flight data monitoring programme shall be non-punitive and contain adequate safeguards to protect the source(s) of the data.

AMC1 ORO.AOC.130 Flight data monitoring — aeroplanes

FLIGHT DATA MONITORING (FDM) PROGRAMME

(a) The safety manager, as defined under AMC1 ORO.GEN.200(a)(1), should be responsible for the identification and assessment of issues and their transmission to the manager(s) responsible for the process(es) concerned. The latter should be responsible for taking appropriate and practicable safety action within a reasonable period of time that reflects the severity of the issue.

(b) An FDM programme should allow an operator to:

(1) identify areas of operational risk and quantify current safety margins;

(2) identify and quantify operational risks by highlighting occurrences of non-standard, unusual or unsafe circumstances;

(3) use the FDM information on the frequency of such occurrences, combined with an estimation of the level of severity, to assess the safety risks and to determine which may become unacceptable if the discovered trend continues;

(4) put in place appropriate procedures for remedial action once an unacceptable risk, either actually present or predicted by trending, has been identified; and

(5) confirm the effectiveness of any remedial action by continued monitoring.

(c) FDM analysis techniques should comprise the following:

(1) Exceedance detection: searching for deviations from aircraft flight manual limits and standard operating procedures. A set of core events should be selected to cover the main areas of interest to the operator and as much as possible, the most siginifcant risks identified by the operator. The event definitions should be continuously reviewed to reflect the operator's current operating procedures.

(2) All flights measurement: a system defining what is normal practice. This may be accomplished by retaining various snapshots of information from each flight.

(3) Statistics — a series of data collected to support the analysis process: this technique should include the number of flights flown per aircraft and sector details sufficient to generate rate

and trend information.

(d) FDM analysis, assessment and process control tools: the effective assessment of information obtained from digital flight data should be dependent on the provision of appropriate information technology tool sets.

(e) Education and publication: sharing safety information should be a fundamental principle of aviation safety in helping to reduce accident rates. The operator should pass on the lessons learnt to all relevant personnel and, where appropriate, industry.

(f) Accident and incident data requirements specified in CAT.GEN.MPA.195 take precedence over the requirements of an FDM programme. In these cases the FDR data should be retained as part of the investigation data and may fall outside the de-identification agreements.

(g) Every crew member should be responsible for reporting events. Significant risk-bearing incidents detected by FDM should therefore normally be the subject of mandatory occurrence reporting by the crew. If this is not the case, then they should submit a retrospective report that should be included under the normal process for reporting and analysing hazards, incidents and accidents.

(h) The data recovery strategy should ensure a sufficiently representative capture of flight information to maintain an overview of operations. Data analysis should be performed sufficiently frequently to enable action to be taken on significant safety issues.

(i) The data retention strategy should aim at providing the greatest safety benefits practicable from the available data. A full dataset should be retained until the action and review processes are complete; thereafter, a reduced dataset relating to closed issues should be maintained for longer-term trend analysis. Programme managers may wish to retain samples of de-identified full-flight data for various safety purposes (detailed analysis, training, benchmarking, etc.).

(j) The data access and security policy should restrict information access to authorised persons. When data access is required for airworthiness and maintenance purposes, a procedure should be in place to prevent disclosure of crew identity.

(k) The procedure to prevent disclosure of crew identity should be written in a document, which should be available to all concerned parties (e.g. airline management, flight crew members, etc.). This procedure should, as a minimum, define:

(1) the aim of the FDM programme;

(2) a data access and security policy that should restrict access to information to specifically authorised persons identified by their position;

(3) the method to obtain de-identified crew feedback on those occasions that require specific flight follow-up for contextual information; where such crew contact is required the authorised person(s) need not necessarily be the programme manager or safety manager, but could be a third party (broker) mutually acceptable to the concerned staff and management;

(4) the data retention policy and accountability, including the measures taken to ensure the security of the data;

(5) the conditions under which advisory briefing or remedial training should take place; this should always be carried out in a constructive and non-punitive manner;

(6) the conditions under which the confidentiality may be withdrawn for reasons of gross negligence or significant continuing safety concern;

(7) the participation of flight crew member representative(s) in the assessment of the data, the action and review process and the consideration of recommendations; and

(8) the policy for publishing the findings resulting from FDM.

(l) Airborne systems and equipment used to obtain FDM data should range from a quick access recorder (QAR) in an aircraft with digital systems, to a crash-protected flight recorder in an older or less sophisticated aircraft. The analysis potential of the reduced data set available in the latter case may reduce the safety benefits obtainable. The operator should ensure that FDM use does not adversely affect the serviceability of equipment required for accident investigation.

GM1 ORO.AOC.130 Flight data monitoring — aeroplanes

IMPLEMENTATION OF AN FDM PROGRAMME

Flight data monitoring is defined in Part DEF to this Regulation. It should be noted that the requirement to establish a FDM programme is applicable to all individual aircraft in the scope of ORO.AOC.130, not to a subset selected by the operator.

(a) FDM analysis techniques and data utilisation

(1) Exceedance detection

(i) FDM programmes are used for detecting exceedances, such as deviations from flight manual limits, standard operating procedures (SOPs), or good airmanship. Typically, a set of core events establishes the main areas of interest that are based on a prior assessment of the most significant risks by the operator. In addition, it is advisable to consider the following risks: risk of runway excursion or abnormal runway contact at take-off or landing, risk of loss of control in flight, risk of airborne collision, and risk of collision with terrain.

Examples: low or high lift-off rotation rate, stall warning, ground proximity warning system (GPWS) warning, flap limit speed exceedance, fast approach, high or low on glideslope, heavy landing.

(ii) Trigger logic expressions may be simple exceedances such as redline values. The majority, however, are composites that define a certain flight mode, aircraft configuration or payload-related condition. Analysis software can also assign different sets of rules dependent on airport or geography. For example, noise sensitive airports may use higher than normal glideslopes on approach paths over populated areas. In addition, it might be valuable to define several levels of exceedance severity (such as low, medium and high).

(iii) Exceedance detection provides useful information, which can complement that provided in crew reports.

Examples: reduced flap landing, emergency descent, engine failure, rejected take-off, go-around, airborne collision avoidance system (ACAS) or GPWS warning, and system malfunctions.

(iv) The operator may also modify the standard set of core events to account for unique situations they regularly experience, or the SOPs they use.

Example: to avoid nuisance exceedance reports from a non-standard instrument departure.

(v) The operator may also define new events to address specific problem areas.

Example: restrictions on the use of certain flap settings to increase component life.

(2) All-flights measurements

FDM data are retained from all flights, not just the ones producing significant events. A selection of parameters is retained that is sufficient to characterise each flight and allow a comparative analysis of a wide range of operational variability. Emerging trends and tendencies may be identified and monitored before the trigger levels associated with exceedances are reached.

Examples of parameters monitored: take-off weight, flap setting, temperature, rotation and lift-off speeds versus scheduled speeds, maximum pitch rate and attitude during rotation, and gear retraction speeds, heights and times.

Examples of comparative analyses: pitch rates from high versus low take-off weights, good versus bad weather approaches, and touchdowns on short versus long runways.

(3) Statistics

Series of data are collected to support the analysis process: these usually include the numbers of flights flown per aircraft and sector details sufficient to generate rate and trend information.

(4) Investigation of incidents flight data

Recorded flight data provide valuable information for follow-up to incidents and other technical reports. They are useful in adding to the impressions and information recalled by the flight crew. They also provide an accurate indication of system status and performance, which may help in determining cause and effect relationships.

Examples of incidents where recorded data could be useful:

- high cockpit workload conditions as corroborated by such indicators as late descent, late localizer and/or glideslope interception, late landing configuration;
- unstabilised and rushed approaches, glide path excursions, etc.;
- exceedances of prescribed operating limitations (such as flap limit speeds, engine overtemperatures); and
- wake vortex encounters, turbulence encounters or other vertical accelerations.

It should be noted that recorded flight data have limitations, e.g. not all the information displayed to the flight crew is recorded, the source of recorded data may be different from the source used by a flight instrument, the sampling rate or the recording resolution of a parameter may be insufficient to capture accurate information.

(5) Continuing airworthiness

Data of all-flight measurements and exceedance detections can be utilised to assist the continuing airworthiness function. For example, engine-monitoring programmes look at measures of engine performance to determine operating efficiency and predict impending failures.

Examples of continuing airworthiness uses: engine thrust level and airframe drag measurements, avionics and other system performance monitoring, flying control performance, and brake and landing gear usage.

(b) FDM equipment

(1) General

FDM programmes generally involve systems that capture flight data, transform the data into an appropriate format for analysis, and generate reports and visualisation to assist in assessing the data. Typically, the following equipment capabilities are needed for effective FDM programmes:

(i) an on-board device to capture and record data on a wide range of in-flight parameters;

(ii) a means to transfer the data recorded on board the aircraft to a ground-based processing station;

(iii) a ground-based computer system to analyse the data, identify deviations from expected performance, generate reports to assist in interpreting the read-outs, etc.; and

(iv) optional software for a flight animation capability to integrate all data, presenting them as a simulation of in-flight conditions, thereby facilitating visualisation of actual events.

(2) Airborne equipment

(i) The flight parameters and recording capacity required for flight data recorders (FDR) to support accident investigations may be insufficient to support an effective FDM programme. Other technical solutions are available, including the following:

(A) Quick access recorders (QARs). QARs are installed in the aircraft and record flight data onto a low-cost removable medium.

(B) Some systems automatically download the recorded information via secure wireless systems when the aircraft is in the vicinity of the gate. There are also systems that enable the recorded data to be analysed on board while the aircraft is airborne.

(ii) Fleet composition, route structure and cost considerations will determine the most cost- effective method of removing the data from the aircraft.

(3) Ground replay and analysis equipment

(i) Data are downloaded from the aircraft recording device into a ground-based processing station, where the data are held securely to protect this sensitive information.

(ii) FDM programmes generate large amounts of data requiring specialised analysis software.

(iii) The analysis software checks the downloaded flight data for abnormalities.

(iv) The analysis software may include: annotated data trace displays, engineering unit listings, visualisation for the most significant incidents, access to interpretative material, links to other safety information and statistical presentations.

(c) FDM in practice

(1) FDM process

Typically, operators follow a closed-loop process in applying an FDM programme, for example:

(i) Establish a baseline: initially, operators establish a baseline of operational parameters against which changes can be detected and measured.

Examples: rate of unstable approaches or hard landings.

(ii) Highlight unusual or unsafe circumstances: the user determines when non-standard, unusual or basically unsafe circumstances occur; by comparing them to the baseline margins of safety, the changes can be quantified.

Example: increases in unstable approaches (or other unsafe events) at particular locations.

(iii) Identify unsafe trends: based on the frequency and severity of occurrence, trends are identified. Combined with an estimation of the level of severity, the risks are assessed

to determine which may become unacceptable if the trend continues.

Example: a new procedure has resulted in high rates of descent that are nearly triggering GPWS warnings.

(iv) Mitigate risks: once an unacceptable risk has been identified, appropriate risk mitigation actions are decided on and implemented.

Example: having found high rates of descent, the SOPs are changed to improve aircraft control for optimum/maximum rates of descent.

(v) Monitor effectiveness: once a remedial action has been put in place, its effectiveness is monitored, confirming that it has reduced the identified risk and that the risk has not been transferred elsewhere.

Example: confirm that other safety measures at the aerodrome with high rates of descent do not change for the worse after changes in approach procedures.

(2) Analysis and follow-up

(i) FDM data are typically compiled every month or at shorter intervals. The data are then reviewed to identify specific exceedances and emerging undesirable trends and to disseminate the information to flight crews.

(ii) If deficiencies in pilot handling technique are evident, the information is usually de-identified in order to protect the identity of the flight crew. The information on specific exceedances is passed to a person (safety manager, agreed flight crew representative, honest broker) assigned by the operator for confidential discussion with the pilot. The person assigned by the operator provides the necessary contact with the pilot in order to clarify the circumstances, obtain feedback and give advice and recommendations for appropriate action. Such appropriate action could include re-training for the pilot (carried out in a constructive and non-punitive way), revisions to manuals, changes to ATC and airport operating procedures.

(iii) Follow-up monitoring enables the effectiveness of any corrective actions to be assessed.

Flight crew feedback is essential for the identification and resolution of safety problems and could be collected through interviews, for example by asking the following:

(A) Are the desired results being achieved soon enough?

(B) Have the problems really been corrected, or just relocated to another part of the system?

(C) Have new problems been introduced?

(iv) All events are usually archived in a database. The database is used to sort, validate and display the data in easy-to-understand management reports. Over time, this archived data can provide a picture of emerging trends and hazards that would otherwise go unnoticed.

(v) Lessons learnt from the FDM programme may warrant inclusion in the operator's safety promotion programmes. Safety promotion media may include newsletters, flight safety magazines, highlighting examples in training and simulator exercises, periodic reports to industry and the competent authority. Care is required, however, to ensure that any information acquired through FDM is de-identified before using it in any training or promotional initiative.

(vi) All successes and failures are recorded, comparing planned programme objectives with expected results. This provides a basis for review of the FDM programme and the foundation for future programme development.

(d) Preconditions for an effective FDM programme

(1) Protection of FDM data

The integrity of FDM programmes rests upon protection of the FDM data. Any disclosure for purposes other than safety management can compromise the voluntary provision of safety data, thereby compromising flight safety.

(2) Essential trust

The trust established between management and flight crew is the foundation for a successful FDM programme. This trust can be facilitated by:

(i) early participation of the flight crew representatives in the design, implementation and operation of the FDM programme;

(ii) a formal agreement between management and flight crew, identifying the procedures for the use and protection of data; and

(iii) data security, optimised by:

(A) adhering to the agreement;

(B) the operator strictly limiting data access to selected individuals;

(C) maintaining tight control to ensure that identifying data is kept securely; and

(D) ensuring that operational problems are promptly addressed by management.

(3) Requisite safety culture

Indicators of an effective safety culture typically include:

(i) top management's demonstrated commitment to promoting a proactive safety culture;

(ii) a non-punitive operator policy that covers the FDM programme;

(iii) FDM programme management by dedicated staff under the authority of the safety manager, with a high degree of specialisation and logistical support;

(iv) involvement of persons with appropriate expertise when identifying and assessing the risks (for example, pilots experienced on the aircraft type being analysed);

(v) monitoring fleet trends aggregated from numerous operations, not focusing only on specific events;

(vi) a well-structured system to protect the confidentiality of the data; and

(vii) an efficient communication system for disseminating hazard information (and subsequent risk assessments) internally and to other organisations to permit timely safety action.

(e) Implementing an FDM programme

(1) General considerations

(i) Typically, the following steps are necessary to implement an FDM programme:

(A) implementation of a formal agreement between management and flight crew;

(B) establishment and verification of operational and security procedures;

(C) installation of equipment;

(D) selection and training of dedicated and experienced staff to operate the programme; and

(E) commencement of data analysis and validation.

(ii) An operator with no FDM experience may need a year to achieve an operational FDM programme. Another year may be necessary before any safety and cost benefits appear. Improvements in the analysis software, or the use of outside specialist service providers, may shorten these time frames.

(2) Aims and objectives of an FDM programme

(i) As with any project there is a need to define the direction and objectives of the work. A phased approach is recommended so that the foundations are in place for possible subsequent expansion into other areas. Using a building block approach will allow expansion, diversification and evolution through experience.

Example: with a modular system, begin by looking at basic safety-related issues only. Add engine health monitoring, etc. in the second phase. Ensure compatibility with other systems.

(ii) A staged set of objectives starting from the first week's replay and moving through early production reports into regular routine analysis will contribute to a sense of achievement as milestones are met.

Examples of short-term, medium-term and long-term goals:

(A) Short-term goals:

– establish data download procedures, test replay software and identify aircraft defects;

– validate and investigate exceedance data; and

– establish a user-acceptable routine report format to highlight individual exceedances and facilitate the acquisition of relevant statistics.

(B) Medium-term goals:

– produce an annual report — include key performance indicators;

– add other modules to the analysis (e.g. continuing airworthiness); and

– plan for the next fleet to be added to programme.

(C) Long-term goals:

– network FDM information across all of the operator's safety information systems;

– ensure FDM provision for any proposed alternative training and qualification programme (ATQP); and

– use utilisation and condition monitoring to reduce spares holdings.

(iii) Initially, focusing on a few known areas of interest will help prove the system's effectiveness.

In contrast to an undisciplined 'scatter-gun' approach, a focused approach is more likely to gain early success.

Examples: rushed approaches, or rough runways at particular aerodromes. Analysis of such known problem areas may generate useful information for the analysis of other areas.

(3) The FDM team

(i) Experience has shown that the 'team' necessary to run an FDM programme could vary in size from one person for a small fleet, to a dedicated section for large fleets. The descriptions below identify various functions to be fulfilled, not all of which need a dedicated position.

(A) Team leader: it is essential that the team leader earns the trust and full support of both management and flight crew. The team leader acts independently of others in line management to make recommendations that will be seen by all to have a high level of integrity and impartiality. The individual requires good analytical, presentation and management skills.

(B) Flight operations interpreter: this person is usually a current pilot (or perhaps a recently retired senior captain or instructor), who knows the operator's route network and aircraft. This team member's in-depth knowledge of SOPs, aircraft handling characteristics, aerodromes and routes is used to place the FDM data in a credible context.

(C) Technical interpreter: this person interprets FDM data with respect to the technical aspects of the aircraft operation and is familiar with the power plant, structures and systems departments' requirements for information and any other engineering monitoring programmes in use by the operator.

(D) Gate-keeper: this person provides the link between the fleet or training managers and flight crew involved in events highlighted by FDM. The position requires good people skills and a positive attitude towards safety education. The person is typically a representative of the flight crew association or an 'honest broker' and is the only person permitted to connect the identifying data with the event. It is essential that this person earns the trust of both management and flight crew.

(E) Engineering technical support: this person is usually an avionics specialist, involved in the supervision of mandatory serviceability requirements for FDR systems. This team member is knowledgeable about FDM and the associated systems needed to run the programme.

(F) Replay operative and administrator: this person is responsible for the day-to-day running of the system, producing reports and analysis.

(ii) All FDM team members need appropriate training or experience for their respective area of data analysis. Each team member is allocated a realistic amount of time to regularly spend on FDM tasks.

GM2 ORO.AOC.130 Flight data monitoring — aeroplanes

EXAMPLES OF FDM EVENTS

The following table provides examples of FDM events that may be further developed using operator and aeroplane specific limits. The table is considered illustrative and not exhaustive. Other examples may be found in the documents published by the European Operators Flight Data Monitoring (EOFDM) forum.

Event Group	Description
Rejected take-off	High speed rejected take-off

Event Group	Description
Take-off pitch	Pitch rate low or high on take-off
	Pitch attitude high during take-off
Unstick speeds	Unstick speed high
	Unstick speed low
Height loss in climb-out	Initial climb height loss 20 ft. above ground level (AGL) to 400 ft. above aerodrome level (AAL)
	Initial climb height loss 400 ft. to 1 500 ft. AAL
Slow climb-out	Excessive time to 1 000 ft. AAL after take-off
Climb-out speeds	Climb-out speed high below 400 ft. AAL
	Climb-out speed high 400 ft. AAL to 1 000 ft. AAL
	Climb-out speed low 35 ft. AGL to 400 ft. AAL
	Climb-out speed low 400 ft. AAL to 1 500 ft. AAL
High rate of descent	High rate of descent below 2 000 ft. AGL
Missed approach	Missed approach below 1 000 ft. AAL
	Missed approach above 1 000 ft. AAL
Low approach	Low on approach
Glideslope	Deviation under glideslope
	Deviation above glideslope (below 600 ft. AGL)
Approach power	Low power on approach
Approach speeds	Approach speed high within 90 seconds of touchdown
	Approach speed high below 500 ft. AAL
	Approach speed high below 50 ft. AGL
	Approach speed low within 2 minutes of touchdown
Landing flap	Late land flap (not in position below 500 ft. AAL)
	Reduced flap landing
	Flap load relief system operation
Landing pitch	Pitch attitude high on landing
	Pitch attitude low on landing
Bank angles	Excessive bank below 100 ft AGL
	Excessive bank 100 ft AGL to 500 ft AAL
	Excessive bank above 500 ft AGL
	Excessive bank near ground (below 20 ft AGL)
Normal acceleration	High normal acceleration on ground
	High normal acceleration in flight flaps up (+/- increment)
	High normal acceleration in flight flaps down(+/- increment)
	High normal acceleration at landing
Abnormal configuration	Take-off configuration warning
	Early configuration change after take-off (flap)
	Speed brake with flap
	Speed brake on approach below 800 ft AAL
	Speed brake not armed below 800 ft AAL
Ground proximity warning	Ground proximity warning system (GPWS) operation – hard warning
	GPWS operation – soft warning
	GPWS operation – windshear warning
	GPWS operation – false warning
Airborne collision avoidance system (ACAS II) warning	ACAS operation – Resolution Advisory
Margin to stall/buffet	Stick shake
	False stick shake
	Reduced lift margin except near ground
	Reduced lift margin at take-off
	Low buffet margin (above 20 000 ft)
Aircraft flight manual limitations	Maximum operating speed limit (VMO) exceedance

Event Group	Description
	Maximum operating speed limit (MMO) exceedance
	Flap placard speed exceedance
	Gear down speed exceedance
	Gear selection up/down speed exceedance
	Flap/slat altitude exceedance
	Maximum operating altitude exceedance

GM3 ORO.AOC.130 Flight data monitoring - aeroplanes

GUIDANCE AND INDUSTRY GOOD PRACTICE

(a) Additional guidance material for the establishment of flight data monitoring may be found in:

(1) International Civil Aviation Organization (ICAO) Doc 10000 'Manual on Flight Data Analysis Programmes (FDAP)'; and

(2) UK Civil Aviation Authority CAP 739 (Flight Data Monitoring), second edition dated June 2013.

(b) Examples of industry good practice for the establishment of flight data monitoring may be found in the documents published by the European Operators Flight Data Monitoring (EOFDM) forum.

ORO.AOC.135 Personnel requirements

(a) In accordance with point ORO.GEN.210 (b), the operator shall nominate persons responsible for the management and supervision of the following areas:

(1) flight operations;

(2) crew member training;

(3) ground operations;

(4) continuing airworthiness or for the continuing airworthiness management contract in accordance with CAR M, as the case may be.

(b) Adequacy and competency of personnel

(1) The operator shall employ sufficient personnel for the planned ground and flight operations.

(2) All personnel assigned to, or directly involved in, ground and flight operations shall:

(i) be properly trained;

(ii) demonstrate their capabilities in the performance of their assigned duties; and

(iii) be aware of their responsibilities and the relationship of their duties to the operation as a whole.

(c) Supervision of personnel

(1) The operator shall appoint a sufficient number of personnel supervisors, taking into account the structure of the operator's organisation and the number of personnel employed.

(2) The duties and responsibilities of these supervisors shall be defined, and any other necessary arrangements shall be made to ensure that they can discharge their supervisory responsibilities.

(3) The supervision of crew members and personnel involved in the operation shall be exercised by individuals with adequate experience and the skills to ensure the attainment of the standards specified in the operations manual.

AMC1 ORO.AOC.135(a) Personnel requirements

NOMINATED PERSONS

(a) The person may hold more than one of the nominated posts if such an arrangement is considered suitable and properly matched to the scale and scope of the operation.

(b) A description of the functions and the responsibilities of the nominated persons, including their names, should be contained in the operations manual.

(c) The holder of an AOC should make arrangements to ensure continuity of supervision in the absence of nominated persons.

(d) The person nominated by the holder of an AOC should not be nominated by another holder of an AOC, unless agreed with the competent authorities concerned.

(e) Persons nominated should be contracted to work sufficient hours to fulfil the management functions associated with the scale and scope of the operation.

AMC2 ORO.AOC.135(a) Personnel requirements

COMBINATION OF NOMINATED PERSONS RESPONSIBILITIES

(a) The acceptability of a single person holding several posts, possibly in combination with being the accountable manager, should depend upon the nature and scale of the operation. The two main areas of concern should be competence and an individual's capacity to meet his/her responsibilities.

(b) As regards competence in different areas of responsibility, there should not be any difference from the requirements applicable to persons holding only one post.

(c) The capacity of an individual to meet his/her responsibilities should primarily be dependent upon the scale of the operation. However, the complexity of the organisation or of the operation may prevent, or limit, combinations of posts which may be acceptable in other circumstances.

(d) In most circumstances, the responsibilities of a nominated person should rest with a single individual. However, in the area of ground operations, it may be acceptable for responsibilities to be split, provided that the responsibilities of each individual concerned are clearly defined.

GM1 ORO.AOC.135(a) Personnel requirements

NOMINATED PERSONS

The smallest organisation that can be considered is the one-man organisation where all of the nominated posts are filled by the accountable manager, and audits are conducted by an independent person.

GM2 ORO.AOC.135(a) Personnel requirements

COMPETENCE OF NOMINATED PERSONS

(a) Nominated persons in accordance with ORO.AOC.135 should be expected to possess the experience and meet the qualification provisions of (b) to (f) respectively. Exceptionally, in particular cases, where the nominated person does not meet these provisions in full, the nominee should have comparable experience and also the ability to perform effectively the functions associated with the post and with the scale of the operation.

(b) Nominated persons for flight operations, crew training and ground operations should have:

(1) practical experience and expertise in the application of aviation safety standards and safe operating practices;

(2) comprehensive knowledge of:

(i) the applicable UAE safety regulations and any associated requirements and procedures;

(ii) the AOC holder's operations specifications; and

(iii) the need for, and content of, the relevant parts of the AOC holder's operations manual;

(3) familiarity with management systems preferably in the area of aviation;

(4) appropriate management experience, preferably in a comparable organisation; and

(5) 5 years of relevant work experience of which at least 2 years should be from the aeronautical industry in an appropriate position.

(c) Flight operations. The nominated person should hold or have held a valid flight crew licence and the associated ratings appropriate to a type of operation conducted under the AOC. In case the nominated person's licence and ratings are not current, his/her deputy should hold a valid flight crew licence and the associated ratings.

(d) Crew training. The nominated person or his/her deputy should be a current type rating instructor on a type/class operated under the AOC. The nominated person should have a thorough knowledge of the AOC holder's crew training concept for flight, cabin and when relevant other crew.

(e) Ground operations. The nominated person should have a thorough knowledge of the AOC holder's ground operations concept.

(f) Continuing airworthiness. The nominated person for continuing airworthiness or for the continuous airworthiness management contract, as the case may be, should have the relevant knowledge, background and experience as detailed in CAR M.

ORO.AOC.140 Facility requirements

In accordance with ORO.GEN.215, the operator shall:

(a) make use of appropriate ground handling facilities to ensure the safe handling of its flights;

(b) arrange operational support facilities at the main operating base, appropriate for the area and type of operation; and

(c) ensure that the available working space at each operating base is sufficient for personnel whose actions may affect the safety of flight operations. Consideration shall be given to the needs of ground crew, personnel concerned with operational control, the storage and display of essential records and flight planning by crews.

GM1 ORO.AOC.140(b);(c) Facility requirements

VFR DAY OPERATIONS WITH AEROPLANES WITH A MOPSC OF LESS THAN 7 AND HELICOPTERS WITH A MOPSC OF LESS THAN 5 TAKING OFF AND LANDING AT THE SAME AERODROME OR OPERATING SITE

Taking into account the size of the operator and the type of operations, appropriate facilities may consist in arrangements for:

(a) suitable office accommodation for the nominated person(s), as requested by ORO.AOC.135, and

(b) adequate working space for the flight preparation to be performed by the flight crew.

ORO.AOC.150 Documentation requirements

(a) The operator shall make arrangements for the production of manuals and any other documentation required and associated amendments.

(b) The operator shall be capable of distributing operational instructions and other information without delay.

SUBPART DEC — DECLARATION

ORO.DEC.100 Declaration

The operator of complex motor-powered aircraft engaged in non-commercial operations, the operator of complex motor-powered aircraft engaged in non-commercial specialised operations, and the commercial specialised operator shall:

(a) provide the competent authority with all relevant information prior to commencing operations, using the form contained in Appendix I to this Part;

(b) notify to the competent authority a list of the alternative means of compliance it intends to use and obtain the necessary approval(s);

(c) maintain compliance with the applicable requirements and with the information given in the declaration;

(d) notify the competent authority without delay of any changes to its declaration or the means of compliance it uses through submission of an amended declaration using the form contained in Appendix I to this Part; and

(e) notify the competent authority when it ceases operation.

AMC1 ORO.DEC.100(a).G Declaration

Authorisation of declared operations

Prior to commencing declared operations, the operator should obtain a written authorisation and an operations specifications issued by the competent authority following the declaration.

AMC1 ORO.DEC.100(d) Declaration

CHANGES

The new declaration should be submitted before the change becomes effective indicating the date as of which the change would apply.

GM1 ORO.DEC.100 Declaration

GENERAL

The intent of the declaration is to:

(a) have the operator acknowledge its responsibilities under the applicable safety regulations and that it holds all necessary approvals;

(b) inform the competent authority of the existence of an operator; and

(c) enable the competent authority to fulfil its oversight responsibilities.

MANAGED OPERATIONS

When the non-commercial operation of a complex motor-powered aircraft is managed by a third party on behalf of the owner, that party may be the operator in the sense of Article 3(13) of CAR-BR, and therefore has to declare its capability and means to discharge the responsibilities associated with the operation of the aircraft to the competent authority.

In such a case, it should also be assessed whether the third party operator undertakes a commercial operation in the sense of Article 3(24) of CAR-BR

GM2 ORO.DEC.100.G Declaration process

Refer to AMC-08 for Declaration and subsequent changes.

SUBPART SPO — COMMERCIAL SPECIALISED OPERATIONS

ORO.SPO.100 Common requirements for commercial specialised operators

(a) A commercial specialised operator shall in addition to ORO.DEC.100 also comply with ORO.AOC.135, ORO.AOC.140 and ORO.AOC.150.

(b) Aircraft shall have a certificate of airworthiness (CofA) in accordance with CAR 21 or shall be leased-in in accordance with (c).

(c) A commercial specialised operator shall obtain prior approval of the competent authority and comply with the following conditions:

(1) for wet leasing-in an aircraft of a foreign operator:

(i) that the safety standards of a foreign operator with regard to continuing airworthiness and air operations are equivalent to the applicable requirements established by CAR-PART V;

(ii) that the aircraft of a foreign operator has a standard CofA issued in accordance with Annex 8 to the Convention on International Civil Aviation;

(iii) that the duration of the wet lease-in does not exceed seven months in any 12 consecutive month period;

(2) for dry leasing-in an aircraft registered in a foreign country:

(i) that an operational need that cannot be satisfied through leasing an aircraft registered in the UAE has been identified;

(ii) that the duration of the dry lease-in does not exceed seven months in any 12 consecutive month period;

(iii) that the safety standards of the foreign aircraft with regard to continuing airworthiness are equivalent to the applicable requirements established by CAR-PART V;

(iv) that the aircraft is equipped in accordance with Part-SPO.

AMC1 ORO.SPO.100(a) Personnel requirements

NOMINATED PERSONS

(a) The person may hold more than one of the nominated posts if such an arrangement is considered suitable and properly matched to the scale and scope of the commercial specialised operation.

(b) A description of the functions and the responsibilities of the nominated persons, including their names, should be contained in the operations manual.

(c) A commercial specialised operator should make arrangements to ensure continuity of supervision in the absence of nominated persons.

(d) The person nominated by a commercial specialised operator should normally not be nominated by another commercial specialised operator.

(e) Persons nominated should be contracted to work sufficient hours to fulfil the management functions associated with the scale and scope of the commercial specialised operation.

AMC2 ORO.SPO.100(a) Personnel requirements

COMBINATION OF NOMINATED PERSONS RESPONSIBILITIES

(a) The acceptability of a single person holding several posts, possibly in combination with being the accountable manager, should depend upon the nature and scale of the commercial specialised operation. The two main areas of concern should be competence and an individual's capacity to meet his/her responsibilities.

(b) As regards competence in different areas of responsibility, there should not be any difference from the requirements applicable to persons holding only one post.

(c) The capacity of an individual to meet his/her responsibilities should primarily be dependent upon the scale of the commercial specialised operation. However, the complexity of the organisation or of the operation may prevent, or limit, combinations of posts which may be acceptable in other circumstances.

(d) In most circumstances, the responsibilities of a nominated person should rest with a single individual. However, in the area of ground operations, it may be acceptable for responsibilities to be split, provided that the responsibilities of each individual concerned are clearly defined.

GM1 ORO.SPO.100(a) Personnel requirements

NOMINATED PERSONS

The smallest organisation that can be considered is the one-man organisation where all of the nominated posts are filled by the accountable manager, and audits are conducted by an independent person.

GM2 ORO.SPO.100(a) Personnel requirements

COMPETENCE OF NOMINATED PERSONS

(a) Nominated persons in accordance with ORO.AOC.135 should normally be expected to possess the experience and meet the licensing provisions that are listed in (b) to (f). There may be exceptional cases where not all of the provisions can be met. In that circumstance, the nominee should have comparable experience and also the ability to perform effectively the functions associated with the post and with the scale of the specialised operation.

(b) Nominated persons should have:

(1) practical experience and expertise in the application of aviation safety standards and safe operating practices;

(2) comprehensive knowledge of:

(i) the applicable UAE safety regulations and any associated requirements and procedures;

(ii) the operator's high-risk specialised operation authorisation, if applicable; and

(iii) the need for, and content of, the relevant parts of the commercial specialised operator's operations manual;

(3) familiarity with management systems preferably in the area of aviation;

(4) appropriate management experience, preferably in a comparable organisation; and

(5) 5 years of relevant work experience of which at least 2 years should be from the aeronautical industry in an appropriate position.

(c) Flight operations. The nominated person should hold or have held a valid flight crew licence and the associated ratings appropriate to the type of commercial specialised operations conducted by the operator. In case the nominated person's licence and ratings are not current, his/her deputy should hold a valid flight crew licence and the associated ratings.

(d) Crew training. The nominated person or his/her deputy should be a current type rating instructor on a type/class operated by the commercial specialised operator. The nominated person should have a thorough knowledge of the operator's crew training concept for flight crew and when relevant other crew.

(e) Ground operations. The nominated person should have a thorough knowledge of the commercial specialised operator's ground operations concept.

(f) Continuing airworthiness. The nominated person should have the relevant knowledge and appropriate experience requirements related to aircraft continuing airworthiness as detailed in Part-M.

AMC1 ORO.SPO.100(c) Common requirements for commercial specialised operators

LEASING OF AIRCRAFT FROM A FOREIGN COUNTRY OPERATOR — INFORMATION TO BE PROVIDED TO THE COMPETENT AUTHORITY

The operator intending to lease-in an aircraft should provide the competent authority with the following information:

(a) the aircraft type, registration markings and serial number;

(b) the name and address of the registered owner;

(c) a copy of the valid certificate of airworthiness;

(d) a copy of the lease agreement or description of the lease provisions, except financial arrangements;

(e) duration of the lease.

The information mentioned above should be accompanied by a statement signed by the lessee that the parties to the lease agreement fully understand their respective responsibilities under the applicable regulations.

GM1 ORO.SPO.100(c) Common requirements for commercial specialised operators

LEASE AGREEMENTS BETWEEN OPERATORS REGISTERED IN THE UAE

No approval is required for any lease agreements between operators having their principle place of business in the UAE.

AMC1 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators

WET LEASE-IN OF AN AIRCRAFT REGISTERED IN A FOREIGN STATE

If the operator is not intending to apply competent authority's safety requirements for air operations and continuing airworthiness when wet leasing-in an aircraft registered in a foreign State, it should demonstrate to the competent authority that the standards complied with are equivalent to the following requirements:

(a) Part-SPO;

(b) Part-ORO:

(1) ORO.GEN.110 and Section 2 of Subpart GEN;

(2) ORO.MLR, excluding ORO.MLR.105;

(3) ORO.FC;

(c) Part-SPA, if applicable;

(d) for continuing airworthiness management of the foreign operator, Part-M Subpart-B, Subpart-C and Subpart-G, excluding M.A.707, and M.A.710;

(e) for the maintenance organisation used by the foreign operator during the lease period: Part-145; and

(f) the operator should provide the competent authority with a full description of the operating procedures and safety assessment demonstrating compliance with the requirements safety objectives set out in points (b) (1)-(3).

AMC2 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators

WET LEASE-IN

The lessee should maintain a record of occasions when lessors are used, for inspection by the competent authority.

GM1 ORO.SPO.100(c)(1) Common requirements for commercial specialised operators

SHORT-TERM WET LEASE-IN

In anticipation of an operational need the operator may enter into a framework agreement with more than one foreign operator provided that these operators comply with ORO.SPO.110(c). These foreign operators should be placed in a list maintained by the lessee.

ORO.SPO.110 Authorisation of high risk commercial specialised operations

(a) A commercial specialised operator shall apply for and obtain an authorisation issued by the competent authority of the operator prior to commencing a high risk commercial specialised operation:

(1) that is carried out over an area where the safety of third parties on the ground is likely to be endangered in the event of an emergency, or

(2) that, as determined by the competent authority of the place where the operation is conducted, due to its specific nature and the local environment in which it is conducted, poses a high risk, in particular to third parties on the ground.

(b) The operator shall provide the following information to the competent authority:

(1) the official name and business name, address, and mailing address of the applicant;

(2) a description of the management system, including organisational structure;

(3) a description of the proposed operation, including the type(s), and number of aircraft to be

operated;

(4) the risk assessment documentation and related standard operating procedures, required by SPO.OP.230;

(5) a statement that all the documentation sent to the competent authority has been verified by the operator and found in compliance with the applicable requirements.

(c) The application for an authorisation or its amendment shall be made in a form and manner established by the competent authority, taking into account the applicable requirements of CAR-BR and the applicable rules.

GM1 ORO.SPO.110(a) Authorisation of high-risk commercial specialised operations

DECLARATION/AUTHORISATION

Any commercial specialised operator should declare its activity to its competent authority, as required by ORO.DEC.100.

GM2 ORO.SPO.110(a) Authorisation of high-risk commercial specialised operations

VALIDITY OF THE AUTHORISATION

The operator may submit an application to its competent authority for a single event, a defined series of flights or for an unlimited duration, depending on the type of operations foreseen.

ORO.SPO.115 Changes

(a) Any change affecting the scope of the authorisation or the authorised operations shall require prior approval of the competent authority. Any change not covered by the initial risk assessment, shall require the submission of an amended risk assessment and SOP to the competent authority.

(b) The application for approval of a change shall be submitted before any such change takes place, in order to enable the competent authority to determine continued compliance with CAR-BR and the applicable rules and to amend, if necessary, the authorisation. The operator shall provide the competent authority with any relevant documentation.

(c) The change shall only be implemented upon receipt of formal approval by the competent authority.

(d) The operator shall operate under the conditions prescribed by the competent authority during such changes, as applicable.

GM1 ORO.SPO.115(a) Changes

GENERAL

Any change to information contained in the authorisation, but not leading to an amendment of the SOPs or the operator's risk assessment should be notified by the commercial specialised operator to the competent authority to assess the need to amend the authorisation.

ORO.SPO.120 Continued validity

(a) An operator holding a specialised operation authorisation shall comply with the scope and

privileges defined in the authorisation.

(b) The operator's authorisation shall remain valid subject to:

(1) the operator remaining in compliance with the relevant requirements of CAR-BR and the applicable rules, taking into account the provisions related to the handling of findings as specified under ORO.GEN.150;

(2) the competent authority being granted access to the operator as defined in ORO.GEN.140 to determine continued compliance with the relevant requirements of CAR-BR and the applicable rules; and

(3) the authorisation not being surrendered or revoked.

(c) Upon revocation or surrender the authorisation shall be returned to the competent authority without delay.

SUBPART MLR — MANUALS, LOGS AND RECORDS

ORO.MLR.100 Operations manual — general

(a) The operator shall establish an operations manual (OM) as specified under 8.2. of Annex II to CAR-BR

(b) The content of the OM shall reflect the requirements set out in this Part, Part-CAT, Part-SPA, Part-NCC and Part-SPO, as applicable, and shall not contravene the conditions contained in the operations specifications to the air operator certificate (AOC), the SPO authorisation or the declaration and the list of specific approvals, as applicable.

(c) The OM may be issued in separate parts.

(d) All operations personnel shall have easy access to the portions of the OM that are relevant to their duties.

(e) The OM shall be kept up-to-date. All personnel shall be made aware of the changes that are relevant to their duties.

(f) Each crew member shall be provided with a personal copy of the relevant sections of the OM pertaining to their duties. Each holder of an OM, or appropriate parts of it, shall be responsible for keeping their copy up-to-date with the amendments or revisions supplied by the operator.

(g) For AOC holders:

(1) for amendments required to be notified in accordance with ORO.GEN.115 (b) and ORO.GEN.130 (c), the operator shall supply the competent authority with intended amendments in advance of the effective date; and

(2) for amendments to procedures associated with prior approval items in accordance with ORO.GEN.130, approval shall be obtained before the amendment becomes effective.

(g1) For SPO authorisation holders, any amendment associated with the authorised standard operating procedures, prior approval shall be obtained before the amendment becomes effective.

(h) Notwithstanding (g) and (g1), when immediate amendments or revisions are required in the interest of safety, they may be published and applied immediately, provided that any approval required has been applied for.

(i) The operator shall incorporate all amendments and revisions required by the competent authority.

(j) The operator shall ensure that information taken from approved documents, and any amendment thereof, is correctly reflected in the OM. This does not prevent the operator from publishing more conservative data and procedures in the OM.

(k) The operator shall ensure that all personnel are able to understand the language in which those parts of the OM which pertain to their duties and responsibilities are written. The content of the OM shall be presented in a form that can be used without difficulty and observes human factors principles.

AMC1 ORO.MLR.100 Operations manual — general

GENERAL

(a) The operations manual (OM) may vary in detail according to the complexity of the operation and of the type and number of aircraft operated.

(b) The OM or parts thereof may be presented in any form, including electronic form. In all cases, the accessibility, usability and reliability should be assured.

(c) The OM should be such that:

(1) all parts of the manual are consistent and compatible in form and content;

(2) the manual can be readily amended; and

(3) the content and amendment status of the manual is controlled and clearly indicated.

(d) The OM should include a description of its amendment and revision process specifying:

(1) the person(s) who may approve amendments or revisions;

(2) the conditions for temporary revisions and/or immediate amendments or revision required in the interest of safety; and

(3) the methods by which operator personnel are advised of the changes.

(e) The OM content may be based on, or may refer to, industry codes of practice.

(f) When compiling an OM, the operator may take advantage of the contents of other relevant documents. Material produced by the operator for the type-related part of the OM may be supplemented with, or substituted by, applicable parts of the aircraft flight manual (AFM) or, where such a document exists, by an aircraft operating manual produced by the manufacturer of the aircraft.

(g) In the case of commercial operations with other-than-complex motor-powered aircraft or non-commercial operations, a 'pilot operating handbook' (POH), or equivalent document, may be used as the type-related part of the OM, provided that the POH covers the normal and abnormal/emergency operating procedures.

(h) For the route and aerodrome part of the OM, material produced by the operator may be supplemented with or substituted by applicable route guide material produced by a specialist company.

(i) If the operator chooses to use material from another source in the OM, either the applicable material should be copied and included directly in the relevant part of the OM, or the OM should contain a reference to the appropriate section of that applicable material.

(j) If the operator chooses to make use of material from another source (e.g. a route manual producer, an aircraft manufacturer or a training organisation), this does not absolve the operator from the responsibility of verifying the applicability and suitability of this material. Any material received from an external source should be given its status by a statement in the OM.

AMC2 ORO.MLR.100 Operations manual — general

CONTENTS OF THE OPERATIONS MANUAL FOR CERTAIN TYPES OF OPERATION

For non-commercial operations with complex motor-powered aircraft, or CAT operations with either single-engined propeller-driven aeroplanes with an MOPSC of 5 or less, or single-engined non-complex helicopters with an MOPSC of 5 or less, taking off and landing at the same aerodrome or operating site, under VFR by day, the OM should contain at least the following information, where applicable:

(a) Table of contents;

(b) Amendment control status and list of effective pages or paragraphs, unless the entire manual is re-issued and the manual has an effective date on it;

(c) Duties, responsibilities and succession of management and operating personnel;

(d) Description of the management system;

(e) Operational control system;

(f) Flight time limitations;

(g) Standard operating procedures (SOPs);

(h) Weather limitations;

(i) Emergency procedures;

(j) Accidents/incidents considerations;

(k) Security procedures;

(l) Minimum equipment list (MEL);

(m) Personnel qualifications and training;

(n) Record-keeping;

(o) Normal flight operations;

(p) Performance operating limitations;

(q) Procedures for the preservation of recordings of the flight recorders in order to prevent inadvertent reactivation, repair or reinstallation of the flight recorders following an accident or a serious incident or when this preservation is directed by the investigating authority;

(r) Handling of dangerous goods;

(s) Procedures for aircraft operated whenever required cosmic or solar radiation detection equipment is carried.

AMC3 ORO.MLR.100 Operations manual — general

CONTENTS — CAT OPERATIONS

(a) The OM should contain at least the following information, where applicable, as relevant for the area and type of operation:

A GENERAL/BASIC

0 ADMINISTRATION AND CONTROL OF OPERATIONS MANUAL

0.1 Introduction:

(a) A statement that the manual complies with all applicable regulations and with the terms and conditions of the applicable AOC.

(b) A statement that the manual contains operational instructions that are to be complied with by the relevant personnel.

(c) A list and brief description of the various parts, their contents, applicability and use.

(d) Explanations and definitions of terms and words needed for the use of

the manual.

0.2 System of amendment and revision:

(a) Details of the person(s) responsible for the issuance and insertion of amendments and revisions.

(b) A record of amendments and revisions with insertion dates and effective dates.

(c) A statement that handwritten amendments and revisions are not permitted, except in situations requiring immediate amendment or revision in the interest of safety.

(d) A description of the system for the annotation of pages or paragraphs and their effective dates.

(e) A list of effective pages or paragraphs.

(f) Annotation of changes (in the text and, as far as practicable, on charts and diagrams).

(g) Temporary revisions.

(h) A description of the distribution system for the manuals, amendments and revisions.

1 ORGANISATION AND RESPONSIBILITIES

1.1. Organisational structure. A description of the organisational structure, including the general organogram and operations departments' organograms. The organogram should depict the relationship between the operations departments and the other departments of the operator. In particular, the subordination and reporting lines of all divisions, departments, etc., which pertain to the safety of flight operations, should be shown.

1.2. Nominated persons. The name of each nominated person responsible for flight operations, crew training and ground operations, as prescribed in ORO.AOC.135. A description of their function and responsibilities should be included.

1.3. Responsibilities and duties of operations management personnel. A description of the duties, responsibilities and authority of operations management personnel pertaining to the safety of flight operations and the compliance with the applicable regulations.

1.4. Authority, duties and responsibilities of the pilot-in-command/commander. A statement defining the authority, duties and responsibilities of the pilot-in-command/commander.

1.5. Duties and responsibilities of crew members other than the pilot-in-command/commander.

2 OPERATIONAL CONTROL AND SUPERVISION

2.1 Supervision of the operation by the operator. A description of the system for supervision of the operation by the operator (see ORO.GEN.110(c)). This should show how the safety of flight operations and the qualifications of personnel are supervised. In particular, the procedures related to the following items should be described:

(a) licence and qualification validity,

(b) competence of operations personnel,

(c) control, analysis and storage of the required records.

2.2 System and responsibility for promulgation of additional operational instructions and information. A description of any system for promulgating information which may be of an operational nature, but which is supplementary to that in the OM. The applicability of this information and the responsibilities for its promulgation should be included.

2.3 Operational control. A description of the procedures and responsibilities necessary to exercise operational control with respect to flight safety.

2.4 Powers of the authority. A description of the powers of the competent authority and guidance to staff on how to facilitate inspections by authority personnel.

3 MANAGEMENT SYSTEM

A description of the management system, including at least the following:

(a) safety policy;

(b) the process for identifying safety hazards and for evaluating and managing the associated risks;

(c) compliance monitoring system;

(d) allocation of duties and responsibilities;

(e) documentation of all key management system processes.

4 CREW COMPOSITION

4.1 Crew composition. An explanation of the method for determining crew compositions, taking account of the following:

(a) the type of aircraft being used;

(b) the area and type of operation being undertaken;

(c) the phase of the flight;

(d) the minimum crew requirement and flight duty period planned;

(e) experience (total and on type), recency and qualification of the crew members;

(f) the designation of the pilot-in-command/commander and, if necessitated by the duration of the flight, the procedures for the relief of the pilot-in-command/commander or other members of the flight crew (see ORO.FC.105);

(g) the designation of the senior cabin crew member and, if necessitated by the duration of the flight, the procedures for the relief of the senior cabin crew member and any other member of the cabin crew.

4.2 Designation of the pilot-in-command/commander. The rules applicable to the designation of the pilot-in-command/commander.

4.3 Flight crew incapacitation. Instructions on the succession of command in the event of flight crew incapacitation.

4.4 Operation on more than one type. A statement indicating which aircraft are considered as one type for the purpose of:

(a) flight crew scheduling; and

(b) cabin crew scheduling.

5 QUALIFICATION REQUIREMENTS

5.1 A description of the required licence, rating(s), qualification/competency (e.g. for routes and aerodromes), experience, training, checking and recency for operations personnel to conduct their duties. Consideration should be given to the aircraft type, kind of operation and composition of the crew.

5.2 Flight crew:

(a) pilot-in-command/commander,

(b) pilot relieving the pilot-in-command/commander,

(c) co-pilot,

(d) pilot relieving the co-pilot,

(e) pilot under supervision,

(f) system panel operator,

(g) operation on more than one type or variant.

5.3 Cabin crew:

(a) senior cabin crew member,

(b) cabin crew member:

(i) required cabin crew member,

(ii) additional cabin crew member and cabin crew member during familiarisation flights,

(c) operation on more than one type or variant.

5.4 Training, checking and supervision personnel:

(a) for flight crew; and

(b) for cabin crew.

5.5 Other operations personnel (including technical crew and crew members other than flight, cabin and technical crew).

6 CREW HEALTH PRECAUTIONS

6.1 Crew health precautions. The relevant regulations and guidance to crew members concerning health, including the following:

(a) alcohol and other intoxicating liquids,

(b) narcotics,

(c) drugs,

(d) sleeping tablets,

(e) anti-depressants,

(f) pharmaceutical preparations,

(g) immunisation,

(h) deep-sea diving,

(i) blood/bone marrow donation,

(j) meal precautions prior to and during flight,

(k) sleep and rest,

(l) surgical operations.

7 FLIGHT TIME LIMITATIONS

7.1 Flight and duty time limitations and rest requirements.

7.2 Exceedance of flight and duty time limitations and/or reductions of rest periods. Conditions under which flight and duty time may be exceeded or rest periods may be reduced and the procedures used to report these modifications.

7.3 A description of the fatigue risk management, including at least the following:

(a) the philosophy and principles;

(b) documentation of processes;

(c) scientific principles and knowledge;

(d) hazard identification and risk assessment processes;

(e) risk mitigation process;

(f) FRM safety assurance processes; and

(g) FRM promotion processes.

8 OPERATING PROCEDURES

8.1 Flight preparation instructions. As applicable to the operation:

8.1.1. Minimum flight altitudes. A description of the method of determination and application of minimum altitudes including:

(a) a procedure to establish the minimum altitudes/flight levels for visual flight rules (VFR) flights; and

(b) a procedure to establish the minimum altitudes/flight levels for instrument flight rules (IFR) flights.

8.1.2. Criteria and responsibilities for determining the adequacy of aerodromes to be used.

8.1.3. Methods and responsibilities for establishing aerodrome operating minima. Reference should be made to procedures for the determination of the visibility and/or runway visual range (RVR) and for the applicability of the actual visibility observed by the pilots, the reported visibility and the reported RVR.

8.1.4. En-route operating minima for VFR flights or VFR portions of a flight and, where single-engined aircraft are used, instructions for route selection with respect to the availability of surfaces that permit a safe forced landing.

8.1.5. Presentation and application of aerodrome and en-route operating minima.

8.1.6. Interpretation of meteorological information. Explanatory material on the decoding of meteorological (MET) forecasts and MET reports relevant to the area of operations, including the interpretation of conditional expressions.

8.1.7. Determination of the quantities of fuel, oil and water methanol carried. The methods by which the quantities of fuel, oil and water methanol to be carried are determined and monitored in-flight. This section should also include instructions on the measurement and distribution of the fluid carried on board. Such instructions should take account of all circumstances likely to be encountered on the flight, including the possibility of in-flight re-planning and of failure of one or more of the aircraft's power plants. The system for maintaining fuel and oil records should also be described.

8.1.8. Mass and centre of gravity. The general principles of mass and centre of gravity including the following:

(a) definitions;

(b) methods, procedures and responsibilities for preparation and acceptance of mass and centre of gravity calculations;

(c) the policy for using standard and/or actual masses;

(d) the method for determining the applicable passenger, baggage and cargo mass;

(e) the applicable passenger and baggage masses for various types of operations and aircraft type;

(f) general instructions and information necessary for verification of the various types of mass and balance documentation in use;

(g) last-minute changes procedures;

(h) specific gravity of fuel, oil and water methanol;

(i) seating policy/procedures;

(j) for helicopter operations, standard load plans.

8.1.9. Air traffic services (ATS) flight plan. Procedures and responsibilities for the preparation and submission of the ATS flight plan. Factors to be considered include the means of submission for both individual and repetitive flight plans.

8.1.10. Operational flight plan. Procedures and responsibilities for the preparation and acceptance of the operational flight plan. The use of the operational flight plan should be described, including samples of the operational flight plan formats in use.

8.1.11. Operator's aircraft technical log. The responsibilities and the use of the operator's aircraft technical log should be described, including samples of the format used.

8.1.12. List of documents, forms and additional information to be carried.

8.1.13. For commercial air transport operations with single-engined turbine aeroplanes in instrument meteorological conditions or at night (CAT SET-IMC) approved in accordance with Subpart L (SET-IMC) of Part-SPA:

(a) the procedure for route selection with respect to the availability of

surfaces, which permits a safe forced landing;

(b) the instructions for the assessment of landing sites (elevation, landing direction, and obstacles in the area); and

(c) the instructions for the assessment of the weather conditions at those landing sites.

8.2 Ground handling instructions. As applicable to the operation:

8.2.1. Fuelling procedures. A description of fuelling procedures, including:

(a) safety precautions during refuelling and defueling including when an auxiliary power unit is in operation or when rotors are running or when an engine is or engines are running and the prop-brakes are on;

(b) refuelling and defuelling when passengers are embarking, on board or disembarking; and

(c) precautions to be taken to avoid mixing fuels.

8.2.2. Aircraft, passengers and cargo handling procedures related to safety. A description of the handling procedures to be used when allocating seats, embarking and disembarking passengers and when loading and unloading the aircraft. Further procedures, aimed at achieving safety whilst the aircraft is on the ramp, should also be given. Handling procedures should include:

(a) special categories of passengers, including children/infants, persons with reduced mobility, inadmissible passengers, deportees and persons in custody;

(b) permissible size and weight of hand baggage;

(c) loading and securing of items in the aircraft;

(d) positioning of ground equipment;

(e) operation of aircraft doors;

(f) safety on the aerodrome/operating site, including fire prevention and safety in blast and suction areas;

(g) start-up, ramp departure and arrival procedures, including, for aeroplanes, push-back and towing operations;

(h) servicing of aircraft;

(i) documents and forms for aircraft handling;

(j) special loads and classification of load compartments; and

(k) multiple occupancy of aircraft seats.

8.2.3. Procedures for the refusal of embarkation. Procedures to ensure that persons who appear to be intoxicated, or who demonstrate by manner or physical indications that they are under the influence of drugs, are refused embarkation. This does not apply to medical patients under proper care.

8.2.4. De-icing and anti-icing on the ground. A description of the de-icing and anti-icing policy and procedures for aircraft on the ground. These should include descriptions of the types and effects of icing and other contaminants on aircraft whilst stationary, during ground movements and during take-off. In addition, a description of the fluid types used should be given, including the

following:

(a) proprietary or commercial names,

(b) characteristics,

(c) effects on aircraft performance,

(d) hold-over times,

(e) precautions during usage.

8.3 Flight Procedures:

8.3.1. VFR/IFR Policy. A description of the policy for allowing flights to be made under VFR, or for requiring flights to be made under IFR, or for changing from one to the other.

8.3.2. Navigation Procedures. A description of all navigation procedures, relevant to the type(s) and area(s) of operation. Special consideration should be given to:

(a) standard navigational procedures, including policy for carrying out independent cross-checks of keyboard entries where these affect the flight path to be followed by the aircraft; and

(b) required navigation performance (RNP), minimum navigation performance specification (MNPS) and polar navigation and navigation in other designated areas;

(c) in-flight re-planning;

(d) procedures in the event of system degradation; and

(e) reduced vertical separation minima (RVSM), for aeroplanes.

8.3.3. Altimeter setting procedures, including, where appropriate, use of:

(a) metric altimetry and conversion tables; and

(b) QFE operating procedures.

8.3.4. Altitude alerting system procedures for aeroplanes or audio voice alerting devices for helicopters.

8.3.5. Ground proximity warning system (GPWS)/terrain avoidance warning system (TAWS), for aeroplanes. Procedures and instructions required for the avoidance of controlled flight into terrain, including limitations on high rate of descent near the surface (the related training requirements are covered in OM-D 2.1).

8.3.6. Policy and procedures for the use of traffic collision avoidance system (TCAS)/airborne collision avoidance system (ACAS) for aeroplanes and, when applicable, for helicopters.

8.3.7. Policy and procedures for in-flight fuel management.

8.3.8. Adverse and potentially hazardous atmospheric conditions. Procedures for operating in, and/or avoiding, adverse and potentially hazardous atmospheric conditions, including the following:

(a) thunderstorms,

(b) icing conditions,

(c) turbulence,

(d) windshear,

(e) jet stream,

(f) volcanic ash clouds,

(g) heavy precipitation,

(h) sand storms,

(i) mountain waves,

(j) significant temperature inversions.

8.3.9. Wake turbulence. Wake turbulence separation criteria, taking into account aircraft types, wind conditions and runway/final approach and take-off area (FATO) location. For helicopters, consideration should also be given to rotor downwash.

8.3.10. Crew members at their stations. The requirements for crew members to occupy their assigned stations or seats during the different phases of flight or whenever deemed necessary in the interest of safety and, for aeroplane operations, including procedures for controlled rest in the flight crew compartment.

8.3.11. Use of restraint devices for crew and passengers. The requirements for crew members and passengers to use safety belts and/or restraint systems during the different phases of flight or whenever deemed necessary in the interest of safety.

8.3.12. Admission to flight crew compartment. The conditions for the admission to the flight crew compartment of persons other than the flight crew. The policy regarding the admission of inspectors from an authority should also be included.

8.3.13. Use of vacant crew seats. The conditions and procedures for the use of vacant crew seats.

8.3.14. Incapacitation of crew members. Procedures to be followed in the event of incapacitation of crew members in-flight. Examples of the types of incapacitation and the means for recognising them should be included.

8.3.15. Cabin safety requirements. Procedures:

(a) covering cabin preparation for flight, in-flight requirements and preparation for landing, including procedures for securing the cabin and galleys;

(b) to ensure that passengers are seated where, in the event that an emergency evacuation is required, they may best assist and not hinder evacuation from the aircraft;

(c) to be followed during passenger embarkation and disembarkation;

(d) when refuelling/defuelling with passengers embarking, on board or disembarking;

(e) covering the carriage of special categories of passengers;

(f) covering smoking on board;

(g) covering the handling of suspected infectious diseases.

8.3.16. Passenger briefing procedures. The contents, means and timing of passenger briefing in accordance with Part-CAT.

8.3.17. Procedures for aircraft operated whenever required cosmic or solar radiation detection equipment is carried.

8.3.18. Policy on the use of autopilot and autothrottle for aircraft fitted with these systems.

8.4 Low visibility operations (LVO). A description of the operational procedures associated with LVO.

8.5 Extended-range operations with two-engined aeroplanes (ETOPS). A description of the ETOPS operational procedures. (Refer to the EASA AMC 20-6)

8.6 Use of the minimum equipment and configuration deviation list(s).

8.7 Non-commercial operations. Information as required by ORO.AOC.125 for each type of non-commercial flight performed by the AOC holder. A description of the differences from CAT operations. Procedures and limitations, for example, for the following:

(a) training flights,

(b) test flights,

(c) delivery flights,

(d) ferry flights,

(e) demonstration flights,

(f) positioning flights,

(g) other non-commercial flights.

8.8 Oxygen requirements:

8.8.1. An explanation of the conditions under which oxygen should be provided and used.

8.8.2. The oxygen requirements specified for the following persons:

(a) flight crew;

(b) cabin crew;

(c) passengers.

8.9 Procedures related to the use of type B EFB applications:

9 DANGEROUS GOODS AND WEAPONS

9.1 Information, instructions and general guidance on the transport of dangerous goods, in accordance with Subpart G of Part-SPA (SPA.DG), including:

(a) operator’s policy on the transport of dangerous goods;

(b) guidance on the requirements for acceptance, labelling, handling, stowage and segregation of dangerous goods;

(c) special notification requirements in the event of an accident or occurrence when dangerous goods are being carried;

(d) procedures for responding to emergency situations involving dangerous goods;

(e) duties of all personnel involved; and

(f) instructions on the carriage of the operator's personnel on cargo aircraft when dangerous goods are being carried.

9.2 The conditions under which weapons, munitions of war and sporting weapons may be carried.

10 SECURITY

Security instructions, guidance, procedures, training and responsibilities, taking into account CAR PART VII Aviation Security Regulations. Some parts of the security instructions and guidance may be kept confidential.

11 HANDLING, NOTIFYING AND REPORTING ACCIDENTS, INCIDENTS AND OCCURRENCES AND USING THE CVR RECORDING

Procedures for handling, notifying and reporting accidents, incidents and occurrences. This section should include the following:

(a) definition of accident, incident and occurrence and of the relevant responsibilities of all persons involved;

(b) illustrations of forms to be used for reporting all types of accident, incident and occurrence (or copies of the forms themselves), instructions on how they are to be completed, the addresses to which they should be sent and the time allowed for this to be done;

(c) in the event of an accident, descriptions of which departments, authorities and other organisations have to be notified, how this will be done and in what sequence;

(d) procedures for verbal notification to air traffic service units of incidents involving ACAS resolution advisories (RAs), bird hazards, dangerous goods and hazardous conditions;

(e) procedures for submitting written reports on air traffic incidents, ACAS RAs, bird strikes, dangerous goods incidents or accidents, and unlawful interference;

(f) reporting procedures. These procedures should include internal safety-related reporting procedures to be followed by crew members, designed to ensure that the pilot-in-command/commander is informed immediately of any incident that has endangered, or may have endangered, safety during the flight, and that the pilot-in-command/commander is provided with all relevant information.

(g) Procedures for the preservation of recordings of the flight recorders following an accident or a serious incident or when so directed by the investigating authority. These procedures should include:

(1) a full quotation of point (a) of CAT.GEN.MPA.195; and

(2) instructions and means to prevent inadvertent reactivation, repair or reinstallation of the flight recorders by personnel of the operator or of third parties, and to ensure that flight recorder recordings are preserved for the needs of the investigating authority.

(h) Procedures required by CAT.GEN.MPA.195 for using the CVR recording or its transcript without prejudice to Accident Investigation Regulations, when applicable.

12 RULES OF THE AIR

(a) Visual and instrument flight rules,

(b) Territorial application of the rules of the air,

(c) Communication procedures, including communication-failure procedures,

(d) Information and instructions relating to the interception of civil aircraft,

(e) The circumstances in which a radio listening watch is to be maintained,

(f) Signals,

(g) Time system used in operation,

(h) ATC clearances, adherence to flight plan and position reports,

(i) Visual signals used to warn an unauthorised aircraft flying in or about to enter a restricted, prohibited or danger area,

(j) Procedures for flight crew observing an accident or receiving a distress transmission,

(k) The ground/air visual codes for use by survivors, and description and use of signal aids,

(l) Distress and urgency signals.

13 LEASING/CODE-SHARE

A description of the operational arrangements for leasing and code-share, associated procedures and management responsibilities.

B AIRCRAFT OPERATING MATTERS — TYPE RELATED

Taking account of the differences between types/classes, and variants of types, under the following headings:

0 GENERAL INFORMATION AND UNITS OF MEASUREMENT

0.1 General information (e.g. aircraft dimensions), including a description of the units of measurement used for the operation of the aircraft type concerned and conversion tables.

1 LIMITATIONS

1.1. A description of the certified limitations and the applicable operational limitations should include the following:

(a) certification status (e.g. (supplemental) type certificate, environmental certification, etc.);

(b) passenger seating configuration for each aircraft type, including a pictorial presentation;

(c) types of operation that are approved (e.g. VFR/IFR, CAT II/III, RNP, flights in known icing conditions, etc.);

(d) crew composition;

(e) mass and centre of gravity;

(f) speed limitations;

(g) flight envelope(s);

(h) wind limits, including operations on contaminated runways;

(i) performance limitations for applicable configurations;

(j) (runway) slope;

(k) for aeroplanes, limitations on wet or contaminated runways;

(l) airframe contamination;

(m) system limitations.

2 NORMAL PROCEDURES

The normal procedures and duties assigned to the crew, the appropriate checklists, the system for their use and a statement covering the necessary coordination procedures between flight and cabin/other crew members. The normal procedures and duties should include the following:

(a) pre-flight,

(b) pre-departure,

(c) altimeter setting and checking,

(d) taxi, take-off and climb,

(e) noise abatement,

(f) cruise and descent,

(g) approach, landing preparation and briefing,

(h) VFR approach,

(i) IFR approach,

(j) visual approach and circling,

(k) missed approach,

(l) normal landing,

(m) post-landing,

(n) for aeroplanes, operations on wet and contaminated runways.

3 ABNORMAL AND/OR EMERGENCY PROCEDURES

The abnormal and/or emergency procedures and duties assigned to the crew, the appropriate checklists, the system for their use and a statement covering the necessary coordination procedures between flight and cabin/other crew members. The abnormal and/or emergency procedures and duties should include the following:

(a) crew incapacitation,

(b) fire and smoke drills,

(c) for aeroplanes, un-pressurised and partially pressurised flight,

(d) for aeroplanes, exceeding structural limits such as overweight landing,

(e) lightning strikes,

(f) distress communications and alerting ATC to emergencies,

(g) engine/burner failure,

(h) system failures,

(i) guidance for diversion in case of serious technical failure,

(j) ground proximity warning, including for helicopters audio voice alerting device (AVAD) warning,

(k) ACAS/TCAS warning for aeroplanes/audio voice alerting device (AVAD) warning for helicopters,

(l) windshear,

(m) emergency landing/ditching,

(n) for aeroplanes, departure contingency procedures.

4 PERFORMANCE

4.0 Performance data should be provided in a form that can be used without difficulty.

4.1 Performance data. Performance material that provides the necessary data for compliance with the performance requirements prescribed in Part-CAT. For aeroplanes, this performance data should be included to allow the determination of the following:

(a) take-off climb limits — mass, altitude, temperature;

(b) take-off field length (for dry, wet and contaminated runway conditions);

(c) net flight path data for obstacle clearance calculation or, where applicable, take-off flight path;

(d) the gradient losses for banked climb-outs;

(e) en-route climb limits;

(f) approach climb limits;

(g) landing climb limits;

(h) landing field length (for dry, wet and contaminated runway conditions) including the effects of an in-flight failure of a system or device, if it affects the landing distance;

(i) brake energy limits;

(j) speeds applicable for the various flight stages (also considering dry, wet and contaminated runway conditions).

4.1.1 Supplementary data covering flights in icing conditions. Any certified performance related to an allowable configuration, or configuration deviation, such as anti-skid inoperative.

4.1.2 If performance data, as required for the appropriate performance class, are not available in the AFM, then other data should be included. The OM may contain cross-reference to the data contained in the AFM where such data are not likely to be used often or in an emergency.

4.2 Additional performance data for aeroplanes. Additional performance data, where applicable, including the following:

(a) all engine climb gradients,

(b) drift-down data,

(c) effect of de-icing/anti-icing fluids,

(d) flight with landing gear down,

(e) for aircraft with 3 or more engines, one-engine-inoperative ferry flights,

(f) flights conducted under the provisions of the configuration deviation list (CDL).

5 FLIGHT PLANNING

5.1 Data and instructions necessary for pre-flight and in-flight planning including, for aeroplanes, factors such as speed schedules and power settings. Where applicable, procedures for engine(s)-out operations, ETOPS (particularly the one-engine-inoperative cruise speed and maximum distance to an adequate aerodrome determined in accordance with Part-CAT and flights to isolated aerodromes should be included.

5.2 The method for calculating fuel needed for the various stages of flight.

5.3 When applicable, for aeroplanes, performance data for ETOPS critical fuel reserve and area of operation, including sufficient data to support the critical fuel reserve and area of operation calculation based on approved aircraft performance data. The following data should be included:

(a) detailed engine(s)-inoperative performance data, including fuel flow for standard and non-standard atmospheric conditions and as a function of airspeed and power setting, where appropriate, covering:

(i) drift down (includes net performance), where applicable;

(ii) cruise altitude coverage including 10 000 ft;

(iii) holding;

(iv) altitude capability (includes net performance); and

(v) missed approach;

(b) detailed all-engine-operating performance data, including nominal fuel flow data, for standard and non-standard atmospheric conditions and as a function of airspeed and power setting, where appropriate, covering:

(i) cruise (altitude coverage including 10 000 ft); and

(ii) holding;

(c) details of any other conditions relevant to ETOPS operations which can cause significant deterioration of performance, such as ice accumulation on the unprotected surfaces of the aircraft, ram air turbine (RAT) deployment, thrust-reverser deployment, etc.; and

(d) the altitudes, airspeeds, thrust settings, and fuel flow used in establishing the ETOPS area of operations for each airframe-engine combination should be used in showing the corresponding terrain and obstruction clearances in accordance with Part-CAT.

6 MASS AND BALANCE

Instructions and data for the calculation of the mass and balance, including the following:

(a) calculation system (e.g. index system);

(b) information and instructions for completion of mass and balance documentation, including manual and computer generated types;

(c) limiting masses and centre of gravity for the types, variants or individual aircraft used by the operator;

(d) dry operating mass and corresponding centre of gravity or index.

7 LOADING

Procedures and provisions for loading and unloading and securing the load in the aircraft.

8 CONFIGURATION DEVIATION LIST

The CDL(s), if provided by the manufacturer, taking account of the aircraft types and variants operated, including procedures to be followed when an aircraft is being dispatched under the terms of its CDL.

9 MINIMUM EQUIPMENT LIST (MEL)

The MEL for each aircraft type or variant operated and the type(s)/area(s) of operation. The MEL should also include the dispatch conditions associated with operations required for a specific approval (e.g. RNAV, RNP, RVSM, ETOPS). Consideration should be given to using the ATA number system when allocating chapters and numbers.

10 SURVIVAL AND EMERGENCY EQUIPMENT INCLUDING OXYGEN

10.1 A list of the survival equipment to be carried for the routes to be flown and the procedures for checking the serviceability of this equipment prior to take-off. Instructions regarding the location, accessibility and use of survival and emergency equipment and its associated checklist(s) should also be included.

10.2 The procedure for determining the amount of oxygen required and the quantity that is available. The flight profile, number of occupants and possible cabin decompression should be considered.

11 EMERGENCY EVACUATION PROCEDURES

11.1 Instructions for preparation for emergency evacuation, including crew coordination and emergency station assignment.

11.2 Emergency evacuation procedures. A description of the duties of all members of the crew for the rapid evacuation of an aircraft and the handling of the passengers in the event of a forced landing, ditching or other emergency.

12 AIRCRAFT SYSTEMS

A description of the aircraft systems, related controls and indications and operating instructions. Consideration should be given to use the ATA number system when allocating chapters and numbers.

C ROUTE/ROLE/AREA AND AERODROME/OPERATING SITE INSTRUCTIONS AND INFORMATION

1 Instructions and information relating to communications, navigation and aerodromes/ operating sites, including minimum flight levels and altitudes for each route to be flown and operating minima for each aerodrome/operating site planned to be used, including the following:

(a) minimum flight level/altitude;

(b) operating minima for departure, destination and alternate aerodromes;

(c) communication facilities and navigation aids;

(d) runway/final approach and take-off area (FATO) data and aerodrome/operating site facilities;

(e) approach, missed approach and departure procedures including noise abatement procedures;

(f) communication-failure procedures;

(g) search and rescue facilities in the area over which the aircraft is to be flown;

(h) a description of the aeronautical charts that should be carried on board in relation to the type of flight and the route to be flown, including the method to check their validity;

(i) availability of aeronautical information and MET services;

(j) en-route communication/navigation procedures;

(k) aerodrome/operating site categorisation for flight crew competence qualification;

(l) special aerodrome/operating site limitations (performance limitations and operating procedures, etc.).

2 Information related to landing sites available for operations approved in accordance with Subpart L (SET-IMC) of Part-SPA, including:

(a) a description of the landing site (position, surface, slope, elevation, etc.);

(b) the preferred landing direction; and

(c) obstacles in the area.

D TRAINING

1 Description of scope: Training syllabi and checking programmes for all operations personnel assigned to operational duties in connection with the preparation and/or conduct of a flight.

2 Content: Training syllabi and checking programmes should include the following:

2.1 for flight crew, all relevant items prescribed in Part-CAT, Part-SPA and ORO.FC;

2.2 for cabin crew, all relevant items prescribed in Part CAT, CAR-CC and ORO.CC;

2.3 for technical crew, all relevant items prescribed in Part-CAT, Part-SPA and ORO.TC;

2.4 for operations personnel concerned, including crew members:

(a) all relevant items prescribed in SPA.DG Subpart G of Part-SPA (SPA.DG); and

(b) all relevant items prescribed in Part-CAT and ORO.SEC; and

2.5 for operations personnel other than crew members (e.g. dispatcher, handling personnel, etc.), all other relevant items prescribed in Part-CAT and in this Part pertaining to their duties.

3 Procedures:

3.1 Procedures for training and checking.

3.2 Procedures to be applied in the event that personnel do not achieve or maintain the required standards.

3.3 Procedures to ensure that abnormal or emergency situations requiring the application of part or all of the abnormal or emergency procedures, and simulation of instrument meteorological conditions (IMC) by artificial means are not simulated during commercial air transport operations.

4 Description of documentation to be stored and storage periods.

(b) Reserved.

(c) If there are sections that, because of the nature of the operation, do not apply, it is recommended that operators maintain the numbering system described in ORO.MLR.101 and above and insert ‘Not applicable’ or ‘Intentionally blank’ where appropriate.

AMC4 ORO.MLR.100 Operations manual — general

CONTENTS – NON-COMMERCIAL SPECIALISED OPERATIONS WITH COMPLEX MOTOR-POWERED AIRCRAFT AND COMMERCIAL SPECIALISED OPERATIONS

(a) The OM should contain at least the following information, where applicable, as relevant to the area and type of operation:

A GENERAL/BASIC

For chapters 0-7 refer to AMC3 ORO.MLR.100.

In addition:

6.2 The relevant regulations and guidance to crew members concerning dangerous goods used for specialised tasks (pesticides and chemicals, etc.).

8 OPERATING PROCEDURES

8.1. Flight preparation instructions. As applicable to the operation:

8.1.1 General procedures;

8.1.2 Minimum flight altitudes. A description of the method of determination and application of minimum altitudes, including a procedure to establish the minimum altitudes/ flight levels;

8.1.3 Criteria and responsibilities for determining the adequacy of aerodromes/operating sites to be used;

8.1.4 Interpretation of meteorological information. Explanatory material on the decoding of MET forecasts and MET reports relevant to the area of operations, including the interpretation of conditional expressions;

8.1.5 Determination of the quantities of fuel, oil and water methanol carried. The methods by which the quantities of fuel, oil and water methanol to be carried are determined and monitored in-flight. The system for maintaining fuel and oil records should also be described;

8.1.6 Procedure for the determination of the mass of loads, the calculation of performance margins and the centre of gravity;

8.1.7 Emergency procedures, e.g. load, fuel or chemical jettison (to include the actions of all personnel);

8.1.8 System for supply of NOTAMS, meteorological and other safety-critical information both at base and in field locations;

8.1.9 Mandatory equipment for specific tasks (mirror, cargo sling, load cell, special radio equipment, radar altimeters, etc.);

8.1.10 Guidance on the CDL and MEL;

8.1.11 Policy on completion and carriage of documents including operator's aircraft technical log and journey log, or equivalent;

8.1.12 Any task-specific standard operating procedures not covered above.

8.2. Ground handling instructions. As applicable to the operation:

8.2.1. Briefing requirements for in-flight and ground task specialists;

8.2.2. Decontamination procedures;

8.2.3. Fuelling procedures, including safety precautions during refuelling and defuelling including quality checks required in the field location, precautions against spillage and environmental damage;

8.2.4. De-icing and anti-icing on the ground. A description of the de-icing and anti-icing policy and procedures for aircraft on the ground.

8.3. Flight procedures. As applicable to the operation:

8.3.1. Procedures relevant to the aircraft type, specific task and area;

8.3.2. Altimeter setting procedures;

8.3.3. Actions following alerts from audio warning devices;

8.3.4. GPWS/TAWS for aeroplanes. Procedures and instructions required for the avoidance of controlled flight into terrain, including limitations on high rate of descent near the surface (the related training requirements are covered in OM-D 2.1);

8.3.5. Policy and procedures for the use of TCAS/ACAS for aeroplanes and, when applicable, for helicopters;

8.3.6. Policy and procedures for in-flight fuel management;

8.3.7. Procedures for operating in adverse and potentially hazardous atmospheric conditions;

8.3.8. Wake turbulence and rotor downwash for helicopters;

8.3.9. Use of restraint devices;

8.3.10. Policy on use of vacant seats;

8.3.11. Cabin safety requirements including smoking.

8.4. Task-specific weather limitations.

8.5. Use of the minimum equipment and configuration deviation list(s).

8.6. Oxygen requirements. An explanation of the conditions under which oxygen should be provided and used (altitude, exposure times, night etc.).

9 DANGEROUS GOODS AND WEAPONS

9.1 Information, instruction and general guidance on the transport of dangerous goods as internal or external loads, including:

9.1.1 The operator's policy on the transport of dangerous goods;

9.1.2 Guidance on the requirements for acceptance, labelling, handling, stowage, and segregation of dangerous goods;

9.1.3 Procedures for responding to emergency situations involving dangerous goods;

9.1.4 Duties of all personnel involved; and

9.1.5 Instructions on carriage of the operator’s personnel on cargo aircraft when dangerous goods are being carried.

9.2 The conditions under which weapons, munitions of war and sporting weapons may be carried.

10 SECURITY

Security instructions, guidance, procedures, training and responsibilities, taking into account CAR PART VII Aviation Security Regulations. Some parts of the security instructions and guidance may be kept confidential.

11 HANDLING, NOTIFYING AND REPORTING ACCIDENTS, INCIDENTS AND OCCURRENCES, AND USING THE CVR RECORDINGS

Procedures for handling, notifying and reporting of accidents, incidents and occurrences. This section should include:

11.1 Definitions of accidents and occurrences and responsibilities of all persons involved;

11.2 Reporting procedures (including any mandatory forms);

11.3 Special notification when dangerous goods are carried; and

11.4 Procedures for the preservation of recordings of the flight recorders in order to prevent inadvertent reactivation, repair or reinstallation of the flight recorders following an accident or a serious incident or when this preservation is directed by the investigating authority.

12 RULES OF THE AIR

In addition to the items referred to in AMC3 ORO.MLR.100, territorial procedures for obtaining permissions and exemptions, e.g. for underslung loads and lowflying clearances.

13 LEASING

Refer to AMC3 ORO.MLR.100.

B AIRCRAFT OPERATING MATTERS — TYPE RELATED

For chapters 0-1 refer to AMC3 ORO.MLR.100.

2 NORMAL PROCEDURES

The normal procedures and duties assigned to the crew, the appropriate checklists and the system for their use, including any task or specific role equipment procedures not contained in the AFM.

3 ABNORMAL AND/OR EMERGENCY PROCEDURES

The abnormal and/or emergency procedures and duties assigned to the crew, the appropriate checklists and the system for their use, including any task or specific role equipment emergency procedures not contained in the AFM.

4 PERFORMANCE

4.1 Performance data should be provided in a form in which it can be used without difficulty.

4.2 Performance data. Performance material which provides the necessary data for compliance with the performance requirements prescribed in Part-SPO.

5 FLIGHT PLANNING

5.1 Data and instructions necessary for pre-flight and in-flight planning.

5.2 Procedures for specialised tasks.

6 MASS AND BALANCE

Instructions and data for the calculation of the mass and balance, including:

6.1 Calculation system (e.g. index system);

6.2 Information and instructions for completion of mass and balance documentation; and

6.3 Limitations.

7 LOADING

Refer to AMC3 ORO.MLR.100.

8 CONFIGURATION DEVIATION LIST (CDL)

Refer to AMC3 ORO.MLR.100.

9 MINIMUM EQUIPMENT LIST (MEL)

The MEL for each aircraft type or variant operated and the type(s)/area(s) of operation. It should also contain procedures to be followed when an aircraft is being dispatched with one or more inoperative items, in accordance with the MEL.

10 SURVIVAL AND EMERGENCY EQUIPMENT INCLUDING OXYGEN

10.1 A list of the survival equipment to be carried, taking into account the nature of the area of operation, such as a hostile or a non-hostile environment.

10.2 A checklist for assessing the serviceability of the equipment and instructions for its use prior to take-off.

10.3 The procedure for determining the amount of oxygen required and the quantity that is available.

11 EMERGENCY EVACUATION PROCEDURES

11.1 Emergency evacuation procedures, crew coordination and occupant handling in the event of a forced landing, ditching or other emergency.

12 AIRCRAFT SYSTEMS

A description of the aircraft systems and all equipment specific to the tasks. Additional equipment, systems or fitting, related special procedures including any supplements to the AFM.

C TASKS AND OPERATING AREAS INSTRUCTIONS AND INFORMATION

Specific instructions related to the specialised tasks and operating areas in accordance with AMC3 ORO. MLR.100.

D TRAINING

1 Training syllabi and checking programmes for all operations personnel assigned to operational duties in connection with the preparation and/or conduct of a flight.

2 Training syllabi and checking programmes should include:

2.1 For flight crew, all relevant items prescribed in Part-SPO, Part-SPA and this Part;

2.2 For other crew members, all relevant items prescribed in Part-SPO and this Part, as applicable;

2.3 For in-flight and ground task specialists concerned, including crew members:

a. All relevant items prescribed in SPA.DG; and

b. All relevant items prescribed in Part-SPO and ORO.SEC; and

2.4 For operations personnel other than crew members, all other relevant items pertaining to their duties prescribed in Part-SPO and this Part.

3 Procedures:

3.1 Procedures for training and checking.

3.2 Procedures to be applied in the event that personnel do not achieve or maintain the required standards.

3.3 A system for tracking expiry dates for qualifications, checks, tests, recency and licences.

4 Description of documentation to be stored and storage periods.

(b) If there are sections that, because of the nature of the operation, do not apply, it is recommended that operators maintain the numbering system described in ORO.MLR.101 and above and insert 'Not applicable' or 'Intentionally blank' where appropriate.

AMC5 ORO.MLR.100 Operations manual — general

CROSSWIND LIMITATIONS IN THE OPERATIONS MANUAL (OM)

When publishing operational crosswind limitations in Part B of the OM in accordance with AMC3 ORO.MLR.100, operators should consider:

(a) the following manufacturer's information:

(1) values published in the 'Limitations' Section of the AFM;

(2) maximum demonstrated crosswind values, when more limiting values are not published in the 'Limitations' Section of the AFM;

(3) gust values; and

(4) additional guidance or recommendations;

(b) operational experience; and

(c) operating-environment factors such as:

(1) runway width;

(2) runway surface condition; and

(3) prevailing weather conditions.

GM1 ORO.MLR.100(k) Operations manual — general

HUMAN FACTORS PRINCIPLES

Guidance material on the application of human factors principles can be found in the ICAO Human Factors Training Manual (Doc 9683).

ORO.MLR.101 Operations manual — structure for commercial air transport

Except for operations with single engined propeller-driven aeroplanes with an MOPSC of 5 or less or single engined non-complex helicopters with an MOPSC of 5 or less, taking off and landing at the same

aerodrome or operating site, under VFR by day, the main structure of the OM shall be as follows:

(a) Part A: General/Basic, comprising all non-type-related operational policies, instructions and procedures;

(b) Part B: Aircraft operating matters, comprising all type-related instructions and procedures, taking into account differences between types/classes, variants or individual aircraft used by the operator;

(c) Part C: Commercial air transport operations, comprising route/role/area and aerodrome/ operating site instructions and information;

(d) Part D: Training, comprising all training instructions for personnel required for a safe operation.

ORO.MLR.105 Minimum equipment list

(a) An operator shall establish minimum equipment list (MEL), based on the relevant master minimum equipment list (MMEL) as defined by the state of design and the type certificate data sheet validated by the competent authority. If an MMEL has not been established as part of the operational suitability data, the MEL may be based on the relevant MMEL accepted by the State of Operator or State of Registry as applicable.

(b) The MEL and any amendment thereto shall be approved by the competent authority.

(c) The operator shall amend the MEL after any applicable change to the MMEL within the acceptable timescales.

(d) In addition to the list of items, the MEL shall contain:

(1) a preamble, including guidance and definitions for flight crews and maintenance personnel using the MEL;

(2) the revision status of the MMEL upon which the MEL is based and the revision status of the MEL;

(3) the scope, extent and purpose of the MEL.

(e) The operator shall:

(1) establish rectification intervals for each inoperative instrument, item of equipment or function listed in the MEL. The rectification interval in the MEL shall not be less restrictive than the corresponding rectification interval in the MMEL;

(2) establish an effective rectification programme;

(3) only operate the aircraft after expiry of the rectification interval specified in the MEL when:

(i) the defect has been rectified; or

(ii) the rectification interval has been extended in accordance with (f).

(f) Subject to approval of the competent authority, the operator may use a procedure for the one time extension of category B, C and D rectification intervals, provided that:

(1) the extension of the rectification interval is within the scope of the MMEL for the aircraft type;

(2) the extension of the rectification interval is, as a maximum, of the same duration as the rectification interval specified in the MEL;

(3) the rectification interval extension is not used as a normal means of conducting MEL item rectification and is used only when events beyond the control of the operator have

precluded rectification;

(4) a description of specific duties and responsibilities for controlling extensions is established by the operator;

(5) the competent authority is notified of any extension of the applicable rectification interval; and

(6) a plan to accomplish the rectification at the earliest opportunity is established.

(g) The operator shall establish the operational and maintenance procedures referenced in the MEL taking into account the operational and maintenance procedures referenced in the MMEL. These procedures shall be part of the operator's manuals or the MEL.

(h) The operator shall amend the operational and maintenance procedures referenced in the MEL after any applicable change to the operational and maintenance procedures referenced in the MMEL.

(i) Unless otherwise specified in the MEL, the operator shall complete:

(1) the operational procedures referenced in the MEL when planning for and/or operating with the listed item inoperative; and

(2) the maintenance procedures referenced in the MEL prior to operating with the listed item inoperative.

(j) Subject to a specific case-by-case approval by the competent authority, the operator may operate an aircraft with inoperative instruments, items of equipment or functions outside the constraints of the MEL but within the constraints of the MMEL, provided that:

(1) the concerned instruments, items of equipment or functions are within the scope of the MMEL as defined in point (a);

(2) the approval is not used as a normal means of conducting operations outside the constraints of the approved MEL and is used only when events beyond the control of the operator have precluded the MEL compliance;

(3) a description of specific duties and responsibilities for controlling the operation of the aircraft under such approval is established by the operator; and

(4) a plan to rectify the inoperative instruments, items of equipment or functions or to return operating the aircraft under the MEL constraints at the earliest opportunity is established.

GM1 ORO.MLR.105(a) Minimum equipment list

GENERAL

(a) The Minimum Equipment List (MEL) is a document that lists the equipment that may be temporarily inoperative, subject to certain conditions, at the commencement of flight. This document is prepared by the operator for their own particular aircraft taking account of their aircraft configuration and all those individual variables that cannot be addressed at MMEL level, such as operating environment, route structure, geographic location, aerodromes where spare parts and maintenance capabilities are available, etc., in accordance with a procedure approved by the competent authority.

(b) The MMEL, as defined in the mandatory part of the operational suitability data established in accordance with CAR-21, is developed in compliance with CS-MMEL or CS-GEN-MMEL. These Certification Specifications contain, among other, guidance intended to standardise the level of relief granted in MMELs, in particular for items that are subject to operational requirements. If a

MMEL established as part of the operational suitability data is not available and items subject to operational requirements are listed in the available MMEL without specific relief or dispatch conditions but only with a reference to the operational requirements, the operator may refer to CS-MMEL or CS-GEN-MMEL guidance material, as applicable, to develop the relevant MEL content for such items.

NON-SAFETY-RELATED EQUIPMENT

(a) Most aircraft are designed and certified with a significant amount of equipment redundancy, such that the airworthiness requirements are satisfied by a substantial margin. In addition, aircraft are generally fitted with equipment that is not required for safe operation under all operating conditions, e.g. instrument lighting in day VMC.

(b) All items related to the airworthiness, or required for the safe operation, of the aircraft and not included in the list are automatically required to be operative.

(c) Equipment, such as entertainment systems or galley equipment, may be installed for passenger convenience. If this non-safety-related equipment does not affect the airworthiness or operation of the aircraft when inoperative, it does not require a rectification interval, and need not be listed in the operator's MEL, if it is not addressed in the MMEL. The exceptions to this are as follows:

(1) Where non-safety-related equipment serves a second function, such as movie equipment being used for cabin safety briefings, operators should develop and include operational contingency procedures in the MEL in case of an equipment malfunction.

(2) Where non-safety-related equipment is part of another aircraft system, for example the electrical system, procedures should be developed and included in the MEL for deactivating and securing in case of malfunction. In these cases, the item should be listed in the MEL, with compensating provisions and deactivation instructions if applicable. The rectification interval will be dependent on the secondary function of the item and the extent of its effect on other systems.

(d) If the operator chooses to list non-safety-related equipment in the MEL, not listed in the MMEL, they should include a rectification interval category. These items may be given a 'D' category rectification interval provided any applicable (M) procedure (in the case of electrically supplied items) is applied.

(e) Operators should establish an effective decision making process for failures that are not listed to determine if they are related to airworthiness and required for safe operation. In order for inoperative installed equipment to be considered non-safety-related, the following criteria should be considered:

(1) the operation of the aircraft is not adversely affected such that standard operating procedures related to ground personnel, and crew members are impeded;

(2) the condition of the aircraft is not adversely affected such that the safety of passengers and/or personnel is jeopardised;

(3) the condition of the aircraft is configured to minimise the probability of a subsequent failure that may cause injury to passengers/personnel and/or cause damage to the aircraft;

(4) the condition does not include the use of required emergency equipment and does not impact emergency procedures such that personnel could not perform them.

AMC1 ORO.MLR.105(b).G Minimum equipment list

OPERATOR INTERNAL APPROVAL

(a) Based on a defined procedure by the operator, the competent authority may grant the privilege of internal approval of certain MEL amendments to the operator, after a satisfactory review of the following:

(1) operator's experience in operating the aircraft type;

(2) compliance history with the requirements;

(3) competencies and knowledge of relevant personnel; and

(4) availability of resources.

(b) This approval will be limited to the following amendments of the MEL:

(1) Incorporation of MMEL revisions, including Temporary Revisions, except items that are marked as "As per Regulations";

(2) Incorporation of MMEL Supplements (initial and revisions) introduced via STC, which are approved by the competent authority, except items that are marked "As per Regulations";

(3) Incorporation of Buyer Furnished Equipment (BFE) item of a non-safety nature, unless such BFE is mandated by the UAE regulations;

(4) Correction of typographical errors.

(c) The operator should submit the MEL (including internally approved amendments), at agreed intervals, to the competent authority for formal acceptance.

(d) The MEL preamble should include the requirements and limitations stated in points (a), (b) and (c).

AMC1 ORO.MLR.105(c) Minimum equipment list

AMENDMENTS TO THE MEL FOLLOWING CHANGES TO THE MMEL — APPLICABLE CHANGES AND ACCEPTABLE TIMESCALES

(a) The following are applicable changes to the MMEL that require amendment of the MEL:

(1) a reduction of the rectification interval;

(2) change of an item, only when the change is applicable to the aircraft or type of operations and is more restrictive.

(b) An acceptable timescale for submitting the amended MEL to the competent authority is 90 days from the effective date specified in the approved change to the MMEL.

(c) Reduced timescales for the implementation of safety-related amendments may be required if the competent authority considers it necessary.

AMC1 ORO.MLR.105(d) Minimum equipment list

MEL FORMAT

(a) The MEL format and the presentation of items and dispatch conditions should reflect those of the MMEL.

(b) The ATA 100/2200 Specification numbering system for MEL items is preferred.

(c) Other formats and item numbering systems may be used provided they are clear and unambiguous.

AMC1 ORO.MLR.105(d)(1) Minimum equipment list

MEL PREAMBLE

The MEL preamble should:

(a) reflect the content of the MMEL preamble as applicable to the MEL scope and extent;

(b) contain terms and definitions used in the MEL;

(c) contain any other relevant specific information for the MEL scope and use that is not originally provided in the MMEL;

(d) provide guidance on how to identify the origin of a failure or malfunction to the extent necessary for appropriate application of the MEL;

(e) contain guidance on the management of multiple unserviceabilities, based on the guidance given in the MMEL; and

(f) contain guidance on placarding of inoperative items to inform crew members of equipment condition, as appropriate. In particular, when such items are accessible to the crew during flight, the control(s) and indicator(s) related to inoperative unit(s) should be clearly placarded.

AMC1 ORO.MLR.105(d)(3) Minimum equipment list

SCOPE OF THE MEL

The MEL should include:

(a) The dispatch conditions associated with flights conducted in accordance with specific approvals held by the operator in accordance with Part-SPA.

(b) Specific provision for particular types of operations carried out by the operator in accordance with ORO.GEN.310 and with ORO. AOC.125.

AMC2 ORO.MLR.105(d)(3) Minimum equipment list

EXTENT OF THE MEL

The operator should include guidance in the MEL on how to deal with any failures that occur between the commencement of the flight and the start of the take-off. If a failure occurs between the commencement of the flight and the start of the take-off, any decision to continue the flight should be subject to pilot judgement and good airmanship. The pilot-in-command/commander may refer to the MEL before any decision to continue the flight is taken.

GM1 ORO.MLR.105(d)(3) Minimum equipment list

SCOPE OF THE MEL

(a) Examples of special approvals in accordance with Part-SPA may be:

(1) RVSM,

(2) ETOPS,

(3) LVO.

(b) Different types of operations carried out by the operator in accordance with ORO.GEN.310 and with ORO.AOC.125:

(1) crew training,

(2) positioning flights,

(3) demonstration flights.

(c) When an aircraft has installed equipment which is not required for the operations conducted, the operator may wish to delay rectification of such items for an indefinite period. Such cases are considered to be out of the scope of the MEL, therefore modification of the aircraft is appropriate and deactivation, inhibition or removal of the item should be accomplished by an appropriate approved modification procedure.

GM2 ORO.MLR.105(d)(3) Minimum equipment list

PURPOSE OF THE MEL

The MEL is an alleviating document having the purpose to identify the minimum equipment and conditions to operate safely an aircraft having inoperative equipment. Its purpose is not, however, to encourage the operation of aircraft with inoperative equipment. It is undesirable for aircraft to be dispatched with inoperative equipment and such operations are permitted only as a result of careful analysis of each item to ensure that the acceptable level of safety, as intended in the applicable airworthiness and operational requirements is maintained. The continued operation of an aircraft in this condition should be minimised.

GM1 ORO.MLR.105(e);(f) Minimum equipment list

RECTIFICATION INTERVAL (RI)

The definitions and categories of rectification intervals are provided in CS-MMEL.

AMC1 ORO.MLR.105(f) Minimum equipment list

RECTIFICATION INTERVAL EXTENSION (RIE) — OPERATOR PROCEDURES FOR THE APPROVAL BY THE COMPETENT AUTHORITY AND NOTIFICATION TO THE COMPETENT AUTHORITY

(a) The operator's procedures to address the extension of rectification intervals and ongoing surveillance to ensure compliance should provide the competent authority with details of the name and position of the nominated personnel responsible for the control of the operator's rectification interval extension (RIE) procedures and details of the specific duties and responsibilities established to control the use of RIEs.

(b) Personnel authorising RIEs should be adequately trained in technical and/or operational disciplines to accomplish their duties. They should have necessary operational knowledge in terms of operational use of the MEL as alleviating documents by flight crew and maintenance personnel and engineering competence. The authorising personnel should be listed by appointment and name.

(c) The operator should notify the competent authority within 1 month of the extension of the applicable rectification interval or within the appropriated timescales specified by the approved procedure for the RIE.

(d) The notification should be made in a form determined by the competent authority and should specify the original defect, all such uses, the reason for the RIE and the reasons why rectification was not carried out within the original rectification interval.

GM1 ORO. MLR.105(f) Minimum equipment list

RECTIFICATION INTERVAL EXTENSION (RIE)

Procedures for the extension of rectification intervals should only be applied under certain conditions, such as a shortage of parts from manufacturers or other unforeseen situations (e.g. inability to obtain equipment necessary for proper troubleshooting and repair), in which case the operator may be unable to comply with the specified rectification intervals.

AMC1 ORO.MLR.105(g) Minimum equipment list

OPERATIONAL AND MAINTENANCE PROCEDURES

(a) The operational and maintenance procedures referenced in the MEL should be based on the operational and maintenance procedures referenced in the MMEL. Modified procedures may, however, be developed by the operator when they provide the same level of safety, as required by the MMEL. Modified maintenance procedures should be developed in accordance with CAR-M.

(b) Providing appropriate operational and maintenance procedures referenced in the MEL, regardless of who developed them, is the responsibility of the operator.

(c) Any item in the MEL requiring an operational or maintenance procedure to ensure an acceptable level of safety should be so identified in the 'remarks' or 'exceptions' column/part/section of the MEL. This will normally be '(O)' for an operational procedure, or '(M)' for a maintenance procedure. '(O)(M)' means both operational and maintenance procedures are required.

(d) The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator.

GM1 ORO.MLR.105(g) Minimum equipment list

OPERATIONAL AND MAINTENANCE PROCEDURES

(a) Operational and maintenance procedures are an integral part of the compensating conditions needed to maintain an acceptable level of safety, enabling the competent authority to approve the MEL. The competent authority may request presentation of fully developed (O) and/or (M) procedures in the course of the MEL approval process.

(b) Normally, operational procedures are accomplished by the flight crew; however, other personnel may be qualified and authorised to perform certain functions.

(c) Normally, maintenance procedures are accomplished by the maintenance personnel; however, other personnel may be qualified and authorised to perform certain functions in accordance with CAR PART V

(d) Operator's manuals may include the OM, the continued airworthiness management organisation manual (CAME) or other documents. Operational and maintenance procedures, regardless of the document where they are contained, should be readily available for use when needed for the application of the MEL.

(e) Unless specifically permitted by a maintenance procedure, an inoperative item may not be removed from the aircraft.

AMC1 ORO.MLR.105(h) Minimum equipment list

OPERATIONAL AND MAINTENANCE PROCEDURES — APPLICABLE CHANGES

(a) Changes to the operational and maintenance procedures referenced in the MMEL are considered applicable and require the amendment of the maintenance and operating procedures referenced in the MEL when:

(1) the modified procedure is applicable to the operator's MEL; and

(2) the purpose of this change is to improve compliance with the intent of the associated MMEL dispatch condition.

(b) An acceptable timescale for the amendments of maintenance and operating procedures, as defined in (a), should be 90 days from the date when the amended procedures referenced in the MMEL are made available. Reduced timescales for the implementation of safety related amendments may be required if the competent authority considers it necessary.

AMC1 ORO.MLR.105(j) Minimum equipment list

OPERATION OF AN AIRCRAFT WITHIN THE CONSTRAINTS OF THE MMEL — OPERATOR'S PROCEDURES FOR THE APPROVAL BY THE COMPETENT AUTHORITY

(a) The operator's procedures to address the operation of an aircraft outside the constraints of the MEL but within the constraints of the MMEL and ongoing surveillance to ensure compliance should provide the competent authority with details of the name and position of the nominated personnel responsible for the control of the operations under such conditions and details of the specific duties and responsibilities established to control the use of the approval.

(b) Personnel authorising operations under such approval should be adequately trained in technical and operational disciplines to accomplish their duties. They should have the necessary operational knowledge in terms of operational use of the MEL as alleviating documents by flight crew and maintenance personnel and engineering competence. The authorising personnel should be listed by appointment and name.

GM1 ORO.MLR.105(j) Minimum equipment list

OPERATION OF AN AIRCRAFT WITHIN THE CONSTRAINTS OF THE MMEL — OPERATOR'S PROCEDURES FOR THE APPROVAL BY THE COMPETENT AUTHORITY

Procedures for the operation of an aircraft outside the constraints of the MEL but within the constraints of the MMEL should only be applied under certain conditions, such as a shortage of parts from manufacturers or other unforeseen situations (e.g. inability to obtain equipment necessary for proper troubleshooting and repair), in which case the operator may be unable to comply with the constraints specified in the MEL.

ORO.MLR.110 Journey log

Particulars of the aircraft, its crew and each journey shall be retained for each flight, or series of flights, in the form of a journey log, or equivalent.

AMC1 ORO.MLR.110 Journey log

GENERAL

(a) The aircraft journey log, or equivalent, should include the following items, where applicable:

(1) aircraft nationality and registration,

(2) date,

(3) name(s) of crew member(s),

(4) duty assignments of crew member(s),

(5) place of departure,

(6) place of arrival,

(7) time of departure,

(8) time of arrival,

(9) hours of flight,

(10) nature of flight (scheduled or non-scheduled),

(11) incidents, observations, if any,

(12) signature of person in charge.

(b) The information, or parts thereof, may be recorded in a form other than on printed paper. Accessibility, usability and reliability should be assured.

(c) 'Journey log, or equivalent' means that the required information may be recorded in documentation other than a log book, such as the operational flight plan or the aircraft technical log.

(d) 'Series of flights' means consecutive flights, which begin and end:

(1) within a 24-hour period;

(2) at the same aerodrome or operating site or remain within a local area specified in the operations manual; and

(3) with the same pilot-in-command/commander of the aircraft.

GM1 ORO.MLR.110 Journey log

SERIES OF FLIGHTS

The term 'series of flights' is used to facilitate a single set of documentation.

ORO.MLR.115 Record-keeping

(a) The following records shall be stored for at least 5 years:

(1) for CAT operators, records of the activities referred to in ORO.GEN.200;

(2) for declared operators, a copy of the operator's declaration, details of approvals held and operations manual.

(3) for SPO authorisation holders, in addition to (a)(2), records related to the risk assessment conducted in accordance with SPO.OP.230 and related standard operating procedures.

(b) The following information used for the preparation and execution of a flight, and associated

reports, shall be stored for three months:

(1) the operational flight plan, if applicable;

(2) route-specific notice(s) to airmen (NOTAM) and aeronautical information services (AIS) briefing documentation, if edited by the operator;

(3) mass and balance documentation;

(4) notification of special loads, including written information to the commander/pilot-in-command about dangerous goods, if applicable;

(5) the journey log, or equivalent; and

(6) flight report(s) for recording details of any occurrence, or any event that the commander/pilot-in- command deems necessary to report or record;

(c) Personnel records shall be stored for the periods indicated below:

Flight crew licence and cabin crew attestation	As long as the crew member is exercising the privileges of the licence or attestation for the aircraft operator
Crew member training, checking and qualifications	3 years
Records on crew member recent experience	15 months
Crew member route and aerodrome/task and area competence, as appropriate	3 years
Dangerous goods training, as appropriate	3 years
Training/qualification records of other personnel for whom a training programme is required	Last 2 training records
Records on cosmic and solar radiation dosage	Until 12 months after the crew member has left the employ of the operator

(d) The operator shall:

(1) maintain records of all training, checking and qualifications of each crew member, as prescribed in Part-ORO; and

(2) make such records available, on request, to the crew member concerned.

(e) The operator shall preserve the information used for the preparation and execution of a flight and personnel training records, even if the operator ceases to be the operator of that aircraft or the employer of that crew member, provided this is within the timescales prescribed in (c).

(f) If a crew member becomes a crew member for another operator, the operator shall make the crew member's records available to the new operator, provided this is within the timescales prescribed in (c).

AMC1 ORO.MLR.115 Record-keeping

TRAINING RECORDS

A summary of training should be maintained by the operator to show every crew member's completion of each stage of training and checking.

GM1 ORO.MLR.115(c) Record-keeping

PERSONNEL RECORDS

'Personnel records' in ORO.MLR.115(c) means detailed crew member training, checking and qualification records. These records include detailed examination records.

GM1 ORO.MLR.115(d) Record-keeping

TRAINING, CHECKING AND QUALIFICATION RECORDS

Training, checking and qualification records include records of all training, checking and qualifications of each crew member, as prescribed in Part-ORO.

SUBPART SEC — SECURITY

ORO.SEC.100 Flight crew compartment security – aeroplanes

(a) In an aeroplane which is equipped with a secure flight crew compartment door, that door shall be capable of being locked, and means shall be provided by which the cabin crew can notify the flight crew in the event of suspicious activity or security breaches in the cabin.

(b) All passenger-carrying aeroplanes that are engaged in the commercial transportation of passengers shall be equipped with an approved secure flight crew compartment door that is capable of being locked and unlocked from either pilot's station and designed to meet the applicable airworthiness requirements, where such airplanes fall within any of the following categories:

(1) aeroplanes with an MCTOM that exceeds 54 500 kg;

(2) aeroplanes with an MCTOM that exceeds 45 500 kg and have an MOPSC of more than 19; or

(3) aeroplanes with an MOPSC of more than 60.

(c) In all aeroplanes which are equipped with a secure flight crew compartment door in accordance with point (b):

(1) that door shall be closed prior to engine start for take-off and shall be locked when required so by security procedures or by the pilot-in-command until engine shutdown after landing, except when deemed to be necessary for authorised persons to access or egress in compliance with national civil aviation security programmes;

(2) means shall be provided for monitoring from either pilot's station the entire door area outside the flight crew compartment to identify persons that request to enter and to detect suspicious behaviour or potential threat.

ORO.SEC.105 Flight crew compartment security – helicopters

If installed, the flight crew compartment door on a helicopter operated for the purpose of carrying passengers shall be capable of being locked from within the flight crew compartment in order to prevent unauthorised access.

ORO.SEC.110.G Aircraft search procedure checklist

For aircraft used in commercial air transport operations, the operator shall ensure that there is on board a checklist of the procedures to be followed in searching for a bomb in case of suspected sabotage and for inspecting aircraft for concealed weapons, explosives or other dangerous devices when a wellfounded suspicion exists that the aircraft may be the object of an act of unlawful interference. The checklist shall be supported by guidance on the appropriate course of action to be taken should a bomb or suspicious object be found and, if applicable, information on the least-risk bomb location specific to the aircraft.

SUBPART FC — FLIGHT CREW

ORO.FC.005 Scope

This Subpart establishes requirements to be met by the operator related to flight crew training, experience and qualification and comprises:

(a) SECTION 1 specifying common requirements applicable to both non-commercial operations of complex motor-powered aircraft and any commercial operation;

(b) SECTION 2 specifying additional requirements applicable to commercial air transport operations, with the exception of commercial air transport operations of passengers conducted under VFR by day, starting and ending at the same aerodrome or operating site and within a local area specified by the competent authority, with:

(1) single-engined propeller-driven aeroplanes having an MCTOM of 5 700 kg or less and an MOPSC of 5 or less; or

(2) other-than-complex motor-powered helicopters, single-engined, with an MOPSC of 5 or less.

(c) SECTION 3 specifying additional requirements for commercial specialised operations and for those referred to in b(1) and (2).

Section 1 — Common requirements

ORO.FC.100 Composition of flight crew

(a) The composition of the flight crew and the number of flight crew members at designated crew stations shall be not less than the minimum specified in the aircraft flight manual or operating limitations prescribed for the aircraft.

(b) The flight crew shall include additional flight crew members when required by the type of operation and shall not be reduced below the number specified in the operations manual.

(c) All flight crew members shall hold a licence and ratings issued or accepted in accordance with CAR-FCL and appropriate to the duties assigned to them.

(d) The flight crew member may be relieved in flight of his/her duties at the controls by another suitably qualified flight crew member.

(e) When engaging the services of flight crew members who are working on a freelance or part-time basis, the operator shall verify that all applicable requirements of this Subpart and the relevant elements of CAR-FCL, including the requirements on recent experience, are complied with, taking into account all services rendered by the flight crew member to other operator(s) to determine in particular:

(1) the total number of aircraft types or variants operated; and

(2) the applicable flight and duty time limitations and rest requirements.

AMC1 ORO.FC.100(c) Composition of flight crew

OPERATIONAL MULTI-PILOT LIMITATION (OML)

The operator should ensure that pilots with an OML on their medical certificate only operate aircraft in multi-pilot operations when the other pilot is fully qualified on the relevant type of aircraft, is not subject to an OML and has not attained the age of 60 years.

ORO.FC.105 Designation as pilot-in-command/commander

(a) In accordance with 8.6. of Annex II to CAR-BR, one pilot amongst the flight crew, qualified as pilot-in-command in accordance with CAR-FCL, shall be designated by the operator as pilot-in-command or, for commercial air transport operations, as commander.

(b) The operator shall only designate a flight crew member to act as pilot-in-command/ commander if he/she has:

(1) the minimum level of experience specified in the operations manual;

(2) adequate knowledge of the route or area to be flown and of the aerodromes, including alternate aerodromes, facilities and procedures to be used;

(3) in the case of multi-crew operations, completed an operator's command course if upgrading from co-pilot to pilot-in-command/commander.

(c) In the case of commercial operations of aeroplanes and helicopters, the pilot-in-command/ commander or the pilot, to whom the conduct of the flight may be delegated, shall have had initial familiarisation training of the route or area to be flown and of the aerodromes, facilities and procedures to be used. This route/area and aerodrome knowledge shall be maintained by operating at least once on the route or area or to the aerodrome within a 12 month period.

(d) Point (c) shall not apply in the case of:

(1) performance class B aeroplanes involved in commercial air transport operations under VFR by day; and

(2) commercial air transport operations of passengers conducted under VFR by day, starting and ending at the same aerodrome or operating site or within a local area specified by the competent authority, with other than complex motor-powered helicopters, single-engined, with a MOPSC of 5.

AMC1 ORO.FC.105(b)(2);(c) Designation as pilot-in-command/commander

ROUTE/AREA AND AERODROME KNOWLEDGE FOR COMMERCIAL OPERATIONS

For commercial operations, the experience of the route or area to be flown and of the aerodrome facilities and procedures to be used should include the following:

(a) Area and route knowledge

(1) Area and route training should include knowledge of:

(i) terrain and minimum safe altitudes;

(ii) seasonal meteorological conditions;

(iii) meteorological, communication and air traffic facilities, services and procedures;

(iv) search and rescue procedures where available; and

(v) navigational facilities associated with the area or route along which the flight is to take place.

(2) Depending on the complexity of the area or route, as assessed by the operator, the following methods of familiarisation should be used:

(i) for the less complex areas or routes, familiarisation by self-briefing with route documentation, or by means of programmed instruction; and

(ii) in addition, for the more complex areas or routes, in-flight familiarisation as a pilot-in-command/commander or co-pilot under supervision, observer, or familiarisation in a flight simulation training device (FSTD) using a database appropriate to the route concerned.

(b) Aerodrome knowledge

(1) Aerodrome training should include knowledge of obstructions, physical layout, lighting, approach aids and arrival, departure, holding and instrument approach procedures, applicable operating minima and ground movement considerations.

(2) The operations manual should describe the method of categorisation of aerodromes and, in the case of CAT operations, provide a list of those aerodrome categorised as B or C.

(3) All aerodromes to which an operator operates should be categorised in one of these three categories:

(i) category A — an aerodrome that meets all of the following requirements:

(A) an approved instrument approach procedure;

(B) at least one runway with no performance limited procedure for take-off and/or landing;

(C) published circling minima not higher than 1 000 ft above aerodrome level;

and

(D) night operations capability.

(ii) category B — an aerodrome that does not meet the category A requirements or which requires extra considerations such as:

(A) non-standard approach aids and/or approach patterns;

(B) unusual local weather conditions;

(C) unusual characteristics or performance limitations; or

(D) any other relevant considerations, including obstructions, physical layout, lighting, etc.

(iii) category C — an aerodrome that requires additional considerations to a category B aerodrome;

(iv) offshore installations may be categorised as category B or C aerodromes, taking into account the limitations determined in accordance with AMC1 SPA. HOFO.115 'Use of offshore locations'.

(c) Prior to operating to a:

(1) category B aerodrome, the pilot-in-command/commander should be briefed, or self-briefed by means of programmed instruction, on the category B aerodrome(s) concerned. The completion of the briefing should be recorded. This recording may be accomplished after completion or confirmed by the pilot-in-command/commander before departure on a flight involving category B aerodrome(s) as destination or alternate aerodromes.

(2) category C aerodrome, the pilot-in-command/commander should be briefed and visit the aerodrome as an observer and/or undertake instruction in a suitable FSTD. The completion of the briefing, visit and/or instruction should be recorded.

AMC1 ORO.FC.105(c) Designation as pilot-in-command/commander

ROUTE/AREA AND AERODROME RECENCY

(a) The 12-month period should be counted from the last day of the month:

(1) when the familiarisation training was undertaken; or

(2) of the latest operation on the route or area to be flown and of the aerodromes, facilities and procedures to be used.

(b) When the operation is undertaken within the last 3 calendar months of that period, the new 12-month period should be counted from the original expiry date.

AMC2 ORO.FC.105(c) Designation as pilot-in-command/commander

ROUTE/AREA AND AERODROME RECENCY — PERFORMANCE CLASS B AEROPLANES OPERATED UNDER VFR BY NIGHT OR IFR IN CAT OPERATIONS AND COMMERCIAL OPERATIONS OTHER THAN CAT

In the case of CAT operations with performance class B aeroplanes operating under visual flight rules (VFR) by night or instrument flight rules (IFR), or commercial operations other than CAT, the knowledge should be maintained as follows:

(a) except for operations to the most demanding aerodromes, by completion of at least 10 flight sectors within the area of operation during the preceding 12 months in addition to any required

self-briefing;

(b) operations to the most demanding aerodromes may be performed only if:

(1) the pilot-in-command/commander has been qualified at the aerodrome within the preceding 36 months by a visit as an operating flight crew member or as an observer;

(2) the approach is performed in visual meteorological conditions (VMC) from the applicable minimum sector altitude; and

(3) an adequate self-briefing has been made prior to the flight.

GM1 ORO.FC.105 (b)(2) Route and aerodrome knowledge

ENVIRONMENTAL KNOWLEDGE RELATED TO THE PREVENTION OF AEROPLANE UPSETS

The knowledge should include understanding of:

(a) the relevant environmental hazards, such as:

- Clear Air Turbulence (CAT),
- Intertropical Convergence Zone (ITCZ),
- thunderstorms,
- microbursts,
- wind shear,
- icing,
- mountain waves,
- wake turbulence, and
- temperature changes at high altitude;

(b) the evaluation and management of the associated risks of the relevant hazards in (a); and

(c) the available mitigating procedures for the relevant hazards in (a) related to the specific route, route area, or aerodrome used by the operator.

GM1 ORO.FC.105(d) Designation as pilot-in-command/commander

PERFORMANCE CLASS B AEROPLANES OPERATED UNDER VFR BY DAY IN CAT OPERATIONS

For CAT operations under VFR by day with performance class B aeroplanes, the operator should take account of any requirement that might be stipulated in specific cases by the State of the aerodrome.

ORO.FC.110 Flight engineer

When a separate flight engineer station is incorporated in the design of an aeroplane, the flight crew shall include one crew member who is suitably qualified in accordance with applicable CAR.

ORO.FC.115 Crew resource management (CRM) training

(a) Before operating, the flight crew member shall have received CRM training, appropriate to his/her role, as specified in the operations manual.

(b) Elements of CRM training shall be included in the aircraft type or class training and recurrent training as well as in the command course.

AMC1 ORO.FC.115 Crew resource management (CRM) training

CRM TRAINING — MULTI-PILOT OPERATIONS

(a) General

(1) Training environment

CRM training should be conducted in the non-operational environment (classroom and computer-based) and in the operational environment (flight simulation training device (FSTD) including other training solutions described in CS-FSTD when available and aircraft). Tools such as group discussions, team task analysis, team task simulation and feedback should be used.

(2) Classroom training

Whenever possible, classroom training should be conducted in a group session away from the pressures of the usual working environment, so that the opportunity is provided for flight crew members to interact and communicate in an environment conducive to learning.

(3) Computer-based training (CBT)

Computer-based training should not be conducted as a stand-alone training method, but may be conducted as a complementary training method.

Complementary training method in the context of EBT: advanced CBT following the aviation blended learning environment, such as virtual reality, chatbots, interactive scenario trainers, etc. may serve as the principal method to deliver training in the non-operational environment. In such case, the classroom training may be the complementary method.

(4) Flight simulation training devices (FSTDs)

Whenever practicable, parts of the CRM training should be conducted in FSTDs that reproduce a realistic operational environment and permit interaction. This includes but is not limited to line-oriented flight training (LOFT) scenarios.

(5) Integration into flight crew training

CRM principles should be integrated into relevant parts of flight crew training and operations including checklists, briefings, abnormal and emergency procedures.

(6) Combined CRM training for flight crew, cabin crew and technical crew

(i) Operators should provide combined training for flight crew, cabin crew and technical crew during recurrent CRM training.

(ii) The combined training should address at least:

(A) effective communication, coordination of tasks and functions of flight crew, cabin crew and technical crew; and

(B) mixed multinational and cross-cultural flight crew, cabin crew and technical crew, and their interaction, if applicable.

(iii) The combined training should be expanded to include medical passengers, if applicable

to the operation.

(iv) Combined CRM training should be conducted by flight crew CRM trainer or cabin crew CRM trainer.

(v) There should be an effective liaison between flight crew, cabin crew and technical crew training departments. Provision should be made for transfer of relevant knowledge and skills between flight crew, cabin crew and technical crew CRM trainers.

(7) Management system

CRM training should address hazards and risks identified by the operator's management system described in ORO.GEN.200.

(8) Competency-based CRM training

(i) Whenever practicable, the compliance-based approach concerning CRM training may be substituted by a competency-based approach such as evidence-based training. In this context, CRM training should be characterised by a performance orientation, with emphasis on standards of performance and their measurement, and the development of training to the specified performance standards.

(ii) CRM training should be an essential element of the alternative training and qualification programme (ATQP) described in ORO.FC.A.245, when the operator applies ATQP.

(9) Contracted CRM training

If the operator chooses not to establish its own CRM training, another operator, a third party or a training organisation may be contracted to provide the training in accordance with ORO.GEN.205. In case of contracted CRM training, the operator should ensure that the content of the course covers the specific culture, the type of operations and the associated procedures of the operator. When crew members from different operators attend the same course, the CRM training should be specific to the relevant flight operations and to the trainees concerned.

(b) Initial operator's CRM training

(1) The flight crew member should complete the initial operator's CRM training once. When the type of operation of a new operator is not different, the new operator should not be required to provide the initial operator's CRM training to this flight crew member a second time.

(2) The initial training should cover all elements specified in Table 1 of (g).

(c) Operator conversion course — CRM training

When the flight crew member undertakes a conversion course with a change of aircraft type or change of operator, elements of CRM training should be integrated into all appropriate phases of the operator's conversion course, as specified in Table 1 of (g).

(d) Annual recurrent CRM training

(1) Annual recurrent CRM training should be provided in such a way that all CRM training elements specified for the annual recurrent training in Table 1 of (g) are covered over a period not exceeding 3 years.

(2) Operators should update their CRM recurrent training programme over a period not exceeding 3 years. The revision of the programme should take into account information from the operator's management system including the results of the CRM assessment.

(e) Command course — CRM training

The operator should ensure that elements of CRM training are integrated into the command course, as specified in Table 1 of (g).

(f) Training elements

The CRM training elements to be covered are specified in Table 1 of (g). The operator should ensure that the following aspects are addressed:

(1) Automation and philosophy on the use of automation

(i) The CRM training should include training in the use and knowledge of automation, and in the recognition of systems and human limitations associated with the use of automation. The operator should, therefore, ensure that the flight crew member receives training on:

(A) the application of the operations policy concerning the use of automation as stated in the operations manual; and

(B) system and human limitations associated with the use of automation, giving special attention to issues of mode awareness, automation surprises and over-reliance including false sense of security and complacency.

(ii) The objective of this training should be to provide appropriate knowledge, skills and attitudes for managing and operating automated systems. Special attention should be given to how automation increases the need for crews to have a common understanding of the way in which the system performs, and any features of automation that make this understanding difficult.

(iii) If conducted in an FSTD, the training should include automation surprises of different origin (system- and pilot-induced).

(2) Monitoring and intervention

Flight crew should be trained in CRM-related aspects of operation monitoring before, during and after flight, together with any associated priorities. This CRM training should include guidance to the pilot monitoring on when it would be appropriate to intervene, if felt necessary, and how this should be done in a timely manner. Reference should be made to the operator procedures for structured intervention as specified in the operations manual.

(3) Resilience development

CRM training should address the main aspects of resilience development. The training should cover:

(i) Mental flexibility

Flight crew should be trained to:

(A) understand that mental flexibility is necessary to recognise critical changes;

(B) reflect on their judgement and adjust it to the unique situation;

(C) avoid fixed prejudices and over-reliance on standard solutions; and

(D) remain open to changing assumptions and perceptions.

(ii) Performance adaptation

Flight crew should be trained to:

(A) mitigate frozen behaviours, overreactions and inappropriate hesitation; and

(B) adjust actions to current conditions.

(4) Surprise and startle effect

CRM training should address unexpected, unusual and stressful situations. The training should cover:

(i) surprises and startle effects; and

(ii) management of abnormal and emergency situations, including:

(A) the development and maintenance of the capacity to manage crew resources;

(B) the acquisition and maintenance of adequate automatic behavioural responses; and

(C) recognising the loss and re-building situation awareness and control.

(5) Cultural differences

CRM training should cover cultural differences of multinational and cross-cultural crews. This includes recognising that:

(i) different cultures may have different communication specifics, ways of understanding and approaches to the same situation or problem;

(ii) difficulties may arise when crew members with different mother tongue communicate in a common language which is not their mother tongue; and

(iii) cultural differences may lead to different methods for identifying a situation and solving a problem.

(6) Operator's safety culture and company culture

CRM training should cover the operator's safety culture, its company culture, the type of operations and the associated procedures of the operator. This should include areas of operations that may lead to particular difficulties or involve unusual hazards.

(7) Case studies

(i) CRM training should cover aircraft type-specific case studies, based on the information available within the operator's management system, including:

(A) accident and serious incident reviews to analyse and identify any associated non-technical causal and contributory factors, and instances or examples of lack of CRM; and

(B) analysis of occurrences that were well managed.

(ii) If relevant aircraft type-specific or operator-specific case studies are not available, the operator should consider other case studies relevant to the scale and scope of its operations.

(g) CRM training syllabus

Table 1 below specifies which CRM training elements should be covered in each type of training. The levels of training in Table 1 can be described as follows:

(1) 'Required' means training that should be instructional or interactive in style to meet the objectives specified in the CRM training programme or to refresh and strengthen knowledge gained in a previous training.

(2) 'In-depth' means training that should be instructional or interactive in style taking full advantage of group discussions, team task analysis, team task simulation, etc., for the acquisition or consolidation of knowledge, skills and attitudes. The CRM training elements should be tailored to the specific needs of the training phase being undertaken.

Table 1 — Flight crew CRM training

CRM training elements	Initial operator's CRM training	Operator conversion course when changing aircraft type	Operator conversion course when changing operator	Annual recurrent training	Command course
General principles					
Human factors in aviation; General instructions on CRM principles and objectives; Human performance and limitations; Threat and error management.	In-depth	Required	Required	Required	Required
Relevant to the individual flight crew member					
Personality awareness, human error and reliability, attitudes and behaviours, self-assessment and self-critique; Stress and stress management; Fatigue and vigilance; Assertiveness, situation awareness, information acquisition and processing.	In-depth	Not required	Not required	Required	In-depth
Relevant to the flight crew					
Automation and philosophy on the use of automation	Required	In-depth	In-depth	In-depth	In-depth
Specific type-related differences	Required	In-depth	Not required	Required	Required
Monitoring and intervention	Required	In-depth	In-depth	Required	Required
Relevant to the entire aircraft crew					
Shared situation awareness, shared information acquisition and processing; Workload management; Effective communication and coordination inside and outside the flight crew compartment;	In-depth	Required	Required	Required	In-depth
Leadership, cooperation, synergy, delegation, decision-making, actions; Resilience development; Surprise and startle effect; Cultural differences.					
Relevant to the operator and the organisation					
Operator's safety culture and company culture, standard operating procedures (SOPs), organisational factors, factors linked to the type of operations;	In-depth	Required	In-depth	Required	In-depth

CRM training elements	Initial operator's CRM training	Operator conversion course when changing aircraft type	Operator conversion course when changing operator	Annual recurrent training	Command course
Effective communication and coordination with other operational personnel and ground services.					
Case studies	In-depth	In-depth	In-depth	In-depth	In-depth

(h) Assessment of CRM skills

(1) Assessment of CRM skills is the process of observing, recording, interpreting and debriefing crews and crew member's performance using an accepted methodology in the context of the overall performance.

(2) The flight crew member's CRM skills should be assessed in the operational environment, but not during CRM training in the non-operational environment. Nevertheless, during training in the non-operational environment, feedback from the flight crew CRM trainer or from trainees on individual and crew performance may be given to the crew members concerned.

(3) The assessment of CRM skills should:

(i) include debriefing the crew and the individual crew member;

(ii) serve to identify additional training, where needed, for the crew or the individual crew member; and

(iii) be used to improve the CRM training system by evaluating de-identified summaries of all CRM assessments.

(4) Prior to the introduction of CRM skills assessment, a detailed description of the CRM methodology, including the required CRM standards and the terminology used for the assessment, should be published in the operations manual.

(5) Methodology of CRM skills assessment

The assessment should be based on the following principles:

(i) only observable behaviours are assessed;

(ii) the assessment should positively reflect any CRM skills that result in enhanced safety; and

(iii) assessments should include behaviour that results in an unacceptable reduction in safety margin.

(6) Operators should establish procedures, including additional training, to be applied in the event that flight crew members do not achieve or maintain the required CRM standards.

AMC2 ORO.FC.115 Crew resource management (CRM) training

CRM TRAINING — SINGLE-PILOT OPERATIONS

(a) For single-pilot helicopter operations with technical crew, AMC1 ORO.FC.115 should be applied.

(b) For single-pilot operations other than those specified in (a), AMC1 ORO.FC.115 should be applied with the following differences:

(1) Relevant training

Training should cover the relevant CRM training, i.e. initial operator's training, the operator conversion course and recurrent training.

(2) Relevant training elements

CRM training should focus on the elements specified in Table 1 of (g) of AMC1 ORO.FC.115 which are relevant to single-pilot operations. Therefore, single-pilot CRM training should include, among others:

(i) situation awareness;

(ii) workload management;

(iii) decision-making;

(iv) resilience development;

(v) surprise and startle effect; and

(vi) effective communication and coordination with other operational personnel and ground services.

(3) Computer-based training

Notwithstanding (a)(3) of AMC1 ORO.FC.115, computer-based training may be conducted as a stand-alone training method.

(4) Operation with ELA2 aircraft

Notwithstanding (1) and (2), for operations with ELA2 aircraft the relevant CRM training and its duration should be determined by the operator, based on the aircraft type and the complexity of the operation.

AMC3 ORO.FC.115 Crew resource management (CRM) training

FLIGHT CREW CRM TRAINER

(a) Applicability

The provisions described herein:

(1) should be fulfilled by flight crew CRM trainers responsible for classroom CRM training; and

(2) are not applicable to:

(i) instructors, holding a certificate in accordance with CAR-PART II (Licensing and Training Organisation Regulations), who conduct CRM training in the operational environment; and

(ii) trainers or instructors conducting training other than CRM training, but integrating CRM elements into this training.

(b) Qualification of flight crew CRM trainer

(1) A training and standardisation programme for flight crew CRM trainers should be established.

(2) A flight crew CRM trainer, in order to be suitably qualified, should:

(i) have adequate knowledge of the relevant flight operations;

(ii) have adequate knowledge of human performance and limitations (HPL), whilst:

(A) having obtained a commercial pilot licence in accordance with CAR-FCL; or

(B) having followed a theoretical HPL course covering the whole syllabus of the HPL examination;

(iii) have completed flight crew initial operator's CRM training;

(iv) have received training in group facilitation skills;

(v) have received additional training in the fields of group management, group dynamics and personal awareness; and

(vi) have demonstrated the knowledge, skills and credibility required to train the CRM training elements in the non-operational environment, as specified in Table 1 of AMC1 ORO.FC.115.

(3) The following qualifications and experiences are also acceptable for a flight crew CRM trainer in order to be suitably qualified:

(i) A flight crew member holding a recent qualification as a flight crew CRM trainer may continue to be a flight crew CRM trainer after the cessation of active flying duties if he/she maintains adequate knowledge of the relevant flight operations.

(ii) A former flight crew member may become a flight crew CRM trainer if he/she maintains adequate knowledge of the relevant flight operations and fulfils the provisions of (2)(ii) to (2)(vi).

(iii) An experienced CRM trainer may become a flight crew CRM trainer if he/she demonstrates adequate knowledge of the relevant flight operations and fulfils the provisions of (2)(ii) to (2)(vi).

(c) Training of flight crew CRM trainer

(1) Training of flight crew CRM trainers should be both theoretical and practical. Practical elements should include the development of specific trainer skills, particularly the integration of CRM into line operations.

(2) The basic training of flight crew CRM trainers should include the training elements for flight crew, as specified in Table 1 of AMC1 ORO.FC.115. In addition, the basic training should include the following:

(i) introduction to CRM training;

(ii) operator's management system;

(iii) characteristics, as applicable:

(A) of the different types of CRM trainings (initial, recurrent, etc.);

(B) of combined training; and

(C) related to the type of aircraft or operation; and

(iv) assessment.

(3) The refresher training of flight crew CRM trainers should include new methodologies, procedures and lessons learned.

(4) Instructors, holding a certificate in accordance with CAR-FCL, who are also CRM trainers, may combine the CRM trainer refresher training with instructor refresher training.

(5) Instructors for other-than complex motor-powered aircraft should be qualified as flight crew CRM trainers for this aircraft category with no additional training, as specified in (2) and (3) when:

(i) holding a certificate in accordance with CAR-FCL,; and

(ii) fulfilling the provisions of (b)(2) or (b)(3).

(6) The training of flight crew CRM trainers should be conducted by flight crew CRM trainers with a minimum of 3 years' experience. Assistance may be provided by experts in order to address specific areas.

(d) Assessment of flight crew CRM trainer

(1) A flight crew CRM trainer should be assessed by the operator when conducting the first CRM training course. This first assessment should be valid for a period of 3 years.

(2) The operator should ensure that the process for the assessment is included in the operations manual describing methods for observing, recording, interpreting and debriefing the flight crew CRM trainer. All personnel involved in the assessment must be credible and competent in their role.

(3).G Personnel conducting assessments on flight crew CRM trainers should be initially accepted by the competent authority.

(e) Recency and renewal of qualification as flight crew CRM trainer

(1) For recency of the 3-year validity period, the flight crew CRM trainer should:

(i) conduct at least 2 CRM training events in any 12-month period;

(ii) be assessed within the last 12 months of the 3-year validity period by the operator; and

(iii) complete CRM trainer refresher training within the 3-year validity period.

(2) The next 3-year validity period should start at the end of the previous period.

(3) For renewal, i.e. when a flight crew CRM trainer does not fulfil the provisions of (1), he/she should, before resuming as flight crew CRM trainer:

(i) comply with the qualification provisions of (b) and (d); and

(ii) complete CRM trainer refresher training.

GM1 ORO.FC.115 Crew resource management (CRM) training

GENERAL

(a) CRM is the effective utilisation of all available resources (e.g. crew members, aircraft systems, supporting facilities and persons) to achieve safe and efficient operation.

(b) The objective of CRM is to enhance the communication and management skills of the flight crew member concerned. Emphasis is placed on the non-technical knowledge, skills and attitudes of flight crew performance.

GM2 ORO.FC.115 Crew resource management (CRM) training

TRAINING ENVIRONMENT, TRAINERS AND INSTRUCTORS

(a) Flight crew CRM training can be separated as follows:

(1) training in the non-operational environment:

(i) classroom; and

(ii) computer-based;

(2) training in the operational environment:

(i) flight simulation training device (FSTD); and

(ii) aircraft.

(b) In general, CRM training is provided as follows:

(1) classroom training by a flight crew CRM trainer;

(2) training in the operational environment by an instructor holding a certificate in accordance with the applicable requirements;

(3) computer-based training as a self-study training method. If needed, directions concerning CRM-related issues are provided by a flight crew CRM trainer or by an instructor holding a certificate in accordance with applicable requirements.

GM3 ORO.FC.115 Crew resource management (CRM) training

MINIMUM TRAINING TIMES

(a) The following minimum training times are appropriate:

(1) multi-pilot operations:

(i) combined CRM training: 6 training hours over a period of 3 years; and

(ii) initial operator's CRM training: 18 training hours with a minimum of 12 training hours in classroom training;

(2) initial operator's CRM training for single-pilot operations: 6 training hours; and

(3) flight crew CRM trainer:

(i) basic training:

(A) 18 training hours for trainees holding an instructor certificate for complex motor-powered aircraft, as specified in CAR FCL, which includes 25-hour training in teaching and learning; or

(B) 30 training hours for trainees who do not hold an instructor certificate as specified in (A); and

(ii) refresher training: 6 training hours.

(b) 'Training hours' means actual training time excluding breaks and assessment.

GM4 ORO.FC.115 Crew resource management (CRM) training

DESIGN, IMPLEMENTATION AND EVALUATION OF CRM TRAINING

The checklist in Table 1 provides guidance on the design, implementation and evaluation of CRM training, and on their incorporation into the operator's safety culture. Elements of the operator's management systems and the competency-based approach are incorporated in the checklist.

Table 1 — Checklist for design, implementation, evaluation and incorporation of CRM training

Step No	Description	Element
1	Needs analysis	Determine the necessary CRM competencies
		Develop CRM training goals
		Ensure the organisation is ready for CRM training
2	Design	Develop CRM training objectives
		Determine what to measure and how to measure it
3	Development	Describe the CRM learning environment
		Develop full-scale prototype of training
		Validate and modify CRM training
4	Implementation	Prepare trainees and environment
		Set a climate for learning (e.g. practice and feedback)
		Implement the CRM training programme
5	Evaluation	Determine training effectiveness
		Evaluate CRM training at multiple levels
		Revise the CRM training programme to improve effectiveness
6	Incorporation	Establish an environment where CRM training is positively recognised
		Reinforce CRM behaviours in daily work
		Provide recurrent CRM training

GM5 ORO.FC.115 Crew resource management (CRM) training

RESILIENCE DEVELOPMENT

(a) The main aspects of resilience development can be described as the ability to:

(1) learn (‘knowing what has happened’);

(2) monitor (‘knowing what to look for’);

(3) anticipate (‘finding out and knowing what to expect’); and

(4) respond (‘knowing what to do and being capable of doing it’).

(b) Operational safety is a continuous process of evaluation of and adjustment to existing and future conditions. In this context, and following the description in (a), resilience development involves an ongoing and adaptable process including situation assessment, self-review, decision and action. Training in resilience development enables crew members to draw the right conclusions from both positive and negative experiences. Based on those experiences, crew members are better prepared to maintain or create safety margins by adapting to dynamic complex situations.

(c) The training topics in (f)(3) of AMC1 ORO.FC.115 are to be understood as follows:

(1) Mental flexibility

(i) The phrase ‘understand that mental flexibility is necessary to recognise critical changes’ means that crew members are prepared to respond to situations for which there is no set procedure.

(ii) The phrase ‘reflect on their judgement and adjust it to the unique situation’ means that crew members learn to review their judgement based on the unique characteristics of the given circumstances.

(iii) The phrase ‘avoid fixed prejudices and over-reliance on standard solutions’ means that crew members learn to update solutions and standard response sets, which have been formed on prior knowledge.

(iv) The phrase 'remain open to changing assumptions and perceptions' means that crew members constantly monitor the situation, and are prepared to adjust their understanding of the evolving conditions.

(2) Performance adaptation

(i) The phrase 'mitigate frozen behaviours, overreactions and inappropriate hesitation' means that crew members correct improper actions with a balanced response.

(ii) The phrase 'adjust actions to current conditions' means that crew members' responses are in accordance with the actual situation.

GM6 ORO.FC.115 Crew resource management (CRM) training

NON-TECHNICAL SKILLS ASSESSMENT

(a) NOTECHS (non-technical skills) is a validated method for assessing flight crew CRM skills. The NOTECHS framework consists of four main categories:

(1) Cooperation: Cooperation is the ability to work effectively in a crew.

(2) Leadership and managerial skills: Effective leadership and managerial skills help to achieve joint task completion within a motivated, fully functioning team through coordination and persuasiveness.

(3) Situation awareness: Situation awareness relates to one's ability to accurately perceive what is in the flight crew compartment and outside the aircraft. It is also one's ability to comprehend the meaning of different elements in the environment and the projection of their status in the near future.

(4) Decision-making: Decision-making is the process of reaching a judgement or choosing an option.

(b) Each of the four categories is subdivided into elements and behavioural markers. The elements are specified in Table 1 with examples of behavioural markers (effective behaviour). The behavioural markers are assessed by a rating scale to be established by the operator.

Table 1 — Categories, elements and behavioural markers of NOTECHS

Category	Element	Behavioural marker (examples)
Cooperation	Team building and maintaining	Establishes atmosphere for open communication and participation
	Considering others	Takes condition of other crew members into account
	Supporting others	Helps other crew members in demanding situations
	Conflict solving	Concentrates on what is right rather than who is right
Leadership and managerial skills	Use of authority and assertiveness	Takes initiative to ensure crew involvement and task completion
	Maintaining standards	Intervenes if task completion deviates from standards
	Planning and coordination	Clearly states intentions and goals
	Workload management	Allocates adequate time to complete tasks
Situation awareness	Awareness of aircraft systems	Monitors and reports changes in systems' states
	Awareness of external environment	Collects information about environment (position, weather and traffic)
	Anticipation	Identifies possible future problems
Decision-making	Problem definition and diagnosis	Reviews causal factors with other crew members
	Option generation	States alternative courses of action
		Asks other crew members for options
	Risk assessment and option selection	Considers and shares estimated risk of alternative courses of action
	Outcome review	Checks outcome against plan

GM7 ORO.FC.115 Crew resource management (CRM) training

FLIGHT CREW CRM TRAINER ASSESSMENT

(a) For assessing flight crew CRM trainers, the operator may nominate experienced flight crew CRM trainers who have demonstrated continued compliance with the provisions for a flight crew CRM trainer and capability in that role for at least 3 years.

(b) An operator that does not have the resources to conduct the assessment may employ a contractor. The standard as regards the assessment is confirmed on a 3-year basis by the operator.

(c) The checklist in Table 1 provides guidance on the assessment of a flight crew CRM trainer. If a flight crew CRM trainer is competent in his/her role, the response to the questions in Table 1 should be 'yes'. When answering the questions in Table 1, justifications and examples related to the responses given should be provided.

Table 1 — Flight crew CRM trainer assessment checklist

Questions to assess a flight crew CRM trainer	Response yes/no
Did the CRM trainer demonstrate the knowledge required for the role?	
Did the CRM trainer support CRM concepts?	
Did the CRM trainer encourage trainees to participate, share their experiences and self-analyse?	
Did the CRM trainer identify and respond to the trainees' needs relative to expertise/experience?	
Did the CRM trainer show how CRM is integrated in technical training and line operations?	
Did the CRM trainer incorporate company CRM standards when appropriate?	
Did the CRM trainer identify and discuss the non-technical reasons involved in accidents, incidents and events included in case studies?	
Did the CRM trainer regularly check for understanding and resolve ambiguities?	
Did the CRM trainer demonstrate effective instruction and facilitation skills?	

ORO.FC.120 Operator conversion training

(a) In the case of aeroplane or helicopter operations, the flight crew member shall complete the operator conversion training course before commencing unsupervised line flying:

(1) when changing to an aircraft for which a new type or class rating is required;

(2) when joining an operator.

(b) The operator conversion training course shall include training on the equipment installed on the aircraft as relevant to flight crew members' roles.

AMC1 ORO.FC.120&130 Operator conversion training and checking & recurrent training and checking

FLIGHT PATH MANAGEMENT (MANUAL OR AUTOMATIC, AS APPROPRIATE) DURING UNRELIABLE AIRSPEED INDICATION AND OTHER FAILURES AT HIGH ALTITUDE IN AEROPLANES WITH A MAXIMUM CRUISING ALTITUDE ABOVE FL300

For the operation of aeroplanes with a maximum cruising altitude above FL300, training elements from the following table should be integrated into:

(a) operator conversion training; and

(b) recurrent training at least every 12 calendar months, such that all elements are covered over a period not exceeding 3 years:

Element	Theoretical Knowledge	Practical training
Basic flight physics principles concerning flight at high altitude, with a particular emphasis on the relative proximity of the critical Mach number and the stall, pitch behaviour, and an understanding of the reduced stall angle of attack when compared with low altitude flight.	•	•
Interaction of the automation (autopilot, flight director, autothrottle/auto-thrust) and the consequences of failures inducing disconnection of the automation.	•	•
Consequences of an unreliable airspeed indication and other failures at high altitude and the need for the flight crew to promptly identify the failure and react with appropriate (minimal) control inputs to keep the aircraft in a safe envelope.	•	•
Degradation of fly-by-wire (FBW) flight control laws/modes and its consequence on aircraft stability and flight envelope protections, including stall warnings.	•	•
Practical training, using appropriate simulators, on manual handling at high altitude in normal and non-normal flight control laws/modes, with particular emphasis on pre-stall buffet, the reduced stall angle of attack when compared with low-altitude flight and the effect of pitch inputs on the aircraft trajectory and energy state.		•
The requirement to promptly and accurately apply the stall recovery procedure, as provided by the aircraft manufacturer, at the first indication of an impending stall. Differences between high-altitude and low-altitude stalls must be addressed.	•	•
Procedures for taking over and transferring manual control of the aircraft, especially for FBW aeroplanes with independent side-sticks.	•	•
Task sharing and crew coordination in high workload/stress conditions with appropriate call-out and acknowledgement to confirm changes to the aircraft flight control law/mode	•	•

ORO.FC.125 Differences training and familiarisation training

(a) Flight crew members shall complete differences or familiarisation training when required by CAR-FCL and when changing equipment or procedures requiring additional knowledge on types or variants currently operated.

(b) The operations manual shall specify when such differences or familiarisation training is required.

AMC1 ORO.FC.125 Differences training and familiarisation training

GENERAL

(a) Differences training requires additional knowledge and training on the aircraft or an appropriate training device. It should be carried out:

(1) when introducing a significant change of equipment and/or procedures on types or variants currently operated; and

(2) in the case of aeroplanes, when operating another variant of an aeroplane of the same type or another type of the same class currently operated; or

(3) in the case of helicopters, when operating a variant of a helicopter currently operated.

(b) Familiarisation training requires only the acquisition of additional knowledge. It should be carried out when:

(1) operating another helicopter or aeroplane of the same type; or

(2) when introducing a significant change of equipment and/or procedures on types or variants currently operated.

ORO.FC.130 Recurrent training and checking

(a) Each flight crew member shall complete annual recurrent flight and ground training relevant to the type or variant of aircraft on which he/she operates, including training on the location and use of all emergency and safety equipment carried.

(b) Each flight crew member shall be periodically checked to demonstrate competence in carrying out normal, abnormal and emergency procedures.

ORO.FC.135 Pilot qualification to operate in either pilot's seat

Flight crew members who may be assigned to operate in either pilot's seat shall complete appropriate training and checking as specified in the operations manual.

ORO.FC.140 Operation on more than one type or variant

(a) Flight crew members operating more than one type or variant of aircraft shall comply with the requirements prescribed in this Subpart for each type or variant, unless credits related to the training, checking, and recent experience requirements are defined in the mandatory part of the operational suitability data, or equivalent, established in accordance with CAR 21 for the relevant types or variants.

(b) Appropriate procedures and/or operational restrictions shall be specified in the operations manual for any operation on more than one type or variant.

ORO.FC.145 Provision of training, checking and assessment

(a) All training, checking and assessment required in this Subpart shall be conducted in accordance with the training programmes and syllabi established by the operator in the operations manual;

(b) When establishing the training programmes and syllabi, the operator shall include the relevant elements defined in the mandatory part of the operational suitability data established in accordance with CAR-21 or equivalent.

(c) In the case of CAT operations, training and checking programmes, including syllabi and use of individual flight simulation training devices (FSTDs), shall be approved by the competent authority.

(d) The FSTD shall replicate the aircraft used by the operator, as far as practicable. Differences between the FSTD and the aircraft shall be described and addressed through a briefing or training, as appropriate.

(e) The operator shall establish a system to adequately monitor changes to the FSTD and to ensure that those changes do not affect the adequacy of the training programmes.

AMC1 ORO.FC.145(b) Provision of training, checking and assessment

NON-MANDATORY (RECOMMENDATION) ELEMENTS OF OPERATIONAL SUITABILITY DATA OR EQUIVALENT

When developing the training programmes and syllabi, the operator should consider the non-mandatory (recommendation) elements for the relevant type that are provided in the operational suitability data established in accordance with CAR 21.

AMC1 ORO.FC.145(d) Provision of training, checking and assessment

FULL FLIGHT SIMULATORS (FFS)

The operator should classify any differences between the aircraft and FFS in accordance with the Air Transport Association (ATA) chapters as follows:

Compliance Levels

(a) Level A differences:

(1) no influence on flight characteristics;

(2) no influence on procedures (normal and/or abnormal);

(3) differences in presentation; and

(4) differences in operation.

Method: self-instruction via the operations manual or flight crew information.

(b) Level B differences:

(1) no influence on flight characteristics;

(2) influence on procedures (normal and/or abnormal); and

(3) possible differences in presentation and operation.

Method: flight crew information, computer-based training, system device training or special instruction by instructor.

(c) Level C differences:

(1) influence on flight characteristics;

(2) influence on procedures (normal and/or abnormal); and

(3) eventually differences in presentation and operation.

Method: special instruction by instructor, a selected partial training on another FSTD or aircraft or a waiver because of previous experience, special instruction or training programme.

(d) Level D differences:

(1) influence on flight characteristics; and/or

(2) influence on procedures (normal and/or abnormal); and/or

(3) differences in presentation and/or operation; and

(4) FSTD is level D qualified and is used for zero flight-time training (ZFTT).

Method: a specified partial training on another FSTD or aircraft or a waiver because of previous experience, special instruction or training programme.

ORO.FC.146 Personnel providing training, checking and assessment

(a) All training, checking and assessment required in this Subpart shall be conducted by appropriately qualified personnel.

(b) In the case of flight and flight simulation training and checking, the personnel that provides the training and conducts the checks shall be qualified in accordance with CAR-FCL.

(c) For an EBT programme, the personnel that performs assessment and provides training shall:

(1) hold a CAR-FCL instructor or examiner certificate;

(2) complete the operator's EBT instructor standardisation programme. This shall include an initial standardisation programme and a recurrent standardisation programme.

Completion of the operator's EBT initial standardisation will qualify the instructor to perform EBT practical assessment.

(d) Notwithstanding point (b) above, the line evaluation of competence shall be conducted by a suitably qualified commander nominated by the operator that is standardised in EBT concepts and the assessment of competencies (line evaluator).

AMC1 ORO.FC.146(c) Personnel providing training, checking and assessment

EBT INSTRUCTOR — INITIAL STANDARDISATION PROGRAMME

(a) Before delivering the operator's EBT programme, the instructor should complete an EBT instructor initial standardisation programme composed of:

(1) EBT instructor training; and

(2) EBT assessment of competence.

EBT INSTRUCTOR TRAINING

(b) The EBT instructor training course should be delivered by at least one pilot who is or has been an EBT instructor, and who has demonstrated proficiency to train the elements specified in point (c) below.

(c) The EBT instructor training course should comprise theoretical and practical training. At the completion of EBT instructor training, the instructor should:

(1) have knowledge of EBT, including the following underlying principles:

(i) competency-based training;

(ii) learning from positive performance;

(iii) building resilience; and

(iv) data-driven training;

(2) demonstrate knowledge of the structure of an EBT module;

(3) demonstrate knowledge of the method of training delivery for each phase of an EBT module;

(4) demonstrate knowledge of the principles of adult learning and how they relate to EBT;

(5) conduct objective observations based on a competency framework, and document evidence of observed performance;

(6) relate specific performance observations of competencies;

(7) analyse trainee performance to determine competency-based training needs and recognise strengths;

(8) evaluate performance using a competency-based grading system;

(9) apply appropriate teaching styles during simulator training to accommodate trainee learning needs;

(10) facilitate trainee learning, focusing on specific competency-based training needs; and

(11) conduct a debrief using facilitation techniques.

(d) An instructor may be given credits for parts of point (c) if the instructor has demonstrated competencies in those topics.

EBT ASSESSMENT OF COMPETENCE

(e) Prior to conducting assessment and training within an EBT programme, the EBT instructor should complete an EBT assessment of competence where the EBT instructor delivers:

(1) an evaluation phase (EVAL) and a manoeuvres training phase (MT); or

(2) a scenario-based training phase (SBT).

(f) The assessment of competence has a validity period of 3 years counted from the end of the month the assessment of competence was conducted.

(g) The EBT assessment of competence should be conducted by a person nominated by the operator, who:

(1) is qualified in accordance with CAR-FCL to conduct an assessment of competence; and

(2) has completed the EBT instructor standardisation.

(h) The EBT assessment of competence may be combined with the assessment of competence required in CAR-FCL.

AMC2 ORO.FC.146(c) Personnel providing training, checking and assessment

EBT INSTRUCTOR — RECURRENT STANDARDISATION PROGRAMME

The EBT instructor should:

(a) conduct six EVAL or SBT phases of an EBT module (or a combination of both) every 36 months. One of the EVAL or SBT should take place in the period of 12 months immediately preceding the expiry date. The 36-month period should be counted from the end of the month the module was taken. If this has not been fulfilled, the EBT instructor should complete an EBT assessment of competence. When the module is undertaken within the last 12 months of the validity period, the new period should be counted from the original expiry date;

(b) receive annual recurrent standardisation. The recurrent standardisation should include:

(1) refresher EBT training; and

(2) concordance training; and

(c) complete an assessment of competence every 3 years. When the assessment of competence is conducted within the 12 months preceding the expiry date, the next assessment of competence should be completed within 36 calendar months of the original expiry date of the previous assessment of competence.

GM1 ORO.FC.146(c) Personnel providing training, checking and assessment

EBT INSTRUCTOR — INITIAL STANDARDISATION

(a) The intent of the practical training is to ensure that EBT instructors have exposure to assessment of performance and root cause identification within an EBT programme.

(b) EBT instructors receive practical assistance and guidance during standardisation in order to apply the learning from EBT instructor training. In particular, the focus should be on assessment of performance and the determination of root cause for remediation, plus facilitated debriefing based on root cause as a learning objective.

(c) The pilot delivering the training may be supported by a subject matter expert (or experts). The personnel providing the EBT training is selected by the operator to assess the instructor capability in delivering EBT and provide effective feedback in order that instructor practice meets the expectations of the operator.

(d) Practical EBT training includes the learning objective ‘Evaluate performance using a competency-based grading system’. This may be done with videos and other multimedia. It means that EBT instructors are exposed to:

(1) different levels of pilot performance. This enables EBT instructors to distinguish between pilots performing lower than the minimum acceptable level of performance (e.g. grade 1) and those whose performance is at an acceptable level in all competencies (e.g. grade 2). This EBT training may also include other performance examples (e.g. 3, 4 and 5); and

(2) different scenarios (e.g. complex to less complex) so that the instructor has exposure to assessments of competency in varying EBT scenarios.

(e) The EBT instructor training course may be a minimum of 14 hours (EBT instructor training alone) and the recommended length is between 21 to 24 hours (EBT instructor training plus assessment of competence).

GM2 ORO.FC.146(c) Personnel providing training, checking and assessment

EBT INSTRUCTOR — RECURRENT STANDARDISATION

(a) Refresher EBT training

The intent of this training is to provide the framework for existing instructors to develop their competence to conduct EBT. Further guidance can be found in the EASA EBT manual.

(b) Concordance training

This training is one of the elements to ensure concordance within the EBT instructor community. Those EBT instructors who do not demonstrate concordance may require further training. The operator's instructor standardisation and concordance assurance programme provides insight in the areas that an instructor (or instructor population) requires concordance training. As such, concordance training varies in content and scale depending on the need for concordance improvement. Instructor concordance training may include candidates grading the same controlled content (e.g. a video or paper case) followed by:

(1) a subsequent comparison of intra-group variance; and

(2) alignment of root-cause analyses between instructors.

GM3 ORO.FC.146(c) Personnel providing training, checking and assessment

EBT INSTRUCTOR COMPETENCY FRAMEWORK

Pilot competencies[1]	
Description:	See pilot competency framework
Instructor observable behaviour (iOB)	See pilot competency framework

[1] For ground instructors, some competencies may not apply. For the instructor assessment of competence, these competencies may not be observed. A review of the records of the instructor may be sufficient.

Management of the learning environment	
Description:	Ensures that the instruction, assessment and evaluation are conducted in a suitable and safe environment
iOB 2.1	Applies TEM in the context of instruction/evaluation
iOB 2.2	Briefs on safety procedures for situations that are likely to develop during instruction/evaluation
iOB 2.3	Intervenes appropriately, at the correct time and level (e.g. progresses from verbal assistance to taking over control)
iOB 2.4	Resumes instruction/evaluation as practicable after any intervention
iOB 2.5	Plans and prepares training media, equipment and resources
iOB 2.6	Briefs on training devices or aircraft limitations that may influence training, when applicable
iOB 2.7	Creates and manages conditions (e.g. airspace, ATC, weather, time, etc.) to be suitable for the training objectives
iOB 2.8	Adapts to changes in the environment whilst minimising training disruptions
iOB 2.9	Manages time, training media and equipment to ensure that training objectives are met

Instruction	
Description:	Conducts training to develop the trainee's competencies
iOB 3.1	References approved sources (operations, technical and training manuals, standards and regulations)
iOB 3.2	States clearly the objectives and clarifies roles for the training
iOB 3.3	Follows the approved training programme
iOB 3.4	Applies instructional methods as appropriate (e.g. explanation, demonstration, learning by discovery, facilitation, in-seat instruction)
iOB 3.5	Sustains operational relevance and realism
iOB 3.6	Adapts the amount of instructor inputs to ensure that the training objectives are met
iOB 3.7	Adapts to situations that might disrupt a planned sequence of events
iOB 3.8	Continuously assesses the trainee's competencies (e.g. by including the root cause(s) of the deficiency(-ies) observed according to the competency framework)
iOB 3.9	Encourages the trainee to self-assess
iOB 3.10	Allows the trainee to self-correct in a timely manner
iOB 3.11	Applies trainee-centred feedback techniques (e.g. facilitation, etc.)
iOB 3.12	Provides positive reinforcement

Interaction with the trainees	
Description:	Supports the trainees' learning and development and demonstrates exemplary behaviour (role model)
iOB 4.1	Shows respect for the trainee (e.g. for culture, language and experience)
iOB 4.2	Shows patience and empathy (e.g. by actively listening, reading non-verbal messages and encouraging dialogue)
iOB 4.3	Manages trainees' barriers to learning
iOB 4.4	Encourages engagement and mutual support between the trainees
iOB 4.5	Coaches the trainees
iOB 4.6	Supports the goal and training policies of the operator/ATO and authority
iOB 4.7	Shows integrity (e.g. honesty and professional principles)
iOB 4.8	Demonstrates acceptable personal conduct, acceptable social practices, content expertise, a model for professional and interpersonal behaviour
iOB 4.9	Actively seeks and accepts feedback to improve own performance

Assessment and evaluation	
Description:	Assesses the competencies of the trainee and contributes to continuous training system improvement
iOB 5.1	Complies with operator/ATO and authority requirements
iOB 5.2	Ensures that the trainee understands the assessment process
iOB 5.3	Applies the competency standards and conditions
iOB 5.4	Assesses trainee's competency (-ies)
iOB 5.5	Performs grading
iOB 5.6	Provides recommendations based on the outcome of the assessment
iOB 5.7	Makes decisions based on the outcome of assessments
iOB 5.8	Provides clear feedback to the trainee
iOB 5.9	Reports strengths and weaknesses of the training system (e.g. training environment, curriculum, assessment/evaluation) including feedback from trainees
iOB 5.10	Suggests improvements for the training system
iOB 5.11	Produces reports using appropriate forms and media

The recommended competency assessment grading system methodology for instructor competencies should be the same as the one used for pilots. This is the Venn model. More information can be found in ORO.FC.231 point (d)(1) and the related AMC and GM, as well as in the EASA EBT manual.

Section 2 — Additional requirements for commercial air transport operations

ORO.FC.200 Composition of flight crew

(a) There shall not be more than one inexperienced flight crew member in any flight crew.

(b) The commander may delegate the conduct of the flight to another pilot suitably qualified in accordance with CAR-FCL provided that the requirements of ORO.FC.105 (b)(1), (b)(2) and (c) are complied with.

(c) Specific requirements for aeroplane operations under instrument flight rules (IFR) or at night.

(1) The minimum flight crew shall be two pilots for all turbo-propeller aeroplanes with a maximum operational passenger seating configuration (MOPSC) of more than nine and all turbojet aeroplanes.

(2) Aeroplanes other than those covered by (c)(1) shall be operated with a minimum crew of two pilots, unless the requirements of ORO.FC.202 are complied with, in which case they may be operated by a single pilot.

(d) Specific requirements for helicopter operations.

(1) For all operations of helicopters with an MOPSC of more than 19 and for operations under IFR of helicopters with an MOPSC of more than 9:

(i) the minimum flight crew shall be two pilots; and

(ii) the commander shall be the holder of an airline transport pilot licence (helicopter) (ATPL(H)) with an instrument rating issued in accordance with CAR-FCL.

(2) Operations not covered by (d)(1) may be operated by a single pilot under IFR or at night provided that the requirements of ORO.FC.202 are complied with.

(e).G Minimum flight crew for single-engined aeroplane operations under VFR.

Single pilot operations on single-engined aeroplanes under VFR with MOPSC of nine or less or MCTOM of 5 700 kg or less, and when allowed by the AFM, may be performed for A to A or A to B operations within UAE or within the region subject to acceptability by the applicable State.

AMC1 ORO.FC.200(a) Composition of flight crew

CREWING OF INEXPERIENCED FLIGHT CREW MEMBERS

The operator should establish procedures in the operations manual taking into account the following elements:

Aeroplanes

(a) The operator should consider that a flight crew member is inexperienced, following completion of a type rating or command course, and the associated line flying under supervision, until he/she has achieved on the type either:

(1) 100 flight hours and flown 10 sectors within a consolidation period of 120 consecutive days; or

(2) 150 flight hours and flown 20 sectors (no time limit).

(b) A lesser number of flight hours or sectors, subject to any other conditions that the competent authority may impose, may be acceptable to the competent authority when one of the following applies:

(1) a new operator is commencing operations;

(2) an operator introduces a new aeroplane type;

(3) flight crew members have previously completed a type conversion course with the same operator;

(4) credits are defined in the operational suitability data or equivalent established in accordance with CAR 21; or

(5) the aeroplane has a maximum take-off mass of less than 10 tonnes or a maximum operational passenger seating configuration (MOPSC) of less than 20.

Helicopters

(c) The operator should consider that, when two flight crew members are required, a flight crew member, following completion of a type rating or command course, and the associated line flying under supervision, is inexperienced until either:

(1) he/she has achieved 50 flight hours on the type and/or in the role within a period of 60 days; or

(2) he/she has achieved 100 flight hours on the type and/or in the role (no time limit).

(d) A lesser number of flight hours, on the type and/or in the role, and subject to any other conditions which the competent authority may impose, may be acceptable to the competent authority when one of the following applies:

(1) a new operator is commencing operations;

(2) an operator introduces a new helicopter type;

(3) flight crew members have previously completed a type conversion course with the same operator (reconversion); or

(4) credits are defined in the operational suitability data or equivalent established in accordance with CAR 21.

ORO.FC.A.201 In-flight relief of flight crew members

(a) The commander may delegate the conduct of the flight to:

(1) another qualified commander; or

(2) for operations only above flight level (FL) 200, a pilot who complies with the following minimum qualifications:

(i) ATPL;

(ii) conversion training and checking, including type rating training, in accordance with ORO.FC.220;

(iii) all recurrent training and checking in accordance with ORO.FC.230 and ORO.FC.240;

(iv) route/area and aerodrome competence in accordance with ORO.FC.105.

(b) The co-pilot may be relieved by:

(1) another suitably qualified pilot;

(2) for operations only above FL 200, a cruise relief co-pilot that complies with the following minimum qualifications:

(i) valid commercial pilot licence (CPL) with an instrument rating;

(ii) conversion training and checking, including type rating training, in accordance with ORO.FC.220 except the requirement for take-off and landing training;

(iii) recurrent training and checking in accordance with ORO.FC.230 except the requirement for take-off and landing training.

(c) A flight engineer may be relieved in flight by a crew member suitably qualified in accordance with applicable national rules.

ORO.FC.202 Single-pilot operations under IFR or at night

In order to be able to fly under IFR or at night with a minimum flight crew of one pilot, as foreseen in ORO.FC.200 (c)(2) and (d)(2), the following shall be complied with:

(a) The operator shall include in the operations manual a pilot's conversion and recurrent training programme that includes the additional requirements for a single-pilot operation. The pilot shall have undertaken training on the operator's procedures, in particular regarding:

(1) engine management and emergency handling;

(2) use of normal, abnormal and emergency checklist;

(3) air traffic control (ATC) communication;

(4) departure and approach procedures;

(5) autopilot management, if applicable;

(6) use of simplified in-flight documentation;

(7) single-pilot crew resource management.

(b) The recurrent checks required by ORO.FC.230 shall be performed in the single-pilot role on the relevant type or class of aircraft in an environment representative of the operation.

(c) For aeroplane operations under IFR the pilot shall have:

(1) a minimum of 50 hours flight time under IFR on the relevant type or class of aeroplane, of which 10 hours are as commander; and

(2) completed during the preceding 90 days on the relevant type or class of aeroplane:

(i) five IFR flights, including three instrument approaches, in a single-pilot role; or

(ii) an IFR instrument approach check.

(d) For aeroplane operations at night the pilot shall have:

(1) a minimum of 15 hours flight time at night which may be included in the 50 hours flight time under IFR in (c)(1); and

(2) completed during the preceding 90 days on the relevant type or class of aeroplane:

(i) three take-offs and landings at night in the single pilot role; or

(ii) a night take-off and landing check.

(e) For helicopter operations under IFR the pilot shall have:

(1) 25 hours total IFR flight experience in the relevant operating environment; and

(2) 25 hours flight experience as a single pilot on the specific type of helicopter, approved for single-pilot IFR, of which 10 hours may be flown under supervision, including five sectors of IFR line flying under supervision using the single-pilot procedures; and

(3) completed during the preceding 90 days:

(i) five IFR flights as a single pilot, including three instrument approaches, carried out on a helicopter approved for this purpose; or

(ii) an IFR instrument approach check as a single pilot on the relevant type of helicopter, flight training device (FTD) or full flight simulator (FFS).

ORO.FC.205 Command course

(a) For aeroplane and helicopter operations, the command course shall include at least the following elements:

(1) training in an FSTD, which includes line oriented flight training (LOFT) and/or flight training;

(2) the operator proficiency check, operating as commander;

(3) command responsibilities training;

(4) line training as commander under supervision, for a minimum of:

(i) 10 flight sectors, in the case of aeroplanes; and

(ii) 10 hours, including at least 10 flight sectors, in the case of helicopters;

(5) completion of a line check as commander and demonstration of adequate knowledge of the route or area to be flown and of the aerodromes, including alternate aerodromes, facilities and procedures to be used; and

(6) crew resource management training.

AMC1 ORO.FC.205 Command course

COMBINED UPGRADING AND CONVERSION COURSE — HELICOPTER

If a pilot is converting from one helicopter type or variant to another when upgrading to commander:

(a) the command course should also include a conversion course in accordance with ORO.FC.220; and

(b) additional flight sectors should be required for a pilot transitioning onto a new type of helicopter.

ORO.FC.215 Initial operator's crew resource management (CRM) training

(a) The flight crew member shall have completed an initial CRM training course before commencing unsupervised line flying.

(b) Initial CRM training shall be conducted by at least one suitably qualified CRM trainer who may be assisted by experts in order to address specific areas.

(c) If the flight crew member has not previously received theoretical training in human factors to the ATPL level, he/she shall complete, before or combined with the initial CRM training, a theoretical course provided by the operator and based on the human performance and limitations syllabus for the ATPL as established in CAR-FCL.

AMC1 ORO.FC.215 Initial operator's crew resource management (CRM) training

TRAINING ELEMENTS AND TRAINER QUALIFICATION

Initial operator's CRM training should:

(a) cover the applicable provisions of AMC1 ORO.FC.115, including the training elements as specified in Table 1 thereof; and

(b) be conducted by a flight crew CRM trainer who is qualified as specified in AMC3 ORO.FC.115.

ORO.FC.220 Operator conversion training and checking

(a) CRM training shall be integrated into the operator conversion training course.

(b) Once an operator conversion course has been commenced, the flight crew member shall not be assigned to flying duties on another type or class of aircraft until the course is completed or terminated. Crew members operating only performance class B aeroplanes may be assigned to flights on other types of performance class B aeroplanes during conversion courses to the extent necessary to maintain the operation.

(c) The amount of training required by the flight crew member for the operator's conversion course shall be determined in accordance with the standards of qualification and experience specified in the operations manual, taking into account his/her previous training and experience.

(d) The flight crew member shall complete:

(1) the operator proficiency check and the emergency and safety equipment training and checking before commencing line flying under supervision (LIFUS); and

(2) the line check upon completion of line flying under supervision. For performance class B aeroplanes, LIFUS may be performed on any aeroplane within the applicable class.

(e) In the case of aeroplanes, pilots that have been issued a type rating based on a zero flight-time training (ZFTT) course shall:

(1) commence line flying under supervision not later than 21 days after the completion of the skill test or after appropriate training provided by the operator. The content of that training shall be described in the operations manual;

(2) complete six take-offs and landings in an FSTD not later than 21 days after the completion of the skill test under the supervision of a type rating instructor for aeroplanes (TRI(A)) occupying the other pilot seat. The number of take-offs and landings may be reduced when credits are defined in the mandatory part of the operational suitability data or equivalent established in accordance with CAR 21. If those take-offs and landings have not been performed within 21 days, the operator shall provide refresher training the content of which shall be described in the operations manual;

(3) conduct the first four take-offs and landings of the LIFUS in the aeroplane under the supervision of a TRI(A) occupying the other pilot seat. The number of take-offs and landings may be reduced when credits are defined in the mandatory part of the operational suitability data established in accordance with CAR 21.

AMC1 ORO.FC.220 Operator conversion training and checking

OPERATOR CONVERSION TRAINING SYLLABUS

(a) General

(1) The operator conversion training should include, in the following order:

(i) ground training and checking, including aircraft systems, and normal, abnormal and emergency procedures;

(ii) emergency and safety equipment training and checking, (completed before any flight training in an aircraft commences);

(iii) flight training and checking (aircraft and/or FSTD); and

(iv) line flying under supervision and line check.

(2) When the flight crew member has not previously completed an operator's conversion course, he/she should undergo general first-aid training and, if applicable, ditching procedures training using the equipment in water.

(3) Where the emergency drills require action by the non-handling pilot, the check should additionally cover knowledge of these drills.

(4) The operator's conversion may be combined with a new type/class rating raining, as required by CAR-FCL.

(5) The operator should ensure that:

(i) Applicable elements of CRM training, as specified in Table 1 of AMC1 ORO.FC.115, are integrated into all appropriate phases of the conversion training and

(ii) the personnel integrating elements of CRM into conversion training are suitably qualified, as specified in AMC3 ORO.FC.115

(b) Ground training

(1) Ground training should comprise a properly organised programme of ground instruction supervised by training staff with adequate facilities, including any necessary audio, mechanical and visual aids. Self-study using appropriate electronic learning aids, computer-based training (CBT), etc., may be used with adequate supervision of the standards achieved. However, if the aircraft concerned is relatively simple, unsupervised private study may be adequate if the operator provides suitable manuals and/or study notes.

(2) The course of ground instruction should incorporate formal tests on such matters as aircraft systems, performance and flight planning, where applicable.

(c) Emergency and safety equipment training and checking

(1) Emergency and safety equipment training should take place in conjunction with cabin/technical crew undergoing similar training with emphasis on coordinated procedures and two-way communication between the flight crew compartment and the cabin.

(2) On the initial conversion course and on subsequent conversion courses as applicable, the following should be addressed:

(i) Instruction on first-aid in general (initial conversion course only); instruction on first-aid as relevant to the aircraft type of operation and crew complement, including those situations where no cabin crew is required to be carried (initial and subsequent).

(ii) Aero-medical topics, including:

(A) hypoxia;

(B) hyperventilation;

(C) contamination of the skin/eyes by aviation fuel or hydraulic or other fluids;

(D) hygiene and food poisoning; and

(E) malaria.

(iii) The effect of smoke in an enclosed area and actual use of all relevant equipment in a

simulated smoke-filled environment.

(iv) Actual fire fighting, using equipment representative of that carried in the aircraft on an actual or simulated fire except that, with Halon extinguishers, an alternative extinguisher may be used.

(v) The operational procedures of security, rescue and emergency services.

(vi) Survival information appropriate to their areas of operation (e.g. polar, desert, jungle or sea) and training in the use of any survival equipment required to be carried.

(vii) A comprehensive drill to cover all ditching procedures where flotation equipment is carried.

This should include practice of the actual donning and inflation of a life-jacket, together with a demonstration or audio-visual presentation of the inflation of life-rafts and/or slide-rafts and associated equipment. This practice should, on an initial conversion course, be conducted using the equipment in water, although previous certified training with another operator or the use of similar equipment will be accepted in lieu of further wet-drill training.

(viii) Instruction on the location of emergency and safety equipment, correct use of all appropriate drills, and procedures that could be required of flight crew in different emergency situations. Evacuation of the aircraft (or a representative training device) by use of a slide where fitted should be included when the operations manual procedure requires the early evacuation of flight crew to assist on the ground.

(d) Flight training

(1) Flight training should be conducted to familiarise the flight crew member thoroughly with all aspects of limitations and normal, abnormal and emergency procedures associated with the aircraft and should be carried out by suitably qualified class and type rating instructors and/or examiners. For specific operations, such as steep approaches, ETOPS, or operations based on QFE, additional training should be carried out, based on any additional elements of training defined for the aircraft type in the operational suitability data in accordance with CAR 21, where they exist.

(2) In planning flight training on aircraft with a flight crew of two or more, particular emphasis should be placed on the practice of LOFT with emphasis on CRM, and the use of crew coordination procedures, including coping with incapacitation.

(3) Normally, the same training and practice in the flying of the aircraft should be given to co-pilots as well as commanders. The ‘flight handling’ sections of the syllabus for commanders and co-pilots alike should include all the requirements of the operator proficiency check required by ORO.FC.230.

(4) Unless the type rating training programme has been carried out in an FSTD usable for ZFTT, the training should include at least three take-offs and landings in the aircraft.

(e) Line flying under supervision (LIFUS)

(1) Following completion of flight training and checking as part of the operator’s conversion course, each flight crew member should operate a minimum number of sectors and/or flight hours under the supervision of a flight crew member nominated by the operator.

(2) The minimum flight sectors/hours should be specified in the operations manual and should be determined by the following:

(i) previous experience of the flight crew member;

(ii) complexity of the aircraft; and

(iii) the type and area of operation.

(3) For performance class B aeroplanes, the amount of LIFUS required is dependent on the complexity of the operations to be performed.

(f) Passenger handling for operations where no cabin crew is required

Other than general training on dealing with people, emphasis should be placed on the following:

(1) advice on the recognition and management of passengers who appear or are intoxicated with alcohol, under the influence of drugs or aggressive;

(2) methods used to motivate passengers and the crowd control necessary to expedite an aircraft evacuation; and

(3) the importance of correct seat allocation with reference to aircraft mass and balance. Particular emphasis should also be given on the seating of special categories of passengers.

(g) Discipline and responsibilities, for operations where no cabin crew is required

Emphasis should be placed on discipline and an individual's responsibilities in relation to:

(1) his/her ongoing competence and fitness to operate as a crew member with special regard to flight and duty time limitation (FTL) requirements; and

(2) security procedures.

(h) Passenger briefing/safety demonstrations, for operations where no cabin crew is required Training should be given in the preparation of passengers for normal and emergency situations.

AMC2 ORO.FC.220 Operator conversion training and checking

OPERATOR CONVERSION TRAINING SYLLABUS — FLIGHT ENGINEERS

(a) Operator conversion training for flight engineers should approximate to that of pilots.

(b) If the flight crew includes a pilot with the duties of a flight engineer, he/she should, after training and the initial check in these duties, operate a minimum number of flight sectors under the supervision of a nominated additional flight crew member. The minimum figures should be specified in the operations manual and should be selected after due note has been taken of the complexity of the aircraft and the experience of the flight crew member.

GM1 ORO.FC.220(b) Operator conversion training and checking

COMPLETION OF AN OPERATOR'S CONVERSION COURSE

(a) The operator conversion course is deemed to have started when the flight training has begun. The theoretical element of the course may be undertaken ahead of the practical element.

(b) Under certain circumstances the course may have started and reached a stage where, for unforeseen reasons, it is not possible to complete it without a delay. In these circumstances, the operator may allow the pilot to revert to the original type.

(c) Before the resumption of the operator conversion course, the operator should evaluate how much of the course needs to be repeated before continuing with the remainder of the course.

GM1 ORO.FC.220(c) Operator conversion training and checking

OPERATOR CONVERSION COURSE (OCC) FOR MULTI-CREW PILOT LICENCE (MPL) HOLDERS

When defining the amount of training for MPL holders, who undertake their first conversion course on a new type or at an operator other than the one that was involved in their training for the MPL, the operator should put a process in place to ensure that corrective action can be taken if post-MPL licence training evaluation indicates the need to do so.

GM1 ORO.FC.220(d) Operator conversion training and checking

LINE FLYING UNDER SUPERVISION

(a) Line flying under supervision provides the opportunity for a flight crew member to carry into practice the procedures and techniques he/she has been made familiar with during the ground and flight training of an operator conversion course. This is accomplished under the supervision of a flight crew member specifically nominated and trained for the task. At the end of line flying under supervision the respective crew member should be able to perform a safe and efficient flight conducted within the tasks of his/her crew member station.

(b) A variety of reasonable combinations may exist with respect to:

(1) a flight crew member's previous experience;

(2) the complexity of the aircraft concerned; and

(3) the type of route/role/area operations.

(c) Aeroplanes

The following minimum figures for details to be flown under supervision are guidelines for operators to use when establishing their individual requirements:

(1) turbo-jet aircraft

(i) co-pilot undertaking first operator conversion course:

(A) total accumulated 100 hours or minimum 40 flight sectors;

(ii) co-pilot upgrading to commander:

(A) minimum 20 flight sectors when converting to a new type;

(B) minimum 10 flight sectors when already qualified on the aeroplane type.

AMC1 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

UPSET PREVENTION AND RECOVERY TRAINING (UPRT) FOR COMPLEX MOTOR-POWERED AEROPLANES WITH A MAXIMUM OPERATIONAL PASSENGER SEATING CONFIGURATION (MOPSC) OF MORE THAN 19

(a) Upset prevention training should:

(1) consist of ground training and flight training in an FSTD or an aeroplane;

(2) include upset prevention elements from Table 1 for the conversion training course; and

(3) include upset prevention elements in Table 1 for the recurrent training programme at least every 12 calendar months, such that all the elements are covered over a period not exceeding 3 years.

Table 1: Elements and respective components of upset prevention training

	Elements and components	Ground training	FSTD/ Aeroplane training
A.	**Aerodynamics**		
1.	General aerodynamic characteristics	•	
2.	Aeroplane certification and limitations	•	
3.	Aerodynamics (high and low altitudes)	•	•
4.	Aeroplane performance (high and low altitudes)	•	•
5.	Angle of attack (AOA) and stall awareness	•	•
6.	Stick shaker or other stall-warning device activation (as applicable)	•	•
7.	Stick pusher (as applicable)	•	•
8.	Mach effects (if applicable to the aeroplane type)	•	•
9.	Aeroplane stability	•	•
10	Control surface fundamentals	•	•
11.	Use of trims	•	•
12.	Icing and contamination effects	•	•
13.	Propeller slipstream (as applicable)	•	•
B.	**Causes of and contributing factors to upsets**		
1.	Environmental	•	
2.	Pilot-induced	•	
3.	Mechanical (aeroplane systems)	•	
C.	**Safety review of accidents and incidents relating to aeroplane upsets**		
1.	Safety review of accidents and incidents relating to aeroplane upsets	•	
D.	**g-load awareness and management**		
1.	Positive/negative/increasing/decreasing g-loads	•	•
2.	Lateral g awareness (sideslip)	•	•
3.	g-load management	•	•
E.	**Energy management**		
1.	Kinetic energy vs. potential energy vs. chemical energy (power)	•	•
F.	**Flight path management**		
1.	Relationship between pitch, power and performance	•	•
2.	Performance and effects of differing power plants (if applicable)	•	•
3.	Manual and automation inputs for guidance and control	•	•
4.	Type-specific characteristics	•	•
5.	Management of go-arounds from various stages during the approach	•	•
6.	Automation management	•	•
7.	Proper use of rudder	•	•
G.	**Recognition**		
1.	Type-specific examples of physiological, visual and instrument clues during developing and developed upsets	•	•
2.	Pitch/power/roll/yaw	•	•
3.	Effective scanning (effective monitoring)	•	•
4.	Type-specific stall protection systems and cues	•	•
5.	Criteria for identifying stalls and upsets	•	•

	Elements and components	Ground training	FSTD/ Aeroplane training
H.	**System malfunction** (including immediate handling and subsequent operational considerations, as applicable)		
1.	Flight control defects	•	•
2.	Engine failure (partial or full)	•	•
3.	Instrument failures	•	•
4.	Loss of reliable airspeed	•	•
5.	Automation failures	•	•
6.	Fly-by-wire protection degradations	•	•
7.	Stall protection system failures including icing alerting systems	•	•
I.	**Manual handling skills (no autopilot, no autothrust/autothrottle and, where possible, without flight directors)**		
1.	Flight at different speeds, including slow flight, and altitudes within the full normal flight envelope		•
2.	Procedural instrument flying and manoeuvring including instrument departure and arrival		•
3.	Visual approach		•
4.	Go-arounds from various stages during the approach (refer to point (d) of GM1 to Appendix 9 to the European Part-FCL for further guidance on go-around training)	•	•
5.	Steep turns		•

(b) Upset recovery training should:

(1) consist of ground training and flight training in an FFS qualified for the training task;

(2) be completed from each seat in which a pilot's duties require him/her to operate; and

(3) include the recovery exercises in Table 2 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years.

Table 2: Exercises for upset recovery training

	Exercises	Ground training	FFS training
A.	**Recovery from developed upsets**		
1.	Timely and appropriate intervention	•	•
2.	Recovery from stall events, in the following configurations; — take-off configuration, — clean configuration low altitude, — clean configuration near maximum operating altitude, and — landing configuration during the approach phase.	•	•
3.	Recovery from nose high at various bank angles	•	•
4.	Recovery from nose low at various bank angles	•	•
5.	Consolidated summary of aeroplane recovery techniques	•	•

(c) The operator should ensure that personnel providing FSTD UPRT are competent and current to deliver the training, and understand the capabilities and limitations of the device used.

(d) An FFS that is used for the training referred to in point (b)(1) should be qualified in accordance with the special evaluation requirements set out in the European CS-FSTD(A) (Issue 2 or later).

AMC2 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

UPSET PREVENTION AND RECOVERY TRAINING (UPRT) FOR COMPLEX MOTOR-POWERED AEROPLANES WITH A MAXIMUM OPERATIONAL PASSENGER SEATING CONFIGURATION (MOPSC) OF 19 OR LESS

(a) Upset prevention training should:

(1) consist of ground training and flight training in an FSTD or an aeroplane;

(2) include upset prevention elements in Table 1 of AMC1 ORO.FC.220&230 for the conversion training course; and

(3) include upset prevention elements in Table 1 of AMC1 ORO.FC.220&230 for the recurrent training programme at least every 12 calendar months, such that all the elements are covered over a period not exceeding 3 years.

(b) Upset recovery training should:

(1) consist of ground training and flight training in an FFS qualified for the training task, if available;

(2) be completed from each seat in which a pilot's duties require him/her to operate; and

(3) include the recovery exercises in Table 2 of AMC1 ORO.FC.220&230 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years.

(c) The operator should ensure that personnel providing FSTD UPRT are competent and current to deliver the training, and understand the capabilities and limitations of the device used.

(d) An FFS that is used for the training referred to in point (b)(1) should be qualified in accordance with the special evaluation requirements set out in the European CS-FSTD(A) (Issue 2 or later).

AMC3 ORO.FC.220&230.G Operator conversion training and checking & recurrent training and checking

CONDUCT OF UPRT

An operator should ensure that:

(a) a flight crew member completes Upset Prevention and Recovery training (UPRT):

(1) before commencing line flying under supervision (LIFUS);

(2) when changing from one type of aeroplane to another type or class for which a new type or class rating is required, unless credit is granted by the competent authority for aeroplanes in the same "family" or with a common type rating (e.g. according to Operations Training Transmission for Airbus Fly by wire aircraft); and

(b) UPRT is included in the flight crew recurrent training programme.

GM1 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

UPSET PREVENTION AND RECOVERY TRAINING (UPRT) FOR COMPLEX MOTOR-POWERED AEROPLANES

The objective of the UPRT is to help flight crew acquire the required competencies in order to prevent or recover from a developing or developed aeroplane upset. Prevention training prepares flight crew to avoid incidents whereas recovery training prepares flight crew to prevent an accident once an upset condition has developed.

HUMAN FACTORS

Threat and Error Management (TEM) and Crew Resource Management (CRM) principles should be integrated into the UPRT. In particular, the surprise and startle effect, and the importance of resilience development should be emphasised.

Training should also emphasise that an actual upset condition may expose flight crew to significant physiological and psychological challenges, such as visual illusions, spatial disorientation and unusual g-forces, with the objective to develop strategies to deal with such challenges.

USE OF FSTD FOR UPRT

The use of an FSTD provides valuable training without the risks associated with aeroplane training. The training envelope (envelope within which all training exercises will be carried out) should be specified by the operator in terms of the range of attitudes, speed and g-loads that can be used for training, taking into account:

(1) the training environment;

(2) the capabilities of the instructors; and

(3) in the case of training in FSTDs, the limitations of the FSTD (as per GM15 to Part-DEF to this Regulation for the FSTD training envelope); and

(4) in the case of training in aeroplanes, the capabilities and certification of the aeroplane, while considering a margin of safety in order to ensure that unintentional deviations from the training envelope will not exceed aeroplane limitations. Different training envelopes may be specified for different aeroplane types even within a single training course.

ADDITIONAL GUIDANCE

Specific guidance to the UPRT elements and exercises contained in the AMC is available from the latest revision of the ICAO Document 10011 ('Manual on UPRT').

Further guidance is available in:

- Revision 2 (as regards training scenarios for UPRT) and Revision 3 of the Aeroplane Upset Recovery Training Aid (AURTA (Revision 2) / AUPRTA (Revision 3)); and
- the Flight Safety Foundation Publication ('A Practical Guide for Improving Flight Path Monitoring'), November 2014.

GM2 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

UPSET PREVENTION TRAINING FOR COMPLEX MOTOR-POWERED AEROPLANES

The recurrent training should prioritise the upset prevention elements and respective components according to the operator's safety risk assessment.

Upset prevention training should use a combination of manoeuvre-based and scenario-based training. Scenario-based training may be used to introduce flight crew to situations which, if not correctly managed, could lead to an upset condition. Relevant TEM and CRM aspects should be included in scenario-based training and the flight crew should understand the limitations of the FSTD in replicating the physiological and psychological aspects of exposure to upset prevention scenarios.

In order to avoid negative training and negative transfer of training, operators should ensure that the selected upset prevention scenarios and exercises take into consideration the limitations of the FSTD and the extent to which it represents the handling characteristics of the actual aeroplane. If it is determined that the FSTD is not suitable, the operator should ensure that the required training outcome can be achieved by other means.

GO-AROUNDS FROM VARIOUS STAGES DURING THE APPROACH

Guidance on go-around training is provided in point (d) of GM1 to Appendix 9 to the European PART-FCL.

GM3 ORO.FC.220&230 Operator conversion training and checking & Recurrent training and checking

UPSET RECOVERY TRAINING FOR COMPLEX MOTOR-POWERED AEROPLANES

The upset recovery training exercises should be manoeuvre-based, which enables flight crew to apply their handling skills and recovery strategy whilst leveraging CRM principles to return the aeroplane from an upset condition to a stabilised flight path.

The flight crew should understand the limitations of the FFS in replicating the physiological and psychological aspects of upset recovery exercises.

In order to avoid negative training and negative transfer of training, operators should ensure that the selected upset recovery exercises take into consideration the limitations of the FFS.

STALL EVENT RECOVERY TRAINING

It is of utmost importance that stall event recovery training takes into account the capabilities of the FFS used. To deliver stall event recovery training, the FFS should be qualified against the relevant UPRT elements of CS-FSTD Issue 2. Stall event recovery training should include training up to the stall (approach-to-stall). Post-stall training may be delivered provided the device has been qualified against the relevant

optional elements of CS-FSTD Issue 2 and the operator demonstrates that negative training or negative transfer of training is avoided. A 'stall event' is defined as an occurrence whereby the aeroplane experiences one or more conditions associated with an approach-to-stall or stall.

Stall event recovery training should emphasise the requirement to reduce the angle of attack (AOA) whilst accepting the resulting altitude loss. High-altitude stall event training should be included so that flight crew appreciate the aeroplane control response, the significant altitude loss during the recovery, and the increased time required. The training should also emphasise the risk of triggering a secondary stall event during the recovery.

Recovery from a stall event should always be in accordance with the stall event recovery procedures of the OEMs. If an OEM-approved recovery procedure does not exist, operators should develop and train the aeroplane-specific stall recovery procedure based on the template in Table 1 below.

'Refer to Revision 3 of the Airplane Upset Prevention and Recovery Training Aid (AUPRTA) for a detailed explanation and rationale on the stall event recovery template as recommended by the OEMs.'

Table 1: Recommended Stall Event Recovery Template

Stall Event Recovery Template		
Pilot Flying - Immediately do the following at first indication of a stall (aerodynamic buffeting, reduced roll stability and aileron effectiveness, visual or aural cues and warnings, reduced elevator (pitch) authority, inability to maintain altitude or arrest rate of descent, stick shaker activation (if installed).) – during any flight phases *except at lift-off*.		
	Pilot Flying (PF)	**Pilot Monitoring (PM)**
1.	**AUTOPILOT – DISCONNECT** (A large out-of-trim condition could be encountered when the autopilot is disconnected.)	**MONITOR** airspeed and attitude throughout the recovery and **ANNOUNCE** any continued divergence
2.	**AUTOTHRUST/AUTOTHROTTLE – OFF**	
3.	**a) NOSE DOWN PITCH CONTROL** apply until stall warning is eliminated **b) NOSE DOWN PITCH TRIM** (as needed) (Reduce the angle of attack (AOA) whilst accepting the resulting altitude loss.)	
4.	**BANK – WINGS LEVEL**	
5.	**THRUST – ADJUST** (as needed) (Thrust reduction for aeroplanes with underwing mounted engines may be needed)	
6.	**SPEEDBRAKES/SPOILERS - RETRACT**	
7.	When airspeed is sufficiently increasing - **RECOVER** to level flight (Avoid the secondary stall due premature recovery or excessive g-loading.)	

NOSE HIGH AND NOSE LOW RECOVERY TRAINING

Nose-high and nose-low recovery training should be in accordance with the strategies recommended by the OEMs contained in the Tables 2 and 3 below. As the OEM procedures always take precedence over the recommendations, operators should consult their OEM on whether any approved type-specific recovery procedures are available prior to using the templates.

Refer to Revision 3 of the Airplane Upset Prevention and Recovery Training Aid (AUPRTA) for a detailed explanation and rationale on the nose high and nose low recovery strategies as recommended by the OEMs.

Table 2: Recommended Nose High Recovery Strategy Template

Nose HIGH Recovery Strategy		
Either pilot - Recognise and confirm the developing situation by announcing: **'Nose High'**		
	PF	**PM**
1.	**AUTOPILOT – DISCONNECT** (A large out of trim condition could be encountered when the AP is disconnected**.**	**MONITOR** airspeed and attitude throughout the recovery and **ANNOUNCE** any continued divergence
2.	**AUTOTHRUST/AUTOTHROTTLE – OFF**	
3.	**APPLY** as much nose-down control input as required to obtain a nose-down pitch rate	
4.	**THRUST – ADJUST** (if required) (Thrust reduction for aeroplanes with underwing mounted engines may be needed.)	
5.	**ROLL – ADJUST** (if required) (Avoid exceeding 60 degrees bank.)	
6.	When airspeed is sufficiently increasing - **RECOVER** to level flight (Avoid the secondary stall due premature recovery or excessive g-loading.)	
NOTE: 1) Recovery to level flight may require use of pitch trim. 2) If necessary, consider reducing thrust in aeroplanes with underwing-mounted engines to aid in achieving nose-down pitch rate. 3) **WARNING:** Excessive use of pitch trim or rudder may aggravate the upset situation or may result in high structural loads.		

Table 3: Recommended Nose Low Recovery Strategy Template

Nose LOW Recovery Strategy Template		
Either pilot - Recognise and confirm the developing situation by announcing: '**Nose Low**' (If the autopilot or autothrust/autothrottle is responding correctly, it may not be appropriate to decrease the level of automation while assessing if the divergence is being stopped.)		
	PF	**PM**
1.	**AUTOPILOT – DISCONNECT** (A large out of trim condition could be encountered when the AP is disconnected.)	**MONITOR** airspeed and attitude throughout the recovery and **ANNOUNCE** any continued divergence
2.	**AUTOTHRUST/AUTOTHROTTLE – OFF**	
3.	**RECOVERY** from stall if required	
4.	**ROLL** in the shortest direction to wings level. (It may be necessary to reduce the g-loading by applying forward control pressure to improve roll effectiveness)	
5.	**THRUST** and **DRAG – ADJUST** (if required)	
6.	**RECOVER** to level flight. (Avoid the secondary stall due premature recovery or excessive g-loading.)	
NOTE: 1) Recovery to level flight may require use of pitch trim. 2) **WARNING:** Excessive use of pitch trim or rudder may aggravate the upset situation or may result in high structural loads.		

GM4 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

Reserved

GM5 ORO.FC.220&230 Operator conversion training and checking & recurrent training and checking

PERSONNEL PROVIDING FSTD UPSET PREVENTION AND RECOVERY TRAINING (UPRT)

It is of paramount importance that personnel providing UPRT in FSTDs have the specific competence to deliver such training, which may not have been demonstrated during previous instructor qualification training. Operators should, therefore, have a comprehensive training and standardisation programme in place, and may need to provide FSTD instructors with additional training to ensure such instructors have and maintain complete knowledge and understanding of the UPRT operating environment, and skill sets.

Standardisation and training should ensure that personnel providing FSTD UPRT:

(1) are able to demonstrate the correct upset recovery techniques for the specific aeroplane type;

(2) understand the importance of applying type-specific Original Equipment Manufacturers (OEMs) procedures for recovery manoeuvres;

(3) are able to distinguish between the applicable SOPs and the OEMs recommendations (if available);

(4) understand the capabilities and limitations of the FSTD used for UPRT, based on the applicable FSTD training envelope;

(5) are aware of the potential of negative transfer of training that may exist when training outside the capabilities of the FSTD;

(6) understand and are able to use the IOS of the FSTD in the context of effective UPRT delivery;

(7) understand and are able to use the FSTD instructor tools available for providing accurate feedback on flight crew performance;

(8) understand the importance of adhering to the FSTD UPRT scenarios that have been validated by the training programme developer; and

(9) understand the missing critical human factor aspects due to the limitations of the FSTD and convey this to the flight crew receiving the training.

ORO.FC.230 Recurrent training and checking

(a) Each flight crew member shall complete recurrent training and checking relevant to the type or variant of aircraft on which they operate.

(b) Operator proficiency check

(1) Each flight crew member shall complete operator proficiency checks as part of the normal crew complement to demonstrate competence in carrying out normal, abnormal and emergency procedures.

(2) When the flight crew member will be required to operate under IFR, the operator proficiency check shall be conducted without external visual reference, as appropriate.

(3) The validity period of the operator proficiency check shall be six calendar months. For operations under VFR by day of performance class B aeroplanes conducted during seasons not longer than eight consecutive months, one operator proficiency check shall be sufficient. The proficiency check shall be undertaken before commencing commercial air transport operations.

(4) The flight crew member involved in operations by day and over routes navigated by reference to visual landmarks with an other-than complex motor-powered helicopter may complete the operator proficiency check in only one of the relevant types held. The operator proficiency check shall be performed each time on the type least recently used for the proficiency check. The relevant helicopter types that may be grouped for the purpose of the operator proficiency check shall be contained in the operations manual.

(5) Notwithstanding ORO.FC.146 (b), for operations of other-than-complex motor-powered helicopters by day and over routes navigated by reference to visual landmarks and performance class B aeroplanes, the check may be conducted by a suitably qualified commander nominated by the operator, trained in CRM concepts and the assessment of CRM skills. The operator shall inform the competent authority about the persons nominated.

(c) Line check

(1) Each flight crew member shall complete a line check on the aircraft to demonstrate competence in carrying out normal line operations described in the operations manual. The validity period of the line check shall be 12 calendar months.

(2) Notwithstanding ORO.FC.146 (b), line checks may be conducted by a suitably qualified commander nominated by the operator, trained in CRM concepts and the assessment of CRM skills.

(d) Emergency and safety equipment training and checking

Each flight crew member shall complete training and checking on the location and use of all emergency and safety equipment carried. The validity period of an emergency and safety equipment check shall be 12 calendar months.

(e) CRM training

(1) Elements of CRM shall be integrated into all appropriate phases of the recurrent training.

(2) Each flight crew member shall undergo specific modular CRM training. All major topics of CRM training shall be covered by distributing modular training sessions as evenly as possible over each three-year period.

(f) Each flight crew member shall undergo ground training and flight training in an FSTD or an aircraft, or a combination of FSTD and aircraft training, at least every 12 calendar months.

(g) The validity periods mentioned in (b)(3), (c) and (d) shall be counted from the end of the month when the check was taken.

(h) When the training or checks required above are undertaken within the last three months of the validity period, the new validity period shall be counted from the original expiry date.

AMC1 ORO.FC.230 Recurrent training and checking

RECURRENT TRAINING SYLLABUS

(a) Recurrent training

Recurrent training should comprise the following:

(1) Ground training

(i) The ground training programme should include:

(A) aircraft systems;

(B) operational procedures and requirements, including ground de-icing/anti-icing and pilot incapacitation; and

(C) accident / incident and occurrence review.

(ii) Knowledge of the ground training should be verified by a questionnaire or other suitable methods.

(iii) When the ground training is conducted within 3 calendar months prior to the expiry of the 12 calendar months period, the next ground and refresher training should be completed within 12 calendar months of the original expiry date of the previous training.

(2) Emergency and safety equipment training

(i) Emergency and safety equipment training may be combined with emergency and safety equipment checking and should be conducted in an aircraft or a suitable alternative training device.

(ii) Every year the emergency and safety equipment training programme should include the following:

(A) actual donning of a life-jacket, where fitted;

(B) actual donning of protective breathing equipment, where fitted;

(C) actual handling of fire extinguishers of the type used;

(D) instruction on the location and use of all emergency and safety equipment carried on the aircraft;

(E) instruction on the location and use of all types of exits;

(F) security procedures.

(iii) Every 3 years the programme of training should include the following:

(A) actual operation of all types of exits;

(B) demonstration of the method used to operate a slide where fitted;

(C) actual fire-fighting using equipment representative of that carried in the aircraft on an actual or simulated fire except that, with Halon extinguishers, an alternative extinguisher may be used;

(D) the effects of smoke in an enclosed area and actual use of all relevant equipment in a simulated smoke-filled environment;

(E) actual handling of pyrotechnics, real or simulated, where applicable;

(F) demonstration in the use of the life-rafts where fitted. In the case of helicopters involved in extended over water operations, demonstration and use of the life-rafts.

Helicopter water survival training

Where life-rafts are fitted for helicopter extended overwater operations (such as sea pilot transfer, offshore operations, regular, or scheduled, coast-to-coast overwater operations), a comprehensive wet drill to cover all ditching procedures should be practised by aircraft crew. This wet drill should include, as appropriate, practice of the actual donning and inflation of a life-jacket, together with a

demonstration or audio-visual presentation of the inflation of life-rafts. Crews should board the same (or similar) life-rafts from the water whilst wearing a life-jacket. Training should include the use of all survival equipment carried on board life-rafts and any additional survival equipment carried separately on board the aircraft;

- consideration should be given to the provision of further specialist training such as underwater escape training. Where operations are predominately conducted offshore, operators should conduct 3-yearly helicopter underwater escape training at an appropriate facility;
- wet practice drill should always be given in initial training unless the crew member concerned has received similar training provided by another operator;

(G) particularly in the case where no cabin crew is required, first-aid, appropriate to the aircraft type, the kind of operation and crew complement.

(iv) The successful resolution of aircraft emergencies requires interaction between flight crew and cabin/technical crew and emphasis should be placed on the importance of effective coordination and two-way communication between all crew members in various emergency situations.

(v) Emergency and safety equipment training should include joint practice in aircraft evacuations so that all who are involved are aware of the duties other crew members should perform. When such practice is not possible, combined flight crew and cabin/technical crew training should include joint discussion of emergency scenarios.

(vi) Emergency and safety equipment training should, as far as practicable, take place in conjunction with cabin/technical crew undergoing similar training with emphasis on coordinated procedures and two-way communication between the flight crew compartment and the cabin.

(3) CRM

Elements of CRM training, as specified in Table 1 of AMC1 ORO.FC.115, should be integrated into all appropriate phases of recurrent training.

(4) Aircraft/FSTD training

(i) General

(A) The aircraft/FSTD training programme should be established in a way that all major failures of aircraft systems and associated procedures will have been covered in the preceding 3 year period.

(B) When engine-out manoeuvres are carried out in an aircraft, the engine failure should be simulated.

(C) Aircraft/FSTD training may be combined with the operator proficiency check.

(D) When the aircraft/FSTD training is conducted within 3 calendar months prior to the expiry of the 12 calendar months period, the next aircraft/FSTD training should be completed within 12 calendar months of the original expiry date of the previous training.

(ii) Helicopters

(A) Where a suitable FSTD is available, it should be used for the aircraft/FSTD training programme. If the operator is able to demonstrate, on the basis of a compliance and risk assessment, that using an aircraft for this training provides equivalent standards of training with safety levels similar to those achieved using an FSTD, the aircraft may be used for this training to the extent necessary.

(B) The recurrent training should include the following additional items, which should be completed in an FSTD:

– settling with power and vortex ring;

– loss of tail rotor effectiveness.

(5) For operations with other-than-complex motor-powered aeroplanes, all training and checking should be relevant to the type of operation and class of aeroplane on which the flight crew member operates with due account taken of any specialised equipment used.

(b) Recurrent checking

Recurrent checking should comprise the following:

(1) Operator proficiency checks

(i) Aeroplanes

Where applicable, operator proficiency checks should include the following manoeuvres as pilot flying:

(A) rejected take-off when an FSTD is available to represent that specific aeroplane, otherwise touch drills only;

(B) take-off with engine failure between V_1 and V_2 (take-off safety speed) or, if carried out in an aeroplane, at a safe speed above V_2;

(C) 3D approach operation to minima with, in the case of multi-engine aeroplanes, one-engine-inoperative;

(D) 2D approach operation to minima;

(E) at least one of the 3D or 2D approach operations should be an RNP APCH or RNP AR APCH operation;

(F) missed approach on instruments from minima with, in the case of multi-engined aeroplanes, one-engine-inoperative;

(G) landing with one-engine-inoperative. For single-engine aeroplanes a practice forced landing is required.

(ii) Helicopters

(A) Where applicable, operator proficiency checks should include the following abnormal/ emergency procedures:

– engine fire;

– fuselage fire;

– emergency operation of under carriage;

– fuel dumping;

– engine failure and relight;

- hydraulic failure;
- electrical failure;
- engine failure during take-off before decision point;
- engine failure during take-off after decision point;
- engine failure during landing before decision point;
- engine failure during landing after decision point;
- flight and engine control system malfunctions;
- recovery from unusual attitudes;
- landing with one or more engine(s) inoperative;
- instrument meteorological conditions (IMC) autorotation techniques;
- autorotation to a designated area;
- pilot incapacitation;
- directional control failures and malfunctions.

(B) For pilots required to engage in IFR operations, proficiency checks include the following additional abnormal/emergency procedures:

- 3D approach operation to minima;
- go-around on instruments from minima with, in the case of multi-engined helicopters, a simulated failure of one engine;
- 2D approach operation to minima;
- at least one of the 3D or 2D approach operations should be an RNP APCH or RNP AR APCH operation;
- in the case of multi-engined helicopters, a simulated failure of one engine to be included in either the 3D or 2D approach operation to minima;
- landing with a simulated failure of one or more engines;
- where appropriate to the helicopter type, approach with flight control system/flight director system malfunctions, flight instrument and navigation equipment failures.

(C) Before a flight crew member without a valid instrument rating is allowed to operate in VMC at night, he/she should be required to undergo a proficiency check at night. Thereafter, each second proficiency check should be conducted at night.

(iii) Once every 12 months the checks prescribed in (b)(1)(ii)(A) may be combined with the proficiency check for revalidation or renewal of the aircraft type rating.

(iv) Operator proficiency checks should be conducted by a type rating examiner (TRE) or a synthetic flight examiner (SFE), as applicable.

(2) Emergency and safety equipment checks

The items to be checked should be those for which training has been carried out in accordance with (a)(2).

(3) Line checks

(i) Line checks should establish the ability to perform satisfactorily a complete line operation, including pre-flight and post-flight procedures and use of the equipment provided, as specified in the operations manual. The route chosen should be such as to give adequate representation of the scope of a pilot's normal operations. When weather conditions preclude a manual landing, an automatic landing is acceptable. The commander, or any pilot who may be required to relieve the commander, should also demonstrate his/her ability to 'manage' the operation and take appropriate command decisions.

(ii) The flight crew should be assessed on their CRM skills in accordance with the methodology described in AMC1 ORO.FC.115 and as specified in the operations manual.

(iii) CRM assessment should not be used as a reason for a failure of the line check, unless the observed behaviour could lead to an unacceptable reduction in safety margin.

(iv) When pilots are assigned duties as pilot flying and pilot monitoring, they should be checked in both functions.

(v) Line checks should be conducted by a commander nominated by the operator. The operator should inform the competent authority about the persons nominated. The person conducting the line check should occupy an observer's seat where installed. His/her CRM assessments should solely be based on observations made during the initial briefing, cabin briefing, flight crew compartment briefing and those phases where he/she occupies the observer's seat.

(A) For aeroplanes, in the case of long haul operations where additional operating flight crew are carried, the person may fulfil the function of a cruise relief pilot and should not occupy either pilot's seat during take-off, departure, initial cruise, descent, approach and landing.

(vi) Where a pilot is required to operate as pilot flying and pilot monitoring, he/she should be checked on one flight sector as pilot flying and on another flight sector as pilot monitoring. However, where the operator's procedures require integrated flight preparation, integrated cockpit initialisation and that each pilot performs both flying and monitoring duties on the same sector, then the line check may be performed on a single flight sector.

(4) When the operator proficiency check, line check or emergency and safety equipment check are undertaken within the final 3 calendar months of validity of a previous check, the period of validity of the subsequent check should be counted from the expiry date of the previous check.

(5) In the case of single-pilot operations with helicopters, the recurrent checks referred to in (b)(1), (2) and (3) should be performed in the single-pilot role on a particular helicopter type in an environment representative of the operation.

(c) Flight crew incapacitation training, except single-pilot operations

(1) Procedures should be established to train flight crew to recognise and handle flight crew incapacitation. This training should be conducted every year and can form part of other recurrent training. It should take the form of classroom instruction, discussion, audio-visual presentation or other similar means.

(2) If an FSTD is available for the type of aircraft operated, practical training on flight crew incapacitation should be carried out at intervals not exceeding 3 years.

(d) Personnel providing training and checking

Training and checking should be provided by the following personnel:

(1) ground and refresher training by suitably qualified personnel;

(2) flight training by a flight instructor (FI), type rating instructor (TRI) or class rating instructor (CRI) or, in the case of the FSTD content, a synthetic flight instructor (SFI), providing that the FI, TRI, CRI or SFI satisfies the operator's experience and knowledge requirements sufficient to instruct on the items specified in paragraphs (a)(1)(i)(A) and (B);

(3) emergency and safety equipment training by suitably qualified personnel;

(4) CRM:

(i) integration of CRM elements into all the phases of the recurrent training by all the personnel conducting recurrent training. The operator should ensure that all personnel conducting recurrent training are suitably qualified to integrate elements of CRM into this training;

(ii) classroom CRM training by at least one CRM trainer, qualified as specified in AMC3 ORO.FC.115, who may be assisted by experts in order to address specific areas.

(5) recurrent checking by the following personnel:

(i) operator proficiency check by a type rating examiner (TRE), class rating examiner (CRE) or, if the check is conducted in an FSTD, a TRE, CRE or a synthetic flight examiner (SFE), trained in CRM concepts and the assessment of CRM skills.

(ii) emergency and safety equipment checking by suitably qualified personnel.

(e) Use of FSTD

(1) Training and checking provide an opportunity to practice abnormal/emergency procedures that rarely arise in normal operations and should be part of a structured programme of recurrent training. This should be carried out in an FSTD whenever possible.

(2) The line check should be performed in the aircraft. All other training and checking should be performed in an FSTD, or, if it is not reasonably practicable to gain access to such devices, in an aircraft of the same type or in the case of emergency and safety equipment training, in a representative training device. The type of equipment used for training and checking should be representative of the instrumentation, equipment and layout of the aircraft type operated by the flight crew member.

(3) Because of the unacceptable risk when simulating emergencies such as engine failure, icing problems, certain types of engine(s) (e.g. during continued take-off or go-around, total hydraulic failure), or because of environmental considerations associated with some emergencies (e.g. fuel dumping) these emergencies should preferably be covered in an FSTD. If no FSTD is available, these emergencies may be covered in the aircraft using a safe airborne simulation, bearing in mind the effect of any subsequent failure, and the exercise must be preceded by a comprehensive briefing.

AMC2 ORO.FC.230 Recurrent training and checking

FLIGHT ENGINEERS

(a) The recurrent training and checking for flight engineers should meet the requirements for pilots and any additional specific duties, omitting those items that do not apply to flight engineers.

(b) Recurrent training and checking for flight engineers should, whenever possible, take place concurrently with a pilot undergoing recurrent training and checking.

(c) The line check should be conducted by a commander or by a flight engineer nominated by the operator, in accordance with national rules, if applicable.

GM1 ORO.FC.230 Recurrent training and checking

LINE CHECK AND PROFICIENCY TRAINING AND CHECKING

(a) Line checks, route and aerodrome knowledge and recent experience requirements are intended to ensure the crew member's ability to operate efficiently under normal conditions, whereas other checks and emergency and safety equipment training are primarily intended to prepare the crew member for abnormal/emergency procedures.

(b) The line check is considered a particularly important factor in the development, maintenance and refinement of high operating standards, and can provide the operator with a valuable indication of the usefulness of his/her training policy and methods. Line checks are a test of a flight crew member's ability to perform a complete line operation, including pre-flight and post-flight procedures and use of the equipment provided, and an opportunity for an overall assessment of his/her ability to perform the duties required as specified in the operations manual. The line check is not intended to determine knowledge on any particular route.

(c) Proficiency training and checking

When an FSTD is used, the opportunity should be taken, where possible, to use LOFT.

GM1 ORO.FC.230(a);(b);(f) Recurrent training and checking

MIXED EVIDENCE-BASED RECURRENT TRAINING AND CHECKING OF FLIGHT CREW CONDUCTED IN FLIGHT SIMULATION TRAINING DEVICES (FSTDs)

ICAO has developed Doc 9995 'Manual of Evidence-based Training', followed by the EASA EBT manual, which is intended to provide guidance to the competent authorities, operators and approved training organisations on the recurrent assessment and training of pilots by establishing a new methodology for the development and conduct of a recurrent assessment and training programme, titled evidence-based training (EBT).

ICAO Doc 9995 and the EASA EBT manual are the reference documents for operators seeking to implement mixed EBT. The purpose of this guidance material (GM) is to enable the implementation of mixed EBT according to the principles established in ICAO Doc 9995 and the EASA EBT manual in the context of the current regulatory framework.

In the current regulatory framework, it is possible to achieve mixed EBT implementation. Implementation of a mixed EBT programme means that some portion of the recurrent assessment and training is dedicated to the application of EBT. This includes the licence proficiency check (LPC) and the operator proficiency check (OPC).

As it is possible to combine LPC and OPC in ORO.FC, this GM is applicable to both checks. Therefore, the EBT programme described in this GM refers to the recurrent training and checking of flight crew, including LPCs and OPCs.

The EBT programme takes into account the differences between aircraft of different generations and the effect of these differences on training. The operator should acquire a thorough knowledge of ICAO Doc 9995 or the EASA EBT manual before implementing this GM. For applicability, see ICAO Doc 9995 or the tables of this section of applicable aeroplane/helicopter types by generation.

Mixed EBT programme

The operator may undertake implementation of the mixed EBT programme according to this GM. The ICAO table of assessment and training topics is defined in ICAO Doc 9995 Chapter 4.3.1 and in Appendices 2 to 7; the EBT programme is defined in AMC2 to AMC7 to ORO.FC.232.

The mixed EBT programme provides operators with the flexibility to adapt programmes according to their specific risks.

The operator should contact the competent authority in order for them to assess the application of the process described in ICAO Doc 9995 or the EBT manual.

Personnel providing training and checking in EBT (Refers to AMC1 ORO.FC.230(d))

ICAO Doc 9995 Chapter 6, or AMC1 and AMC2 to ORO.FC.146(c), contain(s) the guidance for the assessment and training of personnel involved in the conduct of EBT.

Equivalency of malfunctions (Refers to ICAO Doc 9995 Paragraph 3.8.3)

According to ICAO Doc 9995 Chapter 3.8.3 concept, major failures reduce the capability of the aircraft or the ability of the crew to cope with operating conditions to the extent that there would be a significant reduction in functional capabilities, significant increase in crew workload or in conditions impairing crew efficiency.

Clusters of major failures of aircraft systems are determined by reference to malfunction characteristics and the underlying elements of crew performance required to manage them. Equivalency of malfunctions may be used to guide the operator towards the implementation of a mixed EBT programme according to AMC1 ORO.FC.230(a)(4)(i)(A) and ORO.FC.145(d).

Conduct of licence and operator proficiency checks

The EBT programme described in ORO.FC.231 and the ICAO EBT programme described in ICAO Doc 9995 contain modules with three phases: the EVAL, the MT, and the SBT. In order to comply with the regulatory framework, in the mixed EBT programme the LPC and OPC requirements are fulfilled by a combination of the EVAL and the manoeuvres validation phase, which replaces the MT described in the EBT programme or ICAO Doc 9995. The manoeuvres validation phase is defined in Section 2 below. This is a form of mixed EBT implementation, which is described as follows:

1. **Evaluation phase:** This includes check scenarios referred to in CAR-FCL Appendix 9 within an approved mixed EBT programme.

   In order to facilitate the provision of simple and realistic scenarios in accordance with ICAO Doc 9995 Chapters 3.8 and 7.4, the EVAL is not intended to be a comprehensive assessment of all CAR-FCL Appendix 9 items; nevertheless, the list below includes the items that should be included in the EVAL only.

		CAR-FCL or Part-ORO reference	Description
Aeroplane	Helicopter	CAR-FCL Appendix 9 Paragraph 8	The examiner may choose between different skill test or proficiency check scenarios containing simulated relevant operations developed and approved by the competent authority. Full-flight simulators and other training devices, when available, shall be used, as established in this CAR-FCL.
Aeroplanes		CAR-FCL Appendix 9 Paragraph 18 of section A	The test/check should be accomplished under instrument flight rules (IFRs), if instrument rating (IR) is included, and as far as possible be accomplished in a simulated commercial air transport environment. An essential element to be checked is the ability to plan and conduct the flight from routine briefing material.
		CAR-FCL Appendix 9 Item 1.4	Use of checklist prior to starting engines, starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies.
		CAR-FCL Appendix 9 Item 1.6	Before take-off checks.
		CAR-FCL Appendix 9 Item 3.9.1*	Adherence to departure and arrival routes and ATC instructions. The starred item (*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.
Helicopters		CAR-FCL Appendix 9 Paragraph 2 of section C	In case of proficiency check for an IR, the applicant shall pass section 5 of the proficiency check. Failure in more than three items will require the applicant to take the entire section 5 again. An applicant failing not more than three items shall take the failed items again. Failure in any item of the re-check or failure in any other items of section 5 already passed will require the applicant to take the entire check again.
		CAR-FCL Appendix 9 Item 1.3	Starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies
		CAR-FCL Appendix 9 Item 1.4	Taxiing/air taxiing in compliance with air traffic control instructions or with instructions of an instructor
		CAR-FCL Appendix 9 Item 1.5	Pre-take-off procedures and checks
		CAR-FCL Appendix 9 Item 5.2*	Adherence to departure and arrival routes and ATC instructions The starred item (*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.

2. **Manoeuvres validation phase:** The purpose of the manoeuvres validation phase is to check the handling skills necessary to fly critical flight manoeuvres so that they are maintained to a defined level of proficiency. This replaces the MT described in ICAO Doc 9995 Chapter 7.5 and ORO.FC.231(a)(2)(iv)(b)(a). Manoeuvres in this context are not part of the line-orientated flight scenario; they are a sequence of deliberate actions to achieve a prescribed flight path or to perform a prescribed event to a prescribed outcome. All remaining items listed in CAR-FCL Appendix 9, and not included in the EVAL, should be included here. The manoeuvres listed in Doc 9995 or the table of assessment and training topics for the MT that do not form part of the CAR-FCL Appendix 9 mandatory items may be trained after the manoeuvres validation phase.

3. **Scenario-based training phase**: The purpose of the SBT is to further develop pilot core competencies in a learning environment. This does not form part of any LPC or OPC requirement.

It should be noted that if the operator is following an alternative means of compliance to ORO.FC.230(b) Operator proficiency check, the equivalence of using EBT evaluation and manoeuvres validation phases may no longer exist.

Conduct of CRM assessment

The operator is advised to use the EBT grading system (AMC1 ORO.FC.231(d)(1)) and the EBT competencies (AMC1 ORO.FC.231(b)) for the non-technical skills assessment.

Additional guidance on mixed EBT implementation is available in this section's checklist 'Oversight guidance for transition to Mixed EBT Implementation'.

ORO.FC.231 Evidence-based training

(a) EBT PROGRAMME

(1) The operator may substitute the requirements of ORO.FC.230 by establishing, implementing and maintaining a suitable EBT programme approved by the competent authority.

The operator shall demonstrate its capability to support the implementation of the EBT programme (including an implementation plan) and perform a safety risk assessment demonstrating how an equivalent level of safety is achieved.

(2) The EBT programme shall:

(i) correspond to the size of the operator, and the nature and complexity of its activities, taking into account the hazards and associated risks inherent in those activities;

(ii) ensure pilot competence by assessing and developing pilot competencies required for a safe, effective and efficient operation of aircraft;

(iii) ensure that each pilot is exposed to the assessment and training topics derived in accordance with ORO.FC.232;

(iv) include at least six EBT modules distributed across a 3-year programme; each EBT module shall consist of an evaluation phase and a training phase. The validity period of a EBT module shall be 12 months;

(A) The evaluation phase comprises a line-orientated flight scenario (or scenarios) to assess all competencies and identify individual training needs.

(B) The training phase comprises:

(a) the manoeuvres training phase, comprising training to proficiency in certain defined manoeuvres;

(b) the scenario-based training phase, comprising a line-orientated flight scenario (or scenarios) to develop competencies and address individual training needs.

The training phase shall be conducted in a timely manner after the evaluation phase.

(3) The operator shall ensure that each pilot enrolled in the EBT programme completes:

(i) a minimum of two EBT modules within the validity period of the type rating, separated by a period of not less than 3 months. The EBT module is completed when:

(A) the content of the EBT programme is completed for that EBT module (exposure of the pilot to the assessment and training topics); and

(B) an acceptable level of performance in all observed competencies has been demonstrated;

(ii) line evaluation(s) of competence; and

(iii) ground training.

(4) The operator shall establish an EBT instructor standardisation and concordance assurance programme to ensure that the instructors involved in EBT are properly qualified to perform their tasks.

(i) All instructors must be subject to this programme;

(ii) The operator shall use appropriate methods and metrics to assess concordance;

(iii) The operator shall demonstrate that the instructors have sufficient concordance.

(5) The EBT programme may include contingency procedures for unforeseen circumstances that could affect the delivery of the EBT modules. The operator shall demonstrate the need for those procedures. The procedures shall ensure that a pilot does not continue line operations if the performance observed was below the minimum acceptable level. They may include:

(i) a different separation period between EBT modules; and

(ii) different order of the phases of the EBT module.

(b) COMPETENCY FRAMEWORK

The operator shall use a competency framework for all aspects of assessment and training within an EBT programme. The competency framework shall:

(1) be comprehensive, accurate, and usable;

(2) include observable behaviours required for safe, effective and efficient operations;

(3) include a defined set of competencies, their descriptions and their associated observable behaviours.

(c) TRAINING SYSTEM PERFORMANCE

(1) The EBT system performance shall be measured and evaluated through a feedback process in order to:

(i) validate and refine the operator's EBT programme;

(ii) ascertain that the operator's EBT programme develops pilot competencies.

(2) The feedback process shall be included in the operator's management system.

(3) The operator shall develop procedures governing the protection of EBT data.

(d) GRADING SYSTEM

(1) The operator shall use a grading system to assess the pilot competencies. The grading system shall ensure:

(i) a sufficient level of detail to enable accurate and useful measurements of individual performance;

(ii) a performance criterion and a scale for each competency, with a point on the scale which determines the minimum acceptable level to be achieved for the conduct of line operations. The operator shall develop procedures to address low performance of the pilot;

(iii) data integrity;

(iv) data security.

(2) The operator shall verify at regular intervals the accuracy of the grading system against a criterion-referenced system.

(e) SUITABLE TRAINING DEVICES AND VOLUME OF HOURS TO COMPLETE THE OPERATOR'S EBT PROGRAMME

(1) Each EBT module shall be conducted in an FSTD with a qualification level adequate to ensure the correct delivery of the assessment and training topics.

(2) The operator shall provide a sufficient volume of hours in the suitable training device for the pilot to complete the operator's EBT programme. The criteria to determine the volume of the EBT programme are as follows:

(i) The volume corresponds to the size and complexity of the EBT programme;

(ii) The volume is sufficient to complete the EBT programme;

(iii) The volume ensures an effective EBT programme taking into account the recommendations provided by ICAO and the competent authority;

(iv) The volume corresponds to the technology of the training devices used.

(f) EQUIVALENCY OF MALFUNCTIONS

(1) Each pilot shall receive assessment and training in the management of aircraft system malfunctions.

(2) Aircraft system malfunctions that place a significant demand on a proficient crew shall be organised by reference to the following characteristics:

(i) immediacy;

(ii) complexity;

(iii) degradation of aircraft control;

(iv) loss of instrumentation;

(v) management of consequences.

(3) Each pilot shall be exposed to at least one malfunction for each characteristic at the frequency determined by the table of assessment and training topics.

(4) Demonstrated proficiency in the management of one malfunction is considered equivalent to demonstrated proficiency in the management of other malfunctions with the same characteristics.

(g) EQUIVALENCY OF APPROACHES RELEVANT TO OPERATIONS

(1) The operator shall ensure that each pilot receives regular training in the conduct of approach types and approach methods relevant to operations.

(2) This training shall include approaches that place an additional demand on a proficient crew.

(3) This training shall include the approaches that require specific approval in accordance with Part-SPA to this Regulation.

(h) LINE EVALUATION OF COMPETENCE

(1) Each pilot shall periodically undertake a line evaluation of competence in an aircraft to demonstrate the safe, effective and efficient conduct of normal line operations described in the operations manual.

(2) The validity period of a line evaluation of competence shall be 12 months.

(3) The operator approved for EBT may, with the approval of the competent authority, extend the validity of the line evaluation of competence to:

(i) either 2 years, subject to a risk assessment;

(ii) or 3 years, subject to a feedback process for the monitoring of line operations which identifies threats to the operations, minimises the risks of such threats, and implements measures to manage human error in the operations.

(4) For successful completion of the line evaluation of competence, the pilot shall demonstrate an acceptable level of performance in all observed competencies.

(i) GROUND TRAINING

(1) Every 12 calendar months, each pilot shall undergo:

(i) technical ground training;

(ii) assessment and training on the location and use of all emergency and safety equipment carried on the aircraft.

(2) The operator may, with the approval of the competent authority and subject to a risk assessment, extend the period of assessment and training on the location and use of all emergency and safety equipment carried on the aircraft to 24 months.

AMC1 ORO.FC.231(a) Evidence-based training

EBT PROGRAMME SUITABILITY

An operator' s EBT programme is one in which :

(a) training is focused on development of competencies, rather than repetition of tasks;

(b) the development of the programme is based on data-driven EBT training topics with a link to the operator's competency framework;

(c) training needs are addressed through training based on underlying competencies;

(d) the programme includes:

(1) an evaluation phase to identify training needs based on competencies and collect population-based data; to identify the training needs means, the root cause of the deficiency observed should be identified rather than the symptoms of the deficiency;

(2) a manoeuvres training phase (skill retention): to train skill-based manoeuvres (body memory actions). These manoeuvres should place a significant demand on a proficient pilot; and

(3) a scenario-based training phase to focus on identified training needs based on competencies rather than repetition of tasks;

(e) the programme includes the conduct of objective observations based on a competency framework, and documents evidence of the behaviour observed;

(f) there is a customisation of syllabi:

(1) The operator should describe in the operations manual the procedure to customise syllabi. It should include how to:

(i) select the example scenario elements within a training topic that should be included in the EBT programme; and

(ii) contextual i s e the exampl e s cenari o el em ents bas ed on the oper ator' s op era ti onal data (e.g. input from SMS, FDM programme, etc.) and training data.

(2) This customisation should be based on evidence both internal and external to the operator;

(g) performance is evaluated using a competency-based grading system;

(h) instructors grade competencies based on observable behaviours (OBs);

(i) instructors grade the pilot using a defined methodology — observe, record, classify and assess/evaluate (ORCA) is recommended;

(j) instructors have completed the EBT instructor standardisation;

(k) instructors have sufficient concordance based on defined criteria (instructor concordance assurance programme);

(l) the analysis of the pilot's performance is used to determine competency-based training needs;

(m) there is a range of teaching styles during simulator training to accommodate trainee learning needs; and

(n) facilitation techniques in debriefing are incorporated.

AMC2 ORO.FC.231(a) Evidence-based training

UPSET PREVENTION AND RECOVERY TRAINING (UPRT) FOR COMPLEX MOTOR-POWERED AEROPLANES WITH A MAXIMUM OPERATIONAL PASSENGER SEATING CONFIGURATION (MOPSC) OF MORE THAN 19

Operators approved for EBT should follow the provisions for upset prevention and recovery training (UPRT) contained in AMC1 ORO.FC.220&230 'Operator conversion training and checking & recurrent training and checking'. These provisions should be included in the tables of assessment and training topics detailed in ORO.FC.232.

AMC3 ORO.FC.231(a) Evidence-based training

PERSONNEL CONDUCTING ASSESSMENT AND PROVIDING TRAINING

(a) Ground and refresher training should be provided by suitably qualified personnel.

(b) For non-EBT assessment and training: flight training should be provided by a flight instructor (FI), type rating instructor (TRI) or class rating instructor (CRI) or, in the case of the FSTD content, a synthetic flight instructor (SFI). The FI, TRI, CRI or SFI should satisfy the operator's standardisation, experience and knowledge requirements.

(c) Emergency and safety equipment training should be provided by suitably qualified personnel.

(d) CRM training should be provided by an EBT instructor or, for the classroom CRM training, a CRM trainer.

(e) Additional personnel requirements are described in ORO.FC.146 and ORO.FC.231 and in the associated AMC and GM.

GM1 ORO.FC.231(a) Evidence-based training

RECURRENT CREW RESOURCE MANAGEMENT (CRM)

Operators implementing EBT in accordance with ORO.FC.231 may demonstrate compliance with ORO.FC.115 by showing how the recurrent CRM requirements are integrated within the operator's EBT programme. An example of how this may be done is provided in the safety promotion material contained in EASA EBT manual.

GM2 ORO.FC.231(a) Evidence-based training

EBT PROGRAMME — TRANSITION FROM MIXED EBT

The operator may agree with the competent authority the transition measures from mixed EBT to EBT baseline, which may include amongst others that the 3-year programme may include one or more modules in mixed EBT and one or more modules in EBT baseline, provided that all assessment and training topics in ORO.FC.232 are completed in the 3-year programme.

GM3 ORO.FC.231(a) Evidence-based training

CUSTOMISATION OF THE EBT PROGRAMME (SYLLABI)

(a) Syllabi can be customised at three different steps:

(1) The first step would be a syllabus for the whole pilots' population (customisation only at type rating level and/or aircraft generation level). At this step, the operator customises the example scenario elements based on relevant operational data (safety management system, state safety plan, OSD, occurrences, manufacturer data, etc.), and the training topics within the module are the same (same syllabus). At this level, it may be necessary to have a different example scenario element for the different crews within the same module to ensure that pilots are exposed to surprise and unexpected events and thus avoid pilots knowing all the details of the simulator session beforehand.

(2) The second step would be a different syllabus or part of it for the different populations of pilots. For example, some parts of the syllabus are different for the first officers and the captain, or the syllabus is different for the B747 pilots or for the Airbus pilots, etc. At this step, the module or part of the module is different for each population; this may include a different example scenario element for each population (or a different training topic; however, the customisation at training topic level is more difficult to control).

(3) The third step would be syllabi tailored to the individual pilot (pilot customisation — individual syllabus). This step is linked to the proc edures established for the tailored training and the additional training of the pilots following the VENN model.

(b) The procedure to describe the customisation of syllabi must be described in the OM. Customisation is based on evidence that can be gathered on three different levels, two from the inner loop, one from the outer loop.

(1) Inner loop

(i) Individual evidence based on training data (e.g. grading metrics, training reports, questionnaires, etc.), analysed either for an individual pilot or a group of pilots (for example, all first officers, all B747 pilots, all pilots flying an Airbu s model, etc.).

(ii) Operator-specific evidence gathered through the safety management process in accordance with ORO.GEN.200.

(2) Outer loop

Evidence gathered from external sources such as authorities (e.g. state safety plan, etc.), OEMs (e.g. OEBs, OSD, safety documentation such as getting to grip, etc.), etc.

GM4 ORO.FC.231(a) Evidence-based training

EBT PROGRAMME

Further guidance on the EBT programme can be found in the EASA EBT manual.

AMC1 ORO.FC.231(a)(1) Evidence-based training

EXPERIENCE IN MIXED EBT TO SUBSTITUTE ORO.FC.230

(a) The operator should have a minimum experience of 3 years of a mixed EBT programme.

Note: More information on a mixed EBT programme is provided in GM1 ORO.FC.230(a);(b);(f) and in GM2 ORO.FC.A.245.

(b) The operator should demonstrate 2 years of an instructor concordance assurance programme.

(c) The operator should demonstrate 1 year of a valid equivalency of malfunctions.

(d) The operator should demonstrate 1 year of integration of the training data in the customisation of the EBT programme and SMS data for the contextualisation of the example scenario elements.

(e) The operator should demonstrate that there is a verification of the grading system and feedback is provided to the training system performance and to the instructor standard isation concordance assurance.

SUBSTITUTION OF THE REQUIREMENTS OF ORO.FC.230

(f) One complete EBT module substitutes one operator proficiency check (OPC).

(g) The line evaluation of competence substitutes the line check.

AMC1 ORO.FC.231(a)(2) Evidence-based training

EBT PROGRAMME AND ASSSESMENT AND TRAINING TOPICS — RESILIENCE

(a) Compliance with the table of assessment and training topics ensures that crews are presented with an array of realistic changing events that allow for resilience development purposes.

(b) The EBT programme should be designed observing the following principles for resilience development:

(1) Resilience, surprise, and unexpected events

The EBT programme should be designed in such a way that in every cycle the simulator session (or part of it) allows variations so that the pilots are not familiar with the scenarios presented in the simulator session. Variations should be the focus of EBT programme design, and should not be left to the discretion of individual instructors, in order to preserve programme integrity and fairness.

(2) Resilience and decision-making (dilemma)

The EBT programme should be designed in such a way that in every cycle the crews are exposed to a scenario where more than one possible and less than ideal solutions exist, with some unfavourable conditions attached to each solution.

AMC2 ORO.FC.231(a)(2) Evidence-based training

VALIDITY OF THE EBT MODULE

(a) The validity period should be counted from the end of the month when the module was completed. When the module is undertaken within the last 3 months of the validity period, the new validity period should be counted from the original expiry date.

(b) In the context of ORO.FC.130 point (a), the pilot should have a valid module.

GM1 ORO.FC.231(a)(2) Evidence-based training

EBT PROGRAMME AND ASSSESMENT AND TRAINING TOPICS — RESILIENCE

(a) For resilience development, crews should be exposed to an array of realistic changing scenarios. The strategies developed by the crews whilst coping with different causes of action will create opportunities for resilience development.

(b) Resilience and surprise

The operator may create a comprehensive list of scenarios to ensure that each crew is trained in different scenarios avoiding the same scenarios for all crews. This relates to training topic ‘surprise’ and to the customisation of the EBT programme.

(c) Resilience and unexpected events

Exposing crews to rare, fortuitous, events may prepare crews to deal with other unexpected events. For instance, the table of assessment and training topics offers infrequent examples scenario elements such as flying over ‘no fly zone’, etc. The operator may also take infrequent examples from occurrence reporting, or SMS, or manufacturer reports, etc. This relates to decision-making (PSD) — see OB 6. 9 ‘Demonstrates resilience when encountering an unexpected event’.

(d) Dilemma

The operator may create scenarios suitable for training of threat assessment, threat management processes and option generation, leading to an optimum decision-making process. At programme design, as in real life, one ‘correct answer’ should be avoided; instead, the EBT programme should offer the crews a number of less than ideal courses of actions; some with unfavourable conditions attached. This relates to decision-making (PSD) and to the contextualisation of the example scenario element.

GM2 ORO.FC.231(a)(2) Evidence-based training

EBT PROGRAMME — TRAINING PHASE — IN-SEAT INSTRUCTION (ISI)

(a) Effective monitoring and error detection are increasingly important when operating highly reliable automated aircraft.

(b) In-seat instruction may be used as a valuable tool to maintain and develop the training objectives of some of the training topics, such as skills of monitoring, cross-checking, error management, and recognition of mismanaged aircraft state.

GM3 ORO.FC.231(a)(2) Evidence-based training

EBT PROGRAMME — ORDER OF THE PHASES

The order of the phases is intended as follows:

(a) First the EVAL; and

(b) Second, and in a timely manner after the EVAL, the training phases. The training phases are the MT and the SBT and may be delivered in any order.

Further guidance can be found in the EASA EBT manual.

AMC1 ORO.FC.231(a)(3) Evidence-based training

EBT PROGRAMME — ENROLMENT

(a) Enrolment is when a flight crew member commences the first EBT module.

(b) A flight crew member is considered to leave the operator's EBT programme (de-enrolled) when the operator is no longer responsible for the administrative action for the flight crew's licence revalidation under an EBT programme.

(c) The operator should inform the flight crew members who fail to demonstrate an acceptable level of competence and leave the operator's EBT programme (de-enrolled) that they should not exercise the privileges of that type rating.

GM1 ORO.FC.231(a)(3) Evidence-based training

MODULE SEPARATION BY A PERIOD OF NOT LESS THAN 3 MONTHS

(a) The separation begins when the first module finished (end of the training phase) and the second module begins (EVAL).

(b) When the operator decides to do more than two modules during the validity period of the type rating (approximately 1 year), the operator may count the 3 months of separation between the first and the third module if it so wishes.

(c) The separation of 3 months applies even between modules in different validity periods.

AMC1 ORO.FC.231(a)(4) Evidence-based training

INSTRUCTOR CONCORDANCE ASSURANCE PROGRAMME (ICAP)

(a) The ICAP should be able to identify areas of weak concordance to drive improvement in the quality and validity of the grading system.

(b) The ICAP should be adapted to the size and complexity of the instructors' group and the complexity of the operator's EBT programme.

(c) Complex operators should include an ICAP-specific data analysis, demonstrating:

(1) instructor-group assessment homogeneity (agreement);

(2) instructor assessment accuracy (alignment).

(d) The operator should verify the concordance of the instructors:

(1) once every cycle;

(2) for a sufficient number of competency-grade combinations.

(e) The operator should establish procedures to address those instructors who do not meet the standards required.

(f) The operator should maintain a list with the EBT instructors qualified to deliver the EBT programme.

GM1 ORO.FC.231(a)(4) Evidence-based training

INSTRUCTOR CONCORDANCE ASSURANCE PROGRAMME (ICAP)

(a) Instructor concordance is a tool for continuous improvement of the EBT programme as data reliability results in a more accurate and effective training.

(b) The operator may have a more frequent, or even a continuous, assessment of concordance as it provides more opportunities to improve.

(c) Concordance standards are normally set by the operator; however, the competent authority may recommend criteria, as licences' revalidation is performed under EBT.

(d) Individual instructor concordance may be verified:

(1) through uniform standardisation material where at least three different levels of performance are included and for all the competencies at a frequency of 72 months;

(2) by reference to the analysis of the data produced by the instructor every 12 months;

(3) normalisation may be necessary as there is no homogeneity of all EBT modules and the pilots that the instructor assessed; and

(e) Instructor-group assessment homogeneity (agreement) may be inferred from instructors who have observed the same content.

(f) Instructor assessment accuracy (alignment) may be inferred from comparing instructor assessments with an 'assessment standard' consisting of correctly identified competency(-ies) and correctly identified grade levels. Neither the competency(-ies) nor the grade level(s) may be communicated in advance to the instructors. The assessment standards may be set by consensus of a standards group, in order to guard against individual biases.

(g) When the operator uses a small group of instructors (e.g. 10), the data-driven concordance assurance programme may be directly integrated into the annual refresher training, removing the need for the above guidance.

(h) Operators with a complex group of instructors (e.g. a big rotation of instructors, subcontracted instructors, big number of instructors, many different fleets, etc.) may need to implement a more extensive concordance assessment system.

AMC1 ORO.FC.231(a)(5) Evidence-based training

CONTINGENCY PROCEDURES FOR UNFORESEEN CIRCUMSTANCES THAT MAY AFFECT THE DELIVERY OF THE MODULE

(a) The operator should detail in the EBT programme the contingency procedures in the event of unforeseen circumstances that may affect the delivery of the module (e.g. long-term sick pilot).

(b) In case of unforeseen interruption of a module at any point, the missing parts of the module should be rescheduled.

(1) The pilot may continue line flying until the expiry of the validity period unless the performance observed was below the minimum acceptable level.

(2) If the interruption results in an instructor change, the operator should ensure that the instructor completing the module is provided with the details of the performance of the pilots.

(c) In case the pilot misses modules and does not meet the requirements of recent experience (FCL.060):

(1) when the pilot misses one module out of the two modules required, the EVAL of the missing module should be rescheduled before the pilot can resume line operations. The MT and SBT phases of the missing module should be completed 30 days after the EVAL or before the expiry date, whichever occurs first;

(2) when the pilot misses one module in the preceding 12 months but the pilot's rating is expired by less than 3 months, the missing module should be rescheduled before the pilot can resume line operations;

(3) when the pilot misses one module in the preceding 12 months but the pilot's rating is expired by longer than 3 months but shorter than 1 year, the missing module should be rescheduled. The evaluation should be delivered by an EBT instructor (or instructors) with examiner privileges before the pilot can resume line operations;

(4) when the pilot misses two modules and the pilot's rating is valid:

(i) one module should be rescheduled before the pilot can resume line operations using an EBT instructor (or instructors) with examiner privileges; and

(ii) training topics B and C of the other module should be rescheduled before the expiry date.

In such case, the 3-month separation requirement between modules may not apply;

(5) when the pilot misses two modules and the pilot's rating is expired by less than 1 year:

(i) one module should be rescheduled using an EBT instructor (or instructors) with examiner privileges; and

(ii) training topics B and C of the other module should be rescheduled before the pilot can resume line operations.

In such case, the period of 3-month separation between modules may not apply; and

(6) if the amount of time elapsed since the expiry of the rating is more than 1 year, the pilot is de-enrolled. AMC1 FCL.625(c) 'IR — Validity, revalidation and renewal' and AMC1 FCL.740(b) 'Validity and renewal of class and type ratings' apply.

(d) In the case of other situations not covered by points (b) or (c), point (a) applies.

GM1 ORO.FC.231(a)(5) Evidence-based training

CONTINGENCY PROCEDURES — RATINGS RENEWAL

(a) The renewal of ratings (e.g. type rating or instrument rating) in EBT follows the CAR-FCL (IRs and AMC) and is complemented with the provisions covered in AMC1 ORO.FC.231(a)(5). The ATO or the operator will determine the amount of training following CAR-FCL; however, as EBT combines assessment and training, the following guidance is applicable:

(1) Expiry shorter than 3 months may not require additional training in CAR-FCL. In EBT, the missing module is rescheduled with an EBT instructor. Following that, the EBT manager for the type rating may renew the licence without extra training, as the EBT programme is now completed (at least two modules in the last 12 months).

(2) In CAR-FCL, when the expiry is longer than 3 months but shorter than 1 year, there need to be two training sessions. In EBT, there are two cases:

(i) One module is missing: the pilot must complete the missing module (two simulator sessions) before resuming line operations. Following that, the EBT manager for the type rating may renew the licence in accordance with Appendix 10 to the European Part-FCL as the EBT programme is now completed (two modules in the last 12 months).

(ii) Two modules are missing: the pilot must complete one module (two simulator sessions) and training topics B and C of the other missing module (an extra simulator session) with a total of three simulator sessions. Training data is gathered in a short time period; therefore, an EBT instructor with examiner privilege is involved to ensure the proficiency of the pilot.

(b) In case of an expiry longer than 1 year, the requirements of CAR-FCL will be followed and the proficiency checks will be performed in accordance with Appendix 9 as the EBT system may not have sufficient training data for the pilot.

(1) Expiry longer than 1 year but shorter than 3 years: a minimum of three training sessions in which the most important malfunctions in the available system are covered plus a proficiency check in accordance with Appendix 9 to renew the licence.

(2) Expiry longer than 3 years: the pilot should undergo the training for the initial issue of the type rating.

(3) Expiry longer than 7 years: the pilot should undergo the training for the initial issue of the instrument rating.

AMC1 ORO.FC.231(b) Evidence-based training

RECOMMENDED EBT COMPETENCIES (COMPETENCY FRAMEWORK)

(a) The operator should include in its EBT programme at least the following competencies:

Application of knowledge (KNO)	
Description:	Demonstrates knowledge and understanding of relevant information, operating instructions, aircraft systems and the operating environment
OB 0.1	Demonstrates practical and applicable knowledge of limitations and systems and their interaction
OB 0.2	Demonstrates the required knowledge of published operating instructions
OB 0.3	Demonstrates knowledge of the physical environment, the air traffic environment and the operational infrastructure (including air traffic routings, weather, airports)
OB 0.4	Demonstrates appropriate knowledge of applicable legislation.
OB 0.5	Knows where to source required information
OB 0.6	Demonstrates a positive interest in acquiring knowledge
OB 0.7	Is able to apply knowledge effectively

Application of procedures and compliance with regulations (PRO)	
Description:	Identifies and applies appropriate procedures in accordance with published operating instructions and applicable regulations
OB 1.1	Identifies where to find procedures and regulations
OB 1.2	Applies relevant operating instructions, procedures and techniques in a timely manner
OB 1.3	Follows SOPs unless a higher degree of safety dictates an appropriate deviation
OB 1.4	Operates aircraft systems and associated equipment correctly
OB 1.5	Monitors aircraft systems status
OB 1.6	Complies with applicable regulations
OB 1.7	Applies relevant procedural knowledge

Communication (COM)	
Description:	Communicates through appropriate means in the operational environment, in both normal and non-normal situations
OB 2.1	Determines that the recipient is ready and able to receive information
OB 2.2	Selects appropriately what, when, how and with whom to communicate
OB 2.3	Conveys messages clearly, accurately and concisely
OB 2.4	Confirms that the recipient demonstrates understanding of important information
OB 2.5	Listens actively and demonstrates understanding when receiving information
OB 2.6	Asks relevant and effective questions
OB 2.7	Uses appropriate escalation in communication to resolve identified deviations
OB 2.8	Uses and interprets non-verbal communication in a manner appropriate to the organisational and social culture
OB 2.9	Adheres to standard radiotelephone phraseology and procedures
OB 2.10	Accurately reads, interprets, constructs and responds to datalink messages in English

Aeroplane flight path management — automation (FPA)	
Description:	Controls the flight path through automation
OB 3.1	Uses appropriate flight management, guidance systems and automation, as installed and applicable to the conditions
OB 3.2	Monitors and detects deviations from the intended flight path and takes appropriate action
OB 3.3	Manages the flight path to achieve optimum operational performance
OB 3.4	Maintains the intended flight path during flight using automation whilst managing other tasks and distractions
OB 3.5	Selects appropriate level and mode of automation in a timely manner considering phase of flight and workload
OB 3.6	Effectively monitors automation, including engagement and automatic mode transitions

Aeroplane flight path management — manual control (FPM)	
Description:	Controls the flight path through manual control
OB 4.1	Controls the aircraft manually with accuracy and smoothness as appropriate to the situation
OB 4.2	Monitors and detects deviations from the intended flight path and takes appropriate action
OB 4.3	Manually controls the aeroplane using the relationship between aeroplane attitude, speed and thrust, and navigation signals or visual information
OB 4.4	Manages the flight path to achieve optimum operational performance
OB 4.5	Maintains the intended flight path during manual flight whilst managing other tasks and distractions
OB 4.6	Uses appropriate flight management and guidance systems, as installed and applicable to the conditions
OB 4.7	Effectively monitors flight guidance systems including engagement and automatic mode transitions

Leadership & teamwork (LTW)	
Description:	Influences others to contribute to a shared purpose. Collaborates to accomplish the goals of the team
OB 5.1	Encourages team participation and open communication
OB 5.2	Demonstrates initiative and provides direction when required
OB 5.3	Engages others in planning
OB 5.4	Considers inputs from others
OB 5.5	Gives and receives feedback constructively
OB 5.6	Addresses and resolves conflicts and disagreements in a constructive manner
OB 5.7	Exercises decisive leadership when required
OB 5.8	Accepts responsibility for decisions and actions
OB 5.9	Carries out instructions when directed
OB 5.10	Applies effective intervention strategies to resolve identified deviations
OB 5.11	Manages cultural and language challenges, as applicable

Problem-solving — decision-making (PSD)	
Description:	Identifies precursors, mitigates problems, and makes decisions
OB 6.1	Identifies, assesses and manages threats and errors in a timely manner
OB 6.2	Seeks accurate and adequate information from appropriate sources
OB 6.3	Identifies and verifies what and why things have gone wrong, if appropriate
OB 6.4	Perseveres in working through problems whilst prioritising safety
OB 6.5	Identifies and considers appropriate options
OB 6.6	Applies appropriate and timely decision-making techniques
OB 6.7	Monitors, reviews and adapts decisions as required
OB 6.8	Adapts when faced with situations where no guidance or procedure exists
OB 6.9	Demonstrates resilience when encountering an unexpected event

Situation awareness and management of information (SAW)	
Description:	Perceives, comprehends and manages information and anticipates its effect on the operation
OB 7.1	Monitors and assesses the state of the aeroplane and its systems
OB 7.2	Monitors and assesses the aeroplane's energy state, and its anticipated flight path
OB 7.3	Monitors and assesses the general environment as it may affect the operation
OB 7.4	Validates the accuracy of information and checks for gross errors
OB 7.5	Maintains awareness of the people involved in or affected by the operation and their capacity to perform as expected
OB 7.6	Develops effective contingency plans based upon potential risks associated with threats and errors
OB 7.7	Responds to indications of reduced situation awareness

Workload management (WLM)	
Description:	Maintains available workload capacity by prioritising and distributing tasks using appropriate resources
OB 8.1	Exercises self-control in all situations
OB 8.2	Plans, prioritises and schedules appropriate tasks effectively
OB 8.3	Manages time efficiently when carrying out tasks
OB 8.4	Offers and gives assistance
OB 8.5	Delegates tasks
OB 8.6	Seeks and accepts assistance, when appropriate
OB 8.7	Monitors, reviews and cross-checks actions conscientiously
OB 8.8	Verifies that tasks are completed to the expected outcome
OB 8.9	Manages and recovers from interruptions, distractions, variations and failures effectively while performing tasks

AMC2 ORO.FC.231(b) Evidence-based training

ADAPTED COMPETENCY MODEL

(a) An operator seeking to develop an adapted competency model under ORO.GEN.120 should:

(1) identify positive behaviours and use language that avoids ambiguity; and

(2) demonstrate equivalence to the recommended EBT competencies in AMC1 ORO.FC.231(b).

(b) In order to demonstrate equivalence, the operator should map the competencies and observable behaviours to the recommended EBT competencies.

(c) When the operator is translating AMC1 ORO.FC.231(b) into its common language, the application of ORO.GEN.120 may not be necessary. The translation may not be literal.

GM1 ORO.FC.231(b) Evidence-based training

ADAPTED COMPETENCY MODEL/POSITIVE OBSERVABLE BEHAVIOUR

(a) OBs should describe behaviours that contribute to positive pilot performance.

(b) The indicators should clearly describe how a competency is expected to be demonstrated by a crew member in the context of the operational environment.

(c) An operator may make small adjustments in the wording used to describe the OBs of the competency framework in order to improve the understanding of the pilots while maintaining the same meaning.

AMC1 ORO.FC.231(c) Evidence-based training

TRAINING SYSTEM PERFORMANCE — FEEDBACK PROCESS

(a) Feedback process is the continuous process of collecting and analysing assessment and training data from an EBT programme.

(b) The feedback process should use defined metrics to collect data in order to:

(1) identify trends and ensure corrective action where necessary;

(2) identify collective training needs;

(3) review, adjust and continuously improve the training programme;

(4) further develop the training system; and

(5) standardise the instructors (when the standardisation and concordance assurance programme is integrated into the training system performance).

(c) The following defined metrics should be collected as a minimum:

(1) level 0 grading metrics (competent metrics): data metrics providing the information whether the pilot(s) is (are) competent or not;

(2) level 1 grading metrics (competency metrics): quantifiable data from the grading system — numeric grade of the competencies (e.g. 1 to 5);

(3) level 2 grading metrics (observable behaviour metrics): the instructors record predetermined OBs during the session;

(4) level 3 grading metrics (other metrics): the instructors may record other predetermined data (e.g. specific tasks, actions, questions, etc.).

(d) Alternatively, where a system for the measurement of training system performance already exists, the operator may use it and, if necessary, adapt it to meet the demands of EBT.

AMC2 ORO.FC.231(c)&(d) Evidence-based training

FEEDBACK PROCESS — DATA PROTECTION – GRADING SYSTEM

(a) The objective of protecting the EBT data is to avoid inappropriate use of it in order to ensure the continued availability of such data, to maintain and improve pilot competencies.

(b) The data access and security policy should restrict information access to authorised persons.

(c) The data access and security policy should include the measures to ensure the security of the data (e.g. information security standard).

(d) The data access and security policy (including the procedure to prevent disclosure of crew identity) should be agreed by all parties involved (airline management and flight crew member representatives nominated either by the union or the flight crew themselves).

(e) The data access and security policy should be in line with the organisation safety policy in order to not make available or to not make use of the EBT data to attribute blame or liability.

(f) The operator may integrate the security policy within other management systems already in place (e.g. information security management).

GM1 ORO.FC.231(c) Evidence-based training

TRAINING SYSTEM PERFORMANCE — FEEDBACK PROCESS — METRICS

(a) Training metrics within the feedback process are a valuable source of data. Typical metrics may include but are not limited to:

(1) differences in success rates between training topics;

(2) the trainees' feedback (e.g. surveys), which provides a different perspective as to the quality and effectiveness of the training;

(3) instructor concordance assurance: this system is important to measure the effectiveness of the instructor calibration process. It is important to remind that the purpose of this system is not to spy on instructors or to pressure individuals to change their grading;

(4) level 0 grading metrics (competent metrics): Metrics examples: distribution of pilots not competent after the SBT, distribution of pilots not competent in the EVAL and competent after the SBT;

(5) level 1 grading metrics (competency metrics): Metrics examples:

(i) distribution of level of performance within the range of competencies;

(ii) differences in grades between aircraft types;

(6) level 2 grading metrics (observable behaviour metrics): e.g. in specific example scenario elements. Metrics example: differences in displaying OBs between ranks of pilots;

(7) level 3 grading metrics (other metrics such as data based on tasks): for instance, did the pilot calculate the landing distance? Or, did the pilots make a call-out in a specific manoeuvre? This level is usually linked to data collection of the SMS or EBT feedback loop (e.g. was the call-out of the TCAS manoeuvre correct? 'TCAS I have control'). Metrics example: distribution of errors for various training scenarios and aircraft types.

(8) during the simulator session, the operator may consider the level of grading metrics that the instructor needs to collect, taking into consideration the workload of the instructor.

(b) Training metrics are an invaluable component in supporting an EBT programme, but they must be placed in the context of operational data because only the latter can justify the importance of specific training. For this purpose, data from the line evaluation of competence is important to measure the effectiveness of the EBT programme in operations. It may include data from the process for the monitoring of line operations.

(c) Complex operators may, in the context of their safety management system, establish a safety action group dedicated to training: 'trainings afety action group' . This may be a best practice to meet the implementing rule.

GM2 ORO.FC.231(c) Evidence-based training

FEEDBACK PROCESS — DATA PROTECTION – GRADING SYSTEM

(a) The data access and security policy may, as a minimum, define:

(1) a policy for access to information only to specifically authorised persons identified by their position in order to perform their duties. The required authorised person(s) does (do) not need to be the EBT manager; it could be the EBT programme manager or a third party mutually acceptable to unions or staff and management. The third party may also be in charge of ensuring the correct application of the data access and security policy (e.g. the third party is the one activating the system to allow access to the authorised persons);

(2) the identified data retention policy and accountability;

(3) the measures to ensure that the security of the data includes the information security standard (e.g. information security management systems standard e.g. ISO 2700x-ISO 27001, NIST SP 800-53, etc.);

(4) the method to obtain de-identified crew feedback on those occasions that require specific follow-up; and

(b) When there is a need for data protection, it is preferable to de-identify the data rather than anonymise it.

AMC1 ORO.FC.231(d)(1) Evidence-based training

GRADING SYSTEM

(a) The grading system should provide quantifiable data for the measurement of the training system performance.

(b) The grading scale should be 1 to 5, where:

(1) Grade 1 — NOT COMPETENT — determines that the minimum acceptable level of performance was not achieved for the conduct of line operations. An outcome of ADDITIONAL TRAINING REQUIRED and level 2 grading metrics should be recorded.

(2) Grade 2 to 5 determine an outcome of COMPETENT for the conduct of line operations.

(3) Grade 2 (below the average) determines that the minimum acceptable level was achieved fothe conduct of line operations. Additionally, level 2 grading metrics should be recorded.

Minimum performance indicates a need for training (e.g. tailored or additional) to elevate performance. It includes:

(i) a competency graded continuously with 2 in multiple modules, or

(ii) the majority of competencies graded with 2 in a module.

(4) Grade 3 is the average.

(5) Grade 4 determines that the pilot is above the average.

(6) Grade 5 (exemplary) determines that the pilot is above the average and the outcome is enhanced safety, effectiveness and efficiency.

(c) The operator should develop further grading guidance to the above points to help the instructors determine the grade of the pilots they assess.

AMC2 ORO.FC.231(d)(1) Evidence-based training

GRADING SYSTEM — ALTERNATIVE SYSTEM

(a) An operator seeking to develop an alternative grading system under ORO.GEN.120 should:

(1) provide quantifiable data for the measurement of the training system performance; and

(2) demonstrate equivalence to the recommended grading system in AMC1 ORO.FC.231(d)(1).

(b) The grading scale for each competency should:

(3) determine the grade at which the performance is considered:

(i) NOT COMPETENT for the conduct of line operations. An outcome of ADDITIONAL TRAINING REQUIRED and level 2 grading metrics should be recorded; and

(ii) COMPETENT for the conduct of line operations; and

(4) determine for the pilot whose performance is considered competent for the conduct of line operations:

(i) if the pilot needs more training (e.g. tailored or additional training) to elevate their performance to the operator specified norm;

(ii) if the pilot is at the operator specified norm;

(iii) if the pilot is above the average (it can be one or more grades e.g. above the average and exemplary).

(c) The operator should develop further guidance to the above points to help the instructors determine the grade of the pilots they assess.

AMC3 ORO.FC.231(d)(1) Evidence-based training

RECOMMENDED CONDUCT OF THE GRADING — ORCA

(a) Grading the performance of flight crew members during an EBT module should include the following steps:

(1) Observe performance (behaviours) during the simulator session.

(2) Record details of effective and ineffective performance (behaviours) observed during the simulator sess ion ('record' in this context refers to ins tructors taking notes) .

(3) Classify observations against the OBs and allocate the OBs to each competency (or competencies), using amongst others the facilitation technique.

(4) Assess and evaluate (grade): assess the performance by determining the root cause(s) according to the competency framework. Low performance would normally indicate the area of performance to be remediated in subsequent phases or modules. Evaluate (grade) the performance by determining a grade for each competency using a methodology defined by the operator.

(b) As a minimum, the instructor should grade all the observed competencies at:

(1) the end of the EVAL (de-briefing) by providing at least level 1 grading metrics;

(2) the end of the MT (de-briefing) by providing at least level 0 grading metrics; and

(3) at the end of the EBT module (de-briefing) by providing at least level 0 grading metrics (level 1 grading metrics are recommended).

AMC4 ORO.FC.231(d)(1) Evidence-based training

RECOMMENDED GRADING SYSTEM METHODOLOGY — VENN MODEL

(a) To grade a competency, the instructor should assess the associated OBs of each competency against the following dimensions by determining:

(1) what was the outcome of the threat management, error management and undesired aircraft state management relating specifically to the competency being assessed;

(2) how well the flight crew member demonstrated the OB(s) when they were required. This includes:

(i) how many OBs the flight crew member demonstrated over the EBT phase (e.g. EVAL, MT, SBT) when they were required; and

(ii) how often the flight crew member demonstrated the OB(s) when they were required;

Abbreviated word picture VENN model				
	TEM	Observable behaviours		
Grading	OUTCOME (1)	HOW WELL (2)=	HOW MANY (i)+	HOW OFTEN (ii)
1	unsafe situation	ineffectively	few, hardly any	rarely
2	not an unsafe situation	minimally acceptable	some	occasionally
3	safe situation	adequately	many	regularly
4	safe situation	effectively	most	regularly
5	enhanced safety, effectiveness and efficiency	in an exemplary manner	all, almost all	always

(b) Grades should be determined during each EBT module as follows:

(1) EVAL — overall performance of the phase at level 1 grading metrics.

(2) MT — overall performance of the phase at level 0 grading metrics. When the phase is graded 'not competent', it requires level 2 grading metrics.

Note: Only a limited number of competencies may be observed and graded in this phase (e.g. PRO, FPA, FPM); the others are 'to be left in blank' .

(3) SBT — overall performance of the phase at level 1 grading metrics. Unless just culture and the necessary non-jeopardy environment during training may be compromised. In that case, level 0 grading metrics.

Note: In-seat instruction (ISI) should not be included in any assessment.

(c) Where any competency is graded below the minimum acceptable level of performance (grade 1 on a 5-point scale), an outcome of additional FSTD training is required.

(1) Additional level 2 grading metrics must be recorded.

(2) The flight crew member should not be released to unsupervised line operations until each competency is demonstrated at or above the minimum acceptable level of performance.

(d) Where all competencies are determined at or above the minimum acceptable level ofperformance (grade 2 on a 5-point scale), the outcome should be COMPETENT. Consistent grading below the average (2 on a 5-point scale) may indicate a need for training to elevate the performance to the average (grade 3 on a 5-point scale). As a minimum, the following conditions apply:

(1) Any competency graded with 2 requires level 2 grading metrics.

(2) Any competency graded with 2 in any simulator session of the 1st module followed by a grade 2 in the same competency in the EVAL of the 2nd module requires individual tailored training in the SBT of the 2nd module. (First example: 1st Module SBT graded with 2, 2nd Module EVAL graded with 2 in the same competency, thus the 2nd SBT should be an individual tailored training on that competency. Second example: 1s module EVAL graded 2, 2nd module EVAL graded 2 on the same competency, thus the 2nd module SBT should be individual tailored training on that competency).

(3) Any competency graded with 2 in three consecutive modules requires individual tailored training. If at the end of the tailored training (3rd SBT) the competency continues being graded with 2, additional FSTD training is required within the next 3 months. For instance, following the example above, the SBT in the 2nd Module was an individual tailored training. In the 3rd Module during the EVAL the same competency is graded with 2 and individual tailored training is applied. The SBT is graded with 2 again. The pilot may continue line operations but should receive additional FSTD training within the next 3 months.

(4) The operator should not release a flight crew member to unsupervised line operations when more than four competencies (the majority of the competencies — five competencies or above) are graded with 2 in any single simulator session of the module.

(5) Any EVAL graded with 2 in more than three competencies requires individual tailored training in the SBT. If at the end of the module more than three competencies continue being graded with 2, the pilot may continue line operations but should receive additional FSTD training within the next 3 months.

(e) 'Individual tailored training' refers to a simulator session tailored to the pilot's individual training needs, which may require a different programme or syllabus. Normally, it may be done during the SBT and normally there is not an increase of FSTD volume (no extra simulator session). It may require an increased volume of training such as CBT, additional briefings, etc. Any individual tailored training may be substituted by additional FSTD training before the start of the next module.

(f) 'Additional FSTD training' refers to the fact that in addition to the requirements of tailored training, there is an increase of FSTD volume (extra simulator session). It normally happens after individual tailored training.

GM1 ORO.FC.231(d)(1) Evidence-based training

RECOMMENDED CONDUCT OF THE GRADING — ORCA

(a) At the end of the EVAL, after the facilitated de-briefing, the instructor may, as a minimum, record level 1 grading metrics.

(b) The instructor may conduct the simulator session of the EVAL following the principles of a summative assessment and the facilitated de-briefing following the principles of a formative assessment. The MT and SBT simulator sessions may be conducted as a formative assessment.

(c) At the end of each training phase, it is recommended to record level 1 grading metrics unless just culture and the necessary non-jeopardy environment during training may be compromised. In that case, the following alternative may be recommended: level 0 grading metrics for all competencies may be recorded (exceptionally 'not observed' or 'left in blank' may be recorded) and de-identified level 1 grading metrics may be recorded for the data collection and analysis purposes.

GM2 ORO.FC.231(d)(1) Evidence-based training

RECOMMENDED GRADING SYSTEM METHODOLOGY — VENN MODEL

(a) Grades may be determined during each EBT module as follows:

(1) For each assigned grade:

(i) the observed performance should be identified with one or more OBs; and

(ii) the OB(s) should simply link the observed performance to the competency; they are not to be used as a checklist.

(2) At the completion of the EVAL, the grade should be assigned for each competency, based on the overall assessment of the performance during the EVAL.

(3) The underlying philosophy of the individual tailored training and additional FSTD training is the identi fi cati on of the pi lot's i ndividu al trai ning needs during the EVAL or EVALs. However, there may be cases in which such an identification may be complemented using other phases or combination of phases along the EBT programme. Nevertheless, when this happens consistently to a large number of pilots, it may indicate a problem of instructor standardisation.

(4) At the completion of the MT, only a limited number of competencies can be graded. The others are to be left in blank. Note: The grade of a competency as 'not observed' is a relevant set of data to be used in the EBT programme (e.g. may be used for instructor concordance assurance programme, programme design, etc.), while 'competency left in blank' is stating the obvious, which is that MT is a skill retenti on phase and therefore it focuses on only some of the competencies which may provide NO opportunity to observe all the competencies.

(5) At the completion of the module, grades should be assigned for each competency, based on the overall assessment of training during the SBT.

(6) In exceptional occasions, the instructor may have been unable to assess one or two competencies in the EVAL or SBT. A 'not observed' may be graded. The training system performance and concordance assurance system may use these metrics to improve instructors' standardisation and the EBT programme design. When the operator grades the MT alone (instead of grading the MT and EVAL together), a 'not observed' grading may be frequent. It also occurs when the instructor grades each one of the manoeuvres.

(b) The word pictures are standardised according to the VENN model but may be simplified once instructors become familiar with the system.

Word picture VENN model	
Application of procedures (PRO)	
5	The pilot applied procedures in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot applied procedures effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot applied procedures adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot applied procedures at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot applied procedures incorrectly, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Communication (COM)	
5	The pilot communicated in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot communicated effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot communicated adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot communicated at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot communicated ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Flight path management — automation (FPA)	
5	The pilot managed the automation in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot managed the automation effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot managed the automation adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot managed the automation at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot managed the automation ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Flight path management — manual control (FPM)	
5	The pilot controlled the aircraft in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot controlled the aircraft effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot controlled the aircraft adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot controlled the aircraft at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot controlled the aircraft ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Application of knowledge (KNO)	
5	The pilot showed exemplary knowledge, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot showed adequate knowledge, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot showed adequate knowledge, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot showed knowledge at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot showed inadequate knowledge, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Leadership & teamwork (LTW)	
5	The pilot led and worked as a team member in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot led and worked as a team member effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot led and worked as a team member adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot led and worked as a team member at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot led or worked as a team member ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Problem-solving & decision-making (PSD)	
5	The pilot solved problems and made decisions in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot solved problems and made decisions effectively, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot solved problems and made decisions adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot solved problems and made decisions at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot solved problems or made decisions ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Situation awareness (SAW)	
5	The pilot's situation awareness was exemplary, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot's situation awareness was good, by regularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot's situation awareness was adequate, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot's situation awareness was at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot's situation awareness was inadequate, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

Workload management (WLM)	
5	The pilot managed the workload in an exemplary manner, by always demonstrating almost all of the observable behaviours to a high standard when required, which enhanced safety, effectiveness and efficiency
4	The pilot managed the workload effectively, byregularly demonstrating most of the observable behaviours when required, which resulted in a safe operation
3	The pilot managed the workload adequately, by regularly demonstrating many of the observable behaviours when required, which resulted in a safe operation
2	The pilot managed the workload at the minimum acceptable level, by only occasionally demonstrating some of the observable behaviours when required, but which did not result in an unsafe situation
1	The pilot managed the workload ineffectively, by rarely demonstrating any of the observable behaviours when required, which resulted in an unsafe situation

AMC1 ORO.FC.231(d)(2) Evidence-based training

VERIFICATION OF THE ACCURACY OF THE GRADING SYSTEM

(a) The purpose is to provide data to assess the accuracy of the grading system.

(b) The items defined below are based on CAR-FCL Appendix 9. They should be included in the EVAL and MT of the applicable module. The minimum items to be included are: rejected take-off, failure of critical engine between V1 & V2, adherence to departure and arrival, 3D approaches down to a decision height (DH) not less than 60 m (200 ft), engine-out approach & go-around, 2D approach down to the MDH/A, engine-out approach & go-around, engine-out landing.

(c) Instructors should record if the exercises are flown to proficiency using Appendix 9 references (define criteria). Note: Individual pilots' grading and assessment remains according to the EBT grading system and Appendix 10 to the European Part-FCL.

(d) This verification should be performed once every 3 years.

GM1 ORO.FC.231(d)(2) Evidence-based training

VERIFICATION OF THE ACCURACY OF THE GRADING SYSTEM

Items that may be included in a verification of the accuracy of the grading system:

Assessment and training topic	*Flight phase for activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Use of checklist prior to starting engines (1.4 AP9)	GND	Use of checklist prior to starting engines, starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies	This element is not required	Intentionally left in blank	Intentionally left in blank								
Before take-off checks (1.6 AP9)	GND		This element is not required	Intentionally left in blank	Intentionally left in blank								
Rejected take-off at a reasonable speed before reaching V1 (2.6 AP9)	TO	Engine failure after the application of take-off thrust and before reaching V1	PRO - demonstrate adequate knowledge of the technique and procedure for accomplishing a rejected take-off after power-plant/system(s) failure/warnings, including related safety factors; - take into account, prior to beginning the take-off, operational factors which could affect the manoeuvre, such as take-off warning inhibit systems or other aeroplane characteristics, runway length, surface conditions, wind, obstructions that could affect take-off performance and could adversely affect safety; - perform all required pre-take-off checks as required by the appropriate checklist items. FPM - align the aeroplane on the runway centreline; - reduce the power smoothly and promptly, if appropriate to the aeroplane, when power-plant failure is recognised. Maintain the aeroplane under control close to the runway centreline; - use spoilers, prop reverse, thrust reverse, wheel brakes, and other drag/braking devices, as appropriate, maintaining positive control in such a manner as to bring the aeroplane to a safe stop. Accomplish the appropriate power-plant failure or other procedures and/or checklists as set forth in the POH or AFM or SOPs.	From initiation of take-off to complete stop (or as applicable to procedure)	X			X					
3.8.1* Adherence to departure and arrival routes and ATC instructions	CLB APP		This element is not required	Intentionally left in blank									

Assessment and training topic	*Flight phase for activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Take-off with engine failure between V1 and V2 (2.5.2 AP9)	TO	Failure of the critical engine from V1 and before reaching V2 in the lowest CAT I visibility conditions	FPM - establish a bank of approximately 5°, if required, or as recommended by the manufacturer, to maintain coordinated flight, and properly trim for that condition; maintain the operating engine within acceptable operating limits; - establish the best engine inoperative airspeed as appropriate to the aircraft and condition of flight; - establish and maintain the recommended flight attitude and configuration for the best performance for all manoeuvring necessary for the phase of flight; - maintain desired altitude within given limits, when a constant altitude is specified and is within the capability of the aeroplane; - maintain the desired airspeed and heading within given limits. PRO - recognise an engine failure or the need to shut down an engine as simulated by the examiner; - complete engine failure vital action checks from memory; - follow the prescribed aeroplane checklist, and verify the procedures for securing the inoperative engine; - demonstrate proper engine restart or shutdown procedures (whatever appropriate) in accordance with approved procedure/checklist or the manufacturer's recommended procedures and pertinent checklist items; and monitor all functions of the operating engine and make necessary adjustments.	The manoeuvre is considered to be complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement.	X			X					
				The manoeuvre is considered to be complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed.	X			X					

Assessment and training topic	*Flight phase for activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
3.8.3* 3D operations to DH/A of 200 ft (60 m) or to higher minima if required by the approach procedure	APP	Manually, with one engine simulated inoperative; engine failure has to be simulated during final approach before passing 1 000 ft above aerodrome level until touchdown or through the complete missed approach procedure. or Manually, with one engine simulated inoperative; engine failure has to be simulated during final approach after passing the outer marker (OM) within a distance of not more than 4 NM until touchdown or through the complete missed approach procedure.	PRO - select and comply with the ILS or LPV instrument approach procedure to be performed; - prior to final approach course, maintain declared or assigned altitudes within given limits without descending below applicable minimum altitudes and maintain headings within given limits; - select, tune, identify and confirm the operational status of ground and aircraft navigation equipment to be used for the approach procedure. COM - establish two-way communications with ATC using the proper communications phraseology and techniques, either personally, or, if appropriate, direct co-pilot/safety pilot to do so, as required for the phase of flight or approach segment; - comply in a timely manner with all clearances, instructions, and procedures issued by ATC and advice accordingly if unable to comply. FPA/FPM - establish the appropriate aircraft configuration and airspeed/V-speed considering turbulence, wind shear or other meteorological and operating conditions; - complete the aircraft checklist items appropriate to the phase of flight or approach segment, including engine out approach and landing checklist, as appropriate; - apply necessary adjustment to the published DH and visibility criteria for the aeroplane approach category when required, such as NOTAMs, inoperative aeroplane and ground navigation equipment, inoperative visual aids associated with the landing environment; - on final approach course, allow no more than ½ scale deflection of the localiser and/or glideslope indications; - maintain declared approach airspeeds within given limits; - maintain a stabilised descent to the DH to permit completion of the visual portion of the approach and landing with minimal manoeuvring; and - initiate the missed approach procedure, upon reaching the DH, when the required visual references for the intended runway are not obtained. 3D linear vertical deviations (e.g. RNP APCH (LNAV/VNAV) using BaroVNAV): not more than – 75 ft below the vertical profile at any time, and not more than + 75 ft above the vertical profile at or below 1 000 ft above aerodrome level. 3D (LNAV/VNAV) 'linear' lateral deviations: cross-track error/deviation should normally be limited to ± ½ the RNP value associated with the procedure. Brief deviations from this standard up to a maximum of 1 time the RNP value are allowable.	Intentionally left in blank	Intentionally left in blank								

Assessment and training topic	*Flight phase for activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
2D operations down to the MDH/A (3.8.4 AP9)	*APP*	Non-precision approach down to the MDH/A	PRO - select and comply with the PBN, VOR/ LOC/ LOC BC or NDB instrument approach procedure to be performed; - complete the aircraft checklist items appropriate to the phase of flight or approach segment, including engine out approach and landing checklist, as appropriate; - prior to final approach course, maintain declared altitudes in given limits without descending below applicable minimum altitudes, and maintain headings as given; - select, tune, identify, confirm and monitor the operational status of ground and aircraft navigation equipment to be used for the approach procedure. COM - establish two-way communications with ATC using the proper communications phraseology and techniques, either personally, or, if appropriate, direct co-pilot/safety pilot to do so, as required for the phase of flight or approach segment; - comply in a timely manner with all clearances, instructions, and procedures issued by ATC and advise accordingly if unable to comply. FPA/FPM - apply necessary adjustment to the published minimum descent altitude (MDA) and visibility criteria for the aeroplane approach category when required, such as NOTAMs, inoperative aeroplane and ground navigation equipment, inoperative visual aids associated with the landing environment; - on the intermediate and final segments of the final approach course: a. maintain PBN, VOR/ LOC/ LOC BC tracking within ½ scale deflection of the course deviation indicator or within 5 degrees of the desired track in the case of an NDB approach; b. fly the approach in a stabilised manner without descending below the applicable minimum altitudes depicted on the approach chart (+as required/–0 feet); 2D (LNAV) 'linear' lateral deviations: cross-track error/deviation should normally be limited to ± ½ the RNP value associated with the procedure. Brief deviations from this standard up to a maximum of 1 time the RNP value are allowable. c. descend to and accurately maintain the MDA and track to the missed approach point (MAPt) or to the recommended minimum visibility that would permit completion of the visual portion of the approach with a normal rate of descent and minimal manoeuvring; d. maintain declared approach airspeeds (+10/-5 knots); e. initiate the missed approach procedure, if the required visual references for the intended runway are not obtained at the MAPt; f. execute a normal landing from a straight-in or circling approach as required.	Intentionally left in blank	Intentionally left in blank							

Assessment and training topic	*Flight phase for activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Engine-out approach & go-around (4.4* AP9)	APP	Manual go-around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation; Detect deviations through instrument scanning; Maintain spare mental capacity during manual aircraft control; Maintain the aircraft within the flight envelope; Apply knowledge of the relationship between aircraft attitude, speed and thrust.	This manoeuvre should be flown from intercept to centreline until acceleration after go-around. The manoeuvre is considered to be complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement (describe generally critical part of manoeuvre)	X			X					
Engine-out landing (5.5 AP9)	LDG	Landing with the critical engine inoperative		Initiation in a stabilised engine-out configuration from not less than 3 NM final approach, until completion of roll-out	X			X					

GM2 ORO.FC.231(d)(2) Evidence-based training

VERIFICATION OF THE ACCURACY OF THE GRADING SYSTEM — FEEDBACK PROCESS

The verification of the accuracy of the grading system provides valuable data for the training system performance and concordance assurance. Therefore, the verification is necessary from a systemic point of view and the intention is not to measure individual pilot against Appendix 9 criteria.

Concordance agreement between instructors may be high; however, the whole community of instructors may be grading too low or too high (accuracy).

The statistical result of the verification against Appendix 9 criteria can provide the operator with a criterion-referenced system to adjust the accuracy of the grading system. The verification does not require an examiner; EBT instructors may provide the necessary data.

Example 1: For the last 36 months, the operator has a rate of 3 % of pilots scoring 1 (assuming the data is statistically relevant). In this example, the rate of 3 % of the pilots scoring 1 is maintained across all the technical competencies. When the operator performs a verification, the rate of failure would have been only 0.5 %. This may indicate that instructors are rating too low in EBT and therefore some of the pilots scoring 1 should have been graded with a score higher than 1. This may be economically negative for the operator. On the other hand, it could be that the operator has decided to implement higher standards.

Example 2: The operator has an EBT programme with a negligible rate of pilots scoring 1 and a 1 % of pilots scoring 2 in two consecutive recurrent modules. The verification of the technical competencies against Appendix 9 criteria provides a rate of 5 % failure. The EBT manager should further investigate the reason behind this mismatch between EBT and Appendix 9 in the technical competencies. There may be factors influencing this mismatch (e.g. statistical issues, the events in the EBT modules are too benign compared to the events in Appendix 9), which may lead to a corrective action (e.g. redesign of the EBT modules). If the difficulty of the EBT scenarios is equivalent to Appendix 9 and the concordance is high between instructors, then the discrepancy in outcomes might be because the community of instructors are grading too high in the technical competencies (they are grading with 2 when they should have graded 1). Further instructor standardisation will be needed to address this.

The implementation of mixed EBT following GM1 ORO.FC.230(a);(b);(f) provides a good opportunity to fine-tune and verify the accuracy of the grading system because an Appendix 9 licence proficiency check is carried out every year. The authority may not allow full EBT unless the accuracy of the grading system is demonstrated.

Further guidance can be found in the EASA EBT manual.

AMC1 ORO.FC.231(e) Evidence-based training

VOLUME AND FSTD QUALIFICATION LEVEL

(a) The EBT programme has been developed to include a notional exemplar of 48 FSTD hours over a 3 year programme for each flight crew member.

(b) Subject to ORO.GEN.120, the operator may reduce the number of FSTD hours provided that an equivalent level of safety is achieved. The programme should not be less than 36 FSTD hours.

(c) Each EBT module should be conducted in an FSTD with a qualification level adequate to complete proficiency checks; therefore, it should be conducted in a full-flight simulator (FFS) level C or D.

AMC1 ORO.FC.231(f) Evidence-based training

EQUIVALENCY OF MALFUNCTIONS — PROCESS

(a) The equivalency of malfunctions process should be undertaken by subject matter experts (SMEs) who hold or have held a type rating on the aeroplane type.

(b) Steps of the equivalency of malfunctions

Step 1: Look at (review) all aircraft system malfunctions provided by the OEM. For example, FCOM for Airbus, or AFM for other manufacturers, does not normally provide an exhaustive list of malfunctions.

Step 2: Determine and retain in a list only malfunctions that place a significant demand on a proficient crew, in isolation from an environmental or operational context.

Step 3: For each retained malfunction, determine the applicable characteristic or characteristics.

Step 4: Develop the EBT FSTD programme to incorporate malfunctions at the frequency specified in the table of assessment and training topics.

(c) Malfunctions included in the equivalency of malfunctions but not included in the EBT FSTD programme require review and appropriate procedural knowledge training, conducted in a less qualified but suitable alternative environment (classroom, flight procedure training d evice, advance computer-based training, aviation blended learning environment (ABLE), etc.). Further guidance can be found in the EASA EBT manual.

(d) The operator should establish procedures to determine what malfunctions should be included in the FSTD. This may include a different malfunction difficulty between the EVAL and the SBT.

AMC1 ORO.FC.231(f)(3) Evidence-based training

CREW EXPOSURE TO AT LEAST ONE MALFUNCTION FOR EACH CHARACTERISTIC

(a) Unless specified in the OSD, each crew member should be exposed to the characteristics of degraded control and loss of instrumentation in the role of pilot flying.

(b) Notwithstanding point (a), for aircraft types with a limited number of malfunctions in the characteristic of degraded control or loss of instrumentation, the operator may use an alternative means of compliance in accordance with ORO.GEN.120.

GM1 ORO.FC.231(f) Evidence-based training

EQUIVALENCY OF MALFUNCTIONS — SIGNIFICANT DEMAND ON A PROFICIENT CREW

(a) The criteria to determine that a malfunction places a significant demand on a proficient crew are the following:

(1) The procedure includes one or more action items and not only a set of information for crew awareness.

(2) The flight crew's cognitive load (resources required by the mental processes of perception, memory, judgement, and reasoning) significantly increases during or after the application of the associated abnormal or emergency procedure. The cognitive load is considered to be significantly increased when it is well above the cognitive load induced by the application of the normal standard operating procedures.

(3) The flight crew's workload significantly increases during or after the application of the associated abnormal or emergency procedure. The workload is considered to be significantly increased when it is well above the workload induced by the application of the normal standard operating procedures.

(4) The aircraft handling perceived by the pilot when flying in abnormal conditions is different compared to the aircraft handling in normal conditions; e.g. the symmetry of the flight is affected.

(b) The criteria to determine that a malfunction places a significant demand on a proficient crew allow the identification of:

(1) the pilot competencies that are specifically challenged during the management of the related procedure, and

(2) the characteristic of the aircraft system malfunction procedure.

Note: The identification of the pilot competencies allows a consistent assessment to determine the proficiency of the crew member.

Criteria in (a)	Definition	Challenged Competency	Example of procedure characteristics
(1)	The procedure includes one or more action items and not only a set of information for crew awareness.	▪ PRO ▪ KNO	▪ multiple paths within the procedure (e.g. decision trees) ▪ multiple inoperative or degraded systems
(2)	The flight crew's cognitive load (resources required by the mental processes of perception, memory, judgement, and reasoning) significantly increases, during, or after, the application of the abnormal/emergency procedure. The cognitive load is considered to be significantly increased when it is well above the cognitive load induced by the application of the normal standard operating procedures.	▪ SAW ▪ PSD	▪ multiple paths within the procedure (e.g. decision trees) ▪ multiple inoperative or degraded systems ▪ a high potential for undetected errors (e.g. removal of flight protections)
(3)	The flight crew's workload significantly increases, during, or after, the application of the abnormal/emergency procedure. The workload is considered to be significantly increased when it is well above the workload induced by the application of the normal standard operating procedures.	▪ WLM	▪ time criticality; ▪ multiple paths within the procedure (e.g. decision trees); ▪ multiple inoperative or degraded systems; ▪ a high potential for undetected errors (e.g. removal of flight protections); and a significant increase in workload (e.g. removal of automation).
(4)	The aircraft handling perceived by the pilot when flying in abnormal conditions is different compared to the aircraft handling in normal conditions; e.g. the symmetry of the flight is affected.	▪ FPM ▪ FPA	▪ multiple inoperative or degraded systems a high potential for undetected errors (e.g. removal of flight protections)

(c) When a malfunction is placing a significant demand on a proficient crew, it means it has one or more of the malfunction characteristics (see more in GM2.ORO.FC.231(f)).

GM2 ORO.FC.231(f) Evidence-based training

EQUIVALENCY OF MALFUNCTIONS — MALFUNCTION CHARACTERISTICS

The following may be considered suitable definitions for each of the characteristics:

(a) 'Immediacy': System malfunctions that require immediate and urgent crew intervention or decision (e.g. malfunctions with memory items, loss of pressurisation at high altitude, brake failure during landing).

(b) 'Complexity': System malfunctions that require recovery procedures with multiple options to analyse and/or multiple decision paths to apply (e.g. multiple hydraulic system failures, smoke and fumes procedures).

(c) 'Degradation of aircraft control': System malfunctions that result in significant degradation of flight controls in combination with abnormal handling characteristics, such as modification of the normal pitch attitude during approach and landing or reconfiguration of the flight control laws or modes (e.g. jammed stabiliser, flaps/slats inoperative)

(d) 'Loss of instrumentation': System malfunctions that require monitoring and management of the flight path using degraded or alternative displays such as temporary or permanent loss of any flight-path-related parameter displayed on the primary flight display (PFD), head-up display (HUD) or navigation display (ND), including loss of any setting capability of one of these indications. It includes primary instrumentation to monitor and manage primary aircraft systems (e.g. FLAPS indication, loss of fuel indications, etc.).

(e) 'Management of consequences': System malfunctions that affect significantly the flight crew standard task sharing and/or the workload management and/or the decision-making process during an extensive period after the management of the malfunction itself (e.g. fuel leak or fuel not usable, altitude/speed limitations, malfunctions with 'deferred' items in later flight phases).

Note: Equivalency of malfunctions may be undertaken in consultation with the aircraft OEM. The objective of the OEM consultation is to review the operator analysis regarding the OEM operational certification (e.g. OSD) documents and the general OEM operation and training policy.

GM3 ORO.FC.231(f) Evidence-based training

EQUIVALENCY OF MALFUNCTIONS — ISOLATION FROM AN ENVIRONMENTAL OR OPERATIONAL CONTEXT

When considering significant demand on a proficient crew, SMEs may consider that there are no significant environmental and operational threats. For example, the aircraft is close to a suitable aerodrome with environmental conditions permitting all published approaches to be made, with no pre-existing malfunctions and sufficient fuel for several hours (e.g. A320 or B737 overhead Ibiza - Spain, at FL350 with visible moisture at 30 000 ft, at the aerodrome wind calm, CAVOK, ISA).

GM4 ORO.FC.231(f) Evidence-based training

EQUIVALENCY OF MALFUNCTIONS PROCESS — DELPHI

(a) The operator reviews/looks at aircraft system malfunctions provided in the official documentation of the OEM — for example, FCOM for Airbus, or AFM for other manufacturers.

(b) Before launching the equivalency of malfunctions survey and when the aircraft system malfunctions list is very long, the operator may slightly shorten the list by removing the malfunctions that surely will not place a significant demand of a proficient crew (see GM on SIGNIFICANT DEMAND ON A PROFICIENT CREW).

(c) A group of EBT instructors statistically relevant will be selected to perform the equivalency of malfunctions survey. 50 % of the instructors' community will be used as a reference. In small instructors' communities, it may be necessary to refer to 100 %. In operators with large instructors' communities, the number of instructors statisticall relevant may be less than 50 %.

(d) The group of instructors selected in point (c) will rate each of the malfunctions listed in points (a) and (b)

(1) Each instructor will rate each one of the 5 characteristics in each malfunction listed in point (b).

(2) The rate will be 0 when the malfunction does not have the characteristic (the characteristic does not appear in the malfunction).

(3) The rate will be 1 to 5 when the characteristic appears in the malfunction. Rating 1 when the characteristic is not relevant for the malfunction and rate 5 when the characteristic is very relevant.

(4) The instructors will rate individually (e.g. home, classroom, etc.) to avoid exchange of opinions with other instructors.

(e) An average rate of the whole instructors' community as a result of point (d) will be calculated for each characteristic of each malfunction.

(f) A second round of survey will be performed with the same instructors and the same list. This time the operator will provide the average calculated in point (e) and ask them if in light of the average they would like to change their rating. Group discussion may substitute or complement the second survey.

(g) When an instructor changes their rating, the old rate will be discarded.

(h) A new average will be calculated for each characteristic of each malfunction at the end of the second survey. The final average will be rounded to the closest integer number.

(i) The operator may select an average rate of the characteristics (e.g. rate 2 or 3) at which or above which the characteristic is considered to be present in the malfunction, thus it places a significant demand on a proficient crew.

(j) The operator may use the rates of the characteristics to determine the difficulty of the malfunction. As SBT is a developing phase, the operator may select a higher difficulty of the malfunctions selected in this phase. Further guidance can be found in the EASA EBT manual.

(k) The operator may refer to an aircraft OEM malfunction analysis to support all the steps of the session.

(l) A simpler version of the process may be acceptable provided that:

(1) the aircraft manufacturer provides equivalency of malfunction documentation;

(2) there is a minimum of three EBT instructors who have a deep knowledge of aircraft systems; and

(3) the instructors referred to in (2) above are properly standardised. The standardisation is based on the EBT programme design knowledge and in particular the concept, definitions and process of the equivalency of malfunctions. The simplified process may or may not use a survey and use either a two-point scale (0 and 1), three-point scale (1, 2 and 3) or five-point scale (1 to 5).

AMC1 ORO.FC.231(g) Evidence-based training

APPROACHES THAT PLACE AN ADDITIONAL DEMAND ON A PROFICIENT

(a) In order to identify approaches that place an additional demand on a proficient crew, an operator should:

(1) review its operational network;

(2) select approaches with one or more of the following characteristics:

(i) unusual design;

(ii) low frequency of exposure; and

(iii) degraded approach guidance;

(3) select at least one approach of each type and method and include them in the EBT programme at the frequency given in the table of assessment and training topics; and

(4) ensure the approaches selected in (3) cover all the characteristics at the frequency given in the table of assessment and training topics.

Note: The approaches listed within Section 2 of the table of assessment and training topics should be selected in this process.

(b) Any approach that is required to be flown in the PF role specifically should be classified as 'skills retention' and may be trained in the MT.

AMC2 ORO.FC.231(g) Evidence-based training

EQUIVALENCY OF APPROACHES RELEVANT TO OPERATIONS — SPECIFIC APPROVAL

The operator may extend the interval for recurrent training and check ing of approaches that require specific approval as defined in the AMC to Part-SPA (e.g. SPA.LVO) to the frequency given in the EBT programme.

GM1 ORO.FC.231(g) Evidence-based training

EQUIVALENCY OF APPROACHES RELEVANT TO OPERATIONS — APPROACH CHARACTERISTICS

The following may be considered suitable examples for each of the approach characteristics:

(a) Design

(1) Unusual approach design feature — for example, offset final approach track or steep approach, etc.

(2) Unusual runway design feature — for example, non-standard lighting or marking

(b) Frequency

(1) Infrequently visited airfields — for example, alternate airfields

(2) Infrequently flown approaches at commonly visited airfields — for example, circling approach, CAT 2, SA CATI

(c) Degraded guidance

(1) Degraded internal guidance or aircraft equipment — for example, head-up display (HUD) failure

(2) Degraded external guidance or ground equipment — for example, GPS signal failure

GM2 ORO.FC.231(g) Evidence-based training

SELECTED APPROACHES AT THE FREQUENCY GIVEN IN THE EBT PROGRAMME

The table of assessment and training topics for each generation provides the type of approach, flight method and frequency for the crew.

AMC1 ORO.FC.231(h) Evidence-based training

LINE EVALUATION OF COMPETENCE

(a) The purpose of the line evaluation of competence is to verify the capability of the flight crew member(s) to undertake line operations, including preflight and post-flight activities as specified in the operations manual. Therefore, the line evaluation of competence should be performed in the aircraft. The route should be representative of typical sectors undertaken in normal operations. The commander, or any pilot who may be required to relieve the commander, should also demonstrate their competency in the role.

(b) Each flight crew member should be assessed according to the competency framework and grading system approved for their operator's EBT programme.

(c) Flight crew members should be assessed in duties as pilot flying and pilot monitoring; they should be evaluated in each role. Therefore, they should be checked on one flight sector as pilot flying and on another flight sector as pilot monitoring.

(d) The operator should maintain a list and inform the competent authority about the line evaluators suitably qualified to undertake line evaluations of competence.

(e) The person that conducts the line evaluation of competence should occupy an obs erver's seat. For aeroplanes, in the case of long-haul operations where additional operating flight crew members are carried, the person that conducts the line evaluation of competence may fulfil the function of a cruise relief pilot and should not occupy either pilot's seat during take-off, departure, initial cruise, descent, approach and landing.

(f) The validity period should be counted from the end of the month when the line evaluation of competence was undertaken. When the line evaluation of competence is undertaken within the last 3 months of the validity period, the new validity period should be counted from the original expiry date.

AMC2 ORO.FC.231(h) Evidence-based training

LINE EVALUATION OF COMPETENCE — LINE EVALUATOR

(a) The line evaluator should have a valid line evaluation of competence.

(b) The line evaluator should receive an acceptable training based on the EBT instructor training. The EBT assessment of competence is not required.

AMC1 ORO.FC.231(h)(3) Evidence-based training

LINE EVALUATION OF COMPETENCE — EXTENSION OF THE VALIDITY

In order to extend the validity of the line evaluation of competence to:

(a) 2 years, in every cycle, one EVAL for each pilot should be conducted by an EBT instructor (EBT instructors) who has (have) a valid line evaluation of competence in the same operator;

(b) 3 years, in addition to point (a) above, the operator should have a feedback process for the monitoring of line operations which:

(1) identifies threats in the airline's operating environment;

(2) identifies threats within the airline's operations;

(3) assesses the degree of transference of training to the line operations;

(4) checks the quality and usability of procedures;

(5) identifies design problems in the human-machine interface;

(6) understands pilots' shortcuts and workarounds; and

(7) assesses safety margins.

GM1 ORO.FC.231(h) Evidence-based training

LINE EVALUATION OF COMPETENCE

(a) Line evaluation of competence, route and aerodrome knowledge, and recent experience requirements are intended to verify the capability of the flight crew member(s) to operate safely, effectively and efficiently under line operating conditions, including preflight and post-flight activities as specified in the operations manual. Other EBT assessments, legacy checks and emergency and safety equipment training are primarily intended to prepare flight crew members for abnormal/emergency procedures.

(b) The line evaluation of competence is considered a particularly important factor in the development, maintenance and refinement of high operating standards, and can provide the operator with a valuable indication of the usefulness of its training policy and methods.

GM1 ORO.FC.231(h)(4) Evidence-based training

LINE EVALUATOR

(a) AMC1 ORO.FC.146(c) ' EBT instructor training' provides some learning objectives which may be used to qualify the commander nominated by the operator to perform line evaluation of competence. The training may be a minimum of 7 hours, where 1 hour may be done outside the classroom. The use of advance training environments such as advance computer-based training or ABLE may reduce further the need of classroom training. The assessment of competence may not be required. Further guidance can be found in the EASA EBT manual.

(b) The line evaluator training may be included in the EBT instructor standardisation and concordance programme. This option is however limited due to the limited number of line evaluations of competence that are required (every 2 or 3 years), the difficulties in observing the whole range of performance of competencies and the lack of control of the environment during a line evaluation of competence. Therefore, the operator may need to use EBT instructors to maintain an acceptable level of standardisation.

AMC1 ORO.FC.231(i) Evidence-based training

PERFORMANCE-BASED CONTINUOUS TECHNICAL GROUND TRAINING

(a) Technical ground training programme

(1) The objective of the technical ground training programme is to ensure that pilots have adequate:

(i) knowledge of:

(A) the aircraft systems; and

(B) the operational procedures and requirements; and

(ii) awareness of:

(A) the most significant accidents or incidents that could affect their operations following the 'threat and error management model' or an alternative risk model agreed with the authority; and

(B) the occurrences in the airline or occurrences from other airlines that may be relevant for

their operations, accident/incident and occurrence review.

(2) The technical ground training should:

(i) be conducted as part of a 3-year programme;

(ii) allow a customisation of syllabi. The operator should describe in the operations manual the procedure to determine the customisation of syllabi. This customisation should be based on evidence both internal and external to the operator;

(iii) as a minimum, allow the pilot to receive technical ground training every 12 months. The validity period should be counted from the end of the month. When this training is conducted within the last 3 months of the validity period, the new validity period should be counted from the original expiry date.

(3) The technical ground training syllabi should be delivered using different methods and tools.

(i) The selection of the method and tool results from a combination of the learning objectives and the target group receiving the training (WHAT needs to be trained and WHO needs to be trained).

(ii) The selection of the appropriate method and tool should be driven by the desired outcome in terms of adequate knowledge.

(iii) The delivery of the technical ground training syllabi should include the methods or tools to verify if the pilot has acquired the objective of the technical ground training programme. This may be achieved by means a questionnaire, assessment of application of the compe tency 'knowledge' (KNO) or other suitable methods.

(4) The measurement and evaluation of the training system performance through the feedback process should include the performance of the technical ground training.

(b) Emergency and safety equipment training

(1) Training on the location and use of all emergency and safety equipment should be conducted in an aircraft or a suitable alternative training device.

(2) Every year the emergency and safety equipment training programme should include the following:

(i) actual donning of a life jacket, where fitted;

(ii) actual donning of protective breathing equipment, where fitted;

(iii) actual handling of fire extinguishers of the type used;

(iv) instruction on the location and use of all emergency and safety equipment carried on the aircraft;

(v) instruction on the location and use of all types of exits; and

(vi) security procedures.

(3) Every 3 years the programme of training should include the following:

(i) actual operation of all types of exits;

(ii) demonstration of the method used to operate a slide, where fitted;

(iii) actual firefighting using equipment representative of that carried on the aircraft on an actual or simulated fire except that, with Halon extinguishers, an alternative extinguisher may be used;

(iv) the effects of smoke in an enclosed area and actual use of all relevant equipment in a simulated smoke-filled environment;

(v) actual handling of pyrotechnics, real or simulated, where applicable;

(vi) demonstration in the use of the life rafts, where fitted; and

(vii) particularly in the case where no cabin crew is required, first aid appropriate to the aircraft type, the kind of operation and the crew complement.

(4) The successful resolution of aircraft emergencies requires interaction between flight crew and cabin/technical crew and emphasis should be placed on the importance of effective coordination and two-way communication between all crew members in various emergency situations.

(5) Emergency and safety equipment training should include joint practice in aircraft evacuations so that all who are involved are aware of the duties other crew members should perform. When such practice is not possible, combined flight crew and cabin/technical crew training should include joint discussion of emergency scenarios.

(6) Emergency and safety equipment training should, as far as practicable, take place in conjunction with cabin/technical crew undergoing similar training with emphasis on coordinated procedures and two-way communication between the flight crew compartment and the cabin.

(7) The emerg ency and s afety equipment training should include a pilot's assessment of the training received; as a minimum, by means of a questionnaire, or computer-based exercises, or other suitable methods.

(8) When the emergency and safety equipment training is conducted within 3 calendar months prior to the expiry of the 12-calendar-month period, the next emergency and safety equipment training should be completed within 12 calendar months of the original expiry date of the previous training.

(c) Emergency and safety equipment training — extension of period of training

(1) The emergency and safety equipment training programme should establish and maintain at least an equivalent level of proficiency achieved by complying with the provisions of (b). The level of flight crew proficiency in the use of emergency and safety equipment should be demonstrated prior to being granted approval to extend the period of training by the competent authority.

(2) The operator applying for an approval to extend the period of emergency and safety equipment training should provide the competent authority with an implementation plan, including a description of the level of flight crew proficiency to be achieved in the use of emergency and safety equipment. The implementation plan should comprise the following:

(i) A safety case which should:

(A) demonstrate that the required or equivalent level of proficiency in the use of emergency and safety equipment is maintained;

(B) incorporate the programme of implementation, to include controls and validity checks;

(C) minimise risk during all phases of the programme's implementation and operation; and

(D) include oversight, including review and audits.

(ii) The measurement and evaluation of the training system performance through the feedback process should include the performance of the emergency and safety equipment training. The feedback should be used as a tool to validate that the emergency and safety equipment training is correctly implemented; this enables substantiation of the emergency and safety equipment training and ensures that objectives have been met.

(iii) Documentation that details the scope and requirements of the programme, including the following:

(A) the operator's training needs and established operational and training objectives;

(B) a description of the process for designing and obtaining approval for the operator's emergency and safety equipment training programmes. This should include quantified operational and training objectives identified by the operator's internal monitoring programmes. External sources may also be used; and

(C) a description of how the programme will develop a support and feedback process to form a self-correcting training system.

(3) When the emergency and safety equipment training is conducted within 6 calendar months prior to the expiry of the 24-calendar-month period, the next emergency and safety equipment training should be completed within 24 calendar months of the original expiry date of the previous training.

GM1 ORO.FC.231(i) Evidence-based training

PERFORMANCE-BASED CONTINUOUS GROUND TRAINING — INTERNAL AND EXTERNAL EVIDENCE

(a) Operator evidence (inner loop)

(1) Pilot data (individual or group);

(2) Population-based data according to the training metrics determined in the training system performance;

(3) Evidence identified or recognised through the safety management process covered in ORO.GEN.200.

(b) External evidence from the authority and manufacturers (external loop)

(1) Revision of existing rules and regulations, updated versions of the EBT data report, state safety plan;

(2) Training needs derived from updated OSD (if appropriate for ground training), etc.

(c) The evidence drives the selection of the methods and tools.

GM2 ORO.FC.231(i) Evidence-based training

PERFORMANCE-BASED CONTINUOUS GROUND TRAINING — METHODS AND TOOLS

This is a non-exhaustive list of methods and tools to deliver ground training:

— classroom, presentations,

— web-based training,

— self-learning instructions,

— advance CBT such as virtual reality, chatbots, interactive scenario trainers.

ORO.FC.232 EBT programme assessment and training topics

(a) The operator shall ensure that each pilot is exposed to the assessment and training topics.

(b) The assessment and training topics shall be:

(1) derived from safety and operational data that are used to identify the areas for improvement and prioritisation of pilot training to guide in the construction of suitable EBT programmes;

(2) distributed across a 3-year period at a defined frequency;

(3) relevant to the type or variant of aircraft on which the pilot operates.

AMC1 ORO.FC.232 EBT programme assessment and training topics

ASSESSMENT AND TRAINING TOPICS

Each table of assessment and training topics is specific to the aeroplane generation specified in the title. The component elements in the column headings of the matrix are as follows:

(a) Assessment and training topic. A topic or grouping of topics derived from threats, errors or findings from data analysis, to be considered for assessment and mitigation by training.

(b) Frequency. The priority of the topic to be considered in an EBT programme, according to the evidence derived from a large-scale analysis of operational data, is linked to a recommended frequency. There are three levels of frequency:

(1) A — assessment and training topic to be included with defined scenario elements during every EBT module;

(2) B — assessment and training topic to be included with defined scenario elements during every cycle;

(3) C — assessment and training topic to be included with defined scenario elements at least once in the 3-year period of the EBT programme.

(c) Flight phase for activation. The flight phase for the realisation of the critical threat or error in the assessment and training scenario.

(d) Description (includes type of topic, being threat, error or focus). A description of the training topic.

(e) Desired outcome (includes performance criteria or training outcome). Simple evaluative statements on the desired outcome.

(f) Example scenario elements (guidance material). The example scenario elements address the training topic and detail the threat and/or error that the crew are exposed to.

(g) Competency map. Competencies marked are those considered critical in managing the scenario.

AMC2 ORO.FC.232 EBT programme assessment and training topics

GENERATION 4 (JET) — TABLE OF ASSESSMENT AND TRAINING TOPICS

	Assessment and training topic	*Frequency*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Flight phase activation*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix							*Competency map*								
Section 1 — Skill retention. Manoeuvres training phase (MT)															
MT	Rejected take-off	B	Engine failure after the application of take-off thrust and before reaching V1 (CAT I or above)	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	From initiation of take-off to complete stop (or as applicable to the procedure)	X			X					
	Failure of the critical engine between V1 and V2	B	Failure of the critical engine (if applicable) from V1 and before reaching V2 in the lowest CAT I visibility or in LVO meteorological (MET) conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
	Failure of one engine on take-off	B	Failure of one engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO MET conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
			Failure of one engine above V2 (any segment of the TO) in the lowest CAT I visibility or in LVO MET conditions.			The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed.	X		X	X					
	Emergency descent	C	Initiation of emergency descent from normal cruise altitude		CRZ	The manoeuvre is complete once the aircraft is stabilised in emergency descent configuration (and profile).	X		X	X					
	Engine-out approach & landing	B	With the critical engine (if applicable) failed, normal landing		LDG	Initiation in a stabilised engine-out configuration from not less than 3 NM final approach, until completion of roll-out	X			X					
	Engine-out approach & go-around	B	With the critical engine (if applicable) failed, manually flown normal precision approach to DA, followed by a manual go-around — the whole manoeuvre to be flown without visual reference		APP	This manoeuvre should be flown from intercept to centreline until acceleration after go-around. The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement (describe generally the critical part of the manoeuvre).	X			X					
	Go-around	A	Go-around, all engines operative		APP	High energy, initiation during the approach at 150 to 300 m (500 to 1 000 ft) below the missed approach level-off altitude	X		X	X					
						Initiation of a go-around from DA followed by visual circuit and landing	X		X	X					
						During flare/rejected landing	X		X	X					
	Pilot qualification to operate in either pilot's seat	B	As per ORO.FC.235		APP	Complete the manoeuvres mandated in ORO.FC.235.	Intentionally left in blank.								

	Assessment and training topic	Frequency	Description (includes type of topic, being threat, error or focus)	Desired outcome (includes performance criteria OR training outcome)	Flight phase activation	Guidance material (GM) Example scenario elements	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Generation 4 Jet — Recurrent assessment and training matrix							Competency map								
Section 2 — Equivalency of approaches relevant to operations. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
MT	Approach type A or B	B	Approach type A or B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT	Approach type A	B	Approach type A flight method 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or SBT	Approach type A	B	Approach type A flight method 3D or 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or SBT	Approach type B	B	Approach type B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
Section 3 – Equivalency of approaches under specific approvals and take-off under specific approvals. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
MT	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations - specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL or	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL, MT or SBT	SPA rejected take-off (RTO)	B	Engine failure after the application of take-off thrust and before reaching V1 (in low-visibility MET conditions, preferably in the lowest approved visibility) Low-visibility RTO is not required under Part SPA but instead in Appendix 9 Section 6. Note: AMC1 SPA.LVO.120 point (f) does not require a low-visibility RTO. RTO is required only in the initial LVO course (point (g)(1)(iii) of AMC1 SPA.LVO.120).	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope.	TO	RTO — can be combined with the assessment and training topic 'surprise' in EVAL or SBT	X			X					
EVAL, MT or SBT	LVTO	B	Notwithstanding AMC1 SPA.LVO120 point (f)(1) AMC1 SPA.LVO.120 requires SPA manoeuvres in the frequency of the OPC, as OPC is substituted in the EBT programme. Thus, the frequency in EBT is determined in every cycle (B). Low-visibility take-off, preferably in the lowest approved visibility.	Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement.	X			X					

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
Section 4 — Training topics with frequency (A) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Adverse weather	*A*	*GND*	Thunderstorm, heavy rain, turbulence, ice build-up to include de-icing issues, as well as high-temperature conditions. The proper use of anti-ice and de-icing systems should be included generally in appropriate scenarios.	Anticipate adverse weather. Prepare for suspected adverse weather. Recognise adverse weather. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control.	Predictive wind shear warning before take-off, as applicable	X	X				X			
			ALL			Adverse-weather scenario, e.g. thunderstorm activity, precipitation, icing		X			X	X		X	
			TO			Wind shear encounter during take-off, not predictive	X			X			X		X
			TO			Predictive wind shear warning during take-off	X	X				X	X		
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			CRZ			Turbulence that increases to severe turbulence		X			X		X	X	
			CRZ			Wind shear encounter scenario during cruise	X		X			X	X	X	
			APP			Reactive wind shear warning during approach or go-around	X		X	X			X		
			APP			Predictive wind shear warning during approach or go-around	X	X				X	X		
			APP			Thunderstorm encounter during approach or on missed approach	X					X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Non-precision approach in cold-temperature conditions, requiring altitude compensation for temperature, as applicable to the type	X	X					X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP			In approach, unexpected braking action 'good to medium' reported by the preceding aircraft		X				X	X	X	
			APP			Moderate to severe icing conditions during approach effecting aircraft performance	X	X				X	X		
			APP			Reduced visibility even after acquiring the necessary visual reference during approach, due to rain or fog	X	X				X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
EVAL or SBT	Automation management	*A*	*CLB CRZ DES APP*	The purpose of this topic is to encourage and develop effective flight path management through proficient and appropriate use of the flight management system(s), guidance and automation, including transitions between modes, monitoring, mode awareness, vigilance and flexibility needed to change from one mode to another. The means of mitigating errors are included in this topic. The errors are described as mishandled auto flight systems, inappropriate mode selection, mishandled flight management system(s) and inappropriate autopilot usage.	Know how and when to use the flight management system(s), guidance and automation. Demonstrate correct methods for engagement and disengagement of the auto flight system(s). Demonstrate appropriate use of flight guidance, auto thrust and other automation systems. Maintain mode awareness of the auto flight system(s), including engagement and automatic transitions. Revert to different modes when appropriate. Detect deviations from the desired aircraft state (flight path, speed, attitude, thrust, etc.) and take appropriate action. Anticipate mishandled auto flight system. Recognise mishandled auto flight system. Take appropriate action if necessary. Restore correct auto flight state. Identify and manage consequences.	ACAS warning, recovery and subsequent engagement of automation	X		X						
			ALL			FMS tactical programming issues, e.g. step climb, runway changes, late clearances, destination re-programming, executing diversion	X		X						*X*
			CLB CRZ DES APP			Recoveries from terrain avoidance warning systems (TAWS), management of energy state to restore automated flight	X		X	X					
			CLB CRZ DES APP			Amendments to ATC cleared levels during altitude capture modes to force mode awareness and intervention	X		X				*X*		
			TO			Late ATC clearance to an altitude below acceleration altitude	X		X				*X*		
			TO APP			Engine-out special terrain procedures	X		X				*X*		
			CRZ			Forcing autopilot disconnect followed by re-engagement, recovery from low- or high-speed events in cruise	X		X	X			*X*		
			CLB			Engine failure during or after initial climb using automation	X		X						
			CRZ			Engine failure in cruise to onset of descent using automation	X		X						
			CRZ			Emergency decent	X		X						*X*
			DES APP			Managing high-energy descent capturing descent path from above (correlation with unstable approach training)	X		X				*X*		*X*
			APP			No ATC clearance received prior to commencement of approach or final descent	X		X				*X*		
			APP			Reactive wind shear and recovery from the consequent high-energy state	X		X				*X*		
			APP			Automation fail to capture the approach altitude in descent (e.g. last altitude before the FAP). Ideally, the failure occurs when the workload is high (e.g. configuration of the aircraft for final approach).					X	*X*	*X*	*X*	
			APP			Non-precision or infrequently flown approaches using the maximum available level of automation	X		X						*X*
			APP			Gear malfunction during an approach planned with autoland (including autobrake). Competency FPA may or may not be included depending on the impact of such malfunction on the automation.		X	X			*X*		*X*	
			APP			ATC clearances to waypoints beyond the programmed descent point for a coded final descent point during an approach utilising a final descent that is commanded by the flight management system	X		X				*X*		*X*

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
EVAL or SBT	Competencies —non-technical (CRM)	*A*	*APP*	This encapsulates the general CRM principles and objectives. It includes communication; leadership and teamwork; problem-solving and decision-making; situation awareness and management of information; and workload management. Emphasis should be placed on the development of leadership, shown by EBT data sources to be a highly effective competency in mitigating risk and improving safety through pilot performance.	Exposure to an event or sequence of events to allow the pilot to build awareness of human factors in aviation and the human limitations. This includes the development of the following competencies: <u>Communication:</u> Demonstrate: — effective use of language; — responsiveness to feedback; and — capability to state the plans and resolve ambiguities. <u>Leadership and teamwork:</u> Use appropriate authority to ensure focus on the task. Support others in completing tasks. <u>Problem-solving and decision-making:</u> Detect deviations from the desired state, evaluate problems, identify the risk, consider alternatives and select the best course of action. Continuously review progress and adjust plans. <u>Situation awareness and management of information:</u> Have an awareness of the aircraft state in its environment; project and anticipate changes. <u>Workload management:</u> Prioritise, delegate and receive assistance to maximise focus on the task. Continuously monitor the flight progress.	GPS failure prior to commencement of approach associated with position drift and a terrain alert					X	X	X		X
			DES			Cabin crew report of water noise below the forward galley indicating a possible toilet pipe leak, with consequent avionics failures					X	X	X		
			CRZ			Smoke removal but combined with a diversion until landing is completed.		X			X	X	X	X	X
			GND			Apron fuel spilling					X	X		X	
			CRZ			Important water leak in an aircraft galley		X			X	X		X	
			ALL			A relevant number of cabin crew are wounded or incapacitated. Additionally, the cabin crew wounded or incapacitated are the most competent (e.g. senior cabin crew member).					X	X		X	
			ALL			Unruly passenger(s)					X			X	
			GND			Passenger oxygen: passenger service unit open and mask falling down					X	X		X	
			ALL			Passenger with medical problems — medical emergency					X			X	
			CRZ			Credible threat reported to the crew. Stowaway or fugitive on board.		X			X		X	X	
			GND			No METAR or TAFOR is available for destination due to industrial action at the destination airport.	X	X			X	X			
			CRZ			Credible bomb threat reported to crew		X			X		X	X	
			CLB DES			Credible bomb threat or pressurisation problem, but no quick landing possible (due to weather, terrain or other reasons)		X			X	X		X	
			APP			Diversion with low remaining fuel or increased fuel flow due to system malfunction	X				X		X	X	
			APP			ACAS warning immediately following a go-around, with a descent manoeuvre required		X			X	X	X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
EVAL or SBT	Compliance	*A*	*ALL*	Compliance failure. Consequences of not complying with operating instructions (e.g. SOPs). This is not intended to list example scenario elements, but instructors should ensure that observed non-compliances are taken as learning opportunities throughout the programme. In all modules of the programme, the FSTD should as far as possible be treated like an aircraft, and non-compliances should not be accepted simply for expediency.	Recognise that a compliance failure has occurred. Make a verbal announcement. Take appropriate action if necessary. Restore safe flight path if necessary. Manage consequences.	The following are examples of potential compliance failures and are not intended to be developed as scenarios as part of an EBT module: 1. Requesting flap beyond limit speed 2. Flaps or slats in the wrong position for phase of flight or approach 3. Omitting an action as part of a procedure 4. Failing to initiate or complete a checklist 5. Using the wrong checklist for the situation	Intentionally blank								
EVAL or SBT	Go-around management	*A*	APP	Any threat or error that can result in circumstances that require a decision to perform a go-around, in addition to the execution of the go-around. Go-around scenarios should be fully developed to encourage effective leadership and teamwork, in addition to problem-solving and decision-making, plus execution using manual aircraft control or the flight management system(s) and automation as applicable. Design should include the element of surprise, and scenario-based go-arounds should not be predictable and anticipated. This topic is completely distinct from the go-around manoeuvre listed in the MT section that is intended only to practise psychomotor skills and a simple application of the procedures.		Adverse-weather scenario leading to a reactive wind shear warning during approach	X	X					X	X	
			APP			Adverse-weather scenario leading to a predictive wind shear warning during approach or go-around	X	X					X	X	
			APP			Adverse-weather scenario, e.g. thunderstorm activity, heavy precipitation or icing forcing decision at or close to DA/MDA	X					X	X	X	
			APP			DA with visual reference in heavy precipitation with doubt about the runway surface braking capability	X					X	X	X	
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP			Lost or difficult communications resulting in no approach clearance prior to commencement of approach or final descent	X		X				X		
			APP			Birds: large flocks of birds below DA once visual reference has been established				X		X	X		
			APP			System malfunction, landing gear malfunction during the approach									

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
EVAL or SBT	Manual aircraft control	*A*	*CLB CRZ DES APP*	Controls the flight path through manual control	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the normal flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	Flight with unreliable airspeed, which may or may not be recoverable	X			X			X		X
			CLB CRZ DES APP			Alternate flight control modes according to malfunction characteristics	X			X				X	X
			CLB CRZ DES APP			ACAS RA requires the pilot to descend or ATC calls for immediate descent	X	X		X					
			DES			TAWS warning when deviating from planned descent routing, requiring immediate response	X			X	X				
			TO			Scenario immediately after take-off which requires an immediate and overweight landing			X	X	X	X			
			TO			Adverse wind, crosswinds with or without strong gusts on take-off	X			X					
			TO			Adverse weather, wind shear, wind shear encounter during take-off, with or without reactive warnings	X			X			X		
			TO			Engine failure during initial climb, typically 30-60 m (100-200 ft) (autopilot off)	X	X		X				X	
			CRZ			Wind shear encounter scenario during cruise, significant and rapid change in wind speed or down/updrafts, without wind shear warning	X		X			X	X	X	
			APP			Adverse weather, wind shear, wind shear encounter with or without warning during approach	X		X	X			X		
			APP			Adverse weather, deterioration in visibility or cloud base, or adverse wind, requiring a go-around from visual circling approach, during the visual segment	X	X	X	X		X	X	X	
			APP			Interception of the glide slope from above (correlation with unstable approach training)			X				X	X	
			APP LDG			Adverse wind, crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP LDG			Adverse weather, adverse wind, approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP LDG			Circling approach manually flown at night in minimum in-flight visibility to ensure ground reference, minimum environmental lighting and no glide slope guidance lights	X			X			X	X	
			APP LDG			Runway incursion during approach, which can be triggered by ATC at various altitudes or by visual contact during the landing phase	X			X			X		
			LDG			Adverse wind, visibility, type-specific, special consideration for long-bodied aircraft, landing in minimum visibility for visual reference, with crosswind.	X	X		X			X		
			LDG			System malfunction, auto flight failure at DA during a low-visibility approach requiring a go-around flown manually	X		X	X			X		
			APP LDG			Approach planned with autoland, followed by a failure below 1 000 ft requiring a manual go-around and an immediate landing due to fuel shortage	X		X		X		X		
			TO			In-seat instruction: Insufficient engine failure recovery, forcing the pilot monitoring to take over the flight controls		X		X			X	X	
			APP LDG			In-seat instruction: Unstable approach on short final or long landing, forcing the pilot monitoring to take over the flight controls		X		X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
EVAL or SBT	Monitoring, cross-checking, error management, mismanaged aircraft state	*A*	*ALL*	The scenarios should be realistic and relevant, and should be used for the purpose of demonstration and reinforcement of effective monitoring. Modules in the FSTD should be treated like those in an aircraft so that trainees have the opportunity to develop the competency with the practice of the right techniques and attitudes related to these topics through pilot performance, and that instructors have the opportunity to assess and train these topics in a realistic environment. As shown by the EBT data report, these topics are of key importance to improve safety in operations. In addition, the operator may also use these topics to develop scripted role-playing scenarios in the form of ISI. These scenarios cater for the need to monitor flight path excursions from the instructor pilot (PF), detect errors and make appropriate interventions, either verbally or by taking control as applicable. Demonstration scenarios may also be used. Demonstrated role-play should contain realistic and not gross errors, leading at times to a mismanaged aircraft state, which can also be combined with upset management training.	Recognise mismanaged aircraft state. Observe the pilot's behaviour: how the pilot is mitigating errors, performing cross-checking, monitoring performance and dealing with a mismanaged aircraft state, in order to ensure that observed deviations, errors and mistakes are taken as learning opportunities throughout the programme. Monitor flight path excursions. Detect errors and threats through proper cross-checking performance. Make appropriate interventions either verbally or by taking control if applicable. Take appropriate action if necessary. Restore the desired aircraft state. Identify and manage consequences.	Deviations from the flight path, in pitch attitude, speed, altitude, bank angle		X					X		
			ALL			In-seat instruction: Simple automation errors (e.g. incorrect mode selection, attempted engagement without the necessary conditions, entering wrong altitude or speed, failure to execute the desired mode) culminating in a need for direct intervention from the pilot monitoring, and where necessary taking control.		X					X		
			APP			In-seat instruction: Unstable approach or speed/path/vertical rate not congruent with the required state for the given flight condition	X	X					X	X	
			LDG			In-seat instruction: Demonstration exercise — recovery from bounced landing, adverse wind, strong gusts during landing phase, resulting in a bounce and necessitating recovery action from the pilot monitoring	X			X			X		
	Unstable approach	*A*	*DES APP*	Reinforce stabilised approach philosophy and adherence to defined parameters. Encourage go-arounds when crews are outside these parameters. Develop and sustain competencies related to the management of high-energy situations.		ATC or terrain-related environment creating a high-energy descent with the need to capture the optimum profile to complete the approach in a stabilised configuration	X		X				X		
			DES APP			ATC or terrain-related environment creating a high-energy descent leading to unstable conditions and requiring a go-around	X		X				X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 4 Jet — Recurrent assessment and training matrix															
Section 5 — UPRT training topic with frequency (B). Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
EVAL, MT or SBT	Upset prevention training	B	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include upset prevention elements in Table 1 for the recurrent training programme in at least every cycle, such that all the elements are covered over a period not exceeding 3 years. The elements are numbered with letters from A to I in Table 1 of AMC1 ORO.FC.220&230. Each element is made up of several numbered components. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recognising and preventing the development of upset conditions.	Early recognition and prevention of upset conditions. When the differences between LHS and RHS are not significant in the handling of the aircraft, UPRT may be conducted in either seat.	See Table 1 of AMC1 ORO.FC.220&230: Elements and respective components of upset prevention training.	Intentionally blank								
			CRZ			Demonstration of the defined normal flight envelope and any associated changes in flight instruments, flight director systems, and protection systems. This should take the form of an instructor-led exercise to show the crew the points beyond which an upset condition could exist.			X					X	X
			TO APP			Severe wind shear or wake turbulence during take-off or approach			X	X		X	X		
			CRZ			As applicable and relevant to the aircraft type, demonstration at a suitable intermediate level, with turbulence as appropriate; practise steep turns and note the relationship between bank angle, pitch and stalling speed.				X			X		X
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence to trigger overspeed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism).	X		X	X			X		
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence and significant temperature rise to trigger low-speed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism).			X	X			X		X
			CRZ			High-altitude TCAS RA (where the RA is required to be flown in manual flight)	X			X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 6 — Training topics with frequency (B) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Adverse wind	B	TO	Adverse wind/crosswind. This includes tailwind but not ATC misreporting of the actual wind.	Recognise adverse-wind conditions. Observe limitations. Apply the appropriate procedures. Maintain directional control and safe flight path.	Take-off with different crosswind/tailwind/gust conditions						X		X	
			TO			Take-off with unreported tailwind		X			X				
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			APP			Wind exceeding limits on final approach (not reported)	X	X				X	X		
			APP			Wind exceeding limits on final approach (reported) in manual aircraft control	X	X		X		X			
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswind including shifting wind directions				X		X	X		
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP LDG			Crosswind with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Aircraft system malfunctions, including operations under MEL	B	ALL	Any internal failure(s) apparent or not apparent to the crew Any item cleared by the MEL but having an impact upon flight operations — for instance, thrust reverser locked. Malfunctions to be considered should have one or more of the following characteristics: — Immediacy — Complexity — Degradation of aircraft control — Loss of primary instrumentation — Management of consequences The operator should vary malfunctions for each characteristic over the EBT cycle. Unless specified otherwise in the operational suitability data, at least one malfunction with each characteristic should be included in every cycle. Combining characteristics should not reduce the number of malfunctions below seven in each cycle. For each crew member, the characteristics of degraded control and loss of instrumentation should be in the role of pilot flying and the others may be in the role of pilot flying or pilot monitoring. For full details, see the malfunction equivalency methodology.	Recognise system malfunction. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences. Apply crew operating procedures where necessary. Respond appropriately to additional system abnormalities associated with MEL dispatch.	(i) System malfunctions that require immediate and urgent crew intervention or decision, e.g. fire, smoke, loss of pressurisation at high altitude, failures during take-off, brake failure during landing. (ii) System malfunctions that require complex procedures, e.g. multiple hydraulic system failures, smoke and fumes procedures, major electrical system failure. (iii) System malfunctions that result in significant degradation of flight controls in combination with abnormal handling characteristics, e.g. jammed flight controls, certain degradation of FBW control, jammed horizontal stabiliser; flaps and/or slats locked; other malfunctions that result in degraded flight controls. (iv) System failures that require monitoring and management of the flight path using degraded or alternative displays, unreliable primary flight path information, unreliable airspeed, e.g. flight with unreliable airspeed (v) System failures that require extensive management of their consequences (independent of operation or environment), e.g. fuel leak.	*Intentionally blank*								
			TO			MEL items with crew operating procedures applicable during take-off						X			X
			TO			Response to an additional factor that is affected by an MEL item (e.g. system failure, runway state)		X		X		X			X
			GND			Malfunction during preflight preparation and prior to departure	X					X	X		
			CLB			Malfunction after departure	X					X	X		X
			ALL			Malfunctions that require immediate attention (e.g. bleed fault during engine start, hydraulic failure during taxi)	X				X			X	
			CLB CRZ			Fuel leak (management of consequences)	X				X		X		X
			TO			Malfunction on take-off high speed below V1	X				X	X			
			TO			Malfunction on take-off high speed above V1	X					X			
			GND			During taxi to the runway, a spurious brake temperature announcement. The crew had the correct brake temperature moments before the failure.					X	X	X		
			TO			Tyre failure during take-off					X	X		X	
			TO			Malfunction on initial climb	X					X			
			APP			Malfunction on approach	X					X		X	
			APP			Malfunction on go-around	X					X		X	
			LDG			Malfunction during landing	X	X		X		X	X		

	Assessment and training topic	*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Aircraft system management	B	N/A	Normal system operation according to defined instructions	This is not considered as a stand-alone topic. It is linked with the topic 'compliance'. Where a system is not managed according to normal or defined procedures, this is determined as a non-compliance.	See 'compliance' topic above. There are no defined scenarios, but the instructor should focus on learning opportunities when system management non-compliances manifest themselves during other scenarios. Underpinning knowledge of systems and their interactions should be developed and challenged, and not merely the application of normal procedures.	Intentionally blank								X
			CRZ APP LDG			Minimum fuel, caused by extended delays, weather, etc. where the crew would need to manage a minimum fuel situation.					X	X	X	X	
	Approach, visibility close to minimum	B	APP	Any situation where visibility becomes a threat	Recognise actual conditions. Observe aircraft and/or procedural limitations. Apply the appropriate procedures if applicable. Maintain directional control and safe flight path.	Approach in poor visibility	X		X	X				X	
			APP			Approach in poor visibility with deteriorations necessitating a decision to perform a go-around	X		X	X					
			LDG			Landing in poor visibility				X		X	X		
	Landing	B	LDG	Pilots should have opportunities to practise landings in demanding situations at the defined frequency. Data indicates that landing problems have their roots in a variety of factors, including inappropriate decision-making, in addition to manual aircraft control skills if difficult environmental conditions exist. The purpose of this item is to ensure that pilots are exposed to this during the programme.	Landing in demanding environmental conditions, with malfunctions as appropriate	This topic should be combined with the adverse-weather topic, aircraft system malfunctions topic or any topic that can provide exposure to a landing in demanding conditions.	Intentionally blank								
	Runway or taxiway condition	B	GND TO LDG	Contamination or surface quality of the runway, taxiway, or tarmac including foreign objects	Recognise hazardous runway condition. Observe limitations. Take appropriate action. Apply the appropriate procedures correctly. Assure aircraft control.	Planned anticipated hazardous conditions with dispatch information provided to facilitate planning and execution of appropriate procedures						X			X
			GND TO LDG			Unanticipated hazardous conditions, e.g. unexpected heavy rain resulting in flooded runway surface		X			X	X			
			TO			Take-off on runway with reduced cleared width due to snow	X			X	X		X		
			TO			Stop/go decision in hazardous conditions					X	X		X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Surprise	B	TO	The data analysed during the development of the EBT concept indicated substantial difficulties encountered by crews when faced with a threat or error, which was a surprise or an unexpected event. The element of surprise should be distinguished from what is sometimes referred to as the 'startle factor' — the latter being a physiological reaction. Wherever possible, consideration should be given towards variations in the types of scenario, times of occurrences and types of occurrence, so that pilots do not become overly familiar with repetitions of the same scenarios. Variations should be the focus of EBT programme design, and not left to the discretion of individual instructors, in order to preserve programme integrity and fairness.	Exposure to an unexpected event or sequence of events at the defined frequency in order to build resilience.	Rejected take- off	X			X		X			
			ALL			Intentionally blank	Intentionally blank								
EVAL or SBT	Terrain	B	ALL	Alert, warning, or conflict	Anticipate terrain threats. Prepare for terrain threats. Recognise unsafe terrain clearance. Take appropriate action. Apply the appropriate procedures correctly. Maintain aircraft control. Restore safe flight path. Manage consequences.	ATC clearance giving insufficient terrain clearance	X	X			X				X
			ALL			Demonstration of terrain avoidance warning systems (TAWS) (this scenario element may be done in an ISI.)						X	X	X	
			TO CLB			Engine failure where performance is marginal leading to TAWS warning		X		X				X	
			DES APP			ATC provides a wrong QNH		X					X		
			DES			'Virtual mountain' refers to the surprise element of an unexpected warning. Care should be exercised in creating a level of realism, so this can best be achieved by an unusual and unexpected change of route during the descent.						X	X	X	
	Workload, distraction, pressure, stress	B	ALL	This is not considered a topic for specific attention on its own, but more as a reminder to programme developers to ensure that pilots are exposed to immersive training scenarios which expose them to manageable high workload and distractions during the course of the EBT programme, at the defined frequency.	Manage available resources efficiently to prioritise and perform tasks in a timely manner under all circumstances	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*		*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 7 — UPRT Upset recovery training topic with frequency (C). Manoeuvres training phase or scenario-based training phase (MT or SBT)																
MT or SBT	Upset recovery	C	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include the recovery exercises in Table 2 of AMC1 ORO.FC.220&230 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recovery from developed upsets. The same principles apply to the exercises of components 2, 3 and 4 where one exercise may satisfy the requirement to cover the whole component. An aeroplane upset is defined as an undesired aeroplane state in flight characterised by unintentional divergences from parameters normally experienced during line operations or training. An aeroplane upset may involve pitch and/or bank angle divergences as well as inappropriate airspeeds for the conditions.	Recognise upset condition. Make timely and appropriate intervention. Take appropriate action. Assure timely and appropriate intervention. (AMC1 ORO.FC.220&230 Table 2 component 1) Assure aircraft control. Maintain or restore a safe flight path. Assess consequential issues. Manage outcomes. Consolidate the summary of aeroplane recovery techniques. (AMC1 ORO.FC.220&230 Table 2 component 5) Note: The operator should assess if the exercises should be practised for the either seat qualification.	The example scenario elements may be done in ISI, as non-ISI or a combination of both. If done in ISI: The instructor should position the aircraft within but close to the edge of the validated training envelope before handing control to the trainee to demonstrate the restoration of normal flight. Careful consideration should be given to flying within the validated training envelope.		Intentionally blank								
			CLB DES			Table 2 of AMC1 ORO.FC.220&230: Exercises for upset recovery training										
						A	**Recovery from developed upsets**									
						2.	Recovery from stall events in the following configurations: — take-off configuration, — clean configuration low altitude, — clean configuration near maximum operating altitude, and — landing configuration during the approach phase	X			X			X	X	
			CRZ			3.	Recovery from nose high at various bank angles	X			X			X	X	
			CRZ			4.	Recovery from nose low at various bank angles	X			X			X	X	
			CRZ			Demonstration at a normal cruising altitude. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.		X			X			X		
			APP			Demonstration at an intermediate altitude during early stages of the approach. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.		X			X			X		
			CLB DES			Recovery from a wake turbulence position with high-bank angle		X		X	X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 8 — Training topics with frequency (C) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	ATC	C	ALL	ATC error. Omission, miscommunication, garbled, poor quality transmission. All these act as distractions to be managed by the crew. The scenarios should be combined, where possible, with others of the same or higher weighting, the principal reason being to create distractions.	Respond to communications appropriately. Recognise, clarify and resolve any ambiguities. Refuse or question unsafe instructions. Use standard phraseology whenever possible.	ATC role-play: the instructor provides scripted instructions, as a distraction to the crew	X	X			X				
			ALL			Controller error, provided by the instructor according to a defined scripted scenario	X	X				X	X		
			ALL			Frequency congestion, with multiple aircraft using the same frequency		X							
			APP			Destination temporarily closed					X	X	X	X	
			CRZ			Rescue and firefighting services (RFFS) level reduction at destination		X			X		X		
			APP			Runway change before the interception of the localiser or similar navigation aid in azimuth			X		X		X	X	
			GND TO			Stray dogs at the opposite threshold runway		X			X		X		
			ALL			Poor quality transmissions		X							
EVAL or SBT	Engine failure	C	TO	Any engine failure or malfunction, which causes loss or degradation of thrust that affects performance. This is distinct from the engine-out manoeuvres described in the MT section above, which are intended only to practise psychomotor skills and reinforce procedures to manage engine failures.	Recognise engine failure. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences	Engine failure or engine malfunction on take-off low speed	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off high speed below V1	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off above V1	X					X	X	X	
			TO			Engine failure or engine malfunction on initial climb	X					X	X		
			APP			Engine malfunction	X					X		X	
			CRZ			Engine failure in cruise (with autopilot)	X		X				X		
			CRZ			Multiple engine failure in CRZ (volcanic ash, recoverable). Competency FPM may or may not be included depending on the impact on the automation.					X	X	X	X	
			LDG			Engine failure or engine malfunction on landing				X					
EVAL or SBT	Fire and smoke management	C	GND	This includes engine, electric, pneumatic, cargo fire, smoke or fumes.	Recognise fire, smoke or fumes Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Fire in cargo or cabin/cockpit at gate	X	X				X		X	
			GND			Fire during taxi	X	X				X		X	X
			GND			Fire with no cockpit indication	X	X				X		X	X
			TO			Take-off low speed	X			X	X	X			X
			TO			Fire or smoke on take-off high speed below V1	X			X	X	X			
			TO			Fire or smoke on take-off high speed above V1	X				X	X			
			TO			Fire or smoke on initial climb	X				X	X			
			CRZ			Cargo compartment fire or avionics compartment fire						X	X	X	
			APP			Engine fire in approach (extinguishable)		X				X			
			APP			Engine fire in approach (non-extinguishable)		X			X	X			
			CLB *CRZ* *DES*			Lithium battery fire in the cockpit or cabin compartment	X	X			X	X		X	
			APP			Flight deck or cabin fire		X			X	X			X
			GND			Any of the example scenario elements above ending in an evacuation		X			X	X		X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
	Loss of communication	*C*	*GND*	Lost or difficult communications due to either pilot mis-selection or a failure external to the aircraft. This could be for a few seconds or a total loss.	Recognise loss of communications. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative ways to communicate. Manage consequences.	Loss of communications during ground manoeuvring	X	X							
			TO			Loss of communications after take-off	X					X			X
			APP			Loss of communications during approach phase, including go-around	X	X				X	X		X
EVAL or SBT	Managing loading, fuel, performance errors	C	ALL	A calculation error by one or more pilots, or someone involved with the process, or the process itself, e.g. incorrect information on the load sheet	Anticipate the potential for errors in load/fuel/performance data. Recognise inconsistencies. Manage/avoid distractions. Make changes to paperwork/aircraft system(s) to eliminate error. Identify and manage consequences.	This can be a demonstrated error, in that the crew may be instructed to deliberately insert incorrect data — for example, to take off from an intersection with full-length performance information. The crew will be asked to intervene when acceleration is sensed to be lower than normal, and this may be part of the operator procedures, especially when operating mixed fleets with considerable variations in MTOM.	X	X						X	
			TO			Wind report with take-off clearance not consistent with prior performance calculation. ATC, cabin crew or other people are pushing crew to take off quickly.	X				X		X	X	
			GND			Environmental change during taxi (e.g. heavy rain) not consistent with prior take-off performance calculation							X	X	
			GND			Fuel ground staff on industrial action. Only limited amount of fuel available, which is below the calculated fuel for the flight.					X	X	X	X	
			GND			Advise crew that there is a change of the load sheet figures during taxi to the runway. The crew may have limited time due to a calculated take-off time (CTOT) — ATC Slot.	X							X	
			GND			Braking action reported 'medium'. The information is transmitted just before take-off. The flight is subject to a CTOT — ATC slot.					X		X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Navigation	C	GND	External NAV failure. Loss of GPS satellite, ANP exceeding RNP, loss of external NAV source(s)	Recognise a NAV degradation. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative NAV guidance. Manage consequences.	External failure or a combination of external failures degrading aircraft navigation performance on ground	X		X			X	X		
			TO CLB APP LDG			External failure or a combination of external failures degrading aircraft navigation performance in flight		X			X	X	X		
			GND			Standard initial departure change during taxi. The flight may be subject to a CTOT — ATC slot.					X		X	X	
			APP			Loss of runway lighting below decision height		X				X	X		
			CRZ			No fly zone: when the crew changes control frequency, the new ATCO informs the crew that they are flying over an unannounced 'no fly zone' that is not included in the NOTAMs. (To trigger such an event, the context may be as follows: an unexpected military conflict in the territory the aircraft is flying over or the crew is forced to re-route in flight and the new route flies over a city that has an important event such the Olympic games, a G20/G7 submit, or the route is flying near a space rocket launch close to the time of the launch, like the Guiana Space Centre, Cape Cañaveral, etc.).					X	X	X		
	Operations- or type-specific	C	ALL	Intentionally blank	Intentionally blank	Intentionally blank	Intentionally blank								
	Operations of special airport approval	C	APP LDG	See equivalency of approaches relevant to operations.	The operator should comply with the national qualification requirements published in the aeronautical information publication (AIP).	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Pilot incapacitation	C	TO	Consequences for the non-incapacitated pilot	Recognise incapacitation. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	During take-off	X	X			X	X			X
			APP			During approach	X			X				X	X
	Traffic	C	CLB CRZ DES	Traffic conflict. ACAS RA or TA, or visual observation of conflict, which requires evasive manoeuvring	Anticipate potential loss of separation. Recognise loss of separation. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	ACAS warning that requires crew intervention		X				X	X	X	
	Wind shear recovery	C	TO	With or without warnings including predictive. A wind shear scenario is ideally combined with an adverse-weather scenario containing other elements.	Anticipate potential for wind shear. Avoid known wind shear or prepare for suspected wind shear. Recognise wind shear encounter. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control. Recognise out of wind shear condition. Maintain or restore a safe flight path. Assess consequential issues and manage outcomes.	Predictive wind shear warning during take-off					X	X			
			TO			Wind shear encounter during take-off	X				X	X			
			TO			Wind shear encounter after rotation						X		X	
			TO			Predictive wind shear after rotation					X	X			
			APP			Predictive wind shear during approach	X				X	X			
			APP			Wind shear encounter during go-around	X				X	X		X	
			APP			Wind shear encounter during approach	X				X	X			

END GEN4 JET

AMC3 ORO.FC.232 EBT programme assessment and training topics

GENERATION 3 (JET) — TABLE OF ASSESSMENT AND TRAINING TOPICS

	Assessment and training topic	*Frequency*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Flight phase activation*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							*Competency map*								
Section 1 — Skill retention. Manoeuvres training phase (MT)															
MT	Rejected take-off	B	Engine failure after the application of take-off thrust and before reaching V1 (CAT I or above)	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	From initiation of take-off to complete stop (or as applicable to the procedure)	X			X					
	Failure of the critical engine between V1 and V2	A	Failure of the critical engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO meteorological (MET) conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
	Failure of one engine on take-off	B	Failure of one engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO MET conditions		TO	The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
			Failure of one engine above V2 (any segment of the TO) in the lowest CAT I visibility or in LVO MET conditions.			The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed.	X		X	X					
	Emergency descent	C	Initiation of emergency descent from normal cruise altitude		CRZ	The manoeuvre is complete once the aircraft is stabilised in emergency descent configuration (and profile).	X		X	X					
	Engine-out approach & landing	B	With the critical engine (if applicable) failed, normal landing		LDG	Initiation in a stabilised engine-out configuration from not less than 3 NM final approach, until completion of roll-out	X			X					
	Engine-out approach & go-around	B	With the critical engine (if applicable) failed, manually flown normal precision approach to DA, followed by a manual go-around — the whole manoeuvre to be flown without visual reference		APP	This manoeuvre should be flown from intercept to centreline until acceleration after go-around. The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement (describe generally the critical part of the manoeuvre).	X			X					
	Go-around	A	Go-around, all engines operative		APP	High energy, initiation during the approach at 150 to 300 m (500 to 1 000 ft) below the missed approach level-off altitude	X		X	X					
						Initiation of a go-around from DA followed by visual circuit and landing	X		X	X					
						During flare/rejected landing	X		X	X					
	Pilot qualification to operate in either pilot's seat	B	As per ORO.FC.235		APP	Complete the manoeuvres mandated in ORO.FC.235.	Intentionally left in blank.								

	Assessment and training topic	Frequency	Description (includes type of topic, being threat, error or focus)	Desired outcome (includes performance criteria OR training outcome)	Flight phase activation	Guidance material (GM) Example scenario elements	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Generation 4 Jet — Recurrent assessment and training matrix							Competency map								
Section 2 — Equivalency of approaches relevant to operations. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
MT	Approach type A or B	B	Approach type A or B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT	Approach type A	B	Approach type A flight method 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT	Approach type A	B	Approach type A flight method 3D or 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT	Approach type B	B	Approach type B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
Section 3 – Equivalency of approaches under specific approvals and take-off under specific approvals. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
M	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL or SBT	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL, MT or SBT	SPA Rejected take-off (RTO)	B	Engine failure after the application of take-off thrust and before reaching V1 (in low-visibility MET conditions, preferably in the lowest approved visibility) Low-visibility RTO is not required under Part SPA but instead in Appendix 9 Section 6. Note: AMC1 SPA.LVO.120 point (f) does not require a low-visibility RTO. RTO is required only in the initial LVO course (point (g)(1)(iii) of AMC1 SPA.LVO.120).	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	RTO — can be combined with the assessment and training topic 'surprise' in EVAL or SBT	X			X					
EVAL, MT or SBT	LVTO	B	Notwithstanding AMC1 SPA.LVO120 point (f)(1) AMC1 SPA.LVO.120 requires SPA manoeuvres in the frequency of the OPC, as OPC is substituted in the EBT programme. Thus, the frequency in EBT is determined in every cycle (B). Low visibility take-off, preferably in the lowest approved visibility		TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement.	X			X					

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix															
Section 4 — Training topics with frequency (A) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT).															
EVAL or SBT	Adverse weather	A	GND	Thunderstorm, heavy rain, turbulence, ice build-up to include de-icing issues, as well as high-temperature conditions. The proper use of anti-ice and de-icing systems should be included generally in appropriate scenarios.	Anticipate adverse weather. Prepare for suspected adverse weather. Recognise adverse weather. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control.	Predictive wind shear warning before take-off, as applicable	X	X				X			
			ALL			Adverse-weather scenario, e.g. thunderstorm activity, precipitation, icing		X			X	X		X	
			TO			Wind shear encounter during take-off, not predictive	X			X			X		X
			TO			Predictive wind shear warning during take-off	X	X				X	X		
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			CRZ			Turbulence that increases to severe turbulence		X			X		X	X	
			CRZ			Wind shear encounter scenario during cruise	X		X			X	X	X	
			APP			Reactive wind shear warning during approach or go-around	X		X	X			X		
			APP			Predictive wind shear warning during approach or go-around	X					X	X		
			APP			Thunderstorm encounter during approach or on missed approach	X	X				X	X		
			APP			Increasing tailwind on final approach (not reported)				X		X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions	X	X					X		
			APP			Non-precision approach in cold-temperature conditions, requiring altitude compensation for temperature, as applicable to the type	X			X		X			
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)		X				X	X	X	
			APP			In approach, unexpected braking action 'good to medium' reported by the preceding aircraft	X	X				X	X		
			APP			Moderate to severe icing conditions during approach effecting aircraft performance	X	X				X	X		
			APP			Reduced visibility even after acquiring the necessary visual reference during approach, due to rain or fog	X	X				X			
EVAL or SBT	Automation management	A	CLB CRZ DES APP	The purpose of this topic is to encourage and develop effective flight path management through proficient and appropriate use of the flight management system(s), guidance and automation, including transitions between modes, monitoring, mode awareness, vigilance and flexibility needed to change from one mode to another. The means of mitigating errors are included in this topic. The errors are described as mishandled auto flight systems, inappropriate mode selection, mishandled flight management system(s) and inappropriate autopilot usage.	Know how and when to use the flight management system(s), guidance and automation. Demonstrate correct methods for engagement and disengagement of the auto flight system(s). Demonstrate appropriate use of flight guidance, auto thrust and other automation systems. Maintain mode awareness of the auto flight system(s), including engagement and automatic transitions. Revert to different modes when appropriate. Detect deviations from the desired aircraft state (flight path, speed, attitude, thrust, etc.) and take appropriate action.	ACAS warning, recovery and subsequent engagement of automation	X		X						
			ALL			FMS tactical programming issues, e.g. step climb, runway changes, late clearances, destination re-programming, executing diversion	X		X						X
			CLB CRZ DES APP			Recoveries from TAWS, management of energy state to restore automated flight	X		X	X					
			CLB CRZ DES APP			Amendments to ATC cleared levels during altitude capture modes to force mode awareness and intervention	X		X				X		
			TO			Late ATC clearance to an altitude below acceleration altitude	X		X				X		
			TO APP			Engine-out special terrain procedures	X		X				X		
			CRZ			Forcing autopilot disconnect followed by re-engagement, recovery from low- or high-speed events in cruise	X		X	X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
			CLB			Engine failure during or after initial climb using automation	X		X						
			CRZ			Engine failure in cruise to onset of descent using automation	X		X						
			CRZ			Emergency descent	X		X						X
			DES APP			Managing high-energy descent capturing descent path from above (correlation with unstable approach training)	X		X				X		X
			APP			No ATC clearance received prior to commencement of approach or final descent	X		X				X		
			APP			Reactive wind shear and recovery from the consequent high-energy state	X		X				X		
			APP		Anticipate mishandled auto flight system. Recognise mishandled auto flight system. Take appropriate action if necessary. Restore correct auto flight state. Identify and manage consequences.	Automation fail to capture the approach altitude in descent (e.g. last altitude before the FAP). Ideally, the failure occurs when the workload is high (e.g. configuration of the aircraft for final approach).					X	X	X	X	
			APP			Non-precision or infrequently flown approaches using the maximum available level of automation	X		X						X
			APP			Gear malfunction during an approach planned with autoland (including autobrake). Competency FPA may or may not be included depending on the impact of such malfunction on the automation.		X	X			X		X	
			APP			ATC clearances to waypoints beyond the programmed descent point for a coded final descent point during an approach utilising a final descent that is commanded by the flight management system.	X		X				X		X
EVAL or SBT	Competencies — non-technical (CRM)	A	APP	This encapsulates the general CRM principles and objectives. It includes communication; leadership and teamwork; problem-solving and decision-making; situation awareness and management of information; and workload management. Emphasis should be placed on the development of leadership, shown by EBT data sources to be a highly effective competency in mitigating risk and improving safety through pilot performance.	Exposure to an event or sequence of events to allow the pilot to build awareness of human factors in aviation and the human limitations. This includes the development of the following competencies: <u>Communication:</u> Demonstrate: — effective use of language; — responsiveness to feedback; and — capability to state the plans and resolve ambiguities. <u>Leadership and teamwork:</u> Use appropriate authority to ensure focus on the task. Support others in completing tasks.	GPS failure prior to commencement of approach with position drift and a terrain alert.					X	X	X		X
			DES			Cabin crew report of water noise below the forward galley indicating a possible toilet pipe leak, with consequent avionics failures					X	X	X		
			CRZ			Smoke removal but combined with a diversion until landing is completed.		X			X	X	X	X	X
			GND			Apron fuel spilling					X	X		X	
			CRZ			Important water leak in an aircraft galley		X			X	X		X	
			ALL			A relevant number of cabin crew are wounded or incapacitated. Additionally, the cabin crew wounded or incapacitated are the most competent (e.g. senior cabin crew member).					X	X		X	
			ALL			Unruly passenger(s)					X			X	
			GND			Passenger oxygen: passenger service unit open and mask falling down					X	X		X	
			ALL			Passenger with medical problems — medical emergency					X			X	
			CRZ			Credible threat reported to the crew. Stowaway or fugitive on board.		X			X		X	X	
			GND			No METAR or TAFOR is available for destination due to industrial action at the destination airport.	X	X			X	X			
						Credible bomb threat reported to crew		X			X		X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
EVAL or SBT			CLB DES APP		<u>Problem-solving and decision-making:</u> Detect deviations from the desired state, evaluate problems, identify the risk, consider alternatives and select the best course of action. Continuously review progress and adjust plans. <u>Situation awareness and management of information:</u> Have an awareness of the aircraft state in its environment; project and anticipate changes. <u>Workload management:</u> Prioritise, delegate and receive assistance to maximise focus on the task. Continuously monitor the flight progress.	Credible bomb threat or pressurisation problem, but no quick landing possible (due to weather, terrain or other reasons) Diversion with low remaining fuel or increased fuel flow due to system malfunction	X	X			X X	X	X	X X	
			APP			ACAS warning immediately following a go-around, with a descent manoeuvre required		X			X	X	X	X	
EVAL or SBT	Compliance	A	ALL	Compliance failure. Consequences of not complying with operating instructions (e.g. SOPs). This is not intended to list example scenario elements, but instructors should ensure that observed non-compliances are taken as learning opportunities throughout the programme. In all modules of the programme, the FSTD should as far as possible be treated like an aircraft, and non-compliances should not be accepted simply for expediency.	Recognise that a compliance failure has occurred. Make a verbal announcement. Take appropriate action if necessary. Restore safe flight path if necessary. Manage consequences.	The following are examples of potential compliance failures and are not intended to be developed as scenarios as part of an EBT mod: 1. Requesting flap beyond limit speed 2. Flaps or slats in the wrong position for phase of flight or approach 3. Omitting an action as part of a procedure 4. Failing to initiate or complete a checklist 5. Using the wrong checklist for the situation	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
EVAL or SBT	Go-around management	A	APP	Any threat or error that can result in circumstances that require a decision to perform a go-around, in addition to the execution of the go-around. Go-around scenarios should be fully developed to encourage effective leadership and teamwork, in addition to problem-solving and decision-making, plus execution using manual aircraft control or the flight management system(s) and automation as applicable. Design should include the element of surprise, and scenario-based go-arounds should not be predictable and anticipated. This topic is completely distinct from the go-around manoeuvre listed in the MT section that is intended only to practise psychomotor skills and a simple application of the procedures.		Adverse-weather scenario leading to a reactive wind shear warning during approach	X	X					X	X	
			APP			Adverse-weather scenario leading to a predictive wind shear warning during approach or go-around	X	X					X	X	
			APP			Adverse-weather scenario, e.g. thunderstorm activity, heavy precipitation or icing forcing decision at or close to DA/MDA	X					X	X	X	
			APP			DA with visual reference in heavy precipitation with doubt about the runway surface braking capability	X					X	X	X	
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP			Lost or difficult communications resulting in no approach clearance prior to commencement of approach or final descent	X		X				X		
			APP			Birds: large flocks of birds below DA once visual reference has been established				X		X	X		
			APP			System malfunction, landing gear malfunction during the approach									

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
EVAL or SBT	Manual aircraft control	A	CLB CRZ DES APP	Controls the flight path through manual control	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the normal flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	Flight with unreliable airspeed, which may or may not be recoverable	X			X			X		X
			CLB CRZ DES APP			Alternate flight control modes according to malfunction characteristics	X			X				X	X
			CLB CRZ DES APP			ACAS RA requires the pilot to descend or ATC calls for immediate descent	X	X		X					
			DES			TAWS warning when deviating from planned descent routing, requiring immediate response	X			X	X				
			TO			Scenario immediately after take-off which requires an immediate and overweight landing			X	X	X	X			
			TO			Adverse wind, crosswinds with or without strong gusts on take-off	X			X					
			TO			Adverse weather, wind shear, wind shear encounter during take-off, with or without reactive warnings	X			X			X		
			TO			Engine failure during initial climb, typically 30-60 m (100-200 ft) (autopilot off)	X	X		X				X	
			CRZ			Wind shear encounter scenario during cruise, significant and rapid change in wind speed or down/updrafts, without wind shear warning	X		X			X	X	X	
			APP			Adverse weather, wind shear, wind shear encounter with or without warning during approach	X		X	X			X		
			APP			Adverse weather, deterioration in visibility or cloud base, or adverse wind, requiring a go-around from visual circling approach, during the visual segment	X	X	X	X		X	X	X	
			APP			Interception of the glide slope from above (correlation with unstable approach training)			X				X	X	
			APP LDG			Adverse wind, crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP LDG			Adverse weather, adverse wind, approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP LDG			Circling approach manually flown at night in minimum in-flight visibility to ensure ground reference, minimum environmental lighting and no glide slope guidance lights	X			X			X	X	
			APP LDG			Runway incursion during approach, which can be triggered by ATC at various altitudes or by visual contact during the landing phase	X			X			X		
			LDG			Adverse wind, visibility, type-specific, special consideration for long-bodied aircraft, landing in minimum visibility for visual reference, with crosswind	X	X		X			X		
			LDG			System malfunction, auto flight failure at DA during a low-visibility approach requiring a go-around flown manually	X		X	X			X		
			APP LDG			Approach planned autoland, followed by a failure below 1 000 ft requiring a manual go-around and an immediate landing due to fuel shortage	X		X		X		X		
			TO			In-seat instruction: Insufficient engine failure recovery, forcing the pilot monitoring to take over the flight controls		X		X			X	X	
			APP LDG			In-seat instruction: Unstable approach on short final or long landing, forcing the pilot monitoring to take over the flight controls		X		X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
EVAL or SBT	Monitoring, cross-checking, error management, mismanaged aircraft state	A	ALL	The scenarios should be realistic and relevant, and should be used for the purpose of demonstration and reinforcement of effective monitoring. Modules in the FSTD should be treated like those in an aircraft so that trainees have the opportunity to develop the competency with the practice of the right techniques and attitudes related to these topics through pilot performance, and that instructors have the opportunity to assess and train these topics in a realistic environment. As shown by the EBT data report, these topics are of key importance to improve safety in operations. In addition, the operator may also use these topics to develop scripted role-playing scenarios in the form of ISI. These scenarios cater for the need to monitor flight path excursions from the instructor pilot (PF), detect errors and make appropriate interventions, either verbally or by taking control as applicable. Demonstration scenarios may also be used. Demonstrated role-play should contain realistic and not gross errors, leading at times to a mismanaged aircraft state, which can also be combined with upset management training.	Recognise mismanaged aircraft state. Observe the pilot's behaviour: how the pilot is mitigating errors, performing cross-checking, monitoring performance and dealing with a mismanaged aircraft state, in order to ensure that observed deviations, errors and mistakes are taken as learning opportunities throughout the programme. Monitor flight path excursions. Detect errors and threats through proper cross-checking performance. Make appropriate interventions either verbally or by taking control if applicable. Take appropriate action if necessary. Restore the desired aircraft state. Identify and manage consequences.	Deviations from the flight path, in pitch attitude, speed, altitude, bank angle		X					X		
			ALL			In-seat instruction: Simple automation errors (e.g. incorrect mode selection, attempted engagement without the necessary conditions, entering wrong altitude or speed, failure to execute the desired mode) culminating in a need for direct intervention from the pilot monitoring, and where necessary taking control.		X					X		
			APP			In-seat instruction: Unstable approach or speed/path/vertical rate not congruent with the required state for the given flight condition	X	X					X	X	
			LDG			In-seat instruction: Demonstration exercise — recovery from bounced landing, adverse wind, strong gusts during landing phase, resulting in a bounce and necessitating recovery action from the pilot monitoring	X			X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Jet — Recurrent assessment and training matrix							Competency map								
	Unstable approach	A	DES APP	Reinforce stabilised approach philosophy and adherence to defined parameters. Encourage go-arounds when crews are outside these parameters. Develop and sustain competencies related to the management of high-energy situations.		ATC or terrain-related environment creating a high-energy descent with the need to capture the optimum profile to complete the approach in a stabilised configuration	X		X				X		
			DES APP			ATC or terrain-related environment creating a high-energy descent leading to unstable conditions and requiring a go-around	X		X				X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 5 — UPRT training topic with frequency (B). Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
EVAL, MT or SBT	Upset prevention training	B	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include upset prevention elements in Table 1 for the recurrent training programme in at least every cycle, such that all the elements are covered over a period not exceeding 3 years. The elements are numbered with letters from A to I in Table 1 of AMC1 ORO.FC.220&230. Each element is made up of several numbered components. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recognising and preventing the development of upset conditions.	Early recognition and prevention of upset conditions. When the differences between LHS and RHS are not significant in the handling of the aircraft, UPRT may be conducted in either seat.	See Table 1 of AMC1 ORO.FC.220&230: Elements and respective components of upset prevention training.	Intentionally blank								
			CRZ			Demonstration of the defined normal flight envelope and any associated changes in flight instruments, flight director systems, and protection systems. This should take the form of an instructor-led exercise to show the crew the points beyond which an upset condition could exist.			X					X	X
			TO APP			Severe wind shear or wake turbulence during take-off or approach			X	X		X	X		
			CRZ			As applicable and relevant to the aircraft type, demonstration at a suitable intermediate level, with turbulence as appropriate; practise steep turns and note the relationship between bank angle, pitch and stalling speed				X			X		X
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence to trigger overspeed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)	X		X	X			X		
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence and significant temperature rise to trigger low-speed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)			X	X			X		X
			CRZ			High-altitude loss of reliable airspeed	X	X		X			X	X	
			CRZ			High-altitude TCAS RA (where the RA is required to be flown in manual flight)	X			X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 6 — Training topics with frequency (B) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL, MT or SBT	Adverse wind	B	TO		Recognise adverse-wind conditions. Observe limitations. Apply the appropriate procedures. Maintain directional control and safe flight path.	Take-off with different crosswind/tailwind/gust conditions						X		X	
			TO			Take-off with unreported tailwind		X			X				
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			APP			Wind exceeding limits on final approach (not reported)	X	X				X	X		
			APP			Wind exceeding limits on final approach (reported) in manual aircraft control	X	X		X		X			
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswind including shifting wind directions				X		X	X		
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP LDG			Crosswind with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
EVAL or SBT	Aircraft system malfunctions, including operations under MEL	B	ALL	Any internal failure(s) apparent or not apparent to the crew Any item cleared by the MEL but having an impact upon flight operations — for instance, thrust reverser locked. Malfunctions to be considered should have one or more of the following characteristics: — Immediacy — Complexity — Degradation of aircraft control — Loss of primary instrumentation — Management of consequences The operator should vary malfunctions for each characteristic over the EBT cycle. Unless specified otherwise in the operational suitability data, at least one malfunction with each characteristic should be included in every cycle. Combining	Recognise system malfunction. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences. Apply crew operating procedures where necessary. Respond appropriately to additional system abnormalities associated with MEL dispatch.	(i) System malfunctions that require immediate and urgent crew intervention or decision, e.g. fire, smoke, loss of pressurisation at high altitude, failures during take-off, brake failure during landing. (ii) System malfunctions that require complex procedures, e.g. multiple hydraulic system failures, smoke and fumes procedures, major electrical system failure. (iii) System malfunctions that result in significant degradation of flight controls in combination with abnormal handling characteristics, e.g. jammed flight controls, certain degradation of FBW control, jammed horizontal stabiliser; flaps and/or slats locked; other malfunctions that result in degraded flight controls. (iv) System failures that require monitoring and management of the flight path using degraded or alternative displays, unreliable primary flight path information, unreliable airspeed, e.g. flight with unreliable airspeed (v) System failures that require extensive management of their consequences (independent of operation or environment), e.g. fuel leak.	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
			TO			MEL items with crew operating procedures applicable during take-off						X			X
			TO			Response to an additional factor that is affected by an MEL item (e.g. system failure, runway state)		X		X		X			X
			GND			Malfunction during preflight preparation and prior to departure	X					X	X		
			CLB			Malfunction after departure	X					X	X		X
			ALL			Malfunctions that require immediate attention (e.g. bleed fault during engine start, hydraulic failure during taxi)	X				X			X	
			CLB CRZ			Fuel leak (management of consequences)	X				X		X		X
			TO			Malfunction on take-off high speed below V1	X				X	X			
			TO			Malfunction on take-off high speed above V1	X					X			
			GND			During taxi to the runway, a spurious brake temperature announcement. The crew had the correct brake temperature moments before the failure.					X	X	X		
			TO	characteristics should not reduce the number of malfunctions below seven for each cycle. For each crew member, the characteristics of degraded control and loss of instrumentation should be in the role of pilot flying and the others may be in the role of pilot flying or pilot monitoring. For full details, see the malfunction equivalency methodology		Tyre failure during take-off					X	X		X	
			TO			Malfunction on initial climb	X					X			
			APP			Malfunction on approach	X					X		X	
			APP			Malfunction on go-around	X					X		X	
			LDG			Malfunction during landing	X	X		X		X	X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Aircraft system management	B		Normal system operation according to defined instructions	This is not considered as a stand-alone topic. It is linked with the topic 'compliance'. Where a system is not managed according to normal or defined procedures, this is determined as a non-compliance.	See 'compliance' topic above. There are no defined scenarios, but the instructor should focus on learning opportunities when system management non-compliances manifest themselves during other scenarios. Underpinning knowledge of systems and their interactions should be developed and challenged, and not merely the application of normal procedures.	Intentionally blank								X
			CRZ APP LDG			Minimum fuel, caused by extended delays, weather, etc. where the crew would need to manage a minimum fuel situation.					X	X	X	X	
	Approach, visibility close to minimum	B	APP	Any situation where visibility becomes a threat	Recognise actual conditions. Observe aircraft and/or procedural limitations. Apply the appropriate procedures if applicable. Maintain directional control and safe flight path.	Approach in poor visibility	X		X	X				X	
			APP			Approach in poor visibility with deteriorations necessitating a decision to perform a go-around	X		X	X					
			LDG			Landing in poor visibility				X		X	X		
	Landing	B	LDG	Pilots should have opportunities to practise landings in demanding situations at the defined frequency. Data indicates that landing problems have their roots in a variety of factors, including inappropriate decision-making, in addition to manual aircraft control skills if difficult environmental conditions exist. The purpose of this item is to ensure that pilots are exposed to this during the programme.	Landing in demanding environmental conditions, with malfunctions as appropriate	This topic should be combined with the adverse-weather topic, aircraft system malfunctions topic or any topic that can provide exposure to a landing in demanding conditions.	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Surprise	B	ALL	The data analysed during the development of the EBT concept indicated substantial difficulties encountered by crews when faced with a threat or error, which was a surprise or an unexpected event. The element of surprise should be distinguished from what is sometimes referred to as the 'startle factor' — the latter being a physiological reaction. Wherever possible, consideration should be given towards variations in the types of scenario, times of occurrences and types of occurrence, so that pilots do not become overly familiar with repetitions of the same scenarios. Variations should be the focus of EBT programme design, and not left to the discretion of individual instructors, in order to preserve programme integrity and fairness.	Exposure to an unexpected event or sequence of events at the defined frequency in order to build resilience.	Rejected take-off	X			X		X			
						Intentionally blank	Intentionally blank								
EVAL or SBT	Wind shear recovery	B	TO	With or without warnings including predictive. A wind shear scenario is ideally combined with an adverse-weather scenario containing other elements.	Anticipate potential for wind shear. Avoid known wind shear or prepare for suspected wind shear. Recognise wind shear encounter. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control. Recognise out of wind shear condition. Maintain or restore a safe flight path. Assess consequential issues and manage outcomes.	Predictive wind shear warning during take-off					X	X			
			TO			Wind shear encounter during take-off	X				X	X			
			TO			Wind shear encounter after rotation						X		X	
			TO			Predictive wind shear after rotation					X	X			
			APP			Predictive wind shear during approach	X				X	X			
			APP			Wind shear encounter during go-around	X				X	X		X	
			APP			Wind shear encounter during approach	X				X	X			
EVAL or SBT	Workload, distraction, pressure, stress	B	ALL	This is not considered a topic for specific attention on its own, but more as a reminder to programme developers to ensure that pilots are exposed to immersive training scenarios which expose them to manageable high workload and distractions during the course of the EBT programme, at the defined frequency.	Manage available resources efficiently to prioritise and perform tasks in a timely manner under all circumstances	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*		*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 7 — UPRT Upset recovery training topic with frequency (C). Manoeuvres training phase or scenario-based training phase (MT or SBT)																
MT or SBT	Upset recovery	C	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include the recovery exercises in Table 2 of AMC1 ORO.FC.220&230 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recovery from developed upsets. The same principles apply to the exercises of components 2, 3 and 4 where one exercise may satisfy the requirement to cover the whole component. An aeroplane upset is defined as an undesired aeroplane state in flight characterised by unintentional divergences from parameters normally experienced during line operations or training. An aeroplane upset may involve pitch and/or bank angle divergences as well as inappropriate airspeeds for the conditions.	Recognise upset condition. Make timely and appropriate intervention. Take appropriate action. Assure timely and appropriate intervention. (AMC1 ORO.FC.220&230 Table 2 component 1) Assure aircraft control. Maintain or restore a safe flight path. Assess consequential issues. Manage outcomes. Consolidate the summary of aeroplane recovery techniques. (AMC1 ORO.FC.220&230 Table 2 component 5) Note: The operator should assess if the exercises should be practised for the either seat qualification.	The example scenario elements may be done in ISI, as non-ISI or a combination of both. If done in ISI: The instructor should position the aircraft within but close to the edge of the validated training envelope before handing control to the trainee to demonstrate the restoration of normal flight. Careful consideration should be given to flying within the validated training envelope.		Intentionally blank								
			CLB DES			Table 2 of AMC1 ORO.FC.220&230: Exercises for upset recovery training										
						A.	Recovery from developed upsets									
						2.	Recovery from stall events in the following configurations: — take-off configuration, — clean configuration low altitude, — clean configuration near maximum operating altitude, and — landing configuration during the approach phase.	X			X			X	X	
			CRZ			3.	Recovery from nose high at various bank angles	X			X			X	X	
			CRZ			4.	Recovery from nose low at various bank angles	X			X			X	X	
			CRZ			Demonstration at a normal cruising altitude. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.		X			X			X		
			APP			Demonstration at an intermediate altitude during early stages of the approach. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.		X			X			X		
			CLB DES			Recovery from a wake turbulence position with high-bank angle		X		X	X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 8 — Training topics with frequency (C) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	ATC	C	ALL	ATC error. Omission, miscommunication, garbled, poor quality transmission. All these act as distractions to be managed by the crew. The scenarios should be combined, where possible, with others of the same or higher weighting, the principal reason being to create distractions.	Respond to communications appropriately. Recognise, clarify and resolve any ambiguities. Refuse or question unsafe instructions. Use standard phraseology whenever possible.	ATC role-play: the instructor provides scripted instructions, as a distraction to the crew	X	X			X				
			ALL			Controller error, provided by the instructor according to a defined scripted scenario	X	X				X	X		
			ALL			Frequency congestion, with multiple aircraft using the same frequency		X							
			APP			Destination temporarily closed					X	X	X	X	
			CRZ			Rescue and firefighting services (RFFS) level reduction at destination		X			X		X		
			APP			Runway change before the interception of the localiser or similar navigation aid in azimuth			X		X		X	X	
			GND/ TO			Stray dogs at the opposite threshold runway		X			X		X		
			ALL			Poor quality transmissions		X							
EVAL or SBT	Engine failure	C	TO	Any engine failure or malfunction, which causes loss or degradation of thrust that affects performance. This is distinct from the engine-out manoeuvres described in the MT section above, which are intended only to practise psychomotor skills and reinforce procedures to manage engine failures.	Recognise engine failure. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Engine failure or engine malfunction on take-off low speed	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off high speed below V1	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off above V1	X					X	X	X	
			TO			Engine failure or engine malfunction on initial climb	X					X	X		
			APP			Engine malfunction	X					X		X	
			CRZ			Engine failure in cruise (with autopilot)	X		X				X		
			CRZ			Multiple engine failure in CRZ (volcanic ash, recoverable). Competency FPM may or may not be included depending on the impact on the automation.					X	X	X	X	
			LDG			Engine failure or engine malfunction on landing				X					
EVAL or SBT	Fire and smoke management	C	GND	This includes engine, electric, pneumatic, cargo fire, smoke or fumes.	Recognise fire, smoke or fumes. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Fire in cargo or cabin/cockpit at gate	X	X				X		X	
			GND			Fire during taxi	X	X				X		X	X
			GND			Fire with no cockpit indication	X	X				X		X	X
			TO			Take-off low speed	X			X	X	X			X
			TO			Fire or smoke on take-off high speed below V1	X			X	X	X			
			TO			Fire or smoke on take-off high speed above V1	X				X	X			
			TO			Fire or smoke on Initial climb	X				X	X			
			CRZ			Cargo compartment fire or avionics compartment fire.						X	X	X	
			APP			Engine fire in approach (extinguishable)		X				X			
			APP			Engine fire in approach (non-extinguishable)		X			X	X			
			CLB CRZ DES			Lithium battery fire in the cockpit or cabin compartment	X	X			X	X		X	
			APP			Flight deck or cabin fire		X			X	X			X
			GND			Any of the example scenario elements above ending in an evacuation		X			X	X		X	
EVAL or SBT	Loss of communication	C	GND	Lost or difficult communications due to either pilot mis-selection or a failure external to the aircraft. This could be for a few seconds or a total loss.	Recognise loss of communications. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative ways to communicate. Manage consequences.	Loss of communications during ground manoeuvring	X	X				X			
			TO			Loss of communications after take-off	X					X			X
			APP			Loss of communications during approach phase, including go-around	X	X				X	X		X

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Managing loading, fuel, performance errors	C	ALL	A calculation error by one or more pilots, or someone involved with the process, or the process itself, e.g. incorrect information on the load sheet	Anticipate the potential for errors in load/fuel/performance data. Recognise inconsistencies. Manage/avoid distractions. Make changes to paperwork/aircraft system(s) to eliminate error. Identify and manage consequences.	This can be a demonstrated error, in that the crew may be instructed to deliberately insert incorrect data — for example, to take off from an intersection with full-length performance information. The crew will be asked to intervene when acceleration is sensed to be lower than normal, and this may be part of the operator procedures, especially when operating mixed fleets with considerable variations in MTOM.	X	X						X	
			TO			Wind report with take-off clearance not consistent with prior performance calculation. ATC, cabin crew or other people are pushing crew to take off quickly.	X				X		X	X	
			GND			Environmental change during taxi (e.g. heavy rain) not consistent with prior take-off performance calculation							X	X	
			GND			Fuel ground staff on industrial action. Only limited amount of fuel available, which is below the calculated fuel for the flight					X	X	X	X	
			GND			Advise crew that there is a change of the load sheet figures during taxi to the runway. The crew may have limited time due to a calculated take-off time (CTOT) — ATC slot.	X							X	
			GND			Braking action reported 'medium'. The information is transmitted just before take-off. The flight is subject to a CTOT — ATC slot.					X		X	X	
EVAL or SBT	Navigation	C	GND	External NAV failure. Loss of GPS satellite, ANP exceeding RNP, loss of external NAV source(s)	Recognise a NAV degradation. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative NAV guidance. Manage consequences.	External failure or a combination of external failures degrading aircraft navigation performance on ground	X		X			X	X		
			TO CLB APP LDG			External failure or a combination of external failures degrading aircraft navigation performance in flight		X			X	X	X		
			GND			Standard initial departure change during taxi. The flight may be subject to a CTOT — ATC slot.					X		X	X	
			APP			Loss of runway lighting below decision height		X				X	X		
			CRZ			No fly zone: when the crew changes control frequency, the new ATCO informs the crew that they are flying over an unannounced 'no fly zone' that is not included in the NOTAMs. (To trigger such an event, the context may be as follows: an unexpected military conflict in the territory the aircraft is flying over or the crew is forced to re-route in flight and the new route flies over a city that has an important event such the Olympic games, a G20/G7 submit, or the route is flying near a space rocket launch close to the time of the launch, like the Guiana Space Centre, Cape Cañaveral, etc.).					X	X	X		
	Operations- or type-specific	C	ALL	Intentionally blank	Intentionally blank	Intentionally blank	Intentionally blank								
	Operations of special airport approval	C	APP LDG	See equivalency of approaches relevant to operations.	The operator should comply with the national qualification requirements published in the AIP.	Intentionally blank	Intentionally blank								
	Pilot incapacitation	C	TO	Consequences for the non-incapacitated pilot	Recognise incapacitation. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	During take-off	X	X			X	X			X
			APP			During approach	X			X				X	X

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
	Runway or taxiway condition	C	GND TO LDG	Contamination or surface quality of the runway, taxiway, or tarmac including foreign objects	Recognise hazardous runway condition. Observe limitations. Take appropriate action. Apply the appropriate procedures correctly. Assure aircraft control.	Planned anticipated hazardous conditions with dispatch information provided to facilitate planning and execution of appropriate procedures						X			X
			GND TO LDG			Unanticipated hazardous conditions, e.g. unexpected heavy rain resulting in flooded runway surface		X			X	X			
			TO			Take-off on runway with reduced cleared width due to snow	X			X	X		X		
			TO			Stop/go decision in hazardous conditions					X	X		X	
	Terrain	C	ALL	Alert, warning, or conflict	Anticipate terrain threats. Prepare for terrain threats. Recognise unsafe terrain clearance. Take appropriate action. Apply the appropriate procedures correctly. Maintain aircraft control. Restore safe flight path. Manage consequences.	ATC clearance giving insufficient terrain clearance	X	X			X				X
			ALL			Demonstration of terrain avoidance warning systems (TAWS) (this scenario element may be done in an ISI.)						X	X	X	
			TO CLB			Engine failure where performance is marginal leading to TAWS warning		X	X					X	
			DES APP			ATC provides a wrong QNH		X					X		
			DES			'Virtual mountain' refers to the surprise element of an unexpected warning. Care should be exercised in creating a level of realism, so this can best be achieved by an unusual and unexpected change of route during the descent.						X	X	X	
	Traffic	C	CLB CRZ DES	Traffic conflict. ACAS RA or TA, or visual observation of conflict, which requires evasive manoeuvring	Anticipate potential loss of separation. Recognise loss of separation. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	ACAS warning that requires crew intervention		X				X	X	X	

END GEN3 JET

AMC4 ORO.FC.232 EBT programme assessment and training topics

GENERATION 3 (TURBOPROP) — TABLE OF ASSESSMENT AND TRAINING TOPICS

	Assessment and training topic	*Frequency*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Flight phase activation*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
Section 1 — Skill retention. Manoeuvres training phase (MT)															
MT	Rejected take-off	A	Engine failure after the application of take-off thrust and before reaching V1 (may be in LVOs or CAT I or above)	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	From initiation of take-off to complete stop (or as applicable to the procedure)	X			X					
	Failure of the critical engine between V1 and V2	A	Failure of the critical engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO meteorological (MET) conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
	Failure of one engine on take-off	B	Failure of one engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO MET conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
			Failure of one engine above V2 (any segment of the TO) in the lowest CAT I visibility or in LVO MET conditions.			The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed.	X		X	X					
	Emergency descent	C	Initiation of emergency descent from normal cruise altitude		CRZ	The manoeuvre is complete once the aircraft is stabilised in emergency descent configuration (and profile).	X		X	X					
	Engine-out approach & landing	A	With the critical engine (if applicable) failed, normal landing		LDG	Initiation in a stabilised engine-out configuration from not less than 3 NM final approach, until completion of roll-out	X			X					
	Engine-out approach & go-around	A	With the critical engine (if applicable) failed, manually flown normal precision approach to DA, followed by a manual go-around — the whole manoeuvre to be flown without visual reference		APP	This manoeuvre should be flown from intercept to centreline until acceleration after go-around. The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement (describe generally the critical part of the manoeuvre).	X			X					
	Go-around	A	Go-around, all engines operative		APP	High energy, initiation during the approach at 150 to 300 m (500 to 1 000 ft) below the missed approach level-off altitude	X		X	X					
						Initiation of a go-around from DA followed by visual circuit and landing	X		X	X					
						During flare/rejected landing	X		X	X					
	Pilot qualification to operate in either pilot's seat	B	As per ORO.FC.235		APP	Complete the manoeuvres mandated in ORO.FC.235.	Intentionally left blank								

Assessment and training topic		Frequency	Description (includes type of topic, being threat, error or focus)	Desired outcome (includes performance criteria OR training outcome)	Flight phase activation	Guidance material (GM) Example scenario elements	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Generation 3 Turboprop — Recurrent assessment and training matrix							Competency map								
Section 2 — Equivalency of approaches relevant to operations. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)															
MT	Approach type A or B	B	Approach type A or B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT	Approach type A	B	Approach type A flight method 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or SBT	Approach type A	B	Approach type A flight method 3D or 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or SBT	Approach type B	B	Approach type B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
Section 3 — Equivalency of approaches under specific approvals and Take-off under specific approvals. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT															
MT	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL or SBT	SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL, MT or SBT	SPA rejected take-off (RTO)	B	Engine failure after the application of take-off thrust and before reaching V1 (in low-visibility MET conditions, preferably in the lowest approved visibility) Low-visibility RTO is not required under Part SPA but instead in Appendix 9 Section 6. Note: AMC1 SPA.LVO.120 point (f) does not require a low-visibility RTO. RTO is required only in the initial LVO course (point (g)(1)(iii) of AMC1 SPA.LVO.120).	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	RTO — can be combined with the assessment and training topic 'surprise' in EVAL or SBT	X			X					
EVAL, MT or SBT	LVTO	B	Notwithstanding AMC1 SPA.LVO120 point (f)(1) AMC1 SPA.LVO.120 requires SPA manoeuvres in the frequency of the OPC, as OPC is substituted in the EBT programme. Thus, the frequency in EBT is determined in every cycle (B). Low-visibility take-off, preferably in the lowest approved visibility		*TO*	The manoeuvre is complete at a point when the aircraft is stabilised at normal climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement.	X			X					

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
Section 4 — Training topics with frequency (A) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Adverse weather	A	GND	Thunderstorm, heavy rain, turbulence, ice build-up to include de-icing issues, as well as high-temperature conditions. The proper use of anti-ice and de-icing systems should be included generally in appropriate scenarios.	Anticipate adverse weather. Prepare for suspected adverse weather. Recognise adverse weather. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control.	Predictive wind shear warning before take-off, as applicable	X	X				X			
			ALL			Adverse-weather scenario, e.g. thunderstorm activity, precipitation, icing		X			X	X		X	
			TO			Wind shear encounter during take-off, not predictive	X			X			X		X
			TO			Predictive wind shear warning during take-off	X	X				X	X		
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			CRZ			Turbulence that increases to severe turbulence		X			X		X	X	
			CRZ			Wind shear encounter scenario during cruise	X		X			X	X		
			APP			Reactive wind shear warning during approach or go-around	X		X	X			X		
			APP			Predictive wind shear warning during approach or go-around	X	X				X	X		
			APP			Thunderstorm encounter during approach or on missed approach	X					X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Non-precision approach in cold-temperature conditions, requiring altitude compensation for temperature, as applicable to the type	X	X					X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP			In approach, unexpected braking action 'good to medium' reported by the preceding aircraft		X				X	X	X	
			APP			Moderate to severe icing conditions during approach effecting aircraft performance	X	X				X	X		
			APP			Reduced visibility even after acquiring the necessary visual reference during approach, due to rain or fog	X	X				X			
EVAL or SBT	Automation management	A	CLB CRZ DES APP	The purpose of this topic is to encourage and develop effective flight path management through proficient and appropriate use of the flight management system(s), guidance and automation, including transitions between modes, monitoring, mode awareness, vigilance and flexibility needed to change from one mode to another. The means of mitigating errors are included in this topic. The errors are described as mishandled auto flight systems, inappropriate mode	Know how and when to use the flight management system(s), guidance and automation. Demonstrate correct methods for engagement and disengagement of the auto flight system(s). Demonstrate appropriate use of flight guidance, auto thrust and other automation systems. Maintain mode awareness of the auto flight system(s), including engagement and automatic transitions.	ACAS warning, recovery and subsequent engagement of automation	X		X						
			ALL			FMS tactical programming issues, e.g. step climb, runway changes, late clearances, destination re-programming, executing diversion	X		X						X
			CLB CRZ DES APP			Recoveries from TAWS, management of energy state to restore automated flight	X		X	X					
			CLB CRZ DES APP			Amendments to ATC cleared levels during altitude capture modes to force mode awareness and intervention	X		X				X		

Assessment and training topic		*Frequency*	*Flight phase*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
			TO	selection, mishandled flight management system(s) and inappropriate autopilot usage.	Revert to different modes when appropriate. Detect deviations from the desired aircraft state (flight path, speed, attitude, thrust, etc.) and take appropriate action. Anticipate mishandled auto flight system. Recognise mishandled auto flight system. Take appropriate action if necessary. Restore correct auto flight state. Identify and manage consequences.	Late ATC clearance to an altitude below acceleration altitude	X		X				X		
			TO APP			Engine-out special terrain procedures	X		X				X		
			CRZ			Forcing autopilot disconnect followed by re-engagement, recovery from low- or high-speed events in cruise	X		X	X			X		
			CLB			Engine failure during or after initial climb using automation	X		X						
			CRZ			Engine failure in cruise to onset of descent using automation	X		X						
			CRZ			Emergency descent	X		X						X
			DES APP			Managing high-energy descent capturing descent path from above (correlation with unstable approach training)	X		X				X		X
			APP			No ATC clearance received prior to commencement of approach or final descent	X		X				X		
			APP			Reactive wind shear and recovery from the consequent high-energy state	X		X				X		
			APP			Automation fail to capture the approach altitude in descent (e.g. last altitude before the FAP). Ideally, the failure occurs when the workload is high (e.g. configuration of the aircraft for final approach).					X	X	X	X	
			APP			Non-precision or infrequently flown approaches using the maximum available level of automation	X		X						X
			APP			Gear malfunction during an approach planned with autoland (including autobrake). Competency FPA may or may not be included depending on the impact of such malfunction on the automation.		X				X		X	
			APP			ATC clearances to waypoints beyond the programmed descent point for a coded final descent point during an approach utilising a final descent that is commanded by the flight management system	X		X				X		X
EVAL or SBT	Competencies — non-technical (CRM)	A	APP	This encapsulates the general CRM principles and objectives. It includes communication; leadership and teamwork; problem-solving and decision-making; situation awareness and management of information; and workload management. Emphasis should be placed on the development of leadership, shown by EBT data sources to be a highly effective competency in mitigating risk and improving safety through pilot performance.	Exposure to an event or sequence of events to allow the pilot to build awareness of human factors in aviation and the human limitations. This includes the development of the following competencies: <u>Communication:</u> Demonstrate: — effective use of language; — responsiveness to feedback; and — capability to state the plans and resolve ambiguities. <u>Leadership and teamwork:</u> Use appropriate authority to ensure focus on the task. Support others in completing tasks.	GPS failure prior to commencement of approach associated with position drift and a terrain alert					X	X	X		X
			DES			Cabin crew report of water noise below the forward galley indicating a possible toilet pipe leak, with consequent avionics failures					X	X	X		
			CRZ			Smoke removal but combined with a diversion until landing is completed.		X			X	X	X	X	X
			GND			Apron fuel spilling					X	X		X	
			CRZ			Important water leak in an aircraft galley		X			X	X		X	
			ALL			A relevant number of cabin crew are wounded or incapacitated. Additionally, the cabin crew wounded or incapacitated are the most competent (e.g. senior cabin crew member).					X	X		X	
			ALL			Unruly passenger(s)					X			X	
			GND			Passenger oxygen: passenger service unit open and mask falling down					X	X		X	
			ALL			Passenger with medical problems — medical emergency					X			X	
			CRZ			Credible threat reported to the crew. Stowaway or fugitive on board.		X			X		X	X	
			GND			No METAR or TAFOR is available for destination due to industrial action at the destination airport	X	X			X	X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
			CRZ		<u>Problem-solving and decision-making:</u> Detect deviations from the desired state, evaluate problems, identify the risk, consider alternatives and select the best course of action. Continuously review progress and adjust plans. <u>Situation awareness and management of information:</u> Have an awareness of the aircraft state in its environment; project and anticipate changes. <u>Workload management:</u> Prioritise, delegate and receive assistance to maximise focus on the task. Continuously monitor the flight progress.	Credible bomb threat reported to crew		X			X		X	X	
			CLB DES			Credible bomb threat or pressurisation problem, but no quick landing possible (due to weather, terrain or other reasons)		X			X	X		X	
			APP			Diversion with low remaining fuel or increased fuel flow due to system malfunction	X				X		X	X	
			APP			ACAS warning immediately following a go-around, with a descent manoeuvre required		X			X	X	X	X	
EVAL or SBT	Compliance	A	ALL	Compliance failure. Consequences of not complying with operating instructions (e.g. SOPs). This is not intended to list example scenario elements, but instructors should ensure that observed non-compliances are taken as learning opportunities throughout the programme. In all modules of the programme, the FSTD should as far as possible be treated like an aircraft, and non-compliances should not be accepted simply for expediency.	Recognise that a compliance failure has occurred. Make a verbal announcement. Take appropriate action if necessary. Restore safe flight path if necessary. Manage consequences.	The following are examples of potential compliance failures and are not intended to be developed as scenarios as part of an EBT module: 1. Requesting flap beyond limit speed 2. Flaps or slats in the wrong position for phase of flight or approach 3. Omitting an action as part of a procedure 4. Failing to initiate or complete a checklist 5. Using the wrong checklist for the situation	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
EVAL or SBT	Go-around management	A	APP	Any threat or error that can result in circumstances that require a decision to perform a go-around, in addition to the execution of the go-around. Go-around scenarios should be fully developed to encourage effective leadership and teamwork, in addition to problem-solving and decision-making, plus execution using manual aircraft control or the flight management system(s) and automation as applicable. Design should include the element of surprise, and scenario-based go-arounds should not be predictable and anticipated. This topic is completely distinct from the go-around manoeuvre listed in the MT section that is intended only to practise psychomotor skills and a simple application of the procedures.		Adverse-weather scenario leading to a reactive wind shear warning during approach	X	X					X	X	
			APP			Adverse-weather scenario leading to a predictive wind shear warning during approach or go-around	X	X					X	X	
			APP			Adverse-weather scenario, e.g. thunderstorm activity, heavy precipitation or icing forcing decision at or close to DA/MDA	X					X	X	X	
			APP			DA with visual reference in heavy precipitation with doubt about the runway surface braking capability	X					X	X	X	
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP			Lost or difficult communications resulting in no approach clearance prior to commencement of approach or final descent	X		X				X		
			APP			Birds: large flocks of birds below DA once visual reference has been established				X		X	X		
			APP			System malfunction, landing gear malfunction during the approach									

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
	Manual aircraft control	A	CLB CRZ DES APP	Controls the flight path through manual control	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the normal flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	Flight with unreliable airspeed, which may or may not be recoverable	X			X			X		X
			CLB CRZ DES APP			Alternate flight control modes according to malfunction characteristics	X			X				X	X
			CLB CRZ DES APP			ACAS RA requires the pilot to descend or ATC calls for immediate descent	X	X		X					
			DES			TAWS warning when deviating from planned descent routing, requiring immediate response	X			X	X				
			TO			Scenario immediately after take-off which requires an immediate and overweight landing			X	X	X	X			
			TO			Adverse wind, crosswinds with or without strong gusts on take-off	X			X					
			TO			Adverse weather, wind shear, wind shear encounter during take-off, with or without reactive warnings	X			X			X		
			TO			Engine failure during initial climb, typically 30-60 m (100-200 ft) (autopilot off)	X	X		X				X	
			CRZ			Wind shear encounter scenario during cruise, significant and rapid change in wind speed or down/updrafts, without wind shear warning	X		X			X	X	X	
			APP			Adverse weather, wind shear, wind shear encounter with or without warning during approach	X		X	X			X		
			APP			Adverse weather, deterioration in visibility or cloud base, or adverse wind, requiring a go-around from visual circling approach, during the visual segment	X	X	X	X		X	X	X	
			APP			Interception of the glide slope from above (correlation with unstable approach training)			X				X	X	
			APP LDG			Adverse wind, crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP LDG			Adverse weather, adverse wind, approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP LDG			Circling approach manually flown at night in minimum in-flight visibility to ensure ground reference, minimum environmental lighting and no glide slope guidance lights	X			X			X	X	
			APP LDG			Runway incursion during approach, which can be triggered by ATC at various altitudes or by visual contact during the landing phase	X			X			X		
			LDG			Adverse wind, visibility, type-specific, special consideration for long-bodied aircraft, landing in minimum visibility for visual reference, with crosswind	X	X		X			X		
			LDG			System malfunction, auto flight failure at DA during a low-visibility approach requiring a go-around flown manually	X		X	X			X		
			APP LDG			Approach planned with autoland, followed by a failure below 1 000 ft requiring a manual go-around and an immediate landing due to fuel shortage	X		X		X		X		
			TO			In-seat instruction: Insufficient engine failure recovery, forcing the pilot monitoring to take over the flight controls		X		X			X	X	
			APP LDG			In-seat instruction: Unstable approach on short final or long landing, forcing the pilot monitoring to take over the flight controls		X		X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 3 Turboprop — Recurrent assessment and training matrix							*Competency map*								
EVAL or SBT	Monitoring, cross-checking, error management, mismanaged aircraft state	A	ALL	The scenarios should be realistic and relevant, and should be used for the purpose of demonstration and reinforcement of effective monitoring. Modules in the FSTD should be treated like those in an aircraft so that trainees have the opportunity to develop the competency with the practice of the right techniques and attitudes related to these topics through pilot performance, and that instructors have the opportunity to assess and train these topics in a realistic environment. As shown by the EBT data report, these topics are of key importance to improve safety in operations. In addition, the operator may also use these topics to develop scripted role-playing scenarios in the form of ISI. These scenarios cater for the need to monitor flight path excursions from the instructor pilot (PF), detect errors and make appropriate interventions, either verbally or by taking control as applicable. Demonstration scenarios may also be used. Demonstrated role-play should contain realistic and not gross errors, leading at times to a mismanaged aircraft state, which can also be combined with upset management training.	Recognise mismanaged aircraft state. Observe the pilot's behaviour: how the pilot is mitigating errors, performing cross-checking, monitoring performance and dealing with a mismanaged aircraft state, in order to ensure that observed deviations, errors and mistakes are taken as learning opportunities throughout the programme. Monitor flight path excursions. Detect errors and threats through proper cross-checking performance. Make appropriate interventions either verbally or by taking control if applicable. Take appropriate action if necessary. Restore the desired aircraft state. Identify and manage consequences.	Deviations from the flight path, in pitch attitude, speed, altitude, bank angle		X					X		
			ALL			In-seat instruction: Simple automation errors (e.g. incorrect mode selection, attempted engagement without the necessary conditions, entering wrong altitude or speed, failure to execute the desired mode) culminating in a need for direct intervention from the pilot monitoring, and where necessary taking control.		X					X		
			APP			In-seat instruction: Unstable approach or speed/path/vertical rate not congruent with the required state for the given flight condition	X	X					X	X	
			LDG			In-seat instruction: Demonstration exercise — recovery from bounced landing, adverse wind, strong gusts during landing phase, resulting in a bounce and necessitating recovery action from the pilot monitoring	X			X			X		
	Unstable approach	A	DES APP	Reinforce stabilised approach philosophy and adherence to defined parameters. Encourage go-arounds when crews are outside these parameters. Develop and sustain competencies related to the management of high-energy situations.		ATC or terrain-related environment creating a high-energy descent with the need to capture the optimum profile to complete the approach in a stabilised configuration	X		X				X		
			DES APP			ATC or terrain-related environment creating a high-energy descent leading to unstable conditions and requiring a go-around	X		X				X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions					X	X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 5 — UPRT training topic with frequency (B). Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)							*Competency map*								
EVAL, MT or SBT	Upset prevention training	B	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include upset prevention elements in Table 1 for the recurrent training programme in at least every cycle, such that all the elements are covered over a period not exceeding 3 years. The elements are numbered with letters from A to I in Table 1 of AMC1 ORO.FC.220&230. Each element is made up of several numbered components. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recognising and preventing the development of upset conditions.	Early recognition and prevention of upset conditions. When the differences between LHS and RHS are not significant in the handling of the aircraft, UPRT may be conducted in either seat.	See Table 1 of AMC1 ORO.FC.220&230: Elements and respective components of upset prevention training.	Intentionally blank								
			CRZ			Demonstration of the defined normal flight envelope and any associated changes in flight instruments, flight director systems, and protection systems. This should take the form of an instructor-led exercise to show the crew the points beyond which an upset condition could exist.			X					X	X
			TO APP			Severe wind shear or wake turbulence during take-off or approach			X	X		X	X		
			CRZ			As applicable and relevant to the aircraft type, demonstration at a suitable intermediate level, with turbulence as appropriate; practise steep turns and note the relationship between bank angle, pitch and stalling speed				X			X		X
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence to trigger overspeed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)	X		X	X			X		
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence and significant temperature rise to trigger low-speed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)			X	X			X		X
			CRZ			High-altitude loss of reliable airspeed	X	X		X			X	X	
			CRZ			High-altitude TCAS RA (where the RA is required to be flown in manual flight)	X			X			X	X	

Assessment and training topic		Frequency	Flight phase activation	Description (includes type of topic, being threat, error or focus)	Desired outcome (includes performance criteria OR training outcome)	Guidance material (GM) Example scenario elements	PRO	COM	FPA	FPM	LTW	PSD	SAW	WLM	KNO
Section 6 — Training topics with frequency (B) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Aircraft system malfunctions, including operations under MEL	B	ALL	Any internal failure(s) apparent or not apparent to the crew Any item cleared by the MEL but having an impact upon flight operations — for instance, thrust reverser locked. Malfunctions to be considered should have one or more of the following characteristics: — Immediacy — Complexity — Degradation of aircraft control — Loss of primary instrumentation — Management of consequences	Recognise system malfunction. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences. Apply crew operating procedures where necessary. Respond appropriately to additional system abnormalities associated with MEL dispatch	(i) System malfunctions that require immediate and urgent crew intervention or decision, e.g. fire, smoke, loss of pressurisation at high altitude, failures during take-off, brake failure during landing. (ii) System malfunctions that require complex procedures, e.g. multiple hydraulic system failures, smoke and fumes procedures, major electrical system failure. (iii) System malfunctions that result in significant degradation of flight controls in combination with abnormal handling characteristics, e.g. jammed flight controls, certain degradation of FBW control, jammed horizontal stabiliser; flaps and/or slats locked; other malfunctions that result in degraded flight controls. (iv) System failures that require monitoring and management of the flight path using degraded or alternative displays, unreliable primary flight path information, unreliable airspeed, e.g. flight with unreliable airspeed (v) System failures that require extensive management of their consequences (independent of operation or environment), e.g. fuel leak.	Intentionally blank								
			TO			MEL items with crew operating procedures applicable during take-off						X			X
			TO			Response to an additional factor that is affected by an MEL item (e.g. system failure, runway state)		X		X		X			X
			GND			Malfunction during preflight preparation and prior to departure	X					X	X		
			CLB			Malfunction after departure	X					X	X		X
			ALL			Malfunctions that require immediate attention (e.g. bleed fault during engine start, hydraulic failure during taxi)	X				X			X	
			CLB CRZ			Fuel leak (management of consequences)	X				X		X		X
			TO			Malfunction on take-off high speed below V1	X				X	X			
			TO			Malfunction on take-off high speed above V1	X					X			
			GND			During taxi to the runway, a spurious brake temperature announcement. The crew had the correct brake temperature moments before the failure.					X	X	X		
			TO			Tyre failure during take-off					X	X		X	
			TO			Malfunction on initial climb	X					X			
			APP			Malfunction on approach	X					X		X	
			APP			Malfunction on go-around	X					X		X	
			LDG			Malfunction during landing	X	X		X		X	X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
	Aircraft system management	B	CRZ APP LDG	Normal system operation according to defined instructions	This is not considered as a stand-alone topic. It is linked with the topic 'compliance'. Where a system is not managed according to normal or defined procedures, this is determined as a non-compliance	See 'compliance' topic above. There are no defined scenarios, but the instructor should focus on learning opportunities when system management non-compliances manifest themselves during other scenarios. Underpinning knowledge of systems and their interactions should be developed and challenged, and not merely the application of normal procedures.	Intentionally blank								X
						Minimum fuel, caused by extended delays, weather, etc. where the crew would need to manage a minimum fuel situation					X	X	X	X	
EVAL or SBT	Approach, visibility close to minimum	B	APP	Any situation where visibility becomes a threat	Recognise actual conditions. Observe aircraft and/or procedural limitations. Apply the appropriate procedures if applicable. Maintain directional control and safe flight path.	Approach in poor visibility	X		X	X				X	
			APP			Approach in poor visibility with deteriorations necessitating a decision to perform a go-around	X		X	X					
			LDG			Landing in poor visibility				X		X	X		
	Landing	B	LDG	Pilots should have opportunities to practise landings in demanding situations at the defined frequency. Data indicates that landing problems have their roots in a variety of factors, including inappropriate decision-making, in addition to manual aircraft control skills if difficult environmental conditions exist. The purpose of this item is to ensure that pilots are exposed to this during the programme.	Landing in demanding environmental conditions, with malfunctions as appropriate	This topic should be combined with the adverse-weather topic, aircraft system malfunctions topic or any topic that can provide exposure to a landing in demanding conditions.									
EVAL or SBT	Surprise	B	ALL	The data analysed during the development of the EBT concept indicated substantial difficulties encountered by crews when faced with a threat or error, which was a surprise or an unexpected event. The element of surprise should be distinguished from what is sometimes referred to as the 'startle factor' — the latter being a physiological reaction. Wherever possible, consideration should be given towards variations in the types of scenario, times of occurrences and types of occurrence, so that pilots do not become overly familiar with repetitions of the same scenarios. Variations should be the focus of EBT programme design, and not left to the discretion of individual instructors, in order to preserve programme integrity and fairness.	Exposure to an unexpected event or sequence of events at the defined frequency in order to build resilience.	Rejected take-off	X			X		X			
						Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Terrain	B	ALL	Alert, warning, or conflict	Anticipate terrain threats. Prepare for terrain threats. Recognise unsafe terrain clearance. Take appropriate action. Apply the appropriate procedures correctly. Maintain aircraft control. Restore safe flight path. Manage consequences.	ATC clearance giving insufficient terrain clearance	X	X			X				
			ALL			Demonstration of terrain avoidance warning systems (TAWS) (this scenario element may be done in an ISI.)						X	X	X	
			TO CLB			Engine failure where performance is marginal leading to TAWS warning		X		X				X	
			DES APP			ATC provides a wrong QNH		X					X		
			DES			'Virtual mountain' refers to the surprise element of an unexpected warning. Care should be exercised in creating a level of realism, so this can best be achieved by an unusual and unexpected change of route during the descent.						X	X	X	
EVAL or SBT	Wind shear recovery	B	TO	With or without warnings including predictive. A wind shear scenario is ideally combined with an adverse-weather scenario containing other elements.	Anticipate potential for wind shear. Avoid known wind shear or prepare for suspected wind shear. Recognise wind shear encounter. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control. Recognise out of wind shear condition. Maintain or restore a safe flight path. Assess consequential issues and manage outcomes.	Predictive wind shear warning during take-off					X	X			
			TO			Wind shear encounter during take-off	X				X	X			
			TO			Wind shear encounter after rotation						X		X	
			TO			Predictive wind shear after rotation					X	X			
			APP			Predictive wind shear during approach	X				X	X			
			APP			Wind shear encounter during go-around	X				X	X		X	
			APP			Wind shear encounter during approach	X				X	X			
	Workload, distraction, pressure, stress	B	ALL	This is not considered a topic for specific attention on its own, but more as a reminder to programme developers to ensure that pilots are exposed to immersive training scenarios which expose them to manageable high workload and distractions during the course of the EBT programme, at the defined frequency.	Manage available resources efficiently to prioritise and perform tasks in a timely manner under all circumstances.	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 7 — UPRT Upset recovery training topic with frequency (C). Manoeuvres training phase or scenario-based training phase (MT or SBT)															
MT or SBT	Upset recovery	C	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include the recovery exercises in Table 2 of AMC1 ORO.FC.220&230 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recovery from developed upsets. The same principles apply to the exercises of components 2, 3 and 4 where one exercise may satisfy the requirement to cover the whole component. An aeroplane upset is defined as an undesired aeroplane state in flight characterised by unintentional divergences from parameters normally experienced during line operations or training. An aeroplane upset may involve pitch and/or bank angle divergences as well as inappropriate airspeeds for the conditions.	Recognise upset condition. Make timely and appropriate intervention. Take appropriate action. Assure timely and appropriate intervention. (AMC1 ORO.FC.220&230 Table 2 component 1) Assure aircraft control. Maintain or restore a safe flight path. Assess consequential issues. Manage outcomes. Consolidate the summary of aeroplane recovery techniques. (AMC1 ORO.FC.220&230 Table 2 component 5) Note: The operator should assess if the exercises should be practised for the either seat qualification.	The example scenario elements may be done in ISI, as non-ISI or a combination of both. If done in ISI: The instructor should position the aircraft within but close to the edge of the validated training envelope before handing control to the trainee to demonstrate the restoration of normal flight. Careful consideration should be given to flying within the validated training envelope.	Intentionally blank								
			CLB DES			Table 2 of AMC1 ORO.FC.220&230: Exercises for upset recovery training									
			CRZ			A. **Recovery from developed upsets**									
			CRZ			2. Recovery from stall events in the following configurations: — take-off configuration, — clean configuration low altitude, — clean configuration near maximum operating altitude, and — landing configuration during the approach phase.	X			X			X	X	
			CRZ			3. Recovery from nose high at various bank angles	X			X			X	X	
			APP			4. Recovery from nose low at various bank angles	X			X			X	X	
			CLB DES			Demonstration at a normal cruising altitude. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.	X			X			X		
						Demonstration at an intermediate altitude during early stages of the approach. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.	X			X			X		
						Recovery from a wake turbulence position with high-bank angle	X		X	X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 8 — Training topics with frequency (C) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Adverse wind	C	TO	Adverse wind/crosswind. This includes tailwind but not ATC mis-reporting of the actual wind.	Recognise adverse-wind conditions. Observe limitations. Apply the appropriate procedures. Maintain directional control and safe flight path.	Take-off with different crosswind/tailwind/gust conditions						X		X	
			TO			Take-off with unreported tailwind		X			X				
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			APP			Wind exceeding limits on final approach (not reported)	X	X				X	X		
			APP			Wind exceeding limits on final approach (reported) in manual aircraft control	X	X		X		X			
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswind including shifting wind directions				X		X	X		
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP LDG			Crosswind with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	ATC	C	ALL	ATC error. Omission, miscommunication, garbled, poor quality transmission. All these act as distractions to be managed by the crew. The scenarios should be combined, where possible, with others of the same or higher weighting, the principal reason being to create distractions.	Respond to communications appropriately. Recognise, clarify and resolve any ambiguities. Refuse or question unsafe instructions. Use standard phraseology whenever possible.	ATC role-play: the instructor provides scripted instructions, as a distraction to the crew	X	X			X				
			ALL			Controller error, provided by the instructor according to a defined scripted scenario	X	X				X	X		
			ALL			Frequency congestion, with multiple aircraft using the same frequency		X							
			APP			Destination temporarily closed					X	X	X	X	
			CRZ			Rescue and firefighting services (RFFS) level reduction at destination		X			X		X		
			APP			Runway change before the interception of the localiser or similar navigation aid in azimuth			X		X		X	X	
			GND TO			Stray dogs at the opposite threshold runway		X			X		X		
			ALL			Poor quality transmissions		X							
EVAL or SBT	Engine failure	C	TO	Any engine failure or malfunction, which causes loss or degradation of thrust that affects performance. This is distinct from the engine-out manoeuvres described in the MT section above, which are intended only to practise psychomotor skills and reinforce procedures to manage engine failures.	Recognise engine failure. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Engine failure or engine malfunction on take-off low speed	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off high speed below V1	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off above V1	X					X	X	X	
			TO			Engine failure or engine malfunction on initial climb	X					X	X		
			APP			Engine malfunction	X					X		X	
			CRZ			Engine failure in cruise (with autopilot)	X		X				X		
			LDG			Engine failure or engine malfunction on landing				X					
EVAL or SBT	Fire and smoke management	C	GND	This includes engine, electric, pneumatic, cargo fire, smoke or fumes.	Recognise fire, smoke or fumes. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Fire in cargo or cabin/cockpit at gate	X	X				X		X	
			GND			Fire during taxi	X	X				X		X	X
			GND			Fire with no cockpit indication	X	X				X		X	X
			TO			Take-off low speed	X			X	X	X			X
			TO			Fire or smoke on take-off high speed below V1	X			X	X	X			
			TO			Fire or smoke on take-off high speed above V1	X				X	X			
			TO			Fire or smoke on initial climb	X				X	X			
			CRZ			Cargo fire						X	X	X	
			APP			Engine fire in approach (extinguishable)		X				X			
			APP			Engine fire in approach (non-extinguishable)		X			X	X			
			CLB CRZ DES			Lithium battery fire in the cockpit or cabin compartment	X	X			X	X		X	
			APP			Flight deck or cabin fire		X			X	X			X
			GND			Any of the example scenario elements above ending in an evacuation		X			X	X		X	
EVAL or SBT	Loss of communications	C	GND	Lost or difficult communications due to either pilot mis-selection or a failure external to the aircraft. This could be for a few seconds or a total loss.	Recognise loss of communications. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative ways to communicate. Manage consequences.	Loss of communications during ground manoeuvring	X	X							
			TO			Loss of communications after take-off	X					X			X
			APP			Loss of communications during approach phase, including go-around	X	X				X	X		X

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Managing loading, fuel, performance errors	C	ALL	A calculation error by one or more pilots, or someone involved with the process, or the process itself, e.g. incorrect information on the load sheet	Anticipate the potential for errors in load/fuel/performance data. Recognise inconsistencies. Manage/avoid distractions. Make changes to paperwork/aircraft system(s) to eliminate error. Identify and manage consequences.	This can be a demonstrated error, in that the crew may be instructed to deliberately insert incorrect data — for example, to take off from an intersection with full-length performance information. The crew will be asked to intervene when acceleration is sensed to be lower than normal, and this may be part of the operator procedures, especially when operating mixed fleets with considerable variations in MTOM.	X	X						X	
			GND			Fuel ground staff on industrial action. Only limited amount of fuel available, which is below the calculated fuel for the flight.					X	X	X	X	
			GND			Advise crew that there is a change of the load sheet figures during taxi to the runway. The crew may have limited time due to a calculated take-off time (CTOT) — ATC slot.	X							X	
			GND			Braking action reported 'medium'. The information is transmitted just before take-off. The flight is subject to a (CTOT) — ATC slot.					X		X	X	
EVAL or SBT	Navigation	C	GND	External NAV failure. Loss of GPS satellite, ANP exceeding RNP, loss of external NAV source(s)	Recognise a NAV degradation. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative NAV guidance. Manage consequences.	External failure or a combination of external failures degrading aircraft navigation performance on ground	X		X			X	X		
			TO CLB APP LDG			External failure or a combination of external failures degrading aircraft navigation performance in flight		X			X	X	X		
			GND			Standard initial departure change during taxi. The flight may be subject to a CTOT — ATC slot.					X		X	X	
			APP			Loss of runway lighting below decision height		X				X	X		
			CRZ			No fly zone: when the crew changes control frequency, the new ATCO informs the crew that they are flying over an unannounced 'no fly zone' that is not included in the NOTAMs. (To trigger such an event, the context may be as follows: an unexpected military conflict in the territory the aircraft is flying over or the crew is forced to re-route in flight and the new route flies over a city that has an important event such the Olympic games, a G20/G7 submit, or the route is flying near a space rocket launch close to the time of the launch, like the Guiana Space Centre, Cape Cañaveral, etc.).					X	X	X		
	Operations- or type-specific	C	ALL	Intentionally blank	Intentionally blank	Intentionally blank	Intentionally blank								
	Operations of special airport approval	C	APP LDG	See equivalency of approaches relevant to operations.	The operator should comply with the national qualification requirements published in the Aeronautical Information Publication.	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Pilot incapacitation	C	TO	Consequences for the non-incapacitated pilot	Recognise incapacitation. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	During take-off	X	X			X	X			X
			APP			During approach	X			X				X	X
	Runway or taxiway condition	C	GND TO LDG	Contamination or surface quality of the runway, taxiway, or tarmac including foreign objects	Recognise hazardous runway condition. Observe limitations. Take appropriate action. Apply the appropriate procedures correctly. Assure aircraft control.	Planned anticipated hazardous conditions with dispatch information provided to facilitate planning and execution of appropriate procedures						X			X
			GND TO LDG			Unanticipated hazardous conditions, e.g. unexpected heavy rain resulting in flooded runway surface		X			X	X			
			TO			Take-off on runway with reduced cleared width due to snow	X			X	X		X		
			TO			Stop/go decision in hazardous conditions					X	X		X	
EVAL or SBT	Traffic	C	CLB CRZ DES	Traffic conflict. ACAS RA or TA, or visual observation of conflict, which requires evasive manoeuvring	Anticipate potential loss of separation. Recognise loss of separation. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	ACAS warning that requires crew intervention		X				X	X	X	

END GEN3 TURBOPROP

AMC5 ORO.FC.232 EBT programme assessment and training topics

GENERATION 2 (JET) — EBT PROGRAMME — TABLE OF ASSESSMENT AND TRAINING TOPICS

Given the very small number of turbo-jet aeroplanes of the second generation in current use in commercial air transport operations, the operator should apply for an alternative means of compliance to develop a table of assessment and training topics to apply EBT.

AMC6 ORO.FC.232 EBT programme assessment and training topics

GENERATION 2 (TURBOPROP) — TABLE OF ASSESSMENT AND TRAINING TOPICS

	Assessment and training topic	*Frequency*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Flight phase activation*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 2 Turboprop — Recurrent assessment and training matrix							*Competency map*								
Section 1 — Skill retention. Manoeuvres training phase (MT)															
MT	Rejected take-off	A	Engine failure after the application of take-off thrust and before reaching V1 (may be in LVO or CAT I or above)	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	From initiation of take-off to complete stop (or as applicable to the procedure)	X			X					
	Failure of the critical engine between V1 and V2	A	Failure of the critical engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO meteorological (MET) conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
	Failure of one engine on take-off	B	Failure of one engine from V1 and before reaching V2 in the lowest CAT I visibility or in LVO MET conditions.		TO	The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed. Only one failure of the critical engine between V1 and V2 a year may be done in LVO conditions.	X			X					
			Failure of one engine above V2 (any segment of the TO) in the lowest CAT I visibility or in LVO MET conditions.			The manoeuvre is complete at a point when the aircraft is stabilised in a clean configuration with engine-out procedures completed	X		X	X					
	Emergency descent	C	Initiation of emergency descent from normal cruise altitude		CRZ	The manoeuvre is complete once the aircraft is stabilised in emergency descent configuration (and profile).	X		X	X					
	Engine-out approach & landing	A	With the critical engine (if applicable) failed, normal landing		LDG	Initiation in a stabilised engine-out configuration from not less than 3 NM final approach, until completion of roll-out	X			X					
	Engine-out approach & go-around	A	With the critical engine (if applicable) failed, manually flown normal precision approach to DA, followed by a manual go-around — the whole manoeuvre to be flown without visual reference		APP	This manoeuvre should be flown from intercept to centreline until acceleration after go-around. The manoeuvre is complete at a point when the aircraft is stabilised at normal engine-out climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement (describe generally the critical part of the manoeuvre).	X			X					
	Go-around	A	Go-around, all engines operative		APP	High energy, initiation during the approach at 150 to 300 m (500 to 1 000 ft) below the missed approach level-off altitude	X		X	X					
						Initiation of a go-around from DA followed by visual circuit and landing	X		X	X					
						During flare/rejected landing	X		X	X					
	Pilot qualification to operate in either pilot's seat	B	As per ORO.FC.235		APP	Complete the manoeuvres mandated in ORO.FC.235.	Intentionally left in blank.								

		Assessment and training topic	*Frequency*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Flight phase activation*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 2 Turboprop — Recurrent assessment and training matrix								*Competency map*								
Section 2 — Equivalency of approaches relevant to operations. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)																
MT		Approach type A or B	B	Approach type A or B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
MT		Approach type A	B	Approach type A flight method 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or		Approach type A	B	Approach type A flight method 3D or 2D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
EVAL or		Approach type B	B	Approach type B flight method 3D	See equivalency of approaches relevant to operations that place an additional demand on a proficient crew	APP	See equivalency of approaches relevant to operations	X		X	X			X		X
Section 3 – Equivalency of approaches under specific approvals and take-off under specific approvals. Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)																
MT		SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL or SBT		SPA approach(es)	B	Approach requiring specific approval	See equivalency of approaches relevant to operations — specific approval	APP	Approaches flown from FAF to landing or go-around	X		X	X					
EVAL or SBT		SPA rejected Take-off (RTO)	B	Engine failure after the application of take-off thrust and before reaching V1 (in low-visibility MET conditions, preferably in the lowest approved visibility) Low-visibility RTO is not required under Part SPA but instead in Appendix 9 Section 6. Note: AMC1 SPA.LVO.120 point (f) does not require a low-visibility RTO. RTO is required only in the initial LVO course (point (g)(1)(iii) of AMC1 SPA.LVO.120).	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	TO	RTO — can be combined with the assessment and training topic 'surprise' in EVAL or SBT	X			X					
EVAL or SBT		LVTO	B	Notwithstanding AMC1 SPA.LVO120 point (f)(1) AMC1 SPA.LVO.120 requires SPA manoeuvres in the frequency of the OPC, as OPC is substituted in the EBT programme. Thus, the frequency in EBT is determined in every cycle (B). Low-visibility take-off, preferably in the lowest approved visibility		TO	The manoeuvre may is complete at a point when the aircraft is stabilised at normal climb speed with the correct pitch and lateral control, in trim condition and, as applicable, autopilot engagement.	X			X					

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 2 Turboprop — Recurrent assessment and training matrix							*Competency map*								
Section 4 — Training topics with frequency (A) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
EVAL or SBT	Adverse weather	A	GND	Thunderstorm, heavy rain, turbulence, ice build-up to include de-icing issues, as well as high-temperature conditions. The proper use of anti-ice and de-icing systems should be included generally in appropriate scenarios.	Anticipate adverse weather. Prepare for suspected adverse weather. Recognise adverse weather. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control.	Predictive wind shear warning before take-off, as applicable	X	X				X			
			ALL			Adverse-weather scenario, e.g. thunderstorm activity, precipitation, icing		X			X	X		X	
			TO			Wind shear encounter during take-off, not predictive	X			X			X		X
			TO			Predictive wind shear warning during take-off	X	X				X	X		
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			CRZ			Turbulence that increases to severe turbulence		X			X		X	X	
			CRZ			Wind shear encounter scenario during cruise	X		X			X	X	X	
			APP			Reactive wind shear warning during approach or go-around	X		X	X			X		
			APP			Predictive wind shear warning during approach or go-around	X	X				X	X		
			APP			Thunderstorm encounter during approach or on missed approach	X					X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Non-precision approach in cold-temperature conditions, requiring altitude compensation for temperature, as applicable to the type	X	X					X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP			In approach, unexpected braking action 'good to medium' reported by the preceding aircraft		X				X	X	X	
			APP			Moderate to severe icing conditions during approach effecting aircraft performance	X	X				X	X		
			APP			Reduced visibility even after acquiring the necessary visual reference during approach, due to rain or fog	X	X				X			
EVAL or SBT	Aircraft system management	A	N/A	Normal system operation according to defined instructions	This is not considered as a stand-alone topic. It is linked with the topic 'compliance'. Where a system is not managed according to normal or defined procedures, this is determined as a non-compliance.	See 'compliance' topic above. There are no defined scenarios, but the instructor should focus on learning opportunities when system management non-compliances manifest themselves during other scenarios. Underpinning knowledge of systems and their interactions should be developed and challenged, and not merely the application of normal procedures.	Intentionally blank								X
			CRZ APP LDG			Minimum fuel, caused by extended delays, weather, etc. where the crew would need to manage a minimum fuel situation.					X	X	X	X	
EVAL or SBT	Automation management	A	CLB CRZ DES APP	The purpose of this topic is to encourage and develop effective flight path management through proficient and appropriate use of the flight management system(s), guidance and automation, including transitions between modes, monitoring, mode awareness,	Know how and when to use the flight management system(s), guidance and automation. Demonstrate correct methods for engagement and disengagement of the auto flight system(s).	ACAS warning, recovery and subsequent engagement of automation	X		X						
			ALL			FMS tactical programming issues, e.g. step climb, runway changes, late clearances, destination re-programming, executing diversion	X		X						X
			CLB CRZ			Recoveries from TAWS, management of energy state to restore automated flight	X		X	X					

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 2 Turboprop — Recurrent assessment and training matrix							*Competency map*								
			DES APP	vigilance and flexibility needed to change from one mode to another. The means of mitigating errors are included in this topic. The errors are described as mishandled auto flight systems, inappropriate mode selection, mishandled flight management system(s) and inappropriate autopilot usage.	Demonstrate appropriate use of flight guidance, auto thrust and other automation systems. Maintain mode awareness of the auto flight system(s), including engagement and automatic transitions. Revert to different modes when appropriate. Detect deviations from the desired aircraft state (flight path, speed, attitude, thrust, etc.) and take appropriate action. Anticipate mishandled auto flight system. Recognise mishandled auto flight system. Take appropriate action if necessary. Restore correct auto flight state. Identify and manage consequences.									
			CLB CRZ DES APP			Amendments to ATC cleared levels during altitude capture modes to force mode awareness and intervention	X		X				X		
			TO			Late ATC clearance to an altitude below acceleration altitude	X		X				X		
			TO APP			Engine-out special terrain procedures	X		X				X		
			CRZ			Forcing autopilot disconnect followed by re-engagement, recovery from low- or high-speed events in cruise	X		X	X			X		
			CLB			Engine failure during or after initial climb using automation	X		X						
			CRZ			Engine failure in cruise to onset of descent using automation	X		X						
			CRZ			Emergency descent	X		X						X
			DES APP			Managing high-energy descent capturing descent path from above (correlation with unstable approach training)	X		X				X		X
			APP			No ATC clearance received prior to commencement of approach or final descent	X		X				X		
			APP			Reactive wind shear and recovery from the consequent high-energy state	X		X				X		
			APP			Automation fail to capture the approach altitude in descent (e.g. last altitude before the FAP). Ideally, the failure occurs when the workload is high (e.g. configuration of the aircraft for final approach).					X	X	X	X	
			APP			Non-precision or infrequently flown approaches using the maximum available level of automation	X		X						X
			APP			Gear malfunction during an approach planned with autoland (including autobrake). Competency FPA may or may not be included depending on the impact of such malfunction on the automation.		X				X		X	
			APP			ATC clearances to waypoints beyond the programmed descent point for a coded final descent point during an approach utilising a final descent that is commanded by the flight management system	X		X				X		X

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Generation 2 Turboprop — Recurrent assessment and training matrix							*Competency map*								
EVAL or SBT	Competencies — non-technical (CRM)	A	APP	This encapsulates the general CRM principles and objectives. It includes communication; leadership and teamwork; problem-solving and decision-making; situation awareness and management of information; and workload management. Emphasis should be placed on the development of leadership, shown by EBT data sources to be a highly effective competency in mitigating risk and improving safety through pilot performance.	Exposure to an event or sequence of events to allow the pilot to build awareness of human factors in aviation and the human limitations. This includes the development of the following competencies: <u>Communication:</u> Demonstrate: — effective use of language; — responsiveness to feedback; and — capability to state the plans and resolve ambiguities. <u>Leadership and teamwork:</u> Use appropriate authority to ensure focus on the task. Support others in completing tasks. <u>Problem-solving and decision-making:</u> Detect deviations from the desired state, evaluate problems, identify the risk, consider alternatives and select the best course of action. Continuously review progress and adjust plans. <u>Situation awareness and management of information:</u> Have an awareness of the aircraft state in its environment; project and anticipate changes. <u>Workload management:</u> Prioritise, delegate and receive assistance to maximise focus on the task. Continuously monitor the flight progress.	GPS failure prior to commencement of approach associated with position drift and a terrain alert					X	X	X		X
			DES			Cabin crew report of water noise below the forward galley indicating a possible toilet pipe leak, with consequent avionics failures					X	X	X		
			CRZ			Smoke removal but combined with a diversion until landing is completed.		X			X	X	X	X	X
			GND			Apron fuel spilling					X	X		X	
			CRZ			Important water leak in an aircraft galley		X			X	X		X	
			ALL			A relevant number of cabin crew are wounded or incapacitated. Additionally, the cabin crew wounded or incapacitated are the most competent (e.g. senior cabin crew member).					X	X		X	
			ALL			Unruly passenger(s)					X			X	
			GND			Passenger oxygen: passenger service unit open and mask falling down					X	X		X	
			ALL			Passenger with medical problems — medical emergency					X			X	
			CRZ			Credible threat reported to the crew. Stowaway or fugitive on board.		X			X		X	X	
			GND			No METAR or TAFOR is available for destination due to industrial action at the destination airport	X	X			X	X			
			CRZ			Credible bomb threat reported to crew		X			X		X	X	
			CLB DES			Credible bomb threat or pressurisation problem, but no quick landing possible (due to weather, terrain or other reasons)		X			X	X		X	
			APP			Diversion with low remaining fuel or increased fuel flow due to system malfunction	X				X		X	X	
			APP			ACAS warning immediately following a go-around, with a descent manoeuvre required		X			X	X	X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Compliance	A	ALL	Compliance failure. Consequences of not complying with operating instructions (e.g. SOPs). This is not intended to list example scenario elements, but instructors should ensure that observed non-compliances are taken as learning opportunities throughout the programme. In all modules of the programme, the FSTD should as far as possible be treated like an aircraft, and non-compliances should not be accepted simply for expediency.	Recognise that a compliance failure has occurred. Make a verbal announcement. Take appropriate action if necessary. Restore safe flight path if necessary. Manage consequences.	The following are examples of potential compliance failures and are not intended to be developed as scenarios as part of an EBT module: 1. Requesting flap beyond limit speed 2. Flaps or slats in the wrong position for phase of flight or approach 3. Omitting an action as part of a procedure 4. Failing to initiate or complete a checklist 5. Using the wrong checklist for the situation	Intentionally blank								
EVAL or SBT	Go-around management	A	APP	Any threat or error that can result in circumstances that require a decision to perform a go-around, in addition to the execution of the go-around. Go-around scenarios should be fully developed to encourage effective leadership and teamwork, in addition to problem-solving and decision-making, plus execution using manual aircraft control or the flight management system(s) and automation as applicable. Design should include the element of surprise, and scenario-based go-arounds should not be predictable and anticipated. This topic is completely distinct from the go-around manoeuvre listed in the MT section that is intended only to practise psychomotor skills and a simple application of the procedures.		Adverse-weather scenario leading to a reactive wind shear warning during approach	X	X					X	X	
			APP			Adverse-weather scenario leading to a predictive wind shear warning during approach or go-around	X	X					X	X	
			APP			Adverse-weather scenario, e.g. thunderstorm activity, heavy precipitation or icing forcing decision at or close to DA/MDA	X					X	X	X	
			APP			DA with visual reference in heavy precipitation with doubt about the runway surface braking capability	X					X	X	X	
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP			Lost or difficult communications resulting in no approach clearance prior to commencement of approach or final descent	X		X				X		
			APP			Birds: large flocks of birds below DA once visual reference has been established				X		X	X		
			APP			System malfunction, landing gear malfunction during the approach									

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Manual aircraft control	A	CLB CRZ DES APP	Controls the flight path through manual control	Demonstrate manual aircraft control skills with smoothness and accuracy as appropriate to the situation. Detect deviations through instrument scanning. Maintain spare mental capacity during manual aircraft control. Maintain the aircraft within the normal flight envelope. Apply knowledge of the relationship between aircraft attitude, speed and thrust.	Flight with unreliable airspeed, which may or may not be recoverable	X			X			X		X
			CLB CRZ DES APP			Alternate flight control modes according to malfunction characteristics	X			X				X	X
			CLB CRZ DES APP			ACAS RA requires the pilot to descend or ATC calls for immediate descent	X	X		X					
			DES			TAWS warning when deviating from planned descent routing, requiring immediate response	X			X	X				
			TO			Scenario immediately after take-off which requires an immediate and overweight landing			X	X	X	X			
			TO			Adverse wind, crosswinds with or without strong gusts on take-off	X			X					
			TO			Adverse weather, wind shear, wind shear encounter during takeoff, with or without reactive warnings	X			X			X		
			TO			Engine failure during initial climb, typically 30-60 m (100-200 ft) (autopilot off)	X	X		X				X	
			CRZ			Wind shear encounter scenario during cruise, significant and rapid change in wind speed or down/updrafts, without wind shear warning	X		X			X	X	X	
			APP			Adverse weather, wind shear, wind shear encounter with or without warning during approach	X		X	X			X		
			APP			Adverse weather, deterioration in visibility or cloud base, or adverse wind, requiring a go-around from visual circling approach, during the visual segment	X	X	X	X		X	X	X	
			APP			Interception of the glide slope from above (correlation with unstable approach training)			X				X	X	
			APP LDG			Adverse wind, crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
			APP LDG			Adverse weather, adverse wind, approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP LDG			Circling approach manually flown at night in minimum in-flight visibility to ensure ground reference, minimum environmental lighting and no glide slope guidance lights	X			X			X	X	
			APP LDG			Runway incursion during approach, which can be triggered by ATC at various altitudes or by visual contact during the landing phase	X			X			X		
			LDG			Adverse wind, visibility, type-specific, special consideration for long-bodied aircraft, landing in minimum visibility for visual reference, with crosswind	X	X		X			X		
			LDG			System malfunction, auto flight failure at DA during a low-visibility approach requiring a go-around flown manually	X		X	X			X		
			APP LDG			Approach planned with autoland, followed by a failure below 1 000 ft requiring a manual go-around and an immediate landing due to fuel shortage	X		X		X		X		
			TO			In-seat instruction:		X		X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
						Insufficient engine failure recovery, forcing the pilot monitoring to take over the flight controls									
			APP LDG			In-seat instruction: Unstable approach on short final or long landing, forcing the pilot monitoring to take over the flight controls		X		X			X	X	
EVAL or SBT	Monitoring, cross-checking, error management, mismanaged aircraft state	A	ALL	The scenarios should be realistic and relevant, and should be used for the purpose of demonstration and reinforcement of effective monitoring. Modules in the FSTD should be treated like those in an aircraft so that trainees have the opportunity to develop the competency with the practice of the right techniques and attitudes related to these topics through pilot performance, and that instructors have the opportunity to assess and train these topics in a realistic environment. As shown by the EBT data report, these topics are of key importance to improve safety in operations. In addition, the operator may also use these topics to develop scripted role-playing scenarios in the form of ISI. These scenarios cater for the need to monitor flight path excursions from the instructor pilot (PF), detect errors and make appropriate interventions, either verbally or by taking control as applicable. Demonstration scenarios may also be used. Demonstrated role-play should contain realistic and not gross errors, leading at times to a mismanaged aircraft state, which can also be combined with upset management training.	Recognise mismanaged aircraft state. Observe the pilot's behaviour: how the pilot is mitigating errors, performing cross-checking, monitoring performance and dealing with a mismanaged aircraft state, in order to ensure that observed deviations, errors and mistakes are taken as learning opportunities throughout the programme. Monitor flight path excursions. Detect errors and threats through proper cross-checking performance. Make appropriate interventions either verbally or by taking control if applicable. Take appropriate action if necessary. Restore the desired aircraft state. Identify and manage consequences.	Deviations from the flight path, in pitch attitude, speed, altitude, bank angle		X					X		
			ALL			In-seat instruction: Simple automation errors (e.g. incorrect mode selection, attempted engagement without the necessary conditions, entering wrong altitude or speed, failure to execute the desired mode) culminating in a need for direct intervention from the pilot monitoring, and where necessary taking control.		X					X		
			APP			In-seat instruction: Unstable approach or speed/path/vertical rate not congruent with the required state for the given flight condition	X	X					X	X	
			LDG			In-seat instruction: Demonstration exercise — recovery from bounced landing, adverse wind, strong gusts during landing phase, resulting in a bounce and necessitating recovery action from the pilot monitoring	X			X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
	Unstable approach	A	DES APP	Reinforce stabilised approach philosophy and adherence to defined parameters. Encourage go-arounds when crews are outside these parameters. Develop and sustain competencies related to the management of high-energy situations.		ATC or terrain-related environment creating a high-energy descent with the need to capture the optimum profile to complete the approach in a stabilised configuration	X		X				X		
			DES APP			ATC or terrain-related environment creating a high-energy descent leading to unstable conditions and requiring a go-around	X		X				X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswinds including shifting wind directions				X		X	X		
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP LDG			Crosswinds with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 5 — UPRT training topic with frequency (B). Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)							*Competency map*								
EVAL, MT or SBT	Upset prevention training	B	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include upset prevention elements in Table 1 for the recurrent training programme in at least every cycle, such that all the elements are covered over a period not exceeding 3 years. The elements are numbered with letters from A to I in Table 1 of AMC1 ORO.FC.220&230. Each element is made up of several numbered components. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recognising and preventing the development of upset conditions.	Early recognition and prevention of upset conditions. When the differences between LHS and RHS are not significant in the handling of the aircraft, UPRT may be conducted in either seat.	See Table 1 of AMC1 ORO.FC.220&230: Elements and respective components of upset prevention training.	Intentionally blank								
			CRZ			Demonstration of the defined normal flight envelope and any associated changes in flight instruments, flight director systems, and protection systems. This should take the form of an instructor-led exercise to show the crew the points beyond which an upset condition could exist.			X					X	X
			TO APP			Severe wind shear or wake turbulence during take-off or approach			X	X		X	X		
			CRZ			As applicable and relevant to the aircraft type, demonstration at a suitable intermediate level, with turbulence as appropriate; practise steep turns and note the relationship between bank angle, pitch and stalling speed				X			X		X
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence to trigger overspeed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)	X		X	X			X		
			CRZ			At the maximum cruise flight level for the current aircraft weight, turbulence and significant temperature rise to trigger low-speed conditions (if FSTD capability exists, consider use of the vertical wind component to add realism)			X	X			X		X
			CRZ			High-altitude loss of reliable airspeed	X	X		X			X	X	
			CRZ			High-altitude TCAS RA (where the RA is required to be flown in manual flight)	X			X			X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 6 — Training topics with frequency (B) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)							*Competency map*								
EVAL, MT or SBT	Aircraft system malfunctions, including operations under MEL	B	ALL	For full details, see the malfunction equivalency methodology. Any internal failure(s) apparent or not apparent to the crew Any item cleared by the MEL but having an impact upon flight operations — for instance, thrust reverser locked. Malfunctions to be considered should have one or more of the following characteristics: — Immediacy — Complexity — Degradation of aircraft control — Loss of primary instrumentation — Management of consequences The operator should vary malfunctions for each characteristic over the EBT cycle. Unless specified otherwise in the operational suitability data, at least one malfunction with each characteristic should be included in every cycle. Combining characteristics should not reduce the number of malfunctions below seven for each cycle. For each crew member, the characteristics of degraded control and loss of instrumentation should be in the role of pilot flying and the others may be in the role of pilot flying or pilot monitoring. For full details, see the malfunction equivalency methodology.	Recognise system malfunction. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences. Apply crew operating procedures where necessary. Respond appropriately to additional system abnormalities associated with MEL dispatch.	(i) System malfunctions that require immediate and urgent crew intervention or decision, e.g. fire, smoke, loss of pressurisation at high altitude, failures during take-off, brake failure during landing. (ii) System malfunctions that require complex procedures, e.g. multiple hydraulic system failures, smoke and fumes procedures, major electrical system failure. (iii) System malfunctions that result in significant degradation of flight controls in combination with abnormal handling characteristics, e.g. jammed flight controls, certain degradation of FBW control, jammed horizontal stabiliser; flaps and/or slats locked; other malfunctions that result in degraded flight controls. (iv) System failures that require monitoring and management of the flight path using degraded or alternative displays, unreliable primary flight path information, unreliable airspeed, e.g. flight with unreliable airspeed (v) System failures that require extensive management of their consequences (independent of operation or environment), e.g. fuel leak.	Intentionally blank								
			TO			MEL items with crew operating procedures applicable during take-off						X		X	
			TO			Response to an additional factor that is affected by an MEL item (e.g. system failure, runway state)		X		X		X			X
			GND			Malfunction during preflight preparation and prior to departure	X					X	X		
			CLB			Malfunction after departure	X					X	X		X
			ALL			Malfunctions that require immediate attention (e.g. bleed fault during engine start, hydraulic failure during taxi)	X				X			X	
			CRZ CLB			Fuel leak (management of consequences)	X				X		X		X
			TO			Malfunction on take-off high speed below V1	X				X	X			
			TO			Malfunction on take-off high speed above V1	X					X			
			GND			During taxi to the runway, a spurious brake temperature announcement. The crew had the correct brake temperature moments before the failure.					X	X	X		
			TO			Tyre failure during take-off					X	X		X	
			TO			Malfunction on initial climb	X					X			
			APP			Malfunction on approach	X					X		X	
			APP			Malfunction on go-around	X					X		X	
			LDG			Malfunction during landing	X	X		X		X	X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Engine failure	B	TO	Any engine failure or malfunction, which causes loss or degradation of thrust that affects performance. This is distinct from the engine-out manoeuvres described in the MT section above, which are intended only to practise psychomotor skills and reinforce procedures to manage engine failures.	Recognise engine failure. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Engine failure or engine malfunction on take-off low speed	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off high speed below V1	X			X		X		X	
			TO			Engine failure or engine malfunction on take-off above V1	X					X	X	X	
			TO			Engine failure or engine malfunction on initial climb	X					X	X		
			APP			Engine malfunction	X					X		X	
			CRZ			Engine failure in cruise (with autopilot)	X		X				X		
			LDG			Engine failure or engine malfunction on landing				X					
	Landing	B	LDG	Pilots should have opportunities to practise landings in demanding situations at the defined frequency. Data indicates that landing problems have their roots in a variety of factors, including inappropriate decision-making, in addition to manual aircraft control skills if difficult environmental conditions exist. The purpose of this item is to ensure that pilots are exposed to this during the programme.	Landing in demanding environmental conditions, with malfunctions as appropriate	This topic should be combined with the adverse-weather topic, aircraft system malfunctions topic or any topic that can provide exposure to a landing in demanding conditions.	Intentionally blank								
EVAL or SBT	Surprise	B	ALL	The data analysed during the development of the EBT concept indicated substantial difficulties encountered by crews when faced with a threat or error, which was a surprise or an unexpected event. The element of surprise should be distinguished from what is sometimes referred to as the 'startle factor' — the latter being a physiological reaction. Wherever possible, consideration should be given towards variations in the types of scenario, times of occurrences and types of occurrence, so that pilots do not become overly familiar with repetitions of the same scenarios. Variations should be the focus of EBT programme design, and not left to the discretion of individual instructors, in order to preserve programme integrity and fairness.	Exposure to an unexpected event or sequence of events at the defined frequency in order to build resilience.	Rejected take-off	X			X		X			
						Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Terrain	B	ALL	Alert, warning, or conflict	Anticipate terrain threats. Prepare for terrain threats. Recognise unsafe terrain clearance. Take appropriate action. Apply the appropriate procedures correctly. Maintain aircraft control. Restore safe flight path. Manage consequences.	ATC clearance giving insufficient terrain clearance	X	X			X				
			ALL			Demonstration of terrain avoidance warning systems (TAWS) (this scenario element may be done in an ISI.)						X	X	X	
			TO CLB			Engine failure where performance is marginal leading to TAWS warning		X		X				X	
			DES APP			ATC provides a wrong QNH		X					X		
			DES			'Virtual mountain' refers to the surprise element of an unexpected warning. Care should be exercised in creating a level of realism, so this can best be achieved by an unusual and unexpected change of route during the descent.						X	X	X	
EVAL or SBT	Workload, distraction, pressure, stress	B	ALL	This is not considered a topic for specific attention on its own, but more as a reminder to programme developers to ensure that pilots are exposed to immersive training scenarios which expose them to manageable high workload and distractions during the course of the EBT programme, at the defined frequency.	Manage available resources efficiently to prioritise and perform tasks in a timely manner under all circumstances	Intentionally blank	Intentionally blank								

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 7 — UPRT Upset recovery training topic with frequency (C). Evaluation phase, manoeuvres training phase or scenario-based training phase (EVAL, MT or SBT)							*Competency map*								
MT or SBT	Upset recovery	C	N/A	Compliance with AMC1 or AMC2 to ORO.FC.220&230 Include the recovery exercises in Table 2 of AMC1 ORO.FC.220&230 for the recurrent training programme, such that all the exercises are covered over a period not exceeding 3 years. According to the principles of EBT, covering one component should satisfy the requirement to cover the whole element of recovery from developed upsets. The same principles apply to the exercises of components 2, 3 and 4 where one exercise may satisfy the requirement to cover the whole component. An aeroplane upset is defined as an undesired aeroplane state in flight characterised by unintentional divergences from parameters normally experienced during line operations or training. An aeroplane upset may involve pitch and/or bank angle divergences as well as inappropriate airspeeds for the conditions.	Recognise upset condition. Make timely and appropriate intervention. Take appropriate action. Assure timely and appropriate intervention. (AMC1 ORO.FC.220&230 Table 2 component 1) Assure aircraft control. Maintain or restore a safe flight path. Assess consequential issues. Manage outcomes. Consolidate the summary of aeroplane recovery techniques. (AMC1 ORO.FC.220&230 Table 2 component 5) Note: The operator should assess if the exercises should be practised for the either seat qualification.	The example scenario elements may be done in ISI, as non-ISI or a combination of both. If done in ISI: The instructor should position the aircraft within but close to the edge of the validated training envelope before handing control to the trainee to demonstrate the restoration of normal flight. Careful consideration should be given to flying within the validated training envelope.	Intentionally blank								
			CLB DES			Table 2 of AMC1 ORO.FC.220&230: Exercises for upset recovery training									
			CRZ			A. **Recovery from developed upsets**									
			CRZ			2. Recovery from stall events in the following configurations: — take-off configuration, — clean configuration low altitude, — clean configuration near maximum operating altitude, and — landing configuration during the approach phase.	X			X			X	X	
			CRZ			3. Recovery from nose high at various bank angles	X			X			X	X	
			APP			4. Recovery from nose low at various bank angles	X			X			X	X	
			CLB DES			Demonstration at a normal cruising altitude. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.	X			X			X		
						Demonstration at an intermediate altitude during early stages of the approach. Set conditions and disable aircraft systems as necessary to enable trainee to perform stall recovery according to OEM instructions.	X			X			X		
						Recovery from a wake turbulence position with high-bank angle	X		X	X			X		

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
Section 8 — Training topics with frequency (C) in alphabetical order. Evaluation phase or scenario-based training phase (EVAL or SBT)															
	Adverse wind	C	TO	Adverse wind/crosswind. This includes tailwind but not ATC mis-reporting of the actual wind.	Recognise adverse-wind conditions. Observe limitations. Apply the appropriate procedures. Maintain directional control and safe flight path.	Take-off with different crosswind/tailwind/gust conditions						X		X	
			TO			Take-off with unreported tailwind		X			X				
			TO			Crosswinds with or without strong gusts on take-off	X			X					
			APP			Wind exceeding limits on final approach (not reported)	X	X				X	X		
			APP			Wind exceeding limits on final approach (reported) in manual aircraft control	X	X		X		X			
			APP			Increasing tailwind on final approach (not reported)	X	X				X	X		
			APP			Approach and landing in demanding weather conditions, e.g. turbulence, up and downdrafts, gusts and crosswind including shifting wind directions				X		X	X		
			APP			Adverse-wind scenario resulting in increasing tailwind below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below DA (not reported)		X		X		X			
			APP			Adverse-wind scenario including strong gusts and/or crosswind out of limits below 15 m (50 ft) (not reported)		X		X		X			
			APP LDG			Crosswind with or without strong gusts on approach, final approach and landing (within and beyond limits)	X			X		X			
	Approach, visibility close to minimum	C	APP	Any situation where visibility becomes a threat	Recognise actual conditions. Observe aircraft and/or procedural limitations. Apply the appropriate procedures if applicable. Maintain directional control and safe flight path.	Approach in poor visibility	X		X	X				X	
			APP			Approach in poor visibility with deteriorations necessitating a decision to perform a go-around	X		X	X					
			LDG			Landing in poor visibility				X		X	X		
EVAL or SBT	ATC	C	ALL	ATC error. Omission, miscommunication, garbled, poor quality transmission. All these act as distractions to be managed by the crew. The scenarios should be combined, where possible, with others of the same or higher weighting, the principal reason being to create distractions.	Respond to communications appropriately. Recognise, clarify and resolve any ambiguities. Refuse or question unsafe instructions. Use standard phraseology whenever possible.	ATC role-play: the instructor provides scripted instructions, as a distraction to the crew	X	X			X				
						Controller error, provided by the instructor according to a defined scripted scenario	X	X				X	X		
						Frequency congestion, with multiple aircraft using the same frequency		X							
						Destination temporarily closed					X	X	X	X	
						Rescue and firefighting services (RFFS) level reduction at destination		X			X		X		
						Runway change before the interception of the localiser or similar navigation aid in azimuth			X		X		X	X	
						Stray dogs at the opposite threshold runway		X			X		X		
						Poor quality transmissions		X							

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Fire and smoke management	C	GND	This includes engine, electric, pneumatic, cargo fire, smoke or fumes.	Recognise fire, smoke or fumes. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	Fire in cargo or cabin/cockpit at gate	X	X				X		X	
			GND			Fire during taxi	X	X				X		X	X
			GND			Fire with no cockpit indication	X	X				X		X	X
			TO			Take-off low speed	X			X	X	X			X
			TO			Fire or smoke on take-off high speed below V1	X			X	X	X			
			TO			Fire or smoke on take-off high speed above V1	X				X	X			
			TO			Fire or smoke on initial climb	X				X	X			
			CRZ			Cargo fire						X	X	X	
			APP			Engine fire in approach (extinguishable)		X				X			
			APP			Engine fire in approach (non-extinguishable)		X			X	X			
			CLB CRZ DES			Lithium battery fire in the cockpit or cabin compartment	X	X			X	X		X	
			APP			Flight deck or cabin fire		X			X	X			X
			GND			Any of the example scenario elements above ending in an evacuation		X			X	X		X	
EVAL or SBT	Loss of communications	C	GND	Lost or difficult communications due to either pilot mis-selection or a failure external to the aircraft. This could be for a few seconds or a total loss.	Recognise loss of communications. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative ways to communicate. Manage consequences.	Loss of communications during ground manoeuvring	X	X							
			TO			Loss of communications after take-off	X					X			X
			APP			Loss of communications during approach phase, including go-around	X	X				X	X		X
EVAL or SBT	Managing loading, fuel, performance errors	C	ALL	A calculation error by one or more pilots, or someone involved with the process, or the process itself, e.g. incorrect information on the load sheet	Anticipate the potential for errors in load/fuel/performance data. Recognise inconsistencies. Manage/avoid distractions. Make changes to paperwork/aircraft system(s) to eliminate error. Identify and manage consequences.	This can be a demonstrated error, in that the crew may be instructed to deliberately insert incorrect data — for example, to take off from an intersection with full-length performance information. The crew will be asked to intervene when acceleration is sensed to be lower than normal, and this may be part of the operator procedures, especially when operating mixed fleets with considerable variations in MTOM.	X	X						X	
			GND			Fuel ground staff on industrial action. Only limited amount of fuel available, which is below the calculated fuel for the flight.					X	X	X	X	
			GND			Advise crew that there is a change of the load sheet figures during taxi to the runway. The crew may have limited time due to a calculated take-off time (CTOT) — ATC slot.	X							X	
			GND			Braking action reported 'medium'. The information is transmitted just before take-off. The flight is subject to a (CTOT) — ATC slot.					X		X	X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Navigation	C	GND	External NAV failure. Loss of GPS satellite, ANP exceeding RNP, loss of external NAV source(s)	Recognise a NAV degradation. Take appropriate action. Execute the appropriate procedure as applicable. Use alternative NAV guidance. Manage consequences.	External failure or a combination of external failures degrading aircraft navigation performance on ground	X		X			X	X		
			TO CLB APP LDG			External failure or a combination of external failures degrading aircraft navigation performance in flight		X			X	X	X		
			GND			Standard initial departure change during taxi. The flight may be subject to a CTOT — ATC slot.					X		X	X	
			APP			Loss of runway lighting below decision height		X				X	X		
			CRZ			No fly zone: when the crew changes control frequency, the new ATCO informs the crew that they are flying over an unannounced 'no fly zone' that is not included in the NOTAMs. (To trigger such an event, the context may be as follows: an unexpected military conflict in the territory the aircraft is flying over or the crew is forced to re-route in flight and the new route flies over a city that has an important event such the Olympic games, a G20/G7 submit, or the route is flying near a space rocket launch close to the time of the launch, like the Guiana Space Centre, Cape Cañaveral, etc.).					X	X	X		
	Operations- or type-specific	C	ALL	Intentionally blank	Intentionally blank	Intentionally blank	Intentionally blank								
	Operations of special airport approval	C	APP LDG	See equivalency of approaches relevant to operations.	The operator should comply with the national qualification requirements published in the Aeronautical Information Publication.	Intentionally blank	Intentionally blank								
EVAL or SBT	Pilot incapacitation	C	TO	Consequences for the non-incapacitated pilot	Recognise incapacitation. Take appropriate action including correct stop/go decision. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	During take-off	X	X			X	X			X
			APP			During approach	X			X				X	X
EVAL or SBT	Runway or taxiway condition	C	GND TO LDG	Contamination or surface quality of the runway, taxiway, or tarmac including foreign objects	Recognise hazardous runway condition. Observe limitations. Take appropriate action. Apply the appropriate procedures correctly. Assure aircraft control.	Planned anticipated hazardous conditions with dispatch information provided to facilitate planning and execution of appropriate procedures						X			X
			GND TO LDG			Unanticipated hazardous conditions, e.g. unexpected heavy rain resulting in flooded runway surface		X			X	X			
			TO			Take-off on runway with reduced cleared width due to snow	X			X	X		X		
			TO			Stop/go decision in hazardous conditions					X	X		X	

Assessment and training topic		*Frequency*	*Flight phase activation*	*Description (includes type of topic, being threat, error or focus)*	*Desired outcome (includes performance criteria OR training outcome)*	*Guidance material (GM) Example scenario elements*	*PRO*	*COM*	*FPA*	*FPM*	*LTW*	*PSD*	*SAW*	*WLM*	*KNO*
EVAL or SBT	Traffic	C	CLB CRZ DES	Traffic conflict. ACAS RA or TA, or visual observation of conflict, which requires evasive manoeuvring	Anticipate potential loss of separation. Recognise loss of separation. Take appropriate action. Apply the appropriate procedure correctly. Maintain aircraft control. Manage consequences.	ACAS warning that requires crew intervention		X				X	X	X	
EVAL or SBT	Wind shear recovery	C	TO	With or without warnings including predictive. A wind shear scenario is ideally combined with an adverse-weather scenario containing other elements.	Anticipate potential for wind shear. Avoid known wind shear or prepare for suspected wind shear. Recognise wind shear encounter. Take appropriate action. Apply the appropriate procedure correctly. Assure aircraft control. Recognise out of wind shear condition. Maintain or restore a safe flight path. Assess consequential issues and manage outcomes.	Predictive wind shear warning during take-off					X	X			
			TO			Wind shear encounter during take-off	X				X	X			
			TO			Wind shear encounter after rotation						X		X	
			TO			Predictive wind shear after rotation					X	X			
			APP			Predictive wind shear during approach	X				X	X			
			APP			Wind shear encounter during go-around	X				X	X		X	
			APP			Wind shear encounter during approach	X				X	X			

END GEN2 TURBOPROP

AMC7 ORO.FC.232 EBT programme assessment and training topics

GENERATION 1 (JET) — EBT PROGRAMME — TABLE OF ASSESSMENT AND TRAINING TOPICS

Given the very small number of turbo-jet aeroplanes of the first generation in current use in commercial air transport operations and the lack of appropriate FSTDs for recurrent training, it has not been deemed possible to provide a table of assessment and training topics for those aeroplanes and therefore it is not possible to apply EBT.

AMC8 ORO.FC.232 EBT programme assessment and training topics

SCENARIO ELEMENTS AND COMPETENCY MAPPING

(a) The operator may develop scenario elements and a competency map that are more relevant to its operation.

(b) When developing scenario elements, the operator should ensure that there can be no negative training when asking pilots to induce their own errors.

(c) Competencies mapped are those considered critical in managing the scenario. They are determined according to the following principles:

(1) those competencies considered most critical to the successful management of the defined threat or error; or

(2) those competencies most likely to be linked to the root cause of poor performance in the case of unsuccessful management of a defined threat or error.

(d) The competency map may indicate scenarios or combinations of scenarios for development of particular competencies.

(e) The competency map indicates the most critical competencies suggested by design, but the instructor should always assess all observed competencies.

GM1 ORO.FC.232 EBT programme assessment and training topics

TABLE OF ASSESSMENT AND TRAINING TOPICS

(a) The assessment and training topics usually have several example scenario elements. At least one examples scenario element is selected (e.g. Gen 4 topic 'Go-around' in MT has three example scenario elements — the operator may choose one at each module (frequency A)).

(b) Flight phase for activation:

Abbreviation	Flight phase	Description
GND (1)	Flight planning, preflight, engine start & taxi-out	Ground phases up to when the crew increases thrust for taking-off
	Taxi-in, engine shutdown, post- flight & flight closing	From the speed that permits the aircraft to be manoeuvred by means of taxiing for arriving at a parking area until the crew completes post-flight and flight closing duties.
TO (2)	Take-off	This phase begins when the crew increases the thrust for taking-off. It ends after the speed and configuration are established at a defined manoeuvring altitude or to continue the climb for cruise.
CLB (3)	Climb	This phase begins when the crew establishes the aircraft at a defined speed and configuration enabling the aircraft to increase altitude for the purpose of cruise. It ends with the aircraft established at a predetermined constant initial cruise altitude at a defined speed.
CRZ (4)	Cruise	The cruise phase begins when the crew establishes the aircraft at a defined speed and predetermined constant initial cruise altitude and proceeds in the direction of a destination. It ends with the beginning of descent for an approach.
DES (5)	Descent	This phase begins when the crew departs the cruise altitude for an approach at a particular destination. It ends when the crew initiates changes in aircraft configuration and/or speed to facilitate a landing on a particular runway.
APP (6)	Approach	This phase begins when the crew initiates changes in aircraft configuration and/or speeds enabling the aircraft to manoeuvre for landing on a particular runway. It ends when the aircraft is in the landing configuration and the crew is dedicated to land on a specific runway. It also includes go-around where the crew aborts the descent to the planned landing runway during the approach phase. Go-around ends after speed and configuration are established at a defined manoeuvring altitude or to continue the climb for cruise.
LDG (7)	Landing	This phase begins when the aircraft is in the landing configuration and the crew is dedicated to touchdown on a specific runway. It ends when the speed permits the aircraft to be manoeuvred by means of taxiing for arrival at a parking area.
ALL (8)	All	Any or all phases of flight

GM2 ORO.FC.232 EBT programme assessment and training topics

COMPETENCY MAP PROCESS

Note 1. The competency map process may be done in teams of instructors. Then the results are compared and reconciled by a small group of subject matter experts (SMEs).

Note 2. It is always easy to map SAW or KNO as the underlying competency, but there are almost invariably other competencies, especially when there is ineffective management, so the intent should be to balance the mapping of SAW or KNO and map the other predominant competencies within the scenario.

AMC1 ORO.FC.232(b)(1) EBT programme assessment and training topics

EBT DATA REPORT

(a) The data report is a large-scale comprehensive study of operational data. It identifies the areas of pilot training for improvement, providing the prioritisation of germane and relevant training topics to guide in the construction of suitable EBT programmes. The data report uses other studies, a variety of data sources and/or varied methodology to mitigate the inherent bias associated with individual types of data sources.

(b) The data report should:

(1) be endorsed or developed by the competent authority or ICAO;

(2) be reviewed by a team of experts in pilot training, representing airline operators, pilot associations, regulators, and original equipment manufacturers (OEM);

(3) use data or information (training data, operational data and safety data) from the following sources:

(i) accident investigation bodies;

(ii) competent authorities;

(iii) OEM — aircraft;

(iv) safety information;

(v) operators; and

(vi) studies or reports (aviation or scientific);

(4) analyse the data with the following objectives:

(i) to substantiate the need for change in the assessment and training programmes for commercial transport pilots;

(ii) to provide evidence from data analyses to support the derivation of training topics, prioritised according to aircraft generation;

(iii) to challenge and/or corroborate the other sources of data (e.g. Training Criticality Survey and Training Guidance) with operational data;

(iv) to provide feedback regarding the effectiveness of changes implemented through the adoption of competency-based training methodologies; and

(v) to validate or ascertain practices, findings or conclusions made previously by the industry;

(5) include the studies and define the use of such studies in the data report following the criteria

below:

(i) The study is relevant from a training perspective (e.g. if incorporating a training change mitigates the risk found in the study).

(ii) There is evidence that it will assist with the identification of competencies to be developed in training in order to mitigate risks encountered in the evolving operational environment.

(iii) The findings of the study will be corroborative or challenging across the spectrum of the analysis made in the data report.

(iv) The study allows the analysis and comparison of the data or findings in the data report and it is coming from industry-respected research or studies;

(6) include an evidence table for the purpose of:

(i) integrating the evidence of the analyses in points (4) and (5);

(ii) identifying meaningful patterns;

(iii) enabling the grouping of evidence to support the key findings; and

(iv) facilitating the prioritisation of results; and

(7) include a prioritisation of the training topics for the purpose of translating data into useful events and scenarios to assess and develop pilot performance (assessment and training topics). The prioritisation shall:

(i) systematically rank threats, errors and competencies along with the factors leading to accidents and serious incidents from multiple data sources to formulate a table of assessment and training topics;

(ii) be performed for each of the generations of aircraft. This allows highlighting the differences and commonalities between generations; and

(iii) ensure sufficient flexibility in the process to allow enhancement of the training programmes according to the type of operation, culture and type of aircraft.

AMC1 ORO.FC.232(b)(3) EBT programme assessment and training topics

AIRCRAFT TYPES BY GENERATIONS

The operator should only develop an EBT programme for aircraft types for which there is a table of assessment and training topics.

Generation 4 — Jet)	From 1988. EFIS cockpit — FMS equipped FADEC Fly-by-wire control systems Advanced flight envelope protection Integrated auto flight control system — navigation performance, and terrain avoidance systems Generation fatal accident average rate: 0.1/million flights	A318/A319/A320/A321 (including neo), A330, A340-200/300, A340-500/600, B777, A380, B787, A350, Bombardier C Series (A220), Embraer E170/E175/E190/E195
Generation 3 — Jet	From 1969 EFIS cockpit — FMS equipped FADEC Integrated auto flight control system — navigation performance, and terrain avoidance systems Basic flight envelope protection — stick shaker/pusher Generation fatal accident average rate: 0.2/million flights	A310/A300-600, B737-300/400/500, B737-600/700/800 (NG), B737 MAX, B757, B767, B747-400, B747-8, B717, BAE 146, MD11, MD80, MD90, F70, F100, Bombardier CRJ Series, Embraer ERJ 135/145
Generation 3 — Turboprop	From 1992 EFIS cockpit — FMS equipped EEC/ECU or higher engine control Integrated auto flight control system — navigation performance and terrain avoidance systems Basic flight envelope protection — stick shaker/pusher	ATR 42-600, ATR 72-600, Bombardier Dash 8-400, BAE ATP, Saab 2000
Generation 2 — Jet	From 1964 Integrated auto-flight system. EEC/ECU or higher engine control Analogue/CRT instrument display Basic flight envelope protection — stick shaker/pusher Generation fatal accident average rate: 0.7/million flights	A300 (except A300-600), BAC111, B727, B737-100/200, B747-100/200/300, DC9, DC10, F28, L1011
Generation 2 — Turboprop	From 1964 Analogue/CRT instrument display EEC/ECU Basic flight envelope protection — stick shaker/pusher Integrated auto flight control system	ATR 42, ATR 72 (all series except - 600), BAE J-41, Fokker F27/50, Bombardier Dash 7 and Dash 8- 100/200/300 Series, Convair 580- 600 Series, Shorts 330 and 360, Saab 340, Embraer 120
Generation 1 — Jet	From 1952 First commercial jets. Manual engine control Analogue instrument display Not integrated auto flight control system Basic flight envelope protection — stick shaker/pusher, attitude warning Generation fatal accident average rate: 3.0/million flights	DC8, B707

ORO.FC.235 Pilot qualification to operate in either pilot's seat

(a) Commanders whose duties require them to operate in either pilot seat and carry out the duties of a co-pilot, or commanders required to conduct training or checking duties, shall complete additional training and checking as specified in the operations manual. The check may be conducted together with the operator proficiency check prescribed in point ORO.FC.230(b) or in the EBT programme prescribed in point ORO.FC.231.

(b) The additional training and checking shall include at least the following:

(1) an engine failure during take-off;

(2) a one-engine-inoperative approach and go-around; and

(3) a one-engine-inoperative landing.

(c) In the case of helicopters, commanders shall also complete their proficiency checks from left- and right-hand seats, on alternate proficiency checks, provided that when the type rating proficiency check is combined with the operator proficiency check the commander completes his/her training or checking from the normally occupied seat.

(d) When engine-out manoeuvres are carried out in an aircraft, the engine failure shall be simulated.

(e) When operating in the co-pilot's seat, the checks required by ORO.FC.230 for operating in the commander's seat shall, in addition, be valid and current.

(f) The pilot relieving the commander shall have demonstrated, concurrent with the operator proficiency checks prescribed in ORO.FC.230 (b), practice of drills and procedures that would not, normally, be his/her responsibility. Where the differences between left- and right-hand seats are not significant, practice may be conducted in either seat.

(g) The pilot other than the commander occupying the commander's seat shall demonstrate practice of drills and procedures, concurrent with the operator proficiency checks prescribed in ORO.FC.230 (b), which are the commander's responsibility acting as pilot monitoring. Where the differences between left- and right-hand seats are not significant, practice may be conducted in either seat.

AMC1 ORO.FC.235(d) Pilot qualification to operate in either pilot's seat

SINGLE-ENGINE HELICOPTERS — AUTOROTATIVE LANDING

In the case of single-engined helicopters, the auto rotative landing should be carried out from left- and right-hand seats on alternate proficiency checks.

GM1 ORO.FC.235(f);(g) Pilot qualification to operate in either pilot's seat

DIFFERENCES BETWEEN LEFT AND RIGHT-HAND SEATS

The differences between left- and right-hand seats may not be significant in cases where, for example, the autopilot is used.

ORO.FC.240 Operation on more than one type or variant

(a) The procedures or operational restrictions for operation on more than one type or variant established in the operations manual and approved by the competent authority shall cover:

(1) the flight crew members' minimum experience level;

(2) the minimum experience level on one type or variant before beginning training for and operation of another type or variant;

(3) the process whereby flight crew qualified on one type or variant will be trained and qualified on another type or variant; and

(4) all applicable recent experience requirements for each type or variant.

(b) When a flight crew member operates both helicopters and aeroplanes, that flight crew member shall be limited to operations on only one type of aeroplane and one type of helicopter.

(c) Point (a) shall not apply to operations of performance class B aeroplane if they are limited to single-pilot classes of reciprocating engine aeroplanes under VFR by day. Point (b) shall not apply to operations of performance class B aeroplane if they are limited to single-pilot classes of reciprocating engine aeroplanes.

AMC1 ORO.FC.240 Operation on more than one type or variant

GENERAL

(a) Aeroplanes

(1) When a flight crew member operates more than one aeroplane class, type or variant, as determined by the operational suitability data established in accordance with CAR 21 for class-single pilot or type-single pilot, but not within a single licence endorsement, the operator should ensure that the flight crew member does not operate more than:

(i) three reciprocating engine aeroplane types or variants;

(ii) three turbo-propeller aeroplane types or variants;

(iii) one turbo-propeller aeroplane type or variant and one reciprocating engine aeroplane type or variant; or

(iv) one turbo-propeller aeroplane type or variant and any aeroplane within a particular class.

(2) When a flight crew member operates more than one aeroplane type or variant within one or more licence endorsement, as determined by the operational suitability data established in accordance with CAR 21, the operator should ensure that:

(i) the minimum flight crew complement specified in the operations manual is the same for each type or variant to be operated;

(ii) the flight crew member does not operate more than two aeroplane types or variants for which a separate licence endorsement is required, unless credits related to the training, checking, and recent experience requirements are defined in the operational suitability data established in accordance with CAR 21 for the relevant types or variants; and

(iii) only aeroplanes within one licence endorsement are flown in any one flight duty period, unless the operator has established procedures to ensure adequate time for preparation.

(3) When a flight crew member operates more than one aeroplane type or variant as determined by the operational suitability data established in accordance with CAR 21 for type-single pilot and type-multi pilot, but not within a single licence endorsement, the operator should comply with points (a)(2) and (4).

(4) When a flight crew member operates more than one aeroplane type or variant as determined by the operational suitability data established in accordance with CAR 21 for type multi-pilot, but not within a single licence endorsement, or combinations of aeroplane types or variants as determined by the operational suitability data established in accordance with CAR 21 for class single-pilot and type multi-pilot, the operator should comply with the following:

(i) point (a)(2);

(ii) before exercising the privileges of more than one licence endorsement:

(A) flight crew members should have completed two consecutive OPCs and should have:

– 500 hours in the relevant crew position in CAT operations with the same operator; or

– for IFR and VFR night operations with performance class B aeroplanes, 100 hours or flight sectors in the relevant crew position in CAT operations with the same operator, if at least one licence endorsement is related to a class. A check flight should be completed before the pilot is released for duties as commander;

(B) in the case of a pilot having experience with an operator and exercising the privileges of more than one licence endorsement, and then being promoted to command with the same operator on one of those types, the required minimum experience as commander is 6 months and 300 hours, and the pilot should have completed two consecutive OPCs before again being eligible to exercise more than one licence endorsement;

(iii) before commencing training for and operation of another type or variant, flight crew members should have completed 3 months and 150 hours flying on the base aeroplane, which should include at least one proficiency check, unless credits related to the training, checking and recent experience requirements are defined in the operational suitability data established in accordance with CAR 21 for the relevant types or variants;

(iv) after completion of the initial line check on the new type, 50 hours flying or 20 sectors should be achieved solely on aeroplanes of the new type rating, unless credits related to the training, checking and recent experience requirements are defined in the operational suitability data established in accordance with CAR 21 for the relevant types or variants;

(v) recent experience requirements established in CAR Part II for each type operated;

(vi) the period within which line flying experience is required on each type should be specified in the operations manual;

(vii) when credits are defined in the operational suitability data established in accordance with CAR 21 for the relevant type or variant, this should be reflected in the training required in ORO.FC.230 and:

(A) ORO.FC.230 (b) requires two OPCs every year. When credits are defined in

the operational suitability data established in accordance with CAR 21 for OPCs to alternate between the types, each OPC should revalidate the OPC for the other type(s). The OPC may be combined with the proficiency checks for revalidation or renewal of the aeroplane type rating or the instrument rating in accordance with CAR Part II. For EBT programmes, ORO.FC.231(a)(3) requires the pilot to complete a minimum of two modules of the EBT programme, separated by a period of more than 3 months, within a 12-month period. In addition, the pilot is required to be trained according to assessment and training topics distributed across a 3-year period at the defined frequency relevant to the type or variant of aircraft. When credits are defined in the operational suitability data established in accordance with CAR 21, EBT modules should alternate between types. The EBT modules may be combined for revalidation or renewal of the aeroplane type rating or the instrument rating in accordance with CAR Part II. When operating more than one type of different generations, the operator has to fulfil both generation table of assessment and training topics as per ORO.FC.232.

(B) ORO.FC.230 (c) requires one line check every year. When credits are defined in the operational suitability data established in accordance with CAR 21 for line checks to alternate between types or variants, each line check should revalidate the line check for the other type or variant. For EBT programmes, ORO.FC.231(h) requires one line evaluation of competence every year. When credits are defined in the operational suitability data established in accordance with CAR 21 for line evaluation of competence to alternate between types or variants, each line evaluation of competence should revalidate the line evaluation of competence for the other type or variant. In such case, the operator should meet the requirements to extend the validity of the line evaluation of competence to 2 years. Extension to 3 years should not be allowed.

(C) Annual emergency and safety equipment training and checking should cover all requirements for each type.

(b) Helicopters

(1) If a flight crew member operates more than one type or variant, the following provisions should be met:

(i) The recency requirements and the requirements for recurrent training and checking should be met and confirmed prior to CAT operations on any type, and the minimum number of flights on each type within a 3-month period specified in the operations manual.

(ii) ORO.FC.230 requirements with regard to recurrent training.

(iii) When credits related to the training, checking and recent experience requirements are defined in operational suitability data established in accordance with CAR 21 for the relevant types or variants, the requirements of ORO.FC.230 with regard to proficiency checks may be met by a 6 monthly check on any one type or variant operated. However, a proficiency check on each type or variant operated should be completed every 12 months.

(iv) For helicopters with a maximum certified take-off mass (MCTOM) of more than 5 700 kg, or with a maximum operational passenger seating configuration (MOPSC) of more than 19:

(A) the flight crew member should not fly more than two helicopter types, unless credits related to the training, checking and recent experience requirements are defined in operational suitability data established in accordance with CAR 21 for the relevant types or variants;

(B) a minimum of 3 months and 150 hours experience on the type or variant should be achieved before the flight crew member should commence the conversion course onto the new type or variant, unless credits related to the training, checking and recent experience requirements are defined in operational suitability data established in accordance with CAR 21 for the relevant types or variants;

(C) 28 days and/or 50 hours flying should then be achieved exclusively on the new type or variant, unless credits related to the training, checking and recent experience requirements are defined in operational suitability data established in accordance with CAR 21 for the relevant types or variants; and

(D) a flight crew member should not be rostered to fly more than one type or significantly different variant of a type during a single duty period.

(v) In the case of all other helicopters, the flight crew member should not operate more than three helicopter types or significantly different variants, unless credits related to the training, checking and recent experience requirements are defined in operational suitability data established in accordance with CAR 21 for the relevant types or variants.

(c) Combination of helicopter and aeroplane

(1) The flight crew member may fly one helicopter type or variant and one aeroplane type irrespective of their MCTOM or MOPSC.

(2) If the helicopter type is covered by paragraph (b)(1)(iv) then (b)(1)(iv)(B), (C) and (D) should also apply in this case.

AMC2 ORO.FC.240 Operation on more than one type or variant

GENERAL

(a) Terminology

The terms used in the context of the operation of more than one type or variant have the following meaning:

(1) Base aircraft means an aircraft used as a reference to compare differences with another aircraft.

(2) Variant means an aircraft or a group of aircraft within the same pilot type rating that has differences to the base aircraft requiring difference training or familiarisation training.

(3) Credit means the recognition of training, checking or recent experience based on commonalities between aircraft. For substantiation of the credits ODR tables or other appropriate documentation for comparison of the relevant aircraft characteristics may be provided.

(4) Operator difference requirements (ODRs) mean a formal description of differences between types or variants flown by a particular operator.

(b) Philosophy

The concept of operating more than one type or variant depends upon the experience, knowledge and ability of the operator and the flight crew concerned.

The first consideration is whether or not aircraft types or variants are sufficiently similar to allow the safe operation of both.

The second consideration is whether or not the types or variants are sufficiently similar for the training, checking and recent experience. Unless credits have been established by the operational suitability data in accordance with CAR 21, all training, checking and recent experience requirements should be completed independently for each type or variant.

(c) Methodology – Use of Operator Difference Requirement (ODR) Tables

(1) Before assigning flight crew members to operate more than one type or variant of aircraft, the operator should conduct a detailed evaluation of the differences or similarities of the aircraft concerned in order to establish appropriate procedures or operational restrictions. This evaluation should be based on the data established in accordance with CAR 21 for the relevant types or variants, and should be adapted to the operator's specific aircraft configurations. This evaluation should take into account of the following:

(i) the level of technology;

(ii) operational procedures; and

(iii) handling characteristics.

The methodology described below should be used as a means of evaluating aeroplane differences and similarities to justify the operation of more than one type or variant, and when credit is sought.

(2) ODR tables

Before requiring flight crew members to operate more than one type or variant, operators should first nominate one aircraft as the base aircraft from which to show differences with the second aircraft type or variant, the 'difference aircraft', in terms of technology (systems), procedures, pilot handling and aircraft management. These differences, known as operator difference requirements (ODR), preferably presented in tabular format, constitute part of the justification for operating more than one type or variant and also the basis for the associated differences/familiarisation or reduced type rating training for the flight crew.

(3) The ODR tables should be presented as follows:

GENERAL OPERATOR DIFFERENCES REQUIREMENTS TABLE										
DIFFERENCE AIRCRAFT: BASE AIRCRAFT:				COMPLIANCE METHOD						
				TRAINING					CHKG/CURR	
General	**Differences**	**Flt char**	**Proc chg**	**A**	**B**	**C**	**D**	**E**	**FLT CHK**	**REC EXP**
GENERAL	Range ETOPS Certified	No	Yes		CBT					
DIMENSIONS	Configuration per AFM, FCOM	Yes	No		CBT					

SYSTEM OPERATOR DIFFERENCES REQUIREMENTS TABLE										
DIFFERENCE AIRCRAFT: BASE AIRCRAFT:				COMPLIANCE METHOD						
				TRAINING					CHKG/CURR	
System	**Differences**	**Flt char**	**Proc chg**	**A**	**B**	**C**	**D**	**E**	**FLT CHK**	**REC EXP**
21 – AIR CONDITIONING	CONTROLS AND INDICATORS: - Panel layout	No	Yes	HO						
21 - AIR CONDITIONING	PACKS: - Switch type - Automatically controlled - Reset switch for both packs	No	Yes		CBT					

MANOEUVRE OPERATOR DIFFERENCES REQUIREMENTS TABLE										
DIFFERENCE AIRCRAFT: BASE AIRCRAFT:				COMPLIANCE METHOD						
				TRAINING					CHKG/CURR	
Manoeuvre	**Differences**	**Flt char**	**Proc chg**	**A**	**B**	**C**	**D**	**E**	**FLT CHK**	**REC EXP**
Exterior Preflight	Minor differences	No	No	HO						
Preflight	Differences due to systems, ECL	No	Yes		CBT	FTD				
Normal takeoff	FBW handling vs. Conventional; AFDS TAKEOFF: - Autothrottle engagement FMA indications	No	Yes		CBT			FFS		

(4) Compilation of ODR Tables

(i) ODR 1: General

The general characteristics of the candidate aircraft are compared with the base aircraft with regard to:

(A) general dimensions and aircraft design (number and type of rotors, wing span or category);

(B) flight deck general design;

(C) cabin layout;

(D) engines (number, type and position);

(E) limitations (flight envelope).

(ii) ODR 2: Systems

Consideration is given to differences in design between the candidate aircraft and the base aircraft. For this comparison the Air Transport Association (ATA) 100 index is used. This index establishes a system and subsystem classification and then an analysis performed for each index item with respect to the main architectural, functional and operations elements, including controls and indications on the systems control panel.

(iii) ODR 3: Manoeuvres

Operational differences encompass normal, abnormal and emergency situations and include any change in aircraft handling and flight management. It is necessary to establish a list of operational items for consideration on which an analysis of differences can be made.

The operational analysis should take the following into account:

(A) flight deck dimensions (size, cut-off angle and pilot eye height);

(B) differences in controls (design, shape, location and function);

(C) additional or altered function (flight controls) in normal or abnormal conditions;

(D) handling qualities (including inertia) in normal and in abnormal configurations;

(E) aircraft performance in specific manoeuvres;

(F) aircraft status following failure;

(G) management (e.g. ECAM, EICAS, navaid selection, automatic checklists).

(iv) Once the differences for ODR 1, ODR 2 and ODR 3 have been established, the consequences of differences evaluated in terms of flight characteristics (FLT CHAR) and change of procedures (PROC CHNG) should be entered into the appropriate columns.

(v) Difference Levels – crew training, checking and currency

(A) The final stage of an operator's proposal to operate more than one type or variant is to establish crew training, checking and currency requirements. This may be established by applying the coded difference levels from Table 4 to the compliance method column of the ODR Tables.

(B) Differences items identified in the ODR tables as impacting flight characteristics, or procedures, should be analysed in the corresponding ATA section of the ODR manoeuvres. Normal, abnormal and emergency situations should be addressed accordingly.

(d) Difference Levels

(1) Difference levels — General

Difference levels are used to identify the extent of difference between a base and a candidate aircraft with reference to the elements described in the ODR tables. These levels are proportionate to the differences between a base and a candidate aircraft. A range of five difference levels in order of increasing requirements, identified as A through E, are each specified for training, checking, and currency.

Difference levels apply when a difference with the potential to affect flight safety exists between a base and a candidate aircraft. Differences may also affect the knowledge, skills, or abilities required from a pilot. If no differences exist, or if differences exist but do not affect flight safety, or if differences exist but do not affect knowledge, skills, or abilities, then difference levels are neither assigned nor applicable to pilot qualification. When difference levels apply, each level is based on a scale of differences related to design features, systems, or manoeuvres. In assessing the effects of differences, both flight characteristics and procedures are considered since flight characteristics address handling qualities and performance, while procedures include normal, non-normal and emergency items.

Levels for training, checking, and currency are assigned independently, but are linked depending on the differences between a base and candidate aircraft. Training at level E usually identifies that the candidate aircraft is a different type to the base aircraft.

(2) Difference levels are summarised in the table below regarding training, checking, and currency.

DIFFERENCE LEVEL	TRAINING	CHECKING	CURRENCY
A	– Self-instruction	Not applicable or integrated with next proficiency check	Not applicable
B	– Aided instruction	Task or system check	Self-review
C	– System devices	Partial proficiency check using qualified device	Designated system
D	Manoeuvre Training Devices[1] or aircraft to accomplish specific manoeuvres	Partial proficiency check using qualified device[1]	Designated manoeuvre(s)[1]
E	FSTDs[2] or aircraft	Proficiency check using FSTDs[2] or aircraft	As per regulation, using FSTDs[2] or aircraft

Footnote (1):

- *Aeroplane: FTD Level 2, or FFS, or aeroplane*
- *Helicopter: FTD Level 2 and 3, or FFS, or helicopter*

Footnote (2):

- *Aeroplane: FFS Level C or D, or aeroplane*
- *Helicopter: FSTD'S having dual qualification: FFS Level B and FTD Level 3, or FFS Level C or D, or helicopter*

Training Levels A and B require familiarisation training, levels C and D require differences training. Training Level E means that differences are such that type rating training is required.

(3) Difference level — Training

The training differences levels specified represent the minimum requirements. Devices associated with a higher difference level may be used to satisfy a training differences requirement.

(i) Level A training

Level A differences training is applicable to aircraft with differences that can adequately be addressed through self-instruction. Level A training represents a knowledge requirement such that once appropriate information is provided, understanding and compliance can be assumed to be demonstrated.

Training needs not covered by level A training may require level B training, or higher, depending on the outcome of the evaluations described in the aircraft evaluation process (CS FCD.420).

(ii) Level B training

Level B differences training is applicable to aircraft with system or procedure differences that can adequately be addressed through aided instruction.

At level B aided instruction it is appropriate to ensure pilot understanding, emphasise issues, provide a standardised method of presentation of material, or to aid retention of material following training.

(iii) Level C training

Level C differences training can only be accomplished through the use of devices capable of systems training.

Level C differences training is applicable to variants having 'part task' differences that affect skills or abilities as well as knowledge. Training objectives focus on mastering individual systems, procedures, or tasks, as opposed to performing highly integrated flight operations and manoeuvres in 'real time'. Level C may also require self-instruction or aided instruction of a pilot, but cannot be adequately addressed by a knowledge requirement alone. Training devices are required to supplement instruction to ensure attainment or retention of pilot skills and abilities to accomplish the more complex tasks, usually related to operation of particular aircraft systems.

The minimum acceptable training media for level C is interactive computer-based training, cockpit systems simulators, cockpit procedure trainers, part task trainers [such as Inertial Navigation System (INS), Flight Management System (FMS), or Traffic Collision Avoidance System (TCAS) trainers], or similar devices.

(iv) Level D training

Level D differences training can only be accomplished with devices capable of performing flight manoeuvres and addressing full task differences affecting knowledge, skills, or abilities.

Devices capable of flight manoeuvres address full task performance in a dynamic 'real time' environment and enable integration of knowledge, skills and abilities in a simulated flight environment, involving combinations of operationally oriented tasks and realistic task loading for each relevant phase of flight. At level D, knowledge and skills to complete necessary normal, non-normal and emergency procedures are fully addressed for each variant.

Level D differences training requires mastery of interrelated skills that cannot be adequately addressed by separate acquisition of a series of knowledge areas or skills that are interrelated. However, the differences are not so significant, that a full type rating training course is required. If demonstration of interrelationships between the systems was important, the use of a series of separate devices for systems training would not suffice. Training for level D differences requires a training device that has accurate, high fidelity integration of systems and controls and realistic instrument indications. Level D training may also require manoeuvre visual cues, motion cues, dynamics, control loading or specific environmental conditions. Weather phenomena such as low visibility operations or wind shear may or may not be incorporated. Where simplified or generic characteristics of an aircraft type are used in devices to satisfy level D difference training, significant negative training cannot occur as a result of the simplification.

Appropriate devices as described in CS FCD.420(a), satisfying level D differences training range from those where relevant elements of aircraft flight manoeuvring, performance, and handling qualities are incorporated. The use of a Manoeuvre Training Device or aircraft is limited for the conduct of specific manoeuvres or handling differences, or for specific equipment or procedures.

(v) Level E training

Level E differences training is applicable to candidate aircraft having such a significant 'full task' differences that a full type rating training course or a type rating training

course with credit for previous experience on similar aircraft types is required to meet the training objectives.

The training requires a 'high fidelity' environment to attain or maintain knowledge, skills, or abilities that can only be satisfied by the use of FSTDs or the aircraft itself as mentioned in CS FCD.415(a). Level E training, if done in an aircraft, should be modified for safety reasons where manoeuvres can result in a high degree of risk.

When level E differences training is assigned, suitable credit or constraints may be applied for knowledge, skills or abilities related to other pertinent aircraft types and specifies the relevant subjects, procedures or manoeuvres.

(4) Difference level — Checking

Differences checking addresses any pertinent pilot testing or checking. Initial and recurrent checking levels are the same unless otherwise specified.

It may be possible to satisfactorily accomplish recurrent checking objectives in devices not meeting initial checking requirements. In such instances the applicant may propose for revalidation checks the use of certain devices not meeting the initial check requirements.

(i) Level A checking

Level A differences checking indicates that no check related to differences is required at the time of differences training. However, a pilot is responsible for knowledge of each variant flown.

(ii) Level B checking

Level B differences checking indicates that a 'task' or 'systems' check is required following initial and recurring training.

(iii) Level C checking

Level C differences checking requires a partial check using a suitable qualified device. A partial check is conducted relative to particular manoeuvres or systems.

(iv) Level D checking

Level D differences checking indicates that a partial proficiency check is required following both initial and recurrent training. In conducting the partial proficiency check, manoeuvres common to each variant may be credited and need not be repeated. The partial proficiency check covers the specified particular manoeuvres, systems, or devices. Level D checking is performed using scenarios representing a 'real time' flight environment and uses qualified devices permitted for level D training or higher.

(v) Level E checking

Level E differences checking requires that a full proficiency check be conducted in FSTDs or in an aircraft as mentioned in CS FCD.415(a), following both initial and recurrent training. If appropriate, alternating Level E checking between relevant aircraft is possible and credit may be defined for procedures or manoeuvres based on commonality.

Assignment of level E checking requirements alone, or in conjunction with level E currency, does not necessarily result in assignment of a separate type rating.

(5) Difference level — Currency

Differences currency addresses any currency and re-currency levels. Initial and recurrent

currency levels are the same unless otherwise specified.

(i) Level A currency

Level A currency is common to each aircraft and does not require separate tracking. Maintenance of currency in any aircraft suffices for any other variant within the same type rating.

(ii) Level B currency

Level B currency is 'knowledge-related' currency, typically achieved through self-review by individual pilots.

(iii) Level C currency

(A) Level C currency is applicable to one or more designated systems or procedures, and relates to both skill and knowledge requirements. When level C currency applies, any pertinent lower level currency is also to be addressed.

(B) Re-establishing level C currency

When currency is lost, it may be re-established by completing required items using a device equal to or higher than that specified for level C training and checking.

(iv) Level D currency

(A) Level D currency is related to designated manoeuvres and addresses knowledge and skills required for performing aircraft control tasks in real time with integrated use of associated systems and procedures. Level D currency may also address certain differences in flight characteristics including performance of any required manoeuvres and related normal, non-normal and emergency procedures. When level D is necessary, any pertinent lower level currency is also to be addressed.

(B) Re-establishing level D currency

When currency is lost, currency may be re-established by completing pertinent manoeuvres using a device equal to or higher than that specified for level D differences training and checking.

(v) Level E currency

(A) Level E currency requires that recent experience requirements of CAR-FCL and operational requirements be complied with in each aircraft separately. Level E currency may also specify other system, procedure, or manoeuvre currency item(s) necessary for safe operations, and requires procedures or manoeuvres to be accomplished in FSTDs or in an aircraft as mentioned in CS FCD.415(a). Provisions are applied in a way which addresses the required system or manoeuvre experience.

When level E is assigned between aircraft of common characteristics, credit may be permitted. Assignment of level E currency requirements does not automatically lead to a determination on same or separate type rating. Level E currency is tracked by a means that is acceptable to the competent authority.

When CTLC is permitted, any credit or constraints applicable to using FSTDs, as mentioned in CS FCD.415(a), are also to be determined.

(B) Re-establishing level E currency

When currency is lost, currency may be re-established by completing pertinent manoeuvres using a device specified for level E differences training and checking.

(6) Competency regarding non-normal and emergency procedures — Currency

Competency for non-normal and emergency manoeuvres or procedures is generally addressed by checking requirements. Particular non-normal and emergency manoeuvres or procedures may not be considered mandatory for checking or training. In this situation it may be necessary to periodically practice or demonstrate those manoeuvres or procedures specifying currency requirements for those manoeuvres or procedures.

ORO.FC.A.245 Alternative training and qualification programme

(a) The aeroplane operator having appropriate experience may substitute one or more of the following training and checking requirements for flight crew by an alternative training and qualification programme (ATQP), approved by the competent authority:

(1) SPA.LVO.120 on flight crew training and qualifications;

(2) conversion training and checking;

(3) differences training and familiarisation training;

(4) command course;

(5) recurrent training and checking; and

(6) operation on more than one type or variant.

(b) The ATQP shall contain training and checking that establishes and maintains at least an equivalent level of proficiency achieved by complying with the provisions of ORO.FC.220 and ORO.FC.230. The level of flight crew training and qualification proficiency shall be demonstrated prior to being granted the ATQP approval by the competent authority.

(c) The operator applying for an ATQP approval shall provide the competent authority with an implementation plan, including a description of the level of flight crew training and qualification proficiency to be achieved.

(d) In addition to the checks required by ORO.FC.230 and FCL.060 of CAR-FCL, each flight crew member shall complete a line oriented evaluation (LOE) conducted in an FSTD. The validity period of an LOE shall be 12 calendar months. The validity period shall be counted from the end of the month when the check was taken. When the LOE is undertaken within the last three months of the validity period, the new validity period shall be counted from the original expiry date.

(e) After two years of operating with an approved ATQP, the operator may, with the approval of the competent authority, extend the validity periods of the checks in ORO.FC.230 as follows:

(1) Operator proficiency check to 12 calendar months. The validity period shall be counted from the end of the month when the check was taken. When the check is undertaken within the last three months of the validity period, the new validity period shall be counted from the original expiry date.

(2) Line check to 24 calendar months. The validity period shall be counted from the end of the month when the check was taken. When the check is undertaken within the last six months of the validity period, the new validity period shall be counted from the original

expiry date.

(3) Emergency and safety equipment checking to 24 calendar months. The validity period shall be counted from the end of the month when the check was taken. When the check is undertaken within the last six months of the validity period, the new validity period shall be counted from the original expiry date.

AMC1 ORO.FC.A.245 Alternative training and qualification programme

COMPONENTS AND IMPLEMENTATION

(a) Alternative training and qualification programme (ATQP) components

The ATQP should comprise the following:

(1) Documentation that details the scope and requirements of the programme, including the following:

(i) The programme should demonstrate that the operator is able to improve the training and qualification standards of flight crew to a level that exceeds the standards prescribed in ORO.FC and Subpart E of Part-SPA (SPA.LVO).

(ii) The operator's training needs and established operational and training objectives.

(iii) A description of the process for designing and gaining approval for the operator's flight crew qualification programmes. This should include quantified operational and training objectives identified by the operator's internal monitoring programmes. External sources may also be used.

(iv) A description of how the programme will:

(A) enhance safety;

(B) improve training and qualification standards of flight crew;

(C) establish attainable training objectives;

(D) integrate CRM in all aspects of training;

(E) develop a support and feedback process to form a self-correcting training system;

(F) institute a system of progressive evaluations of all training to enable consistent and uniform monitoring of the training undertaken by flight crew;

(G) enable the operator to be able to respond to new aeroplane technologies and changes in the operational environment;

(H) foster the use of innovative training methods and technology for flight crew instruction and the evaluation of training systems; and

(I) make efficient use of training resources, specifically to match the use of training media to the training needs.

(2) A task analysis to determine:

(i) knowledge;

(ii) required skills;

(iii) associated skill-based training; and

(iv) validated behavioural markers, where appropriate.

For each aeroplane type/class to be included within the ATQP the operator should establish a systematic review that determines and defines the various tasks to be undertaken by the flight crew when operating that type/class. Data from other types/classes may also be used. The analysis should determine and describe the knowledge and skills required to complete the various tasks specific to the aeroplane type/class and/or type of operation. In addition, the analysis should identify the appropriate behavioural markers that should be exhibited. The task analysis should be suitably validated in accordance with (b)(3). The task analysis, in conjunction with the data gathering programme(s), permits the operator to establish a programme of targeted training together with the associated training objectives.

(3) Curricula. The curriculum structure and content should be determined by task analysis, and should include proficiency objectives, including when and how these objectives should be met.

(i) The training programme should have the following structure:

(A) Curriculum, specifying the following elements:

(a) Entry requirements: a list of topics and content, describing what training level will be required before start or continuation of training.

(b) Topics: a description of what will be trained during the lesson.

(c) Targets/Objectives

(1) Specific target or set of targets that have to be reached and fulfilled before the training course can be continued.

(2) Each specified target should have an associated objective that is identifiable both by the flight crew and the trainers.

(3) Each qualification event that is required by the programme should specify the training that is required to be undertaken and the required standard to be achieved.

(B) Daily lesson plan

(a) Each lesson/course/training or qualification event should have the same basic structure. The topics related to the lesson should be listed and the lesson targets should be unambiguous.

(b) Each lesson/course or training event whether classroom, CBT or simulator should specify the required topics with the relevant targets to be achieved.

(4) A specific training programme for:

(i) each aeroplane type/class within the ATQP;

(ii) instructors (class rating instructor rating/synthetic flight instructor authorisation/type rating instructor rating — CRI/SFI/TRI), and other personnel undertaking flight crew instruction; and

(iii) examiners (class rating examiner/synthetic flight examiner/type rating examiner — CRE/SFE/TRE).

This should include a method for the standardisation of instructors and examiners.

Personnel who perform training and checking of flight crew in an operator's ATQP should receive the following additional training on:

(A) ATQP principles and goals;

(B) knowledge/skills/behaviour as learnt from task analysis;

(C) line-oriented evaluation (LOE)/ LOFT scenarios to include triggers/ markers/ event sets/observable behaviour;

(D) qualification standards;

(E) harmonisation of assessment standards;

(F) behavioural markers and the systemic assessment of CRM;

(G) event sets and the corresponding desired knowledge/skills and behaviour of the flight crew;

(H) the processes that the operator has implemented to validate the training and qualification standards and the instructors part in the ATQP quality control; and

(I) line-oriented quality evaluation (LOQE).

(5) A feedback loop for the purpose of curriculum validation and refinement, and to ascertain that the programme meets its proficiency objectives.

(i) The feedback should be used as a tool to validate that the curricula are implemented as specified by the ATQP; this enables substantiation of the curriculum, and that proficiency and training objectives have been met. The feedback loop should include data from operations flight data monitoring, the advanced flight data monitoring (FDM) programme and LOE/LOQE programmes. In addition, the evaluation process should describe whether the overall targets/objectives of training are being achieved and should prescribe any corrective action that needs to be undertaken.

(ii) The programme's established quality control mechanisms should at least review the following:

(A) procedures for approval of recurrent training;

(B) ATQP instructor training approvals;

(C) approval of event set(s) for LOE/LOFT;

(D) procedures for conducting LOE and LOQE.

(6) A method for the assessment of flight crew during conversion and recurrent training and checking.

The assessment process should include event-based assessment as part of the LOE. The assessment method should comply with ORO.FC.230.

(i) The qualification and checking programmes should include at least the following elements:

(A) a specified structure;

(B) elements to be tested/examined;

(C) targets and/or standards to be attained;

(D) the specified technical and procedural knowledge and skills, and behavioural markers to be exhibited.

(ii) An LOE event should comprise tasks and sub-tasks performed by the crew under a

specified set of conditions. Each event has one or more specific training targets/objectives, which require the performance of a specific manoeuvre, the application of procedures, or the opportunity to practise cognitive, communication or other complex skills. For each event the proficiency that is required to be achieved should be established. Each event should include a range of circumstances under which the crews' performance is to be measured and evaluated. The conditions pertaining to each event should also be established and they may include the prevailing meteorological conditions (ceiling, visibility, wind, turbulence, etc.), the operational environment (navigation aid inoperable, etc.), and the operational contingencies (non-normal operation, etc.).

(iii) The markers specified under the operator's ATQP should form one of the core elements in determining the required qualification standard. A typical set of markers is shown in the table below:

EVENT	MARKER
Awareness of aeroplane systems:	1. Monitors and reports changes in automation status
	2. Applies closed loop principle in all relevant situations
	3. Uses all channels for updates
	4. Is aware of remaining technical resources

(iv) The topics/targets integrated into the curriculum should be measurable and progression on any training/course is only allowed if the targets are fulfilled.

(7) A data monitoring/analysis programme consisting of the following:

(i) A flight data monitoring (FDM) programme, as described in AMC1 ORO.AOC.130. Data collection should reach a minimum of 60 % of all relevant flights conducted by the operator before ATQP approval is granted. This proportion may be increased as determined by the competent authority.

(ii) An advanced FDM when an extension to the ATQP is requested: an advanced FDM programme is determined by the level of integration with other safety initiatives implemented by the operator, such as the operator's safety management system. The programme should include both systematic evaluations of data from an FDM programme and flight crew training events for the relevant crews. Data collection should reach a minimum of 80 % of all relevant flights and training conducted by the operator. This proportion may be varied as determined by the competent authority.

The purpose of an FDM or advanced FDM programme for ATQP is to enable the operator to:

(A) provide data to support the programme's implementation and justify any changes to the ATQP;

(B) establish operational and training objectives based upon an analysis of the operational environment; and

(C) monitor the effectiveness of flight crew training and qualification.

(iii) Data gathering: the data analysis should be made available to the person responsible for ATQP within the organisation. The data gathered should:

(A) include all fleets that are planned to be operated under the ATQP;

(B) include all crews trained and qualified under the ATQP;

(C) be established during the implementation phase of ATQP; and

(D) continue throughout the life of the ATQP.

(iv) Data handling: the operator should establish a procedure to ensure the confidentiality of individual flight crew members, as described by AMC1 ORO.AOC.130.

(v) The operator that has a flight data monitoring programme prior to the proposed introduction of ATQP may use relevant data from other fleets not part of the proposed ATQP.

(b) Implementation. The operator should develop an evaluation and implementation process, including the following stages:

(1) A safety case that demonstrates equivalency of:

(i) the revised training and qualification standards compared to the standards of ORO.FC and/ or Subpart E of Part-SPA (SPA.LVO) prior to the introduction of ATQP; and

(ii) any new training methods implemented as part of ATQP.

The safety case should encompass each phase of implementation of the programme and be applicable over the lifetime of the programme that is to be overseen. The safety case should:

– demonstrate the required level of safety;

– ensure the required safety is maintained throughout the lifetime of the programme; and

– minimise risk during all phases of the programme's implementation and operation.

The elements of a safety case include:

– planning: integrated and planned with the operation (ATQP) that is to be justified;

– criteria;

– safety-related documentation, including a safety checklist;

– programme of implementation to include controls and validity checks; and

– oversight, including review and audits.

Criteria for the establishment of a safety case. The safety case should:

– be able to demonstrate that the required or equivalent level of safety is maintained throughout all phases of the programme;

– be valid to the application and the proposed operation;

– be adequately safe and ensure the required regulatory safety standards or approved equivalent safety standards are achieved;

– be applicable over the entire lifetime of the programme;

– demonstrate completeness and credibility of the programme;

– be fully documented;

– ensure integrity of the operation and the maintenance of the operations and

training infrastructure;

- ensure robustness to system change;
- address the impact of technological advance, obsolescence and change; and
- address the impact of regulatory change.

(2) A task analysis, as required by (a)(2), to establish the operator's programme of targeted training and the associated training objectives.

(3) A period of operation whilst data is collected and analysed to validate the safety case and task analysis. During this period the operator should continue to operate in accordance with ORO.FC and/or Subpart E of Part-SPA (SPA.LVO), as applicable. The length of this period should be determined by the competent authority.

GM1 ORO.FC.A.245 Alternative training and qualification programme

TERMINOLOGY

(a) 'Line-oriented evaluation (LOE)' is an evaluation methodology used in the ATQP to evaluate trainee performance, and to validate trainee proficiency. LOEs consist of flight simulator scenarios that are developed by the operator in accordance with a methodology approved as part of the ATQP. The LOE should be realistic and include appropriate weather scenarios and, in addition, should fall within an acceptable range of difficulty. The LOE should include the use of validated event sets to provide the basis for event- based assessment.

(b) 'Line-oriented quality evaluation (LOQE)' is one of the tools used to help evaluate the overall performance of an operation. LOQEs consist of line flights that are observed by appropriately qualified operator personnel to provide feedback to validate the ATQP. The LOQE should be designed to look at those elements of the operation that are unable to be monitored by FDM or Advanced FDM programmes.

(c) 'Skill-based training' requires the identification of specific knowledge and skills. The required knowledge and skills are identified within an ATQP as part of a task analysis and are used to provide targeted training.

(d) 'Event-based assessment' is the assessment of flight crew to provide assurance that the required knowledge and skills have been acquired. This is achieved within an LOE. Feedback to the flight crew is an integral part of event-based assessment.

(e) Safety case means a documented body of evidence that provides a demonstrable and valid justification that the ATQP is adequately safe for the given type of operation.

GM2 ORO.FC.A.245 Alternative training and qualification programme

EVIDENCE-BASED RECURRENT TRAINING AND CHECKING OF FLIGHT CREW CONDUCTED IN FLIGHT SIMULATION TRAINING DEVICES (FSTDs)

It is possible to implement EBT in accordance with ICAO Doc 9995 in the framework of an approved alternative training and qualification programme (ATQP). GM1 ORO.FC.230(a);(b);(f) may be used to guide the operator towards EBT according to ORO.FC.A.245 of this Regualtion.

An operator holding approval for ATQP and wishing to implement EBT may use the guidance material in GM1 ORO.FC.230(a);(b);(f) for the conduct of the Licence Proficiency Check, or where the Licence Proficiency Check and Operator Proficiency Check are combined. For this purpose, the evaluation phase is equivalent to the line-oriented evaluation (LOE) described in ORO.FC.A.245(d).

AMC1 ORO.FC.A.245(a) Alternative training and qualification programme

OPERATOR EXPERIENCE

The appropriate experience should be at least 2 years' continuous operation.

AMC1 ORO.FC.A.245(d)(e)(2) Alternative training and qualification programme

COMBINATION OF CHECKS

(a) The line-orientated evaluation (LOE) may be undertaken with other ATQP training.

(b) The line check may be combined with a line-oriented quality evaluation (LOQE).

ORO.FC.A.250 Commanders holding a CPL(A)

(a) The holder of a CPL(A) (aeroplane) shall only act as commander in commercial air transport on a single-pilot aeroplane if either of the following conditions is met:

(1) when carrying passengers under VFR outside a radius of 50 NM (90 km) from an aerodrome of departure, he/she has a minimum of 500 hours of flight time on aeroplanes or holds a valid instrument rating; or

(2) when operating on a multi-engine type under IFR, he/she has a minimum of 700 hours of flight time on aeroplanes, including 400 hours as pilot-in-command. These hours shall include 100 hours under IFR and 40 hours in multi-engine operations. The 400 hours as pilot-in-command may be substituted by hours operating as co-pilot within an established multi-pilot crew system prescribed in the operations manual, on the basis of two hours of flight time as co-pilot for one hour of flight time as pilot-in command;

(3) when operating on a single-engined aeroplane under IFR, he/she has a minimum of 700 hours of flight time on aeroplanes, including 400 hours as pilot-in-command. Those hours shall include 100 hours under IFR. The 400 hours as pilot-in-command may be substituted by hours operating as co-pilot within an established multi-pilot crew system prescribed in the operations manual, on the basis of two hours of flight time as co-pilot for one hour of flight time as pilot-in command.

(b) For operations under VFR by day of performance class B aeroplanes (a)(1) shall not apply.

ORO.FC.H.250 Commanders holding a CPL(H)

(a) The holder of a CPL(H) (helicopter) shall only act as commander in commercial air transport on a single- pilot helicopter if:

(1) when operating under IFR, he/she has a minimum of 700 hours total flight time on helicopters, including 300 hours as pilot-in-command. These hours shall include 100 hours under IFR. The 300 hours as pilot-in-command may be substituted by hours operating as co-pilot within an established multi-pilot crew system prescribed in the operations manual on the basis of two hours of flight time as co-pilot for one hour flight time as pilot-in command;

(2) when operating under visual meteorological conditions (VMC) at night, he/she has:

(i) a valid instrument rating; or

(ii) 300 hours of flight time on helicopters, including 100 hours as pilot-in-command and 10 hours as pilot flying at night.

Section 3 — Additional requirements for commercial specialised operations and CAT operations referred to in ORO.FC.005 b(1) and (2)

ORO.FC.330 Recurrent training and checking — operator proficiency check

(a) Each flight crew member shall complete operator proficiency checks to demonstrate his/her competence in carrying out normal, abnormal and emergency procedures, covering the relevant aspects associated with the specialised tasks described in the operations manual.

(b) Appropriate consideration shall be given when operations are undertaken under IFR or at night.

(c) The validity period of the operator proficiency check shall be 12 calendar months. The validity period shall be counted from the end of the month when the check was taken. When the operator proficiency check is undertaken within the last three months of the validity period, the new validity period shall be counted from the original expiry date.

SUBPART CC — CABIN CREW

ORO.CC.005 Scope

This Subpart establishes the requirements to be met by the operator when operating an aircraft with cabin crew and comprises:

(a) Section 1 specifying common requirements applicable to all operations, and

(b) Section 2 specifying additional requirements only applicable to commercial air transport operations.

Section 1 — Common requirements

ORO.CC.100 Number and composition of cabin crew

(a) For the operation of aircraft with an MOPSC of more than 19, at least one cabin crew member shall be assigned when carrying one or more passenger(s).

(b) For the purpose of complying with point (a), the minimum number of cabin crew members shall be the greatest number amongst the following:

(1) the number of cabin crew members established during the aircraft certification process in accordance with the applicable certification specifications, for the aircraft cabin configuration used by the operator;

(2) if the number under point (1) has not been established, the number of cabin crew members established during the aircraft certification process for the maximum certified passenger seating configuration reduced by 1 for every whole multiple of 50 passenger seats of the aircraft cabin configuration used by the operator falling below the maximum certified seating capacity;

(3) one cabin crew member for every 50, or fraction of 50, passenger seats installed on the same deck of the aircraft to be operated.

(c) For operations with more than one cabin crew member, the operator shall nominate one cabin crew member accountable to the pilot-in-command or the commander.

(d) By way of derogation from point (a), non-commercial operations with aircraft with an MOPSC of more than 19 may be performed without an operating cabin crew member, subject to the prior approval by the competent authority. To obtain the approval, the operator shall ensure that all of the following conditions are fulfilled:

(1) there are maximum 19 passengers on board;

(2) the operator has developed procedures for that operation.

AMC1 ORO.CC.100 Number and composition of cabin crew

DETERMINATION OF THE NUMBER AND COMPOSITION OF CABIN CREW

(a) When determining the minimum number of cabin crew required to operate aircraft engaged in CAT operations, factors to be taken into account should include:

(1) the number of doors/exits;

(2) the type(s) of doors/exits and the associated assisting evacuation means;

(3) the location of doors/exits in relation to cabin crew stations and the cabin layout;

(4) the location of cabin crew stations taking into account direct view requirements and cabin crew duties in an emergency evacuation including:

(i) opening floor level doors/exits and initiating stair or slide deployment;

(ii) assisting passengers to pass through doors/exits; and

(iii) directing passengers away from inoperative doors/exits, crowd control and passenger flow management;

(5) actions required to be performed by cabin crew in ditching, including the deployment of slide- rafts and the launching of life-rafts;

(6) additional actions required to be performed by cabin crew members when responsible for a pair of doors/exits; and

(7) the type and duration of the flight to be operated.

(b) When scheduling cabin crew for a flight, the operator should establish procedures that take account of the experience of each cabin crew member. The procedures should specify that the required cabin crew includes some cabin crew members who have at least 3 months experience as an operating cabin crew member.

GM1 ORO.CC.100 Number and composition of cabin crew

MINIMUM NUMBER OF CABIN CREW

(a) When determining the minimum required cabin crew for its specific aircraft cabin configuration, the operator should:

(1) request information regarding the minimum number of cabin crew established by the aircraft type certificate (TC) holder or other design organisation responsible for showing compliance with the evacuation requirements of the applicable Certification Specifications; and

(2) take into account the factors specified in AMC1 ORO.CC.100, as applicable.

(b) The number of cabin crew referred to in ORO.CC.100 (b)(1) means either:

(1) the number of cabin crew who actively participated in the aircraft cabin during the relevant emergency evacuation demonstration, or who were assumed to have taken part in the relevant analysis, carried out by the aircraft TC holder when demonstrating the maximum passenger seating capacity (MPSC) of the aircraft type at the time of initial type certification; or

(2) a lower number of cabin crew who actively participated in a subsequent emergency evacuation demonstration, or who were assumed to have taken part in the relevant analysis, and for which approval has been obtained for a cabin configuration other than the MPSC, either by the TC holder or by another design organisation. The operator should obtain a clear indication of that number which is specified in the related documentation.

AMC1 ORO.CC.100(d)(2) Number and composition of cabin crew

PROCEDURES FOR NON-COMMERCIAL OPERATIONS WITH NO OPERATING CABIN CREW ON BOARD AN AIRCRAFT WITH AN MOPSC OF MORE THAN 19 AND MAXIMUM 19 PASSENGERS

The operator should asses the risk of operating a flight with no cabin crew member and ensure that the following procedures mitigate the risks and provide appropriate level of protection of the aircraft occupants:

(a) Flight crew members assigned to these flights should receive training on operations where no cabin crew is required in accordance with ORO.FC.220 and ORO.FC.230.

(b) The operator should consider the categories of passengers to be carried on such flights, who may be knowledgeable or not about the aircraft type and procedures in normal, abnormal and emergency situations.

(c) The procedures should cover at least the following elements, if applicable:

(1) communication and coordination between flight crew members and passengers;

(2) flight crew member incapacitation;

(3) cabin surveillance;

(4) rapid egress from the aircraft in case of rapid disembarkation or evacuation;

(5) operation and use of emergency exits and assisting evacuation means;

(6) location and use of oxygen;

(7) location and use of life jackets;

(8) passenger seating in order to maintain:

(9) an easy access to emergency exits;

(10) timely communication with flight crew member(s); and

(11) the required mass and balance of the aircraft;

(12) passenger briefing in accordance with Part-CAT, including information on the location and use of equipment not displayed in the operator's safety briefing material, such as a fire extinguisher, first aid equipment (e.g. first aid kit, defibrillator), smoke hood, etc.; and

(13) any additional safety instructions that are deemed necessary to ensure passenger protection.

GM1 ORO.CC.100(d)(2) Number and composition of cabin crew

CATEGORIES OF PASSENGERS

(a) The operator should adapt the procedures for non-commercial operations with an aircraft with an MOPSC of more than 19 and maximum 19 passengers and no operating cabin crew on board to the categories of passengers to be carried on such flight. This includes but is not limited to the following groups:

(1) Passengers who are already familiar with the aircraft environment, the procedures in normal operations, abnormal and emergency situations or trained on the aircraft type, e.g. non-operating aircrew members, maintenance personnel, etc.

(2) Passengers who are not familiar with the aircraft environment or procedures in normal operations, abnormal and emergency situations, e.g. operator's guests, employees, etc.

(3) Passengers who travel frequently on such flights. The operator may consider providing these passengers with training covering all safety and emergency procedures for the given aircraft type as described in AMC1.1 CAT.OP.MPA.170. The operator should be able to show evidence of their training. These passengers may also be provided with an extended briefing to facilitate communication with flight crew and coordination of all passengers in case of an abnormal or emergency situation.

(4) Special categories of passengers (see CAT.OP.MPA.155).

(b) The operator may include in its procedures a ratio of the categories of passengers described in (a) above that can travel on the same flight.

ORO.CC.110 Conditions for assignment to duties

(a) Cabin crew members shall only be assigned to duties on an aircraft if they:

(1) are at least 18 years of age;

(2) have been assessed, in accordance with the applicable requirements of CAR-MED, as physically and mentally fit to perform their duties and discharge their responsibilities safely; and

(3) have successfully completed all applicable training and checking required by this Subpart and are competent to perform the assigned duties in accordance with the procedures specified in the operations manual.

(b) Before assigning to duties cabin crew members who are working on a freelance or part-time basis, the operator shall verify that all applicable requirements of this Subpart are complied with, taking into account all services rendered by the cabin crew member to any other operator(s), to determine in particular:

(1) the total number of aircraft types and variants operated; and

(2) the applicable flight and duty time limitations and rest requirements.

(c) Operating cabin crew members, as well as their role with regard to the safety of passengers and flight, shall be clearly identified to the passengers.

ORO.CC.115 Conduct of training courses and associated checking

(a) A detailed programme and syllabus shall be established by the operator for each training course in accordance with the applicable requirements of this Subpart, and of CAR-CC where applicable, to cover the duties and responsibilities to be discharged by the cabin crew members.

(b) Each training course shall include theoretical and practical instruction together with individual or collective practice, as relevant to each training subject, in order that the cabin crew member achieves and maintains the adequate level of proficiency in accordance with this Subpart.

(c) Each training course shall be:

(1) conducted in a structured and realistic manner; and

(2) performed by personnel appropriately qualified for the subject to be covered.

(d) During or following completion of all training required by this Subpart, each cabin crew member shall undergo a check covering all training elements of the relevant training programme, except for crew resource management (CRM) training. Checks shall be performed by personnel appropriately qualified to verify that the cabin crew member has achieved and/or maintains the required level of proficiency.

(e) CRM training courses and CRM modules where applicable shall be conducted by a cabin crew CRM trainer. When CRM elements are integrated in other training, a cabin crew CRM trainer shall manage the definition and implementation of the syllabus.

GM1 ORO.CC.115 Conduct of training courses and associated checking

EQUIPMENT AND PROCEDURES

The following definitions apply for the purpose of training programmes, syllabi and the conduct of training and checking on equipment and procedures:

(a) 'Safety equipment' means equipment installed/carried to be used during day-to-day normal operations for the safe conduct of the flight and protection of occupants (e.g. seat belts, child restraint devices, safety card, safety demonstration kit).

(b) 'Emergency equipment' means equipment installed/carried to be used in case of abnormal

and emergency situations that demand immediate action for the safe conduct of the flight and protection of occupants, including life preservation (e.g. drop-out oxygen, crash axe, fire extinguisher, protective breathing equipment, manual release tool, slide-raft).

(c) 'Normal procedures' means all procedures established by the operator in the operations manual for day-to-day normal operations (e.g. pre-flight briefing of cabin crew, pre-flight checks, passenger briefing, securing of galleys and cabin, cabin surveillance during flight).

(d) 'Emergency procedures' means all procedures established by the operator in the operations manual for abnormal and emergency situations. For this purpose, 'abnormal' refers to a situation that is not typical or usual, deviates from normal operation and may result in an emergency.

AMC1 ORO.CC.115(c) Conduct of training courses and associated checking

TRAINING METHODS AND TRAINING DEVICES

(a) The operator should establish training methods that take into account the following:

(1) training should include the use of cabin training devices, audio-visual presentations, computer-based training and other types of training, as most appropriate to the training element; and

(2) a reasonable balance between the different training methods should be ensured so that the cabin crew member achieves the level of proficiency necessary for a safe performance of all related cabin crew duties and responsibilities.

(b) When assessing the representative training devices to be used, the operator should:

(1) take into account that a representative training device may be used to train cabin crew as an alternative to the use of the actual aircraft or required equipment;

(2) ensure that those items relevant to the training and checking intended to be given accurately represent the aircraft or equipment in the following particulars:

(i) layout of the cabin in relation to doors/exits, galley areas and safety and emergency equipment stowage as relevant;

(ii) type and location of passenger seats and cabin crew stations;

(iii) doors/exits in all modes of operation, particularly in relation to the method of operation, mass and balance and operating forces, including failure of power-assist systems where fitted; and

(iv) safety and emergency equipment of the type provided in the aircraft (such equipment may be 'training use only' items and, for oxygen and protective breathing equipment, units charged with or without oxygen may be used); and

(3) assess the following factors when determining whether a door/exit can be considered to be a variant of another type:

(i) door/exit arming/disarming;

(ii) direction of movement of the operating handle;

(iii) direction of door/exit opening;

(iv) power-assist mechanisms; and

(v) assisting evacuation means such as slides and ropes.

AMC1 ORO.CC.115(d) Conduct of training courses and associated checking

CHECKING

(a) Checking required for each training course should be accomplished by the method appropriate to the training element to be checked. These methods include:

(1) practical demonstration;

(2) computer-based assessment;

(3) in-flight checks;

(4) oral or written tests.

(b) Training elements that require individual practical participation may be combined with practical checks.

AMC2 ORO.CC.115(d).G Conduct of training courses and associated checking

CHECKING PERSONNEL

Except for first-aid, the checking personnel must be accepted by the competent authority.

AMC1 ORO.CC.115(e) Conduct of training courses and associated checking

CREW RESOURCE MANAGEMENT (CRM) TRAINING – MULTI CABIN CREW OPERATIONS

(a) General

(1) Training environment

CRM training should be conducted in the non-operational environment (classroom and computer-based) and in the operational environment (cabin training device and aircraft). Tools such as group discussions, team task analysis, team task simulation and feedback should be used.

(2) Classroom training

Whenever possible, classroom training should be conducted in a group session away from the pressures of the usual working environment, so that the opportunity is provided for cabin crew members to interact and communicate in an environment conducive to learning.

(3) Computer-based training

Computer-based training should not be conducted as a stand-alone training method, but may be conducted as a complementary training method.

(4) Cabin training devices and aircraft

Whenever practicable, relevant parts of CRM training should be conducted in representative cabin training devices that reproduce a realistic operational environment, or in the aircraft. During practical training, interaction should be encouraged.

(5) Integration into cabin crew training

CRM principles should be integrated into relevant parts of cabin crew training and operations, including checklists, briefings and emergency procedures.

(6) Combined CRM training for flight crew and cabin crew

(i) Operators should provide combined training for flight crew and cabin crew during recurrent CRM training.

(ii) The combined training should address at least:

(A) effective communication, coordination of tasks and functions of flight crew and cabin crew; and

(B) mixed multinational and cross-cultural flight crew and cabin crew, and their interaction, if applicable.

(iii) Combined CRM training should be conducted by flight crew CRM trainer or cabin crew CRM trainer.

(iv) There should be an effective liaison between flight crew and cabin crew training departments. Provision should be made for transfer of relevant knowledge and skills between flight crew and cabin crew CRM trainers.

(7) Management system

CRM training should address hazards and risks identified by the operator's management system described in ORO.GEN.200.

(8) Competency-based CRM training

Whenever practicable, the compliance-based approach concerning CRM training may be substituted by a competency-based approach. In this context, CRM training should be characterised by a performance orientation, with emphasis on standards of performance and their measurement, and the development of training to the specified performance standards.

(9) Contracted CRM training

If the operator chooses not to establish its own CRM training, another operator, a third party or a training organisation may be contracted to provide the training in accordance with ORO.GEN.205. In case of contracted CRM training, the operator should ensure that the content of the course covers the specific culture, the type of operations and the associated procedures of the operator. When crew members from different operators attend the same course, the CRM training should be specific to the relevant flight operations and to the trainees concerned.

(b) Operator's CRM training

The operator's CRM training should cover all elements listed in Table 1 of (g).

(c) Operator aircraft type conversion CRM training

If the cabin crew member undertakes the operator's conversion training on an aircraft type, the applicable CRM training elements should be covered as specified in Table 1 of (g).

(d) Annual recurrent CRM training

(1) Annual recurrent CRM training should be provided in such a way that all CRM training elements specified for the annual recurrent training in Table 1 of (g) are covered over a period not exceeding 3 years.

(2) Operators should update their recurrent CRM training programme over a period not exceeding 3 years. The revision of the programme should take into account information from the operator's management system.

(e) Senior cabin crew member course

(1) CRM training for senior cabin crew members should be the application of knowledge gained in previous CRM training and operational experience relevant to the specific duties and responsibilities of a senior cabin crew member. The operator should ensure that for the senior cabin crew member course the CRM training elements are integrated into the training, as specified in Table 1 of (g).

(2) During the training the senior cabin crew member should demonstrate the ability:

(i) to manage the operation; and

(ii) to take appropriate leadership and management decisions.

(f) Training elements

The CRM training elements to be covered are specified in Table 1 of (g). The operator should ensure that the following aspects are addressed:

(1) Resilience development

CRM training should address the main aspects of resilience development. The training should cover:

(i) Mental flexibility

Cabin crew should be trained to:

(A) understand that mental flexibility is necessary to recognise critical changes;

(B) reflect on their judgement and adjust it to the unique situation;

(C) avoid fixed prejudices and over-reliance on standard solutions; and

(D) remain open to changing assumptions and perceptions.

(ii) Performance adaptation

Cabin crew should be trained to:

(A) mitigate frozen behaviours, overreactions and inappropriate hesitation; and

(B) adjust actions to current conditions.

(2) Surprise and startle effect

CRM training should address unexpected, unusual and stressful situations including interruptions and distractions. Therefore, CRM training should be designed to prepare cabin crew to master sudden events and associated uncontrolled reactions.

(3) Cultural differences

CRM training should cover cultural differences of multinational and cross-cultural crews. This includes recognising that:

(i) different cultures may have different communication specifics, ways of understanding and approaches to the same situation or problem;

(ii) difficulties may arise when crew members with different mother tongue communicate in a common language which is not their mother tongue; and

(iii) cultural differences may lead to different methods for identifying a situation and solving a problem.

(4) Operator's safety culture and company culture

CRM training should cover the operator's safety culture, its company culture, the type of operations and the associated procedures of the operator. This should include areas of operations that may lead to particular difficulties or involve unusual hazards.

(5) Case studies

(i) CRM training should cover aircraft type-specific case studies, based on the information available within the operator's management system, including:

(A) accident and serious incident reviews to analyse and identify any associated non-technical causal and contributory factors, and instances or examples of lack of CRM; and

(B) analysis of occurrences that were well managed.

(ii) If relevant aircraft type-specific or operator-specific case studies are not available, the operator should consider other case studies relevant to the scale and scope of its operations.

(g) CRM training syllabus

Table 1 below specifies which CRM training elements should be covered in each type of training. The levels of training in Table 1 can be described as follows:

(1) 'Required' means training that should be instructional or interactive in style to meet the objectives specified in the CRM training programme or to refresh and strengthen knowledge gained in a previous training.

(2) 'In-depth' means training that should be instructive or interactive in style taking full advantage of group discussions, team task analysis, team task simulation, etc., for the acquisition or consolidation of knowledge, skills and attitudes. The CRM training elements should be tailored to the specific needs of the training phase being undertaken.

Table 1 – Cabin crew CRM training

CRM training elements	Operator's CRM training	Operator aircraft type conversion training	Annual recurrent training	Senior cabin crew member (SCC) course
General principles				
Human factors in aviation; General instructions on CRM principles and objectives; Human performance and limitations; Threat and error management.	Required	Required	Required	Required
Relevant to the individual cabin crew member				
Personality awareness, human error and reliability, attitudes and behaviours, self-assessment and self-critique; Stress and stress management; Fatigue and vigilance; Assertiveness, situation awareness, information acquisition and processing	Required	Required	Required (3-year cycle)	Required
Relevant to the entire aircraft crew				
Shared situation awareness, shared information acquisition and processing; Workload management; Effective communication and coordination between all crew members including the flight crew as well as inexperienced cabin crew members; Leadership, cooperation, synergy, delegation, decision- making, actions; Resilience development; Surprise and startle effect; Cultural differences; Identification and management of the passenger human factors: crowd control, passenger stress, conflict management, medical factors.	In-depth	Required when relevant to the type(s)	Required (3-year cycle)	In-depth
Specifics related to aircraft types (narrow-/wide-bodied, single-/multi-deck), flight crew and cabin crew composition and number of passengers	Required	In-depth	Required (3-year cycle)	In-depth
Relevant to the operator and the organisation				
Operator's safety culture and company culture, standard operating procedures (SOPs), organisational factors, factors linked to the type of operations Effective communication and coordination with other operational personnel and ground services Participation in cabin safety incident and accident reporting	In-depth	Required when relevant to the type(s)	Required (3-year cycle)	In-depth
Case-studies	In-depth	Required when relevant to the type(s)	In-depth	In-depth

AMC2 ORO.CC.115(e) Conduct of training courses and associated checking

CREW RESOURCE MANAGEMENT (CRM) TRAINING — SINGLE CABIN CREW OPERATIONS

For single cabin crew operations, AMC1 ORO.CC.115(e) should be applied with the following differences:

(a) Relevant training elements

CRM training should focus on the elements specified in Table 1 of (g) of AMC1 ORO.CC.115(e) which are relevant to single cabin crew operations. Therefore, single cabin crew CRM training should include, among others:

(1) situation awareness;

(2) workload management;

(3) decision-making;

(4) resilience development;

(5) surprise and startle effect; and

(6) effective communication and coordination with

(i) the flight crew; and
(ii) other operational personnel and ground services.

(b) Computer-based training

Notwithstanding (a)(3) of AMC1 ORO.CC.115(e), computer-based training may be conducted as a stand-alone training method for a cabin crew member operating on aircraft with a maximum operational passenger seating configuration of 19 or less.

AMC3 ORO.CC.115(e) Conduct of training courses and associated checking

CABIN CREW CRM TRAINER

(a) Applicability

The provisions described herein:

(1) should be fulfilled by cabin crew CRM trainers responsible for classroom CRM training; and

(2) are not applicable to trainers or instructors conducting training other than CRM training, but integrating CRM elements into this training. Nevertheless, trainers or instructors who are integrating CRM elements into the aircraft type training, recurrent training or senior cabin crew member training should have acquired relevant knowledge of human performance and limitations, and have completed appropriate CRM training.

(b) Qualification of cabin crew CRM trainer

(1) A training and standardisation programme for cabin crew CRM trainers should be established.

(2) The cabin crew CRM trainer, in order to be suitably qualified, should:

(i) have adequate knowledge of the relevant flight operations;

(ii) have received instructions on human performance and limitations (HPL);

(iii) have completed an introductory CRM course, as required in CAR-CC, and an operator's CRM training, as specified in AMC1 ORO.CC.115(e);"

(iv) have received training in group facilitation skills;

(v) have received additional training in the fields of group management, group dynamics and personal awareness; and

(vi) have demonstrated the knowledge, skills and credibility required to train the CRM training elements in the non-operational environment, as specified in Table 1 of AMC1 ORO.CC.115(e).

(3) An experienced CRM trainer may become a cabin crew CRM trainer if he/she demonstrates a satisfactory knowledge of the relevant flight operations and the cabin crew working environment, and fulfils the provisions specified in (2)(ii) to (2)(vi).

(c) Training of cabin crew CRM trainer

(1) Training of cabin crew CRM trainers should be both theoretical and practical. Practical elements should include the development of specific trainer skills, particularly the integration of CRM into day-to-day operations.

(2) The basic training of cabin crew CRM trainers should include the training elements for cabin crew, as specified in Table 1 of AMC1 ORO.CC.115(e). In addition, the basic training should include the following:

(i) introduction to CRM training;

(ii) operator's management system; and

(iii) characteristics, as applicable:

(A) of the different types of CRM trainings (initial, recurrent, etc.);

(B) of combined training; and

(C) related to the type of aircraft or operation.

(3) The refresher training of cabin crew CRM trainers should include new methodologies, procedures and lessons learned.

(4) The training of cabin crew CRM trainers should be conducted by cabin crew CRM trainers with a minimum of 3 years' experience. Assistance may be provided by experts in order to address specific areas.

(d) Assessment of cabin crew CRM trainer

(1) A cabin crew CRM trainer should be assessed by the operator when conducting the first CRM training course. This first assessment should be valid for a period of 3 years.

(2) Assessment is the process of observing, recording, interpreting and debriefing the cabin crew CRM trainer. The operator should describe the assessment process in the operations manual. All personnel involved in the assessment must be credible and competent in their role.

(3).G Personnel conducting assessments on cabin crew CRM trainers should be initially accepted by the competent authority.

(e) Recency and renewal of qualification as cabin crew CRM trainer

(1) For recency of the 3-year validity period, the cabin crew CRM trainer should:

(i) conduct at least 2 CRM training events in any 12-month period;

(ii) be assessed within the last 12 months of the 3-year validity period by the operator; and

(iii) complete CRM trainer refresher training within the 3-year validity period.

(2) The next 3-year validity period should start at the end of the previous period.

(3) For renewal, i.e. when a cabin crew CRM trainer does not fulfil the provisions of (1), he/she should, before resuming as cabin crew CRM trainer:

(i) comply with the qualification provisions of (b) and (d); and

(ii) complete CRM trainer refresher training.

GM1 ORO.CC.115(e) Conduct of training courses and associated checking

CRM - GENERAL

(a) CRM is the effective utilisation of all available resources (e.g. crew members, aircraft systems, and supporting facilities) to achieve safe and efficient operation.

(b) The objective of CRM is to enhance the communication and management skills of the crew member, as well as the importance of effective coordination and two-way communication between all crew members.

GM2 ORO.CC.115(e) Crew resource management (CRM) training

MINIMUM TRAINING TIMES

(a) The following minimum training times are appropriate:

(1) multi cabin crew operations:

(i) combined CRM training: 6 training hours over a period of 3 years; and

(ii) operator's CRM training: 6 training hours;

(2) operator's CRM training for single cabin crew operations: 4 training hours for a cabin crew member operating on aircraft with a maximum operational passenger seating configuration of 19 or less;

(3) cabin crew CRM trainer:

(i) basic training:

(A) 18 training hours when the operator can justify that the trainee already has received sufficient and suitable instruction on training skills in order to conduct CRM training courses; or

(B) 30 training hours for trainees not fulfilling (A); and

(ii) refresher training: 6 training hours.

(b) 'Training hours' means actual training time excluding breaks.

GM3 ORO.CC.115(e) Crew resource management (CRM) training

DESIGN, IMPLEMENTATION AND EVALUATION OF CRM TRAINING

The checklist in Table 1 provides guidance on the design, implementation and evaluation of CRM training, and on their incorporation into the operator's safety culture. Elements of the operator's management systems and the competency-based approach are incorporated in the checklist.

Table 1 — Checklist for design, implementation, evaluation and incorporation of CRM training

Step No	Description	Element
1	Needs analysis	Determine the necessary CRM competencies
		Develop CRM training goals
		Ensure the organisation is ready for CRM training
2	Design	Develop CRM training objectives
		Determine what to measure and how to measure it
3	Development	Describe the CRM learning environment
		Develop full-scale prototype of training
		Validate and modify CRM training
4	Implementation	Prepare trainees and environment
		Set a climate for learning (e.g. practice and feedback)
		Implement the CRM training programme
5	Evaluation	Determine training effectiveness
		Evaluate CRM training at multiple levels
		Revise the CRM training programme to improve effectiveness
6	Incorporation	Establish an environment where CRM training is positively recognised
		Reinforce CRM behaviours in daily work
		Provide recurrent CRM training

GM4 ORO.CC.115(e) Crew resource management (CRM) training

RESILIENCE DEVELOPMENT

(a) The main aspects of resilience development can be described as the ability to:

(1) learn ('knowing what has happened');

(2) monitor ('knowing what to look for');

(3) anticipate ('finding out and knowing what to expect'); and

(4) respond ('knowing what to do and being capable of doing it').

(b) Operational safety is a continuous process of evaluation of and adjustment to existing and future conditions. In this context, and following the description in (a), resilience development involves an ongoing and adaptable process including situation assessment, self-review, decision and action. Training on resilience development enables crew members to draw the right conclusions from both positive and negative experiences. Based on those experiences, crew members are better prepared to maintain or create safety margins by adapting to dynamic complex situations.

(c) The training topics in (f)(1) of AMC1 ORO.CC.115(e) are to be understood as follows:

(1) Mental flexibility

(i) The phrase 'understand that mental flexibility is necessary to recognise critical changes' means that crew members are prepared to respond to situations for which there is no set procedure.

(ii) The phrase 'reflect on their judgement and adjust it to the unique situation' means that crew members learn to review their judgement based on the unique characteristics of the given circumstances.

(iii) The phrase 'avoid fixed prejudices and over-reliance on standard solutions' means that crew members learn to update solutions and standard response sets, which have been formed on prior knowledge.

(iv) The phrase 'remain open to changing assumptions and perceptions' means that crew members constantly monitor the situation, and are prepared to adjust their understanding of the evolving conditions.

(2) Performance adaptation

(i) The phrase 'mitigate frozen behaviours, overreactions and inappropriate hesitation' means that crew members correct improper actions with a balanced response.

(ii) The phrase 'adjust actions to current conditions' means that crew members' responses are in accordance with the actual situation.

GM5 ORO.CC.115(e) Conduct of training courses and associated checking

CABIN CREW CRM TRAINER ASSESSMENT

(a) For assessing cabin crew CRM trainers, the operator may nominate experienced cabin crew CRM trainers who have demonstrated continued compliance with the provisions for a cabin crew CRM trainer and capability in that role for at least 3 years.

(b) An operator that does not have the resources to conduct the assessment may employ a contractor. The standard as regards the assessment is confirmed on a 3-year basis by the operator.

(c) The checklist in Table 1 provides guidance on the assessment of a cabin crew CRM trainer. If a cabin crew CRM trainer is competent in his/her role, the response to the questions in Table 1 should be 'yes'. When answering the questions in Table 1, justifications and examples related to the responses given should be provided.

Table 1 - Cabin crew CRM trainer assessment checklist

Questions to assess a cabin crew CRM trainer	Response yes/no
Did the CRM trainer demonstrate the knowledge required for the role?	
Did the CRM trainer support CRM concepts?	
Did the CRM trainer encourage trainees to participate, share their experiences and self-analyse?	
Did the CRM trainer identify and respond to the trainees' needs relative to expertise/experience?	
Did the CRM trainer show how CRM is integrated in technical training?	
Did the CRM trainer incorporate company CRM standards when appropriate?	
Did the CRM trainer identify and discuss the non-technical reasons involved in accidents, incidents and events included in case studies?	
Did the CRM trainer regularly check for understanding and resolve ambiguities?	
Did the CRM trainer demonstrate effective instruction and facilitation skills?	

ORO.CC.120 Initial training course

(a) Each new entrant who does not already hold a valid cabin crew attestation issued in accordance with CAR-CC:

(1) shall be provided with an initial training course as specified in CC.TRA.220 of CAR-CC; and
(2) shall successfully undergo the associated examination before undertaking other training required by this Subpart.

(b) Elements of the initial training programme may be combined with the first aircraft type specific training and operator conversion training, provided that the requirements of CC.TRA.220 are met and any such element(s) are recorded as elements of the initial training course in the training records of the cabin crew members concerned.

AMC1 ORO.CC.120(a)(1) Initial training course

NEW ENTRANTS IN OPERATIONS OTHER THAN COMMERCIAL AIR TRANSPORT OPERATIONS

(a) When a new entrant to an operator conducting operations other than CAT is a cabin crew member, not holding a valid cabin crew attestation, who has already acquired experience as cabin crew in operations other than CAT, credit may be granted to the elements of the initial training programme he/she has previously completed if such training elements are documented in his/her training records.

(b) In such a case, the operator should ensure that:

(1) the full training programme, as specified in Appendix 1 to CAR-CC, has been covered, and

(2) the new entrant successfully undergoes the examination required by ORO.CC.120(a)(2).

ORO.CC.125 Aircraft type specific training and operator conversion training

(a) Each cabin crew member shall have completed appropriate aircraft type specific training and operator conversion training, as well as the associated checks, before being:

(1) first assigned by the operator to operate as a cabin crew member; or

(2) assigned by that operator to operate on another aircraft type.

(b) When establishing the aircraft type specific and the operator conversion training programmes and syllabi, the operator shall include, where available, the relevant elements defined in the mandatory part of the operational suitability data established in accordance with CAR 21

(c) The aircraft type specific training programme shall:

(1) involve training and practice on a representative training device or on the actual aircraft; and

(2) cover at least the following aircraft type specific training elements:

(i) aircraft description as relevant to cabin crew duties;

(ii) all safety equipment and systems installed relevant to cabin crew duties;

(iii) operation and actual opening, by each cabin crew member, of each type or variant of normal and emergency doors and exits in the normal and emergency modes;

(iv) demonstration of the operation of the other exits including flight crew compartment windows;

(v) fire and smoke protection equipment where installed;

(vi) evacuation slide training, where fitted;

(vii) operation of the seat, restraint system and oxygen system equipment relevant to pilot incapacitation.

(d) The operator conversion training programme for each aircraft type to be operated shall:

(1) involve training and practice on a representative training device or on the actual aircraft;

(2) include training in the operator's standard operating procedures for cabin crew members to be first assigned to duties by the operator;

(3) cover at least the following operator specific training elements as relevant to the aircraft type to be operated:

(i) description of the cabin configuration;

(ii) location, removal and use of all portable safety and emergency equipment carried on-board;

(iii) all normal and emergency procedures;

(iv) passenger handling and crowd control;

(v) fire and smoke training including the use of all related fire-fighting and protective equipment representative of that carried on-board;

(vi) evacuation procedures;

(vii) pilot incapacitation procedures;

(viii) applicable security requirements and procedures;

(ix) crew resource management.

AMC1 ORO.CC.125(c) Aircraft type specific training and operator conversion training

TRAINING PROGRAMME — AIRCRAFT TYPE SPECIFIC TRAINING

The following aircraft type specific training elements should be covered as relevant to the aircraft type:

(a) Aircraft description

(1) type of aircraft, principal dimensions, narrow or wide bodied, single or double deck;

(2) speed, altitude, range;

(3) passenger seating capacity;

(4) flight crew number and minimum number of required cabin crew;

(5) cabin doors/exits location and sill height;

(6) cargo and unpressurised areas as relevant;

(7) aircraft systems relevant to cabin crew duties;

(8) flight crew compartment — general presentation, pilot seats and their mechanism,

emergency exits, storage;

(9) required cabin crew stations;

(10) flight crew compartment security — general: door components and use;

(11) access to avionics bay where relevant;

(12) lavatories — general: doors, systems, calls and signs; and

(13) least risk bomb location.

(b) Safety and emergency equipment and aircraft systems installed

Each cabin crew member should receive realistic training on, and demonstration of, the location and use of all aircraft type specific safety and emergency equipment and aircraft systems installed, with emphasis on the following:

(1) slides, and where non-self-supporting slides are carried, the use of any associated assisting evacuation means;

(2) life-rafts and slide-rafts, including the equipment attached to, and/or carried in, the raft;

(3) drop-out oxygen system; and

(4) communication equipment.

(c) Operation of doors and exits

This training should be conducted in a representative training device or in the actual aircraft and should include failure of power assist systems where fitted and the action and forces required to operate and deploy evacuation slides. Training should also include operation and actual opening of the flight crew compartment security door when installed.

(d) Fire and smoke protection equipment

Each cabin crew member should be trained in using fire and/or smoke protection equipment where fitted.

(e) Evacuation slide training

(1) Each cabin crew member should descend an evacuation slide from a height representative of the aircraft main deck sill height.

(2) The slide should be fitted to a representative training device or to the actual aircraft.

(3) A further descent should be made when the cabin crew member qualifies on an aircraft type in which the main deck exit sill height differs significantly from any aircraft type previously operated.

(f) Operation of equipment related to pilot incapacitation

The training should cover any type specific elements or conditions relevant to cabin crew actions to be taken in case of pilot incapacitation. Each cabin crew member should be trained to operate all equipment that must be used in case of pilot incapacitation.

AMC1 ORO.CC.125(d) Aircraft type-specific training and operator conversion training

TRAINING PROGRAMME — OPERATOR CONVERSION TRAINING

The following training elements should be covered as relevant to the aircraft type and the related operator's specifics:

(a) Description of the cabin configuration

The description should cover all elements specific to the operator's cabin configuration and any differences with those previously covered in accordance with AMC1 ORO.CC.125(c), including:

(1) required and additional cabin crew stations — location (including direct view), restraint systems, control panels;

(2) passenger seats — general presentation and associated operator's specific features and equipment;

(3) designated stowage areas;

(4) lavatories — operator's specific features, equipment and systems additional to the aircraft type specific elements;

(5) galley — location, appliances, water and waste system, including shut-off, sinks, drains, stowage, control panels, calls and signs;

and where applicable

(6) crew rest areas — location, systems, controls, safety and emergency equipment;

(7) cabin dividers, curtains, partitions;

(8) lift location, use, controls;

(9) stowage for the containment of waste;

(10) passenger hand rail system or alternative means; and

(11) in-flight entertainment (IFE) system, if installed (e.g. central system or hand-held device(s) such as PEDs for the use by passenger(s) as applicable and its safety aspects.

(b) Safety and emergency equipment

Each cabin crew member should receive realistic training on and demonstration of the location and use of all safety and emergency equipment carried, including:

(1) life jackets, infant life jackets and flotation devices;

(2) first-aid and drop-out oxygen, including supplementary systems;

(3) fire extinguishers and protective breathing equipment (PBE);

(4) crash axe or crowbar;

(5) emergency lights including torches;

(6) communication equipment, including megaphones;

(7) slide rafts and life rafts' survival packs and their contents;

(8) pyrotechnics (actual or representative devices);

(9) first-aid kits, emergency medical kits and their contents; and

(10) other portable safety and emergency equipment, where applicable.

(c) Normal and emergency procedures

Each cabin crew member should be trained on the operator's normal and emergency procedures as applicable, with emphasis on the following:

(1) passenger briefing, safety demonstration and cabin surveillance;

(2) severe air turbulence;

(3) non–pressurisation, slow and sudden decompression, including the donning of portable oxygen equipment by each cabin crew member;

(4) other in-flight emergencies; and

(5) carriage of special categories of passengers (SCPs).

(d) Passenger handling and crowd control

Training should be provided on the practical aspects of passenger preparation and handling, as well as crowd control, in various emergency situations as applicable to the operator's specific aircraft cabin configuration, and should cover the following:

(1) communications between flight crew and cabin crew and use of all communications equipment, including the difficulties of coordination in a smoke-filled environment;

(2) verbal commands;

(3) the physical contact that may be needed to encourage people out of a door/exit and onto a slide;

(4) redirection of passengers away from unusable doors/exits;

(5) marshalling of passengers away from the aircraft;

(6) evacuation of special categories of passengers with emphasis on passengers with disabilities or reduced mobility; and

(7) authority and leadership.

(e) Fire and smoke training

(1) Each cabin crew member should receive realistic and practical training in the use of all fire-fighting equipment, including protective clothing representative of that carried in the aircraft.

(2) Each cabin crew member should:

(i) extinguish an actual fire characteristic of an aircraft interior fire except that, in the case of halon extinguishers, an alternative extinguishing agent may be used; and

(ii) exercise the donning and use of PBE in an enclosed simulated smoke-filled environment with particular emphasis on identifying the actual source of fire and smoke.

(f) Evacuation procedures

Training should include all the operator's procedures that are applicable to planned or unplanned evacuations on land and water. It should also include, where relevant, the additional actions required from cabin crew members responsible for a pair of doors/exits and the recognition of when doors/exits are unusable or when evacuation equipment is unserviceable.

(g) Pilot incapacitation procedures

Unless the minimum flight crew is more than two, each cabin crew member should be trained in the procedure for pilot incapacitation. Training in the use of flight crew checklists, where required by the operator's standard operating procedures (SOPs), should be conducted by a practical demonstration.

(h) CRM

(1) The operator should ensure that all applicable CRM training and CRM training elements, as specified in Table 1 of AMC1 ORO.CC.115 (e), are covered to the level required in the

column 'Operator aircraft type conversion training'.

(2) The operator's CRM training and the CRM training covered during the operator aircraft type conversion training should be conducted by at least one cabin crew CRM instructor.

AMC1 ORO.CC.125 & ORO.CC.130 Aircraft type specific training and operator conversion training & differences training

TRAINING PROGRAMMES

The programmes and syllabi of aircraft type specific training, operator conversion training and differences training should take into account the cabin crew member's previous training as documented in his/her training records.

AMC1 ORO.CC.125(b) & ORO.CC.130(c) Aircraft type specific training and operator conversion training & differences training

NON-MANDATORY (RECOMMENDATIONS) ELEMENTS OF OPERATIONAL SUITABILITY DATA

When developing the training programmes and syllabi for aircraft-type specific training and for differences training, the operator should consider the non-mandatory (recommendations) elements for the relevant type that are provided in the operational suitability data established in accordance with CAR 21.

ORO.CC.130 Differences training

(a) In addition to the training required in ORO.CC.125, the cabin crew member shall complete appropriate training and checking covering any differences before being assigned on:

(1) a variant of an aircraft type currently operated; or

(2) a currently operated aircraft type or variant with different:

(i) safety equipment;

(ii) safety and emergency equipment location; or

(iii) normal and emergency procedures.

(b) The differences training programme shall:

(1) be determined as necessary on the basis of a comparison with the training programme completed by the cabin crew member, in accordance with ORO.CC.125 (c) and (d), for the relevant aircraft type; and

(2) involve training and practice in a representative training device or the actual aircraft as relevant to the difference training element to be covered.

(c) When establishing a differences training programme and syllabus for a variant of an aircraft type currently operated, the operator shall include, where available, the relevant elements defined in the mandatory part of the operational suitability data established in accordance with CAR 21.

See also:

AMC1 ORO.CC.125 & ORO.CC.130 Aircraft type specific training and operator conversion training & differences training

AMC1 ORO.CC.125(b) & ORO.CC.130(c) Aircraft type specific training and operator conversion training & differences training

ORO.CC.135 Familiarisation

After completion of aircraft type specific training and operator conversion training on an aircraft type, each cabin crew member shall complete appropriate supervised familiarisation on the type before being assigned to operate as a member of the minimum number of cabin crew required in accordance with ORO.CC.100.

AMC1 ORO.CC.135 Familiarisation

FAMILIARISATION FLIGHTS AND AIRCRAFT FAMILIARISATION VISITS

(a) For CAT operations, familiarisation of cabin crew to a new aircraft type or variant should be completed in accordance with the following, as relevant:

(1) New entrant cabin crew

Each new entrant cabin crew member having no previous comparable operating experience should participate in:

(i) a familiarisation visit, as described in (c), to the aircraft to be operated; and

(ii) familiarisation flights, as described in (b).

(2) Cabin crew operating on a subsequent aircraft type

A cabin crew member assigned to operate on a subsequent aircraft type with the same operator should participate either in:

(i) a familiarisation flight, as described in (b); or

(ii) a familiarisation visit, as described in (c), to the aircraft type to be operated.

(b) Familiarisation flights

(1) During familiarisation flights, the cabin crew member should be assigned in addition to the minimum number of cabin crew required in accordance with ORO.CC.100 and if applicable ORO. CC.200.

(2) Familiarisation flights should be:

(i) conducted under the supervision of the senior cabin crew member;

(ii) structured and conducted with the cabin crew member participating in pre-flight, in-flight and post-flight safety duties;

(iii) operated with the cabin crew member wearing the operator's cabin crew uniform; and

(iv) recorded in the training record of the cabin crew member.

(c) Aircraft familiarisation visits

(1) Aircraft visits should enable the cabin crew member to become familiar with the aircraft environment and its equipment. Accordingly, aircraft visits should be conducted by appropriately qualified persons. The aircraft visit should provide an overview of the aircraft's exterior, interior and aircraft systems with emphasis on the following:

(i) interphone and public address systems;

(ii) evacuation alarm systems;

(iii) emergency lighting;

(iv) smoke detection systems;

(v) safety and emergency equipment;

(vi) flight crew compartment;

(vii) cabin crew stations;

(viii) lavatories;

(ix) galleys, galley security and water shut-off;

(x) cargo areas if accessible from the passenger compartment during flight;

(xi) circuit breaker panels located in the passenger compartment;

(xii) crew rest areas;

(xiii) doors/exits location and environment; and

(xiv) IFE system used for conveying safety-related information.

(2) An aircraft familiarisation visit may be combined with the aircraft type specific training or operator conversion training required by ORO.CC.125.

(d) For cabin crew members assigned to operations other than CAT, familiarisation should be completed by means of an aircraft familiarisation visit, or a familiarisation flight, as appropriate taking into account the aircraft type to be operated by the cabin crew member.

ORO.CC.140 Recurrent training

(a) Each cabin crew member shall complete annually recurrent training and checking.

(b) Recurrent training shall cover the actions assigned to each member of the cabin crew in normal and emergency procedures and drills relevant to each aircraft type and/or variant to be operated.

(c) Aircraft type specific training elements:

(1) Recurrent training shall include annually touch-drills by each cabin crew member for simulating the operation of each type or variant of normal and emergency doors and exits for passenger evacuation.

(2) Recurrent training shall also include at intervals not exceeding three years:

(i) operation and actual opening by each cabin crew member, in a representative training device or in the actual aircraft, of each type or variant of normal and emergency exits in the normal and emergency modes;

(ii) actual operation by each cabin crew member, in a representative training device or in the actual aircraft, of the flight crew compartment security door, in both normal and emergency modes, and of the seat and restraint system, and a practical demonstration of the oxygen system equipment relevant to pilot incapacitation;

(iii) demonstration of the operation of all other exits including the flight crew compartment windows; and

(iv) demonstration of the use of the life raft, or slide raft, where fitted.

(d) Operator specific training elements:

(1) Recurrent training shall include annually:

(i) by each cabin crew member:

(A) location and handling of all safety and emergency equipment installed or carried on board; and

(B) the donning of life-jackets, portable oxygen and protective breathing equipment (PBE);

(ii) stowage of articles in the passenger compartment;

(iii) procedures related to aircraft surface contamination;

(iv) emergency procedures;

(v) evacuation procedures;

(vi) incident and accident review;

(vii) crew resource management;

(viii) aero-medical aspects and first aid including related equipment;

(ix) security procedures.

(2) Recurrent training shall also include at intervals not exceeding three years:

(i) use of pyrotechnics (actual or representative devices);

(ii) practical demonstration of the use of flight crew checklists;

(iii) realistic and practical training in the use of all fire-fighting equipment, including protective clothing, representative of that carried in the aircraft;

(iv) by each cabin crew member:

(A) extinguishing a fire characteristic of an aircraft interior fire;

(B) donning and use of PBE in an enclosed simulated smoke-filled environment.

(e) Validity periods:

(1) The annual recurrent training validity period shall be 12 calendar months counted from the end of the month when the check was taken.

(2) If the recurrent training and checking required in (a) are undertaken within the last three calendar months of the validity period, the new validity period shall be counted from the original expiry date.

(3) For the additional triennial training elements specified in (c)(2) and (d)(2), the validity period shall be 36 calendar months counted from the end of the month when the checks were taken.

AMC1 ORO.CC.140 Recurrent training

TRAINING PROGRAMMES

(a) Elements of the annual recurrent training programme

(1) Training on the location and handling of safety and emergency equipment should include all relevant oxygen systems, and any equipment such as defibrillators if carried on board.

(2) Training on emergency procedures should cover pilot incapacitation procedures and crowd control techniques.

(3) CRM training should satisfy the following:

(i) the applicable training elements specified in Table 1 of AMC1 ORO.CC.115(e) should be covered within a 3-year cycle to the level required by column 'Annual Recurrent Training';

(ii) the definition and implementation of the CRM training programme should be managed by a cabin crew CRM trainer; and

(iii) when CRM training is provided by stand-alone modules, it should be conducted by at least one cabin crew CRM trainer.

(b) Additional triennial elements of recurrent training programme

(1) Training on the operation of normal and emergency doors/exits should cover failure of power assist systems where fitted. This should include the actions and forces required to operate and deploy evacuation slides, and additional training when relevant for cabin crew members responsible for a pair of doors/exits.

(2) Training in the use of all firefighting equipment, including protective clothing, representative of that carried in the aircraft should include individual practice by each cabin crew member to extinguish a fire characteristic of an aircraft interior fire except that, in the case of halon extinguishers, an alternative extinguishing agent may be used. Training should place particular emphasis on identifying the actual source of fire or smoke.

(3) Training on normal and emergency procedures for special categories of passengers (SCPs) should cover the specific procedures established by the operator for the carriage of SCPs. The operator may determine that such training is to be completed at shorter intervals, taking into account the route structure, passenger profiles, aircraft types operated, seasonal demands and operations.

ORO.CC.145 Refresher training

(a) When a cabin crew member, during the preceding six months within the validity period of the last relevant recurrent training and checking:

(1) has not performed any flying duties, he/she shall, before being reassigned to such duties, complete refresher training and checking for each aircraft type to be operated; or

(2) has not performed flying duties on one particular aircraft type, he/she shall, before being reassigned to duties, complete on that aircraft type:

(i) refresher training and checking; or

(ii) two familiarisation flights in accordance with ORO.CC.135.

(b) The refresher training programme for each aircraft type shall at least cover:

(1) emergency procedures;

(2) evacuation procedures;

(3) operation and actual opening, by each cabin crew member, of each type or variant of normal and emergency exits and of the flight crew compartment security door in the normal and emergency modes;

(4) demonstration of the operation of all other exits including the flight crew compartment windows;

(5) location and handling of all relevant safety and emergency equipment installed or carried on- board.

(c) The operator may elect to replace refresher training by recurrent training if the reinstatement of the cabin crew member's flying duties commences within the validity period of the last recurrent training and checking. If that validity period has expired, refresher training may only be replaced by aircraft type specific and operator conversion training as specified in ORO.CC.125.

AMC1 ORO.CC.145 Refresher training

TRAINING PROGRAMME

(a) Training on emergency procedures should include pilot incapacitation procedures and crowd control techniques as applicable to the aircraft type; and

(b) Operation of doors and exits by each cabin crew member should include failure of power assist systems where fitted as well as the action and forces required to operate and deploy evacuation slides.

GM1 ORO.CC.145 Refresher training

FREQUENCY OF REFRESHER TRAINING

For aircraft with complex equipment or procedures, the operator should consider the need for refresher training to be completed by cabin crew members who have been absent from flying duties for less than 6 months.

Section 2 — Additional requirements for commercial air transport operations

ORO.CC.200 Senior cabin crew member

(a) When more than one cabin crew member is required, the composition of the cabin crew shall include a senior cabin crew member nominated by the operator.

(b) The operator shall nominate cabin crew members to the position of senior cabin crew member only if they:

(1) have at least one year of experience as operating cabin crew member; and

(2) have successfully completed a senior cabin crew training course and the associated check.

(c) The senior cabin crew training course shall cover all duties and responsibilities of senior cabin crew members and shall include at least the following elements:

(1) pre-flight briefing;

(2) cooperation with the crew;

(3) review of operator requirements and legal requirements;

(4) accident and incident reporting;

(5) human factors and crew resource management (CRM); and

(6) flight and duty time limitations and rest requirements.

(d) The senior cabin crew member shall be responsible to the commander for the conduct and coordination of normal and emergency procedures specified in the operations manual, including for discontinuing non-safety-related duties for safety or security purposes.

(e) The operator shall establish procedures to select the most appropriately qualified cabin crew member to act as senior cabin crew member if the nominated senior cabin crew member becomes unable to operate. Changes to these procedures shall be notified to the competent authority.

AMC1 ORO.CC.200(c) Senior cabin crew member

TRAINING PROGRAMME

The senior cabin crew member training course should at least cover the following elements:

(a) Pre-flight briefing:

(1) operating as a crew;

(2) allocation of cabin crew stations and responsibilities; and

(3) consideration of the particular flight, aircraft type, equipment, area and type of operation, including extended range operations with two-engine aeroplanes (ETOPS) and special categories of passengers with emphasis on passengers with disabilities or reduced mobility, infants and stretcher cases.

(b) Cooperation within the crew:

(1) discipline, responsibilities and chain of command;

(2) importance of coordination and communication; and

(3) pilot incapacitation.

(c) Review of operator requirements and legal requirements:

(1) passenger briefing, safety briefing cards;

(2) securing of galleys;

(3) stowage of cabin baggage;

(4) electronic equipment;

(5) procedures when fuelling with passengers on board;

(6) turbulence; and

(7) documentation.

(d) Accident and incident reporting.

(e) Human factors and CRM:

The operator should ensure that all applicable elements specified in Table 1 of AMC1 ORO.CC.115(e) are integrated into the training and covered to the level required by Column 'Senior Cabin Crew Course'.

(f) Flight and duty time limitations and rest requirements (FTL).

AMC1 ORO.CC.200(d) Senior cabin crew member

RESPONSIBILITY TO THE COMMANDER

When the level of turbulence so requires, and in the absence of any instructions from the flight crew, the senior cabin crew member should be entitled to discontinue non-safety-related duties and advise the flight crew of the level of turbulence being experienced and the need for the fasten seat belt signs to be switched on. This should be followed by the cabin crew securing the passenger cabin and other relevant areas.

AMC1 ORO.CC.200(e) Senior cabin crew member

UNABLE TO OPERATE

(a) Replacement of senior cabin crew member at a base of the operator

A senior cabin crew member who did not report for or cannot commence the assigned flight or series of flights originating from a base of the operator should be replaced without undue delay. The flight should not depart unless another senior cabin crew member has been assigned.

(b) Replacement of incapacitated or unavailable senior cabin crew member

(1) A senior cabin crew member, who becomes incapacitated during a flight or series of flights, or unavailable at a stopover (layover) point, should be replaced without undue delay by another senior cabin crew member qualified on the concerned aircraft type/variant. If there is no other senior cabin crew member, the most appropriately qualified cabin crew member should be assigned to act as senior cabin crew member in order to reach a base of the operator.

(2) If during the series of flights the aircraft transits via a base of the operator, the assigned cabin crew member acting as senior cabin crew member should be replaced by another senior cabin crew member.

AMC2 ORO.CC.200(e) Senior cabin crew member

MOST APPROPRIATELY QUALIFIED CABIN CREW MEMBER

Selection of the most appropriately qualified cabin crew member should take into account if the individual's experience as operating cabin crew member is adequate for the conduct of duties required of a senior cabin crew member. The selected cabin crew member should have operational experience on the concerned aircraft type/variant.

GM1 ORO.CC.200(e) Senior cabin crew member

REPLACEMENT OF INCAPACITATED OR UNAVAILABLE SENIOR CABIN CREW MEMBER BY ANOTHER SENIOR CABIN CREW MEMBER

To ensure that another senior cabin crew member is assigned without undue delay, the operator should take appropriate measures. These include, but are not limited to, the following:

(a) to ensure that a flight or series of flights do not depart from an aerodrome where a senior cabin crew member is available or can be made available, the operator may:

(1) appoint a senior cabin crew member originally assigned to another flight and who is available at the concerned base or stopover (layover) point if the reporting time for that flight provides sufficient time to find a replacement; or

(2) assign a senior cabin crew member who is on standby to operate the flight or to position to the destination where the nominated senior cabin crew member has become incapacitated or unavailable to operate;

(b) the operator should utilise another senior cabin crew member if she/he is among the operating crew on the same flight;

(c) in case of unavailable senior cabin crew member, the operator should use the available time and resources to replace him/her at the stopover (layover) point with another senior cabin crew member;

(d) the operator should consider including the identification of the most appropriately qualified cabin crew member in pre-flight briefings.

GM2 ORO.CC.200(e) Senior cabin crew member

FLIGHT OR SERIES OF FLIGHTS

Flight or series of flights refers to a period that commences when a cabin crew member is required to report for duty, which includes a sector or a series of sectors, and finishes when the aircraft finally comes to rest and the engines are shut down, at the end of the last sector on which the cabin crew member acts as an operating crew member.

ORO.CC.205 Reduction of the number of cabin crew during ground operations and in unforeseen circumstances

(a) Whenever passengers are on board an aircraft, the minimum number of cabin crew members required in accordance with point ORO.CC.100 shall be present in the aircraft and ready to act.

(b) By way of derogation from point (a), the minimum number of cabin crew members may be

reduced in either of the following cases:

(1) during normal ground operations not involving refuelling or defuelling when the aircraft is at its parking station;

(2) in unforeseen circumstances if the number of passengers carried on the flight is reduced. In this case, a report shall be submitted to the competent authority after completion of the flight;

(3) for the purpose of providing in-flight rest during the cruise phase, either in accordance with the maximum daily FDP with the use of extensions due to in-flight rest or as a fatigue mitigation implemented by the operator.

(c) For the purposes of points (b)(1) and (b)(2), the operator's procedures of the operations manual shall ensure that:

(1) an equivalent level of safety is achieved with the reduced number of cabin crew members, in particular for evacuation of passengers;

(2) despite the reduced number of cabin crew members a senior cabin crew member is present in accordance with point ORO.CC.200;

(3) at least one cabin crew member is required for every 50, or fraction of 50, passengers present on the same deck of the aircraft;

(4) in the case of normal ground operations with aircraft requiring more than one cabin crew member, the number determined in accordance with point (3) shall be increased by one cabin crew member per each pair of floor level emergency exits.

(d) For the purposes of point (b)(3), the operator shall:

(1) conduct a risk assessment to determine the number of cabin crew members who are to be present and ready to act at all times during cruise;

(2) identify measures to mitigate the effects of having a lower number of cabin crew members being present and ready to act during cruise;

(3) establish in the operations manual specific procedures, including for the in-flight rest of the senior cabin crew member, that ensure at all times appropriate passenger handling and efficient management of any abnormal or emergency situations;

(4) specify, in the flight time specification scheme in accordance with Subpart FTL, the conditions under which in-flight rest may be provided to the cabin crew members.

GM1 ORO.CC.205(a) Reduction of the number of cabin crew during ground operations and in unforeseen circumstances

CABIN CREW PRESENT AND READY TO ACT

'Present and ready to act' means that cabin crew members should be awake and in a state of alertness that enables them to fulfil their responsibilities and perform their duties as required by any situation in accordance with all applicable normal and emergency procedures established in the operations manual.

GM1 ORO.CC.205(b)(2) Reduction of the number of cabin crew during ground operations and in unforeseen circumstances

UNFORESEEN CIRCUMSTANCES

Unforeseen circumstances in this context refer to incapacitation and unavailability of a senior cabin crew member or a cabin crew member as follows:

(a) 'Incapacitation' means a sudden degradation of medical fitness that occurs during flight duty period either in-flight or during a flight transit of the same flight duty period away from operator's base and that precludes the senior cabin crew member or cabin crew member from performing his/her duties. Incapacitation prior to dispatch of the aircraft from a base of the operator does not substantiate a reduction of the cabin crew complement below the minimum required.

(b) 'Unavailability' means circumstances at a stopover (layover) destination that preclude the senior cabin crew member or cabin crew member from reporting for the flight duty period, such as traffic jams that prevent the senior cabin crew member or cabin crew member from presenting himself/herself at the crew pick-up point in time, difficulties with local authorities, health problems, death, etc. Unavailability does not refer to insufficient number or absence of cabin crew members on standby, or absence from work due to pregnancy, maternity/paternity leave, parental leave, medical leave, sick leave, or any other absence from work.

AMC1 ORO.CC.205(c)(1) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances

PROCEDURES WITH REDUCED NUMBER OF CABIN CREW

(a) During ground operations, if reducing the applicable minimum required number of cabin crew, the operator should ensure that the procedures required by ORO.CC.205 (c)(1) specify that:

(1) electrical power is available on the aircraft;

(2) a means of initiating an evacuation is available to the senior cabin crew member or at least one member of the flight crew is in the flight crew compartment;

(3) cabin crew stations and associated duties are specified in the operations manual; and

(4) cabin crew remain aware of the position of servicing and loading vehicles at and near the exits.

Additionally, in the case of passengers' embarkation:

(5) the senior cabin crew member should have performed the pre-boarding safety briefing to the cabin crew; and

(6) the pre-boarding cabin checks should have been completed.

(b) If, in unforeseen circumstances, the number of cabin crew members is reduced below the applicable minimum required number, for example in the event of incapacitation or unavailability of cabin crew, the procedures established for this purpose in the operations manual should take into consideration at least the following:

(1) reduction of passenger numbers;

(2) reseating of passengers with due regard to doors/exits and other applicable limitations; and

(3) relocation of cabin crew taking into account the factors specified in AMC1 ORO.CC.100 and any change of procedures.

AMC1 ORO.CC.205(d) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances

RISK ASSESSMENT FOR CRUISE PHASE OPERATION WITH A LOWER NUMBER OF CABIN CREW MEMBERS

When conducting the risk assessment required under ORO.CC.205(d), the operator should:

(a) assess the risks as relevant to the type and duration of the flight to be operated, aeroplane type, cabin configuration, passenger seating capacity, the number and qualification of the operating cabin crew members, and the particular flight duty period (FDP);

(b) determine how many cabin crew members should be present and ready to act at any time to realistically manage the normal and emergency procedures to be applied during cruise; and

(c) evaluate the time and conditions necessary for the cabin crew members taking in-flight rest to reach their assigned cabin crew stations in case of an emergency.

AMC2 ORO.CC.205(d) Reduction of the number of cabin crew members during ground operations and in unforeseen circumstances

SPECIFIC PROCEDURES FOR CRUISE PHASE OPERATION WITH A LOWER NUMBER OF CABIN CREW MEMBERS IN THE PASSENGER COMPARTMENT

(a) When establishing the specific procedures for cruise phase operation with a lower number of cabin crew members in the passenger compartment, the operator should at least consider the following:

(1) Normal procedures including at least:

(i) surveillance of the passenger compartment, including the lavatories and the galleys;

(ii) management of, and assistance to, passengers;

(iii) crew communication and coordination, including the necessary contact with and support to the flight crew as specified by the operator.

(2) Emergency procedures including at least those to be applied in case of:

(i) medical emergency;

(ii) unruly behaviour;

(iii) unlawful interference or bomb threat;

(iv) slow depressurisation;

(v) decompression;

(vi) fire or smoke event;

(vii) emergency descent, taking into account that the procedure to be applied may vary depending on the causing event (e.g. depressurisation or fire).

(b) Specific procedures for cruise phase operation with a lower number of cabin crew should describe:

(1) how to re-assign duties and responsibilities of cabin crew members or senior crew members who take in-flight rest to another cabin crew member considering the experience and qualification of the cabin crew member or senior cabin crew member; and

(2) how cabin crew members taking in-flight rest can be again ready to act and reach their assigned cabin crew stations in case of an emergency.

ORO.CC.210 Additional conditions for assignment to duties

Cabin crew members shall only be assigned to duties, and operate, on a particular aircraft type or variant if they:

(a) hold a valid attestation issued in accordance with CAR-CC;

(b) are qualified on the type or variant in accordance with this Subpart;

(c) comply with the other applicable requirements of this Subpart and Part-CAT;

(d) wear the operator's cabin crew uniform.

GM1 ORO.CC.210(d) Additional conditions for assignment to duties

OPERATOR'S CABIN CREW UNIFORM

The uniform to be worn by operating cabin crew should be such as not to impede the performance of their duties, as required for the safety of passengers and flight during operations, and should allow passengers to identify the operating cabin crew including in an emergency situation.

GM2 ORO.CC.210(d).G Additional conditions for assignment to duties

OTHER PERSONNEL

Other personnel, such as Child minders, Escorts, Entertainers, Interpreters, Medical personnel, Secretaries and Security staff and Technical staff, who undertake tasks in the cabin, should not wear a uniform which might identify them to passengers as cabin crew members unless they comply with the requirements of this Subpart and any other applicable requirements relevant to Cabin Crew.

ORO.CC.215 Training and checking programmes and related documentation

(a) Training and checking programmes including syllabi required by this Subpart shall be approved by the competent authority and specified in the operations manual.

(b) After a cabin crew member has successfully completed a training course and the associated check, the operator shall:

(1) update the cabin crew member's training records in accordance with ORO.MLR.115; and

(2) provide him/her with a list showing updated validity periods as relevant to the aircraft type(s) and variant(s) on which the cabin crew member is qualified to operate.

GM1 ORO.CC.215(b)(2) Training and checking programmes and related documentation

LIST OF AIRCRAFT TYPE/VARIANT QUALIFICATION(S)

When providing the updated validity list of aircraft type/variant qualifications to cabin crew members having successfully completed a training course and the associated checking, the operator must use the format given in Appendix IV to CAR-CC.

ORO.CC.250 Operation on more than one aircraft type or variant

(a) A cabin crew member shall not be assigned to operate on more than three aircraft types, except that, with the approval of the competent authority, the cabin crew member may be assigned to operate on four aircraft types if for at least two of the types:

(1) safety and emergency equipment and type-specific normal and emergency procedures are similar; and

(2) non-type-specific normal and emergency procedures are identical.

(b) For the purpose of (a) and for cabin crew training and qualifications, the operator shall determine:

(1) each aircraft as a type or a variant taking into account, where available, the relevant elements defined in the mandatory part of the operational suitability data established in accordance with CAR 21 for the relevant aircraft type or variant; and

(2) variants of an aircraft type to be different types if they are not similar in the following aspects:

(i) emergency exit operation;

(ii) location and type of portable safety and emergency equipment;

(iii) type-specific emergency procedures.

AMC1 ORO.CC.250(b) Operation on more than one aircraft type or variant

DETERMINATION OF AIRCRAFT TYPES AND VARIANTS

(a) When determining similarity of location and type of portable safety and emergency equipment, the following factors should be assessed:

(1) all portable safety and emergency equipment is stowed in the same, or in exceptional circumstances, in substantially the same location;

(2) all portable safety and emergency equipment requires the same method of operation;

(3) portable safety and emergency equipment includes:

(i) fire-fighting equipment;

(ii) protective breathing equipment (PBE);

(iii) oxygen equipment;

(iv) crew life-jackets;

(v) torches;

(vi) megaphones;

(vii) first-aid equipment;

(viii) survival and signalling equipment; and

(ix) other safety and emergency equipment, where applicable.

(b) The type-specific emergency procedures to be considered should include at least the following:

(1) land and water evacuation;

(2) in-flight fire;

(3) non-pressurisation, slow and sudden decompression; and

(4) pilot incapacitation.

(c) When determining similarity of doors/exits in the absence of operational suitability data established in accordance with CAR 21 for the relevant aircraft type(s) or variant(s), the following factors should be assessed, except for self-help exits, such as type III and type IV exits, that need not be included in the assessment:

(1) door/exit arming and disarming;

(2) direction of movement of the operating handle;

(3) direction of door/exit opening;

(4) power assist mechanisms; and

(5) assisting evacuation means.

GM1 ORO.CC.250 Operation on more than one aircraft type or variant

SAFETY BRIEFING FOR CABIN CREW

When changing aircraft type or variant during a series of flight sectors, the cabin crew safety briefing should include a representative sample of type-specific normal and emergency procedures and safety and emergency equipment applicable to the actual aircraft to be operated for the immediately subsequent flight sector.

ORO.CC.255 Single cabin crew member operations

(a) The operator shall select, recruit, train and check the proficiency of cabin crew members to be assigned to single cabin crew member operations according to criteria appropriate to this type of operation.

(b) Cabin crew members who have no previous operating experience as single cabin crew member shall only be assigned to such type of operation after they have:

(1) completed training as required in (c) in addition to other applicable training and checking required by this Subpart;

(2) successfully passed the checks verifying their proficiency in discharging their duties and responsibilities in accordance with the procedures specified in the operations manual; and

(3) undertaken familiarisation flying of at least 20 hours and 15 sectors on the relevant aircraft type under the supervision of an appropriately experienced cabin crew member.

(c) The following additional training elements shall be covered with particular emphasis to reflect single cabin crew operations:

(1) responsibility to the commander for the conduct of normal and emergency procedures;

(2) importance of coordination and communication with the flight crew, in particular when managing unruly or disruptive passengers;

(3) review of operator requirements and legal requirements;

(4) documentation;

(5) accident and incident reporting; and

(6) flight and duty time limitations and rest requirements.

SUBPART TC — TECHNICAL CREW IN HEMS, HHO OR NVIS OPERATIONS

ORO.TC.100 Scope

This Subpart establishes the requirements to be met by the operator when operating an aircraft with technical crew members in commercial air transport helicopter emergency medical service (HEMS), night vision imaging system (NVIS) operations or helicopter hoist operations (HHO).

ORO.TC.105 Conditions for assignment to duties

(a) Technical crew members in commercial air transport HEMS, HHO or NVIS operations shall only be assigned duties if they:

(1) are at least 18 years of age;

(2) are physically and mentally fit to safely discharge assigned duties and responsibilities;

(3) have completed all applicable training required by this Subpart to perform the assigned duties;

(4) have been checked as proficient to perform all assigned duties in accordance with the procedures specified in the operations manual.

(b) Before assigning to duties technical crew members who are self-employed and/or working on a freelance or part-time basis, the operator shall verify that all applicable requirements of this Subpart are complied with, taking into account all services rendered by the technical crew member to other operator(s) to determine in particular:

(1) the total number of aircraft types and variants operated;

(2) the applicable flight and duty time limitations and rest requirements.

GM1 ORO.TC.105 Conditions for assignment to duties

GENERAL

(a) The technical crew member in HEMS, HHO or NVIS operations should undergo an initial medical examination or assessment and, if applicable, a re-assessment before undertaking duties.

(b) Any medical assessment or re-assessment should be carried out according to best aero-medical practice by a medical practitioner who has sufficiently detailed knowledge of the applicant's medical history.

(c) The operator should maintain a record of medical fitness for each technical crew member.

(d) Technical crew members should:

(1) be in good health;

(2) be free from any physical or mental illness that might lead to incapacitation or inability to perform crew duties;

(3) have normal cardio-respiratory function;

(4) have normal central nervous system;

(5) have adequate visual acuity 6/9 with or without glasses;

(6) have adequate hearing; and

(7) have normal function of ear, nose and throat.

ORO.TC.110 Training and checking

(a) The operator shall establish a training programme in accordance with the applicable requirements of this Subpart to cover the duties and responsibilities to be performed by technical crew members.

(b) Following the completion of initial, operator conversion, differences and recurrent training, each technical crew member shall undergo a check to demonstrate their proficiency in carrying out normal and emergency procedures.

(c) Training and checking shall be conducted for each training course by personnel suitably qualified and experienced in the subject to be covered. The operator shall inform the competent authority about the personnel conducting the checks.

AMC1 ORO.TC.110 Training and checking

GENERAL

(a) Elements of training that require individual practice may be combined with practical checks.

(b) The checks should be accomplished by the method appropriate to the type of training including:

(1) practical demonstration;

(2) computer-based assessment;

(3) in-flight checks; and/or

(4) oral or written tests.

AMC1 ORO.TC.110 (a) Training and checking

CRM TRAINING

The technical crew training programme for initial, operator conversion and recurrent training should include relevant CRM training elements as specified in AMC1 ORO.FC.115.

ORO.TC.115 Initial training

Before undertaking the operator conversion training, each technical crew member shall complete initial training, including:

(a) general theoretical knowledge on aviation and aviation regulations covering all elements relevant to the duties and responsibilities required of technical crew;

(b) fire and smoke training;

(c) survival training on ground and in water, appropriate to the type and area of operation;

(d) aero-medical aspects and first-aid;

(e) communication and relevant CRM elements of ORO.FC.115 and ORO.FC.215.

AMC1 ORO.TC.115 Initial training

ELEMENTS

(a) The elements of initial training mentioned in ORO.TC.115 should include in particular:

(1) General theoretical knowledge on aviation and aviation regulations relevant to duties and responsibilities:

(i) the importance of crew members performing their duties in accordance with the operations manual;

(ii) continuing competence and fitness to operate as a crew member with special regard to flight and duty time limitations and rest requirements;

(iii) an awareness of the aviation regulations relating to crew members and the role of the competent and inspecting authority;

(iv) general knowledge of relevant aviation terminology, theory of flight, passenger distribution, meteorology and areas of operation;

(v) pre-flight briefing of the crew members and the provision of necessary safety information with regard to their specific duties;

(vi) the importance of ensuring that relevant documents and manuals are kept up-to-date with amendments provided by the operator;

(vii) the importance of identifying when crew members have the authority and responsibility to initiate an evacuation and other emergency procedures; and

(viii) the importance of safety duties and responsibilities and the need to respond promptly and effectively to emergency situations.

(2) Fire and smoke training:

(i) reactions to emergencies involving fire and smoke and identification of the fire sources;

(ii) the classification of fires and the appropriate type and techniques of application of extinguishing agents, the consequences of misapplication, and of use in a confined space; and

(iii) the general procedures of ground-based emergency services at aerodromes.

(3) When conducting extended overwater operations, water survival training, including the use of personal flotation equipment.

(4) Before first operating on an aircraft fitted with life-rafts or other similar equipment, training on the use of this equipment, including practice in water.

(5) Survival training appropriate to the areas of operation (e.g. polar, desert, jungle, sea or mountain).

(6) Aero-medical aspects and first aid, including:

(i) instruction on first aid and the use of first-aid kits; and

(ii) the physiological effects of flying.

(7) Effective communication between technical crew members and flight crew members, including common language and terminology.

ORO.TC.120 Operator conversion training

Each technical crew member shall complete:

(a) operator conversion training, including relevant CRM elements,

(1) before being first assigned by the operator as a technical crew member; or

(2) when changing to a different aircraft type or class, if any of the equipment or procedures mentioned in (b) are different.

(b) Operator conversion training shall include:

(1) the location and use of all safety and survival equipment carried on the aircraft;

(2) all normal and emergency procedures;

(3) on-board equipment used to carry-out duties in the aircraft or on the ground for the purpose of assisting the pilot during HEMS, HHO or NVIS operations.

AMC1 ORO.TC.120&.125 Operator conversion training and differences training

ELEMENTS

(a) Operator conversion training mentioned in ORO.TC.120 (b) and differences training mentioned in ORO. TC.125 (a) should include the following:

(1) Fire and smoke training, including practical training in the use of all fire fighting equipment as well as protective clothing representative of that carried in the aircraft. Each technical crew member should:

(i) extinguish a fire characteristic of an aircraft interior fire except that, in the case of Halon extinguishers, an alternative extinguishing agent may be used; and

(ii) practise the donning and use of protective breathing equipment (when fitted) in an enclosed, simulated smoke-filled environment.

(2) Practical training on operating and opening all normal and emergency exits for passenger evacuation in an aircraft or representative training device and demonstration of the operation of all other exits.

(3) Evacuation procedures and other emergency situations, including:

(i) recognition of planned or unplanned evacuations on land or water — this training should include recognition of unusable exits or unserviceable evacuation equipment;

(ii) in-flight fire and identification of fire source; and

(iii) other in-flight emergencies.

(4) When the flight crew is more than one, training on assisting if a pilot becomes incapacitated, including a demonstration of:

(i) the pilot's seat mechanism;

(ii) fastening and unfastening the pilot's seat restraint system;

(iii) use of the pilot's oxygen equipment, when applicable; and

(iv) use of pilots' checklists.

(5) Training on, and demonstration of, the location and use of safety equipment, including the following:

(i) life rafts, including the equipment attached to, and/or carried in, the raft, where applicable;

(ii) life jackets, infant life jackets and flotation devices, where applicable;

(iii) fire extinguishers;

(iv) crash axe or crow bar;

(v) emergency lights, including portable lights;

(vi) communication equipment, including megaphones;

(vii) survival packs, including their contents;

(viii) pyrotechnics (actual or representative devices);

(ix) first-aid kits, their contents and emergency medical equipment; and

(x) other safety equipment or systems, where applicable.

(5) Training on passenger briefing/safety demonstrations and preparation of passengers for normal and emergency situations.

(6) Training on the use of dangerous goods, if applicable.

(7) Task-specific training.

AMC2 ORO.TC.120&.125 Operator conversion training and differences training

GENERAL

(a) The operator should determine the content of the conversion or differences training taking account of the technical crew member's previous training as documented in the technical crew member's training records.

(b) Aircraft conversion or differences training should be conducted according to a syllabus and include the use of relevant equipment and emergency procedures and practice on a representative training device or on the actual aircraft.

(c) The operator should specify in the operations manual the maximum number of types or variants that can be operated by a technical crew member.

ORO.TC.125 Differences training

(a) Each technical crew member shall complete differences training when changing equipment or procedures on types or variants currently operated.

(b) The operator shall specify in the operations manual when such differences training is required.

See also:

AMC1 ORO.TC.120&.125 Operator conversion training and differences training

AMC2 ORO.TC.120&.125 Operator conversion training and differences training

ORO.TC.130 Familiarisation flights

Following completion of the operator conversion training, each technical crew member shall undertake familiarisation flights prior to operating as a required technical crew member in HEMS, HHO or NVIS operations.

ORO.TC.135 Recurrent training

(a) Within every 12-month period, each technical crew member shall undergo recurrent training relevant to the type or class of aircraft and equipment that the technical crew member operates. Elements of CRM shall be integrated into all appropriate phases of the recurrent training.

(b) Recurrent training shall include theoretical and practical instruction and practise.

AMC1 ORO.TC.135 Recurrent training

ELEMENTS

(a) The 12-month period mentioned in ORO.TC.135 (a) should be counted from the last day of the month when the first checking was made. Further training and checking should be undertaken within the last 3 calendar months of that period. The new 12-month period should be counted from the original expiry date.

(b) The recurrent practical training should include every year:

(1) emergency procedures, including pilot incapacitation;

(2) evacuation procedures;

(3) touch-drills by each technical crew member for opening normal and emergency exits for (passenger) evacuation;

(4) the location and handling of emergency equipment and the donning by each technical crew member of life jackets and protective breathing equipment (PBE), when applicable;

(5) first aid and the contents of the first-aid kit(s);

(6) stowage of articles in the cabin;

(7) use of dangerous goods, if applicable;

(8) incident and accident review; and

(9) crew resource management: all major topics of the initial CRM training should be covered over a period not exceeding 3 years.

(c) Recurrent training should include every 3 years:

(1) practical training on operating and opening all normal and emergency exits for passenger evacuation in an aircraft or representative training device and demonstration of the operation of all other exits;

(2) practical training in the use of all firefighting equipment as well as protective clothing representative of that carried in the aircraft. Each technical crew member should:

(i) extinguish a fire characteristic of an aircraft interior fire except that, in the case of Halon extinguishers, an alternative extinguishing agent may be used; and

(ii) practise the donning and use of protective breathing equipment (when fitted) in

an enclosed, simulated smoke-filled environment;

(3) use of pyrotechnics (actual or representative devices); and

(4) demonstration of the use of the life raft, where fitted.

ORO.TC.140 Refresher training

(a) Each technical crew member who has not undertaken duties in the previous six months shall complete the refresher training specified in the operations manual.

(b) The technical crew member who has not performed flying duties on one particular aircraft type or class during the preceding six months shall, before being assigned on that type or class, complete either:

(1) refresher training on the type or class; or

(2) two familiarisation sectors on the aircraft type or class.

AMC1 ORO.TC.140 Refresher training

ELEMENTS

(a) Refresher training may include familiarisation flights.

(b) Refresher training should include at least the following:

(1) emergency procedures, including pilot incapacitation;

(2) evacuation procedures;

(3) practical training on operating and opening all normal and emergency exits for passenger evacuation in an aircraft or representative training device and demonstration of the operation of all other exits; and

(4) the location and handling of emergency equipment, and the donning of life jackets and protective breathing equipment, when applicable.

SUBPART FTL — FLIGHT AND DUTY TIME LIMITATIONS AND REST REQUIREMENTS

Section 1 — General

ORO.FTL.100.G Applicability

(a) All operators shall comply with Subpart Q of CAR-OPS 1, Issue 07 of 03 September 2020 or Subpart Q of CAR-OPS 3, Issue 04 of 21 March 2021 as applicable.

(b) All approved flight and duty time limitation schemes and variations issued in accordance with the applicable Subpart Q shall continue to be valid.

(c) Waivers and exemptions issued in accordance with the applicable Subpart Q shall continue to be valid in accordance with point 3.G of Article 6 of the Cover Regulation.

(d) Helicopter operators shall comply with the provisions laid down in CAR-OPS 1.1120 Standard Provisions Applicable to a Scheme and the AMCs and GMs thereto when applying for an FDTL Variation to the standard provisions.

APPENDIX TO PART-ORO

Appendix I to Part-ORO

DECLARATION in accordance with UAE Civil Aviation Regulations					
Operator Name: Place in which the operator has its principal place of business or, if the operator has no principal place of business, place in which the operator is established or residing and place from which the operations are directed: Name and contact details of the accountable manager(1):					
Aircraft operation					
Starting date of operation and applicability date of the change:					
Information on aircraft, operation and continuing airworthiness management organisation(2):					
Type(s) of aircraft, registration(s) and main base:					
Aircraft MSN	Aircraft type	Aircraft registration(3)	Main base	Type(s) of operation (4)	Organisation responsible for the continuing airworthiness management(5)
Where applicable, details of approvals held (attach list of specific approvals, including specific approvals granted by a foreign country, to the declaration, if applicable).					
Where applicable, details of specialised operations authorisation held (attach authorisations, if applicable).					
Where applicable, list of alternative means of compliance with references to the associated AMCs they replace (attach AltMoC).					
Statements (All Operations)					
☐ The operator complies, and will continue to comply, with the essential requirements set out in CAR Basic Regulations and with the requirements of CAR AIR OPERATIONS. ☐ The management system documentation, including the operations manual, comply with the requirements of Part-ORO, Part-SPA, Part-NCC or Part-SPO to CAR AIR OPERATIONS and all flights will be carried out in accordance with the provisions of the operations manual as required by point ORO.GEN.110(b) of Part-ORO to that Regulation. (Not applicable for NCO).					
☐ All aircraft operated hold a valid certificate of airworthiness in accordance with CAR 21 or meet the specific airworthiness requirements applicable to aircraft registered in a foreign country and subject to a lease agreement.					
☐ All flight crew members hold a licence in accordance with CAR-FCL as required by point ORO.FC.100(c) of Part-ORO to CAR AIR OPERATIONS and cabin crew members, where applicable, are trained in accordance with Subpart CC of Part-ORO to CAR AIR OPERATIONS.					
☐ (If applicable) The operator has implemented and demonstrated conformance to a recognised industry standard. Reference of the standard: Certification body: Date of the last conformity audit:					
☐ The operator will notify to the competent authority any changes in circumstances affecting its compliance with the essential requirements set out in Annex V to CAR Basic Regulations and with the requirements of CAR AIR OPERATIONS as declared to the competent authority through this declaration and any changes to the information and lists of AltMoC included in and annexed to this declaration, as required by point ORO.GEN.120(a) of Part-ORO to CAR AIR OPERATIONS.					
☐ The operator confirms that the information disclosed in this declaration is correct.					

NCO Operators Only ☐ The operator will notify to the competent authority on conduct of SPO as per SPO.GEN.005 highlighting the applicable regulations.
Date, name and signature of the accountable manager
(1) In the case of NCO operation not managed by a third-party operator, the owner is the accountable manager. (2) If there is not enough space to list the information in the space of the declaration, the information shall be listed in a separate annex. The annex shall be dated and signed. (3) If the aircraft is also registered with an AOC holder, specify the AOC number of the AOC holder. (4) "Type(s) of operation" refers to the type of operations conducted with the aircraft, e.g. non-commercial operations or specialised operations such as aerial photography flights, aerial advertising flights, news media flights, television and movie flights, parachute operations, skydiving, maintenance check flights. Information about the organisation responsible for the continuing airworthiness management includes the name of the organisation, the address and the approval reference.